

SEALED BID FORMAT FOR INTERIOR FURNISHING WORKS AT SBI AMBALAPUZHA BRANCH(EXISTING PREMISES), ALAPPUZHA AS PER UNIFORM LAYOUT					
	DESCRIPTION OF WORK	Qty	Unit	Rate	Amount
1	Providing and fixing of single window system without partitions as shown in the drawings comprising of each counter size 1500 to 1750mm & 2500mm length or as per layout and 1200 mm height or as per layout with below specifications and provisions . Counter and writing top at front, with counter 1500to 1750mm length and 1000mm width at about 750mm height. The top shall be fixed with 19mm plywood (IS303marine grade) of approved make with curved bend in front modesty as per drawing and fixed with white corian top of 6mm thick of approved brand. 18mm plywood of approved make for sides and for front shaped support and finished with 1mm laminate of approved colour. Front counter support for 750mm height with 18mm plywood finished with 1mm laminate of approved colour and shade. Below counter top additional 18mm plywood finished with 1mm laminate is fixed to pattern as shown.12mm thick clear float glass to shape with etching is fixed with SS glazed clips fixed at front (600mm) and sides (450mm) above the counter as shown in the drawing.	16	RM		
	Modesty fixed with 8mm thick of Aqua Blue shade of Saint Gobain glass or equivalent fixed 3M stickering suitable at 18mm thick Plywood vertical finished with 1mm laminate. The side partitions of the counter, boxing on either side to shape as shown in the drawing with 18mm plywood of approved make and to be finished with 1mm laminate of approved colour from floor level to 1200mm level at places shown in the drawing. Necessary wicket shutters are to be provided using 18mm plywood and finished with 1mm laminate of approved colour and shape as shown in the drawing.				
	One set of 3 drawers about 450mm width, 712.5mm height and 600mm deep supported with 18mm plywood at bottom sides and rear. Drawers 3 nos of equal height made out of 12 mm thick lamination of approved colour, wiht necessary lipping. Telescopic drawerd slides, locking arrangements, 100mm long brush finish S.S handles etc complete. Top most cash drawer should be arraged with provision for denomination with 8mm thick plywood. Cash denomination seperation to be provided for 1 draw unit of the SWO, preferable the top draw wiht plywood. Thsi draw unit has to be provided wiht automatic lock. M.S powder coated Telescopic keyboard and MS wire manager of 50mm dia of approved quality.Foot rest cum CPU stand of required length with 18mm thickness plywood to shape as shown in the drawing.				

	All concerned faces of MDF/plywood finished with one coat of wood preservative paint and exposed faces of steam beach beading polished to the satisfaction of the Engineer. The inner side of the unit finished with 1mm laminate. The MDF boards/plywood and corrain materials are as approved by Bank. The rate should include locks, MS powder coated keyboard trays, Telescopic drawer slides, 100mm SS brush finish handle with necessary hardware fittings etc complete. The rate of low partition is not included and is paid separately.				
2	SINGLE WINDOW SYSTEM (With Out Front Glass). The same as above specification without front glass.	3	RM		
3	LOW HEIGHT PARTITION FOR SINGLE WINDOW SYSTEM:Providing and fixing of Low height partitions for Single window system of 750 mm height from finished floor level, as per the drawing.Hardwood section of 50 X 50 mm ,vertically at about 60 cm centers and 3 Nos Horizontally of the same size of frame at floor level, 750 mm and at 1200 mm level. 50 X 25 mm at 370 mm level, fixed in position. 8 mm Plywood on both sides of framework finished with 1 mm laminate of approved color and shade with grooves on both sides. Top of the partition finished with laminate of 1mm thick. The side portion glazing shall be done with "Blue Laminated / Lacquered transperated glass of 12mm thick of approved brand and shall be fixed with 'Doma' (or) equivalent brand 'SS ' 'D' brackets. The curved 12mm thick lacquered transperant toughened glass shall be fixed at front size in between counters as per drawing and shall be fixed suitably with 'SS' brackets. Partition on rear similar to side partition, but solid partition. One door shutter for each cabin for 675 mm width and 1200 mm height, similar to door shutter item.All concealed faces of plywood and frame work finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the client.In door area concealed 50 mmX50 mm Second class TW frame to be ProvidedMeasurement for the partition area shall be considered from the floor level to false ceiling level only.	55	Sq.m		

4	<p>Custom Made Low Height Partition: for CO cabin. Providing and fixing in position of custom made low height partitions of the height 1500mm as per shape shown in the drawing (750mm solid partitions and 750mm glass above) Providing and fixing of Low height partitions. Hardwood section of 50 X 50 mm, vertically at about 60 cm centers and 3 Nos Horizontally of the same size of frame at floor level, 750 mm and at 1200 mm level. 50 X 25 mm at 370 mm level, fixed in position. 8 mm Plywood on both sides of framework finished with 1 mm laminate of approved color and shade with grooves on both sides. Top of the partition finished with laminate of 1mm thick. The side portion glazing shall be done with "Blue Laminated / Lacquered transperated glass of 12mm thick of approved brand and shall be fixed with 'Doma' (or) equivalent brand 'SS ' 'D' brackets. The curved 12mm thick lacquered transperant toughened glass shall be fixed at front size in between counters as per drawing and shall be fixed suitably with 'SS' brackets. Partition on rear similar to side partition, but solid partition. One door shutter for each cabin for 675 mm width and 1200 mm height, similar to door shutter item. All concealed faces of plywood and frame work finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the client. In door area concealed 50 mm X 50 mm Second class TW frame to be Provided Measurement for the partition area shall be considered from the floor level to false ceiling level only.</p>	15	Sq.m		
5	<p>Custom Made Full Height Solid Partition: Supply and set in position of custom made double skin full height partitions as per shape and size shown in the drawing. Frame Work Detail: Harwood sections of thickness 50 X 50mm, vertically at about 60cm centers varied along columns wall ends, junctions of walls, as necessary. Horizontally of the same size of frames at floor level, 750 mm, 1500 mm, 2100 mm, and roof level. 50 X 25 mm at 350 Lining Work: 8 mm Plywood of approved make on both sides of framework from floor level to 6" above false ceiling level, and to be finished with 1mm laminate of approved color and shaped on both sides including necessary grooves and steam beach beadings.</p> <p>NOTE: All concealed faces of plywood and frame work should be finished with coat of wood preservation paint and exposed faces of steam beach beading/ laminate finish to be polished with melamine to the satisfaction of the Bank and Architects. In door area concealed Measurement for the partition area shall be considered from floor level to false ceiling level only.</p>	20	Sq.m		

6	<p>Full Height Partly Solid & Partly Glazed Partition: Providing and fixing in position of double skin partition, partly paneled and partly glazed as per details shown in the drawing. Frame Work Detail: Harwood section of thickness 50 X 50 mm ,vertically at about 60 cm centers varied along columns, wall ends , junctions of walls, as necessary. Horizontally of the same size of frame at floor level, 900 mm, 2100 mm, and roof level. 50 X 25 mm at 450 mm level. Lining Work: 8 mm plywood of approved make on both sides of framework from floor level to 900 mm level and 2100 mm level to 6" above false ceiling level finished with 1 mm laminate of approved color and shade. Between 900 mm and 2100 mm level, 8 mm thick clear float glass with etching fixed with necessary Dorma (or) equivalent make 'D' bracket of SS finish of 12mm thick. The glass opening 'jamb' portion finished with laminate. Measurement for the partition area shall be considered from the floor level to false ceiling level only.</p>	45	Sq.m		
7	<p>Fully glazed Door Providing and fixing frameless fully glazed 12mm thick toughened float glass fixed with necessary patch fittings (Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, screws, sealant wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking systems, 1 pair of 600mm long S. S. (H Shape) Handles of approved make, floor springs, and any necessary hardware items. (DORMA MAKE Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 32mm dia X 600mm length)</p>	10	Sq.m		
8	<p>Fully Glazed - Fixed Glass Partition - Providing and fixing of fixed glass partitions with 12mm thick float plain glass using PT standard fittings like PT90/PT 92 of Dorma make at the top and bottom including cutting, making holes in glass and fixing the fittings in floors, ceiling etc and making the same good with necessary screws, 3M vinyl sticker as per approved colour, design and pattern, sealants etc complete.</p>	10	Sq.m		
9	<p>Partly Glazed And Partly Paneled Doors with teak frame 75x50mm, with 35mm thick finished flush shutter finished with 1 mm laminate on both sides with necessary grooves. 8mm clear float glass of size 250x1400 mm fixed with necessary grooves.</p>	2	No		
10	<p>FALSE CEILING: NOTE: The false ceiling area will be measured in flat area only.</p>				

	<p>Gypsum Board False Ceiling Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprising Frame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls alround perimeter side of the ceiling. The intermediate channels suspened from ceiling,through starp hangers 25 X 0.5 mm (MF 8)at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A)for light fittings, Air conditioners Ducts,vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to from grids with 2 coats of plastic emulsion paint of approved color and one coat of putty over a coat primer etc, complete.</p>	275	Sq.m		
11	BM Table				
	<p>Providing and fixing BM Table of size 1800 x 850 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood post formed with 1 mm thickness flexy laminate of approved color and brand with both size half rounded edge and anotheOn front and side of drawer finished with 1mm thk laminate and additional 18mm thick Plywood is fixed on front side to pattern with necessary grooves and finished with 1mm thick laminate.Foot rest cum CPU stand of required length with same 18 mm Plywood waxed and finished with varnish of app color and shadeMS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality . One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick Plywood and finished with 1mm thick laminate at front side of approved color and shade with necessary lipping, telescopic drawer slides, locking arrangement, 100 mm long brush finish S.S. handles, etc. complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade the table modesty shall be fixed with 8mm thick of Aqua blue shade of saint Gobain (or) equivalent toughened glass panel fixed on the 18mm thick to be fixed on front vertical laminated Plywood Board with SS studs.</p>	1	No		

12	<p>Side Tables For BM Providing and fixing side unit for Manager / BM table to detail as per drg. of size 1200mm x 450mm, 18 mm Plywood for bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be 25mm thick Plywood Board with 1mm thick flexy laminate of approved color and brand with front side half rounded edge and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc.,complete. 12 mm glass with edges rounded to be provided for the table top</p> <p>All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.</p>	1	No		
13	<p>Officers Table Providing and fixing Officer Table of size 1500 x 750 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood Board post formed with 1mm thick flexy laminate of approved color and brand with both side half rounded edge and another two side edges with 3mm thick band strip. 12 mm glass with edge rounded to be provided for the table top. Aqua blue shade of saint Gobain (or) equivalent toughened glass panel fixed on the 18mm thick to be fixed on front vertical laminated Plywood Board with SS studs. MS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality .One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick</p> <p>All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade</p>	5	No		

14	<p>Officer table to detail as per drg. of size 1000mm x 450mm, 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary TW lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc.,complete.12 mm glass with edges rounded to be provided for the table top</p> <p>Providing and fixing side unit for Cash Officer table to detail as per drg. of size 1000mm x 450mm, 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary TW lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc.,complete.12 mm glass with edges rounded to be provided for the table top</p> <p>All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.</p>	6	No		
15	<p>Low Level Storage :Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.</p> <p>All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.</p>	20	Sq.m		

16	System Room table				
	Providing and fixing System running table of width 750mm & 750mm height. The table will have 3 drawer and stand for CPU. And drawer provided with a handle of appropriate size. The table will have a M.S wire manager of 50 mm dia of approved quality. Providing and fixing System running table of width 750mm & 750mm height. The table will have 3 drawer and stand for CPU. And drawer provided with a handle of appropriate size. The table will have a M.S wire manager of 50 mm dia of approved quality. The table will also be provided with footrest made of steem beach wood 75 x 32mm. The table top Plywood finished with 1mm thickness flexy laminate of approved color and brand with two sides shall be half rounded edge and another two sides with edge band strip of 3mm thickness. The table will be provided with a M.S powder coated keyboard tray. All the exposed Plywood surface to be finished with 1mm thick laminate of approved color and shade. All concealed faces will be painted with two coats of paint of approved shade. All steem beech surfaces to be finished in polish and melamine	3	RM		
17	Column Panelling Providing and fixing cladding around the columns to detail as per drawing comprising 18mm thick Plywood with necessary stiffner on both ways of required nos and finished with 1 mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacqured glass as per drawing. 8mm thick MDF board jally work (CNC cutting) of approved design / pattern finished with white colour high gloss duco paint fixed over the laminate finish surface.	35	Sq.m		
18	Providing and fixing wall panelling to detail as shown in the drawing with 18mm thick Plywood finished with 1mm thick laminate	10	Sq.m		
19	Writing Ledge Providing and fixing of rectangular writing Desk of size 1200mm to a height of 120cm as per drawing, the vertical support shall be of 4nos finished with 25mm thick plywood finished with post forming with half rounded edge on outer side with 1mm flexy laminate. The top shall be of 18mm Plywood finished with 1mm laminate on both sides and edges finished with circular edge band. The glass top over the plywood circular top shall be of 12mm thick toughened glass to be velled edge/ edge polished and supported by intermediate vertical 12mm thick Plywood, finished with laminate on both side. The compartment shall be 4nos as per drawing. vertical support shall be 230mm height and all edge shall be with edge band of same color. The writing desk shall be fixed on a circular 18mm thick plywood platform and export surface shall be finished with 1mm thick laminate the interior space of platform with 1mm white laminate.	1	No		

20	Grahakmitra Table:Providing and fixing Officer Table of size 1200 x 750 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood post formed with 1mm thick flexy laminate of approved color and brand with both side half rounded edge and another two side edges with 3mm thick band strip.On front and side of drawer finished with 1mm thk laminate and additional 18mm Plywood is fixed on front side to pattern with necessary grooves and finished with 1mm thick laminate.12 mm glass with edges rounded to be provided for the table top. The front fascia of the table to be provided with 12 mm thick glass properly fixed with SS studs.MS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality .One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick plywood.	2	RM		
	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and sha				
21	Painting banking hall using approved quality 'Asian Paint' or equivalenttwo coaaaats after applying putty finish	250	Sq.m		
22	Providing and fixing back drop behind grahakmitra table and made of 8mm thick acrylic sheet, over Plywood wall panellingfinished with approved laminate. The matter shall be clear vinyl printing reverse type and the digital printing shall be done on rear side	5	Sq.m		
	TOTAL				
	GST@18%				
	GRAND TOTAL				