

**STATE BANK OF INDIA**  
**ALUVA CATHOLIC CENTRE - WEALTH HUB**  
**(EXISTING PREMISES)**

	Name of Work	Sealed bid format for the interior furnishing work of Aluva Catholic centre branch for accomodating wealth hub			
	Name and address of the contractor				
Sl No.	Description of work	Unit	Quantity	Rate	Amount
1	Providing and fixing of Low height partitions with 12 mm glass with etching for a height of 45 cm above the solid partition. The edges of the glass to be polished. The bottom portion of the partition is of double skin type for a height of 75 cm from the finished floor level, as per the drawing. Hardwood section of 50 X 50 mm ,vertically and horizontally at about 60 cm c/c. 8 mm Plywood on both sides of framework finished with 1 mm laminate of approved color and shade with grooves on both sides. Top of the partition finished with laminate of 1mm thick. Partition on rear similar to side partition, but solid partition. One door shutter for each cabin for 675 mm width and 1200 mm height, similar to door shutter item.All concealed faces of plywood and frame work finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the client.In door area concealed 50 mmX50 mm Second class TW frame to be Provided.	5	Sq.m		
2	Custom Made Full Height Solid Partition:Supply and set in position of custom made double skin full height partitions as per shape and size shown in the drawing.Frame Work Detail:Harwood sections of thickness 50 X 50mm,vertically at about 60cm centers varied along columns wall ends, junctions of walls, as necessary. Horizontally of the same size of frames at floor level,750 mm, 1500 mm,2100 mm, and roof level. 50 X 25 mm at 350 Lining Work:8 mm Plywood of approved make on both sides of framework from floor level to 6"above false ceiling level, and to be finished with 1mm laminate of approved color on both sides including necessary grooves and steam beach beadings, doors wherever required in matching pattern with 10 x 4 cm hard wood frames, all best quality hardware, godrej lock etc complete. NOTE:All concealed faces of plywood and frame work should be finished with coat of wood preservation paint and exposed faces of steam beach beading/ laminate finish to be polished with melamine to the satisfaction of the Bank and Architects. Measurement for the partition area shall be considered from floor level to false ceiling level only.	20	Sq.m		

SI No.	Description of work	Unit	Quantity	Rate	Amount
3	Slim line partition of approved make :- supply and installation of full height straight glass partition clear float glass and proprietary electroplated as approved colour with aluminium sections of the SLIM LINE TWIN STYLE TWIN PRO SECTION NO. 6633 (35mm x 25mm) and 6634 (35mm x 20mm) male and female sections providing inside with rubber gaskets in top & bottom upto false ceiling level. The glass joints shall be filled with silicon sealant on both side. Rate shall include for providing transport charges, handling, loading and unloading, Installation, protecting the module and glass till handing over, testing, commissioning all necessary hardware's, scaffolding, wastage, Structural supports if any, etc. complete and all as per manufacturers specifications as directed. Etching stickers are to be provided as per design. The partition is to be firmly fixed to the floor and ceiling. The partition up to false ceiling only be measured.	52	Sq.m		
4	Providing and fixing fully glazed door ( 2 shutters) of 12 mm thick toughened glass with pencil polish edges around with etching patterns and bevelled at edges. The door shall be fixed with DORMA patch fitting assembly inclusive of top and bottom patches, floor springs, bottom locks, SS brushed handle of 60 cm long and 2.5 cm dia. Lock of approved make etc. to be fixed to the door, the edge of the glass to be polished.	5	Sq.m		
5	<p>FALSE CEILING:NOTE:The false ceiling area will be measured in flat area only.</p> <p>Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprising Frame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls around perimeter side of the ceiling. The intermediate channels suspended from ceiling, through sharp hangers 25 X 0.5 mm (MF 8) at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A) for light fittings, Air conditioners Ducts, vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to form grids with 2 coats of plastic emulsion paint of approved color and one coat of putty over a coat primer etc, complete.</p>	80	Sq.m		

Sl No.	Description of work	Unit	Quantity	Rate	Amount
6	Officers Table Providing and fixing Officer Table of size 1500 x 750 X 750 mm high to detail as shown in drg. Comprising table top out of 25mm thick Plywood Board post formed with 1mm thick flexy laminate of approved color and brand with both side half rounded edge and another two side edges with 3mm thick band strip. 12 mm glass with edge rounded to be provided for the table top. Aqua blue shade of saint Gobain (or) equivalent toughened glass panel fixed on the 18mm thick to be fixed on front vertical laminated Plywood Board with SS studs. MS Powder coated Keyboard tray and 50mm Dia MS wire manager of approved quality .One set of 4 drawers about 450mm wide, 712.5 mm high and 600mm deep to shape supported with 18 mm Plywood at bottom, sides and rear. 4 nos. of drawers out of which 3 nos. of equal height and 1 no. drawer at the top most of 75mm high made out of 12 mm thick All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach beading polished to the satisfaction of the Bank. The inside faces of drawer should be waxed and finished with varnish of app color and shade	9	No		
7	Side Tables For OFFICER - Providing and fixing side unit for Officer table to detail as per drg. of size 1200mm x 450mm, 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary reeper. The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip. Side hung shutter in both the panels using 18 mm Plywood and finished with 1mm laminate of approved color and shade, including all necessary TW lipping, Box Type hinges, Locking arrangement, 100 mm long S.S brush finish handles, tower bolt, ball catch etc., complete. All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.	1	No		
8	Providing and fixing side table of size 1000 x 450 mm for tables as detailed above	8	No		

Sl No.	Description of work	Unit	Quantity	Rate	Amount
9	<p>Low Level Storage :Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.</p> <p>All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.</p>	6	Sq.m		
10	<p>Column PanelingProviding and fixing cladding around the columns to detail as per drawing comprising 18mm thick Plywood with necessary stiffner on both ways of required nos and finished with 1 mm thick laminate of approved colour and shade. The surface has also fixed with 8 mm thick Lacqured glass as per drawing. 8mm thick MDF board jally work (CNC cutting) of approved design / pattern finished with white colour high gloss duco paint fixed over the laminate finish surface.</p>	15	Sq.m		
11	Painting banking hall using approved quality ' Asian paint or equivalent two coats after applying putty finish	100	Sq.m		
	<b>TOTAL</b>				
	<b>GST</b>				
	<b>TOTAL AMOUNT</b>				