

## Interior Furnishing Works for SBI SMECCC, Dehradun

S.No.	Description	Quantity	Unit	Rate	Amount ( in Rs.)
Note	Rate should be inclusive of material,labour,tools, machinery, scaffolding, final disposal of debris, cleaning, cutting, wastage, etc. all taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills.				
[A] FURNISHING WORKS					
TABLES					
1.1	A.G.M. TABLE SIZE: 7'-0" X 3'-0" X2'-6" Ht. with 3.5-4mm Veneer finish on Table Top, laminate finish on sides & front and all other visible surfaces etc complete as follows-	1.00	NO		
	Supplying and installation of Table as per the following description and as design/ details, Table Top: Providing and fixing 18 mm thick IS 303 BWR grade plywood with 3.5-4mm thick Teak veneer with melamine finish with necessary intermediate support. Table top shall be supported by 18 mm thick BWR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick bevelled toughened glass with polished edges. The top level of the glass shall be 750mm. Apron (Modesty Panel) made from 18 mm thick BWR grade plywood finished with veneer. Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with veneer for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be				
	Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWR grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWR grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame.				
	Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop. All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade.As per drawing and instruction of Architect/Bank, work to be completed.				
1.2	AGM SIDE CREDENZA (SIDE TABLE)				
	Providing & fixing Side Credenza of size 4'-0" x 1'-6" x 2'-6". Outer exposed structure with to be made with 18mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 18 mm thk BWR Ply and shelves to be made with 18 mm thk. BWR ply.	1.00	NO.		
	All exposed and top portion of the credenza to be finished with 3.5-4mm thk. veneer and finished with melamine polish. All the other internal surfaces to be finished with 0.8mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffele), SS towerbolts etc. All shutters to be made overlapping the frame. As per drawing and instruction of Architect/Bank, work to be Completed.				
2.1	CHIEF MANAGER TABLE				

	Table but size 5'-6" x 2'-9" x 2'-6" Table as per the following description and as design/ details, Table Top: Providing and fixing 18 mm thick IS 303 BWR grade plywood with 1mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick BWR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick bevelled toughened glass with polished edges. The top level of the glass shall be 750mm. Apron (Modesty Panel) made from 18mm thick BWR grade plywood finished with veneer. Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with veneer for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing.	2.00	NO.		
	Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWR grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWR grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame.				
	Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop. All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade. As per drawing and instruction of Architect/Bank, work to be completed.				
<b>2.2</b>	<b>SIDE CREDENZA for CM</b> same as above Item (Size 3'-6" x 1'-6" x 2'-	2.00	NO.		
	Providing & fixing Side Credenza Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 25 mm thk BWR Ply and shelves to be made with 19 mm thk.BWR ply. The top portion of the side and rear credenza to be finished with 1mm thk. laminate of approved shade and All edges to be provide with 2mm Edge binding tape. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffele), SS towerbolts etc. All shutters to be made overlapping the frame. As per drawing and instruction of Architect/Bank, work to be Completed Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
<b>3</b>	<b>OFFICER AND STAFF TABLE</b>				
<b>3.1</b>	Same as above for CM Table but Size: 5'-0" x 2'-6". (Without Top Glass)	26.00	NO.		
<b>3.2</b>	<b>SIDE CREDENZA for Officer &amp; Staff</b> same as above for C.M Side Credenza except (Size 3'-0" x 1'-6" x 2'-6") but, all external surfaces including top to be finished with 1.0mm thick Laminate of approved shades.	26.00	NO.		
<b>4.1</b>	<b>RUNNING COUNTER</b> (Laminate Finish on Table Top and Drawer Pedastal with 4 Nos Drawer in table )	3.00	RMT		
	Providing and fixing Running counter having width of 2'-0" using 18mm thick BWR BOARD Board for Top and vertical support, complete. 1.0 mm thick Laminate finish on table Top and edge & sides the surface finished with 0.8 MM laminate, complete with a drawer pedastal unit after every 4'-0" as each table unit and as directed.				
<b>4.2</b>	<b>Linear Running Counter</b>				

	Providing and Fixing linear running counter Work Station having a size of (4'x 2'-0" X 2'-6"ht.) in 25 mm thk. BWR Board of approved make for table top and side supports, front apron in 12mm.thk. BWR board as per the design / drawing including design fixed with studs, including finishing the same in 1 mm thk Laminate of approved make and shade. A drawer unit of size 1'-4" x 1'-8" x 2'-5" in 18mm BWR board with three drawers as per the drawing etc complete. Rate shall be inclusive of P/F 12mm.thk. front glass 1'-6" ht. on table top for work station with edge polish with S.S. "D" brackets. Additional glass 1' wide 12mm to be fixed for writing purpose and it should be fixed on the low height partition complete with brackets. Keyboards to be of EBCO make only. For CPU: P/F 19mm thk ply stand 18" x 9" to be fixed with on the verticals /apron of the table as directed. All exposed surfaces whether inner side or or outside must be 1mm laminated with approved laminate shade. (Low height partitions abutting the counters shall be paid separately.)	25.00	R.Mt.		
4.3	Providing and fixing <b>12 mm thick Toughened Glass divider on running counter Top</b> as follows.	6.00	SQMT		
	Providing and fixing 12 mm thick Toughened float glass with polished edges as per shape and design to be fixed with necessary S.S Brush finish brackets & support on table top and wooden partition as directed with necessary cut out in glass. All edges of glass shall have Diamond cut polished edges as directed. Brief list of make are as under or any equivalent make will be permitted by the Engineer. Glass- Asaahi/ Tata / Modi guard / Saint gobain Square bracket (50 mm x 12.5 mm ) S.S finish - Oswal / Riddhi / Swift or				
5	<b>MEETING ROOM TABLE</b>				
	Providing and placing in position Meeting Room tables of approx. size: 900mm in diameter . Providing & Fixing Meeting Table of shape as per design made from 50mm X 40mm T. W. Wood framework 450mm center to center both ways for table top covered with 12mm thick BWR ply for bottom, 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. All exposed surfaces shall be finish with approved color 1 mm thk. laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be inclusive of Brush Finish Stainless Steel Tray with POP UP Flap for electrical switches including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound, cleaning the site etc. complete as per the detail drawing and instruction of Engineer.	1.00	NO.		
6	<b>STORAGE CABINATE</b>				
	Supplying and providing storage cabinate same as above but with <b>1mm laminate</b> on all exposed surfaces like Top, Front Shutter, sides, back if exposed and 0.8 MM laminate from inside, storage to have 2mm thick edge binding tape of same colour as laminate on Edges .	9.00	SQMT		
	Size : Depth 1'-6" and height as per dwg. having openable shutter as directed. Storage Cabinet shall be made from 19mm thick BWR Ply, for Top with laminate finish and 19mm thick BWR Ply for verticle, shelves, shutters and 8mm thick BWR PLY for backing with 0.8 mm thick laminate on all internal surface. with verticle (at 3'-0" c/c) shelves at 1'-3" c/c Openable shutters in 19 mm thick BWR Ply with all auto hinges, towers bolts, powder coated handle, ball catches, SS approved make multi purpose lock complete, Edges to have 2mm thick edge binding tape of same colour as laminate. Only front surface area shall be measured for payment purpose.				
7	<b>ELECTRIC CUPBOARD</b>	4.00	SQMT		
	Providing and fixing Electric cup board using 19 mm thick bison board for frame sides verticle and shelves and front shutters with aluminium framing of 50x25x1.5mm thick with 6mm thick bison panel on both side finished with 1.0 mm thick laminate on all exposed surface and fire proof paint & synthetic enamel paint on all internal surface. Shutter with approved make lock handle, hinges, ball catchers, SS Perforated jali shall be provided in shutter for ventilation, complete as directed, depth of cup board 1'-3". Shutter height as required and above area fixed Type with same Aluminum frame and bison board laminate finish up to false ceiling bottom.				
8	<b>P/F LOW HEIGHT WOODEN PARTITION WITH BOTH SIDE LAN</b>	80.00	SQMT		
	Providing & fixing in position Low height wooden partitions with 450mm high glass panel finished with laminate on both sides comprising as under:				
(i)	Total Height of the partitions shall be from 1200 mm including 300 mm high 12 mm clear glass panel as per approved drawing.				

(ii)	Framing : Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium sections placed bothways (horizontal and vertical) not exceeding 450 mm c/c rigidly fixed to floor, wall / columns etc including extending end/intermediate vertical members not exceeding 1500 mm c/c for total finished height of LHP.				
(iii)	Skin : Providing & fixing 8 mm thick HDMR/ HDWR board on both sides of the framework and all-round vertical posts extending up to total height of				
(iv)	Finishing :- Providing and fixing 1.00mm thick approved quality and shade laminates using approve quality adhesive, over ply as per approved design & pattern including providing grooves as per Architectural drawing and as directed by the Engineer-in-charge.				
(v)	Glazing :- Providing and fixing 12mm thick approved make clear float glass panels (not exceeding 1.50 m in length) with polished edges on all sides, fixed using suitable CP Brass /SS 'D' brackets placed not exceeding 450mm c/c on horizontal surface of partition and at both ends on vertical posts to				
(vi)	Providing finished section size 70/75 x 8mm thick seasoned second class Teak wood moulding to all exposed edges of partition including applying 2 or more coats of melamine polish / Duco paint including necessary preparatory work for surface preparation with putty, priming coat, sealer coat etc. complete as per sample approved by the Bank.				
(vii)	Making necessary cutouts for electrical conduits / cables & switchboard etc., including providing additional supports wherever required complete as per drawings and as directed by Engineer.				
(viii)	The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
9	<b>P/F FULL HEIGHT SOLID WOODEN PARTITION WITH BOTH SIDE LAMINATE</b>	44.00	SQMT		
	Providing & fixing in position full height solid/opaque wooden partitions finished with laminate on both sides comprising as under:-				
(i)	Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm (may slightly vary as per unavoidable site conditions) both ways (horizontal and vertical) fixed rigidly on floor, wall / column & ceiling.				
(ii)	Plywood skin:- Providing & fixing 8 mm thick HDMR/HDWR board on both sides of the framework.				
(iii)	Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approve quality adhesive complete.				
(iv)	Making suitable cutouts/ openings/ channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.				
(v)	Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.				
(vi)	Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.				
(vii)	The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
	Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				
10	<b>Laminated Flush Door for Washroom &amp; Kitchen with TW</b>				
	Providing and fixing waterproof wooden flush doors with 4"x2" Teak wood frame as above & Shutter with 35mm thickness finished with 1mm laminate on both sides, edges of door to have teak wood edging all around & including all fitting & fixtures like Door handle & bolt lock, Al. Tower bolts, door closer door stopper as per specification, including polish and finishing as per drawing and instructions of engineer in charge.	4.00	SQMT		
11	<b>GLASS PARTITIONS AND DOORS</b>				

11.1	<b>FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED GLASS UPTO 7' LEVEL WITH SOLID PARTITION ABOVE 7' LEVEL</b>	8.00	SQMT		
	Providing & fixing full height glazed partition with 12mm Toughened glass of approved make up to 7' level height with solid partition above 7'-0" level up to false ceiling bottom.				
	The glazed panels shall be fixed to the existing floor and false ceiling with all necessary SS brackets (D, C or U type) Vertical joints between the glass panels shall be sealed with suitable transparent sealant.				
	The solid partition above 7'-0" level shall be made with aluminium framework of size 63mm X 38.10mm X 1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 8mm HDMR/ HDWR board finished with 1.0mm thick laminate as per direction.				
	Providing, placing in position & erecting full height partition in desired shape, framework shall be of 50 x 50 x 1.5 mm thick aluminum square section placed at 500 mm c/c both ways or as directed.				
	Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				
11.2	<b>FULLY GLAZED DOOR</b>				
	Providing and fixing position 12 mm fully glazed toughened glass door, single/ double shutter, of approx. size 900/ 1500 x 2100/2400 mm	16.00	SQMT		
	Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed / solid / gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures & hardware.				
	Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank.				
11.3	<b>POLYESTER FILM OVER GLAZED PARTITIONS</b>				
	Providing and fixing in position high impact resistant Polyester Films of approved design & pattern, which once installed on glass, give additional strength to glass, reduce glare & prevent glass from splintering on impact. thickness not less than 4 Mil (100 mic.) or 7 Mil (175 mic.)	19.00	Sq.Mt.		
12	<b>WALL/ COLUMN PANELING WITH LAMINATE FINISH.</b>				
	Providing and fixing in position wooden paneling to column / walls finished with laminate comprising as under:-	230.00	SQMT		
(i)	Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall/ columns in perfect line, level				
(ii)	Panel Finishing:- Providing & fixing 11 mm thick approved make HDMR/ HDWR/HDHMR board and additional 5.5mm HDMR/HDWR/HDHMR in layers to create grooves as per the design to Aluminum framework finished with 1.00 mm thick approved quality and shade laminate, using approved adhesive, in approved pattern & design, including providing grooves, decorative moldings etc. as per Architectural drawings and as directed at site by the Engineer-in-charge.				
(iii)	Providing approved quality, seasoned, full length, Teak Wood moulding 15 mm thick with adequate width as required at site, to all openings, cutouts etc duly polished with melamine polish complete as directed by the Engineer-in-				
(iv)	The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site.				

(v)	Applying 2 or more coats of melamine polish to exposed edges of paneling, moulded beadings etc. including preparation of surface, sealer coats etc. complete including wastage of material, if any, scaffolding for execution of work at all heights and locations etc. complete.				
	Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				
13	<b>PANELLING WITH CHARCOAL FLUTING PANELS FROM EUROPRATEEK OR VENTURA MAKE</b>				
	Wall paneling made from framework of 25 x 25 x 1.20 mm thick hollow aluminum sections spaced 600mm c/c, over which Charcoal fluted wooden panel of 10mm +/-2mm shall be fixed as per the design in the drawing or as	63.00	SQMT		
(i)	Framework:- Made out of 25 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect				
(ii)	Panel Finishing:- Providing & fixing 10mm +/- 2mm thick approved finished Wooden Panelling fixed on the aluminum sections with tongue and groove joints in line and level.				
(iii)	The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site.				
14	<b>BACK PAINTED GLASS + LOGO</b>				
14.1	Back painted glass (Lacquer Glass) paneling: Providing and fixing in position wooden paneling to column / walls finished with Back painted (Lacquer Glass) comprising as under:-	6.50	SQMT		
(i)	Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed upto 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb.				
(ii)	Panel Finishing:- Providing & fixing 9 mm thick approved make BWR plywood to Aluminum framework finished with 8 mm thick approved quality and make back painted Lacquer Glass panels of required size, rigidly fixed using 3M adhesive / double side self-adhesive tape complete as directed by				
(iii)	The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards etc., including providing necessary wooden/aluminum section members support at cutouts, providing scaffolding for execution of work at all heights, complete as per drawings and as directed by the Engineer-in-charge at site.				
14.2	<b>LOGO:-</b> Providing and fixing in position with SS studs or as directed laser cut Logo as per design made from 18 mm MDF board (exterior grade) and finished with spray/enamel paint as directed complete.	1.00	SQMT		
15	<b>P/A WALL PAPERS on wall</b>				
	Providing and laying panelling on wall having 8mm th BWR BOARD Board with Wallpaper approved by Architect / Bank's Engineer (wallpaper basic price of Rs 100.00/Sq.Ft) fixed on wall with Aluminium framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways etc. complete as directed	10.00	SQMT		
16	<b>CUSTOMER WRITING DESK</b>				
	Writing Desk Size 3'-0" x 1'-3" x 0'-6"+3'-0" ht.	1.00	NO		
	Verticle Sides and bottom shall be made out of 36mm (2X18mm thick BWR BOARD Board) and back side 12mm thick BWR BOARD Board with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm th Toughend glass with polished edges making different divisions by 18mm thick BWR BOARD Board with laminate on both side for slips or forms as per detail drawing and instruction complete. (Drawing as enclosed herewith) Laminate to be provided on all visible surface				
17	<b>NOTICE BOARD</b>				
	Size of Notice board shall be 1200x600 & 150 mm deep.	1.00	No		

	Providing and fixing Notice Board with 18mm BWR BOARD Board frame & sides finished with 1.0 mm thk Decorative texture laminate, Box to have 75x35mm teak wood shutters with 6mm clear glass. The back to have 5-6mm thick BWR BOARD Board and 12mm soft Ply covered with cloth of approved shade. The item shall include polishing the wood surfaces etc. complete to the satisfaction of Architect/Bank's Engineer.				
<b>18</b>	<b>PELMET</b>				
	Providing and fixing pelmet made of 18-19 mm thick BWR board, up to 300 mm high and in line with external glazing as per details of Architect. Rate to include finishing exposed surfaces of the Pelmet with 1mm laminate. Edge of Board covered with Edge binding tape.	24.00	R.Mt.		
<b>19</b>	<b>ROLLER BLINDS</b>				
	Providing, fabricating and fixing vertical roller blinds of approved make preferably of "Vista Levelor" with a woven made acrylic coated fabric of 100% polyester of thickness 0.50 – 0.60 mm ( +/- 5% tolerance) with the main properties like resistance to Cracking & Fraying, dust repellence, UV proof and virtually maintenance free along with the Vista accessories of like Head rail , Roller tube Idler, Bottom rail, chain, matching colour installation brackets etc. including all fixtures and fittings of Vista like Rainbow curtain rods with electric resistance welded MS pipe having a corrugated virgin PVC extrusions reinforced to minimize friction, finials and along with standard anchoring arrangements etc. all complete done in workmanlike manner as per the approved design, colour and including necessary scaffolding as directed.	56.00	SQMT		
	<b>FALSE CEILING WORK</b>				
<b>20</b>	<b>P/F GYPSUM BOARD FALSE CEILING</b>				
	Providing and fixing false ceiling at all height including providing and fixing of frame work made galvanized M.S. sections as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval.	237.00	SQMT		
	Fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of Engineer in charge including cost of painting the false ceiling with two coats of acrylic emulsion paint over a cost of putty				
	12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095-(Part I) :2011 (Board with BIS certification marks) to be used.				
<b>21</b>	<b>Laminated Wooden False Ceiling</b>				
	Same as Gypsum false ceiling but instead gypsum boards providing, making, and fixing 8 mm thick. BWR ply, with molding of approved design shall be fixed as per drawing or as directed by Architect, with decorative molding patty. The plywood should be finished with 1 mm thick. Laminate of approved colour (wooden finish) and quality.	3.00	SQMT		
<b>22</b>	<b>MINERAL FIBRE GRID TILE CEILING:</b>				

	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections ( galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc.	120.00	SQMT		
	Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge.				
<b>23</b>	<b>Baffle False Ceiling</b>				
	Providing and fixing of BAFFLE CEILING system which consists of approved colour consisting of Baffle 50mm wide X 100mm Height X 0.6mm thick square edge baffle having a length upto 4 mtr., coil coated (chromatised for maximum bond between metal and paint, enamelled twice under high temperature, visible side with a full primer and finish coat, the inner side with a primer coating and skin coat on a continuous paint line) corrosion resistant minimum alloy for higher strength. The baffle shall be bolted on to a U10 top & bottom cover, which will be fixed on to L-shaped galvanised steel angle. The baffle shall be fixed in a module of 100-150mm as per architects specifications. The L shaped galvanised angle is spaced at a centre to centre distance 1200mm. The L-shaped galvanised angle is suspended by means of suspension angle and anchor fasteners at a centre to centre distance of 1200mm.				
	Baffle ceiling should be of extruded aluminium section of armstrong, unistone, durlum or equivalent. It should be uniformly distributed at a maximum spcaing of 150 mm c/c and finish shall be wood grain finish( red oak or cherry) or any other colour/finish as per architect's instruction and client's requirement.	35.00	SQMT		
	<b>NOTE :-</b>				
	For False ceiling Items the false ceiling design can be curved/architectural design, steps, cove etc. However only Board surface area shall be measured for the purpose of payment. Nothing extra for design or curve or steps upto 150-200 MM except cove measured in R.MT and paid in item				
	Existing floor to slab height on the site shall vary. Ceiling shall be hung from the existing slab through hanger's. Rate quoted in the tender shall be applicable for all floor levels /all floor height (approx. 4-4.5 Mtr floor to floor) including scaffolding, etc complete.				
	The rate of falseceiling items also includes 6 mm ply backing for supporting light fixtures in the false ceiling.				
	The rate of False ceiling items also includes making all necessary cut outs & frame work for electrical fixtures / air conditioning work coves etc.				
<b>24</b>	<b>PAINTING</b>				
<b>24.1</b>	Providing and painting Synthetic Enamel Paint after removing old paint & preparing the base for the same and applying 2 or more coats of paint complete. complete to the satisfaction of Architect/Bank's Engineer.	20.00	SQMT		
<b>24.2</b>	Providing & painting the walls, ceiling with Plastic Emulsion paint after preparing the base by removing existing paint/ finish and applying 2-3 coats of birla white putty for making the surface plane & smooth & applying 2 or more coats of plastic emulsion paint with final coat done with rollers etc complete. Complete to the satisfaction of Architect/Bank's Engineer.	300.00	SQMT		

24.3	Providing & applying approx. 12mm thick POP punning on wall to give a clean smooth and plumb surface.	15.00	SQMT		
24.4	Providing & applying texture paint (Base price 90-1005/ S.FT) in two or more shades with roller & spray, after preparing the base for the same (Okios, Acro or Equivalent) .	20.00	SQMT		
35	Providing and placing in position planter box of size 450mm wide & 450mm high made of 18mm thick BWR board. Inside finished with 1.0mm thick laminate and outside finished with 3.5mm thick veneer. Exposed edges of board finished with 6mm thick steam bech wood lipping. All wood work and veneer shall be finished with two or more coats of Melamine polish over one coat of sealer. All complete as per approval of Architect /Client	5.00	NO.		
36	P/P <b>perforated Stainless Steel dustbins</b> of thickness 16 SWG & grade 304, of size 250mm dia & 450mm height & weight 3.5kg per piece without lid with perforations of not more than 8mm. (The sample should be got approved by Bank / Architect in advance before placing the order)	45.00	NO.		
38	<b>GLASS SHELF FOR TROPHY:</b> P/F Glass shelves 3 - 4 feet length, 10 mm thk, 9" deep with necessary SS brackets edge polishing, etc complete.	8.00	SQMT		
<b>Total</b>					