|       | BOQ FOR INTERIOR WORK OF<br>SBI, HLC AND AMCC BRANCH,BARPETA , /   | ASSAM. |      |           |             |
|-------|--|--------|------|-----------|-------------|
| SI.No | Description of items   | Unit   | Qnty | Rate(Rs.) | Amount(Rs.) |
| 1     | Supply and installing of size- 2130 mm x 1830 mm x 750 mm including cost of side credenza (1080mm x 600mm x 750 mm) for Chief Manager/ Branch Manager made up of 19mm thick Block board all around, finshed with not less than 1 mm thick laminate of colour, shade & brand as approved. The table cost to include (pedestal), three drawers of 450 mm wide made with 6mm/12mm ply on right hand side on telescopic slider and a keyboard tray 250mm wide, CPU stand, foot rest as per design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/ bidding of required size stained to match the desk and melamine finished. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved brand. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy. | Each   | 2    |           |             |
| 2     | Fabricating and installing <b>Tables</b> of overall size - 1680mm x 1830mm x 750 mm<br>including cost of side credenza (1230mm x 450mm x 750mm) made up of 19mm thick<br>block board of approved brand all around and finished with not less than 1.0 mm thick<br>laminate of brand, colour and shade as approved by the Bank. The table cost to<br>include three drawers of 375 mm wide made with 6mm/12mm ply on right hand side<br>on telescopic slider, a keyboard tray 250mm wide, foot rest & CPU stand. The works to<br>include all hardwares such as: castors, brass hinges, ball catchers, fully extendable<br>drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of<br>single control type. All exposed edges to have wooden lipping/bidding of requierd size,<br>stained to match the desk and melamine finished.Design and detail of the counters<br>shall be as per Bank's new uniform colour, layout & elevation policy. All the surfaces to<br>be in laminate finish & <b>8mm thick glass duly finished to be placed on table</b> and<br>necessary cut-out to accommodate wires, edges to be m/c polished, with m.s. powder<br>coated wire manager complete as per Bank's new uniform colour, layout & elevation<br>policy.<br>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or<br>equivalent.<br>Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.   | Each   | 12   |           |             |
| 3     | Fabricating and installing <b>Grahak Mitra table</b> of overall size - 1520mm x 600mm x 750<br>mm in straight or curved profile made up of 19mm thick block board of approved brand<br>all around and finished with not less than 1.0 mm thick laminate of brand, colour and<br>shade as approved by the Bank. The table cost to include three drawers of 375 mm<br>wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard<br>tray 250mm wide, foot rest & CPU stand. The works to include all hardwares such as:<br>castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks ,<br>handles etc. of Godrej or approved make. Locks to be of single control type.Design and<br>detail of the counters shall be as per Bank's new uniform colour, layout & elevation<br>policy. All exposed edges to have wooden lipping/bidding of requierd size, stained to<br>match the desk and melamine finished. All the surfaces to be in laminate finish & <b>8mm</b><br><b>thick glass duly finished to be placed on table</b> and necessary cut-out to<br>accommodate wires, edges to be m/c polished, with m.s. powder coated wire manager<br>complete as per Bank's new uniform colour, layout & elevation policy.<br>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or<br>equivalent.<br>Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.   | Each   | 1    |           |             |

|   |  |     |     | <br> |
|---|--|-----|-----|------|
| 4 | RUNNING COUNTER 600 MM WIDE: Providing Running Counter 600 mm wide of 19<br>mm thick block board finished with not less than 1 mm thick laminate of colour , shade<br>and brand as approved. Running counter at every 1520 mm interval consist of Drawers<br>of 450 mm wide made with 6mm/12 mm ply on right hand side on telescopic slider and<br>a keyboard tray 250 mm wide CPU stand and footrest as per design and direction of<br>Bank. All design in conformity with Banks New Uniform Layout Scheme.   | RM  | 0   |      |
| 5 | Low ht storage unit: Providing and fixing storage units of size 450 mm x 750 mm, made up of 19 mm thick block board of approved brand on top & vertical support and finished with not less than 1.0 mm thick laminate of approved brand on side and top. The storage units shall have openable/sliding shutters made up of 19mm thick plywood and finished in 1.0 mm thick laminate of approved shade. The storage units shall have intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to have teak wood lipping/bidding of required size, stained to match the desk and melamine finished.Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy. All inner surface to be finished with mat finish enamel paint of approve brancd. The works to include all hardwares such as: castors, brass hinges, ball catchers, locks , handles etc. of Godrej or approved make. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent.   |     | 60  |      |
| 6 | Fabricating and fixing <b>column/wall paneling</b> of BM Chamber with 12 mm thick ply<br>finshied with not less than 1.0 mm thick laminate of approved shade & brand over<br>25mm x 35 mm (thickness not less than 1.5 mm) alluminium section framework of<br>approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical).<br>Panelling framework to be secured to wall surface / column surface<br>Design and detail shall be as per direction of EIC and Bank's new uniform colour,<br>layout & elevation policy.<br>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or<br>equivalent.<br>Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.   | SQM | 60  |      |
| 7 | Fabricating and fixing <b>full height semi glazed partition</b> , made of 6 mm ply of approved brand in both side and to be finished with not less than 1.0 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm ( thickness not less than 1.5 mm) alluminium section framework at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood moulding duly polished.Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy. All exposed edge shall be covered with teakwood lipping/bidding with polishing complete in all respect. Payment will be made for the area upto false ceiling only. <b>Rate shall inclueds etching of glass as requierd by bank</b> . Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent.  | SQM | 130 |      |
| 8 | Fabricating and fixing <b>full height solid partition</b> , made of 6 mm ply of approved brand<br>in both side and to be finished with not less than 1.0 mm thick laminate of approved<br>brand, colour and shade over 50 mm x 50 mm ( thickness not less than 1.5 mm)<br>alluminium section framework at spacing not exceeding 600 mm both ways (horizontal<br>and vertical). Frame should be firmly fixed to the ceiling. Middile portion at 900 mm to<br>2100 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd)<br>fixed with 10 mm thick teak wood moulding duly polished. Design and detail of the<br>counters shall be as per Bank's new uniform colour, layout & elevation policy. All<br>exposed edge shall be covered with teakwood lipping/bidding with polishing complete<br>in all respect. Payment will be made for the area upto false ceiling only. <b>Rate shall<br/>inclueds etching of glass as requierd by bank</b> .<br>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or<br>equivalent.<br>Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent. | SQM | 58  |      |

|    |  |     |     | <br> |
|----|--|-----|-----|------|
| 9  | Providing and fixing <b>low height semi glazed wooden partitions</b> made of 6 mm ply of<br>approved brand in both side and to be finished with not less than 1.0 mm thick<br>laminate of approved brand, colour and shade over 50 mm x 50 mm ( thickness not<br>less than 1.5 mm) alluminium section framework of approved brand at spacing not<br>exceeding 600 mm both ways (horizontal and vertical). Top portion from 900 mm to<br>1500 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd)<br>fixed with 10 mm thick teak wood moulding duly polished as per designe and direction<br>by bank. All exposed edge shall be covered with teakwood lipping with polishing<br>complete in all respect. Rate shall includes making provision for fixing of counter top 12<br>mm glass on its edges with neccessary fixing arrangment as directed. <b>Design and<br/>detail of the counters shall be as per Bank's new uniform colour, layout &amp;<br/>elevation policy. Rate shall includes etching of glass as requierd by bank.</b><br>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or<br>equivalent.<br>Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent. | SQM | 44  |      |
| 10 | Providing and fixing <b>Semi glazed doors shutter</b> made up of 38 mm thick block board<br>of approved brand and quality, finshed both side with not less than 1.0 mm thick<br>laminate of approved brand, colour and shade. Middile portion at 900 mm to 2100 mm<br>height shall have 6 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10<br>mm thick teak wood bidding duly polished N C lacquer as per design and direction by<br>bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250<br>mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic<br>door closer of Godrej or approve make. Design and detail of the counters shall be as<br>per Bank's new uniform colour, layout & elevation policy. All exposed edge shall be<br>covered with teakwood lipping with polishing complete all respect. <b>Rate shall inclueds<br/>etching of glass as requierd by bank</b> .<br>Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or<br>equivalent.<br>Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.  | SQM | 12  |      |
| 11 | Providing and fixing Solid <b>doors shutter</b> made up of 38 mm thick block board of approved brand and quality, finshed both side with not less than 1.0 mm thick laminate of approved brand, colour and shade. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make.Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy. All exposed edge shall be covered with teakwood lipping with polishing complete all respect. <b>Rate shall includes etching of glass as requierd by bank.</b> Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.   | SQM | 10  |      |
| 12 | MAIN GATE : Providing and fixing glazed door made of 12 mm thick float glass with frosted film fixed in between top & bottom rail and side stile of plywood framework of size 125 mm x 50 mm. The framework to be finished with not less than 1.0 mm thick laminate on both side. Glass to have acid etched design pattern with logo as directed. Doors to be mounted on heavy duty floor spring/door closer. Rate shall inclueds all hardwears such as: Two nos S.S. finish handle, lock, door stoper, hinge, tower bolt etc. of approved make.   | SQM | 8   |      |
| 13 | False ceiling : Providing and fixing suspended false ceiling with 600x600 mm size & 12mm thick mineral fiber ceiling tiles of Armstrong dune or approved make. Suspender, frame work as per manufacturer's specifications. The item to include cost of making necessary cut-outs for lights/air-conditioning grills as per design direction by bank.   | SQM | 315 |      |
| 14 | Gypsum board false ceiling : Providing and fixing suspended 12mm thick Gypsum board false ceiling with GI framework of standard gauge and as per the specifications of India Gypsum Co. The rate to include painting with lustre paint and making necessary design,pattern & cut outs for light fittings, cove light etc. complete as per design direction by bank.  |     | 80  |      |

|    | NOTE :The estimated cost is exclusive of statutory taxes (  | GST)on wo | ork contrac | t |  |
|----|---|-----------|-------------|---|--|
|    | Total   |           |             |   |  |
| 16 | Supplying , Providing and fixing Godrej cylindrical night latch lock at cash enclosure doors.   | EACH      | 4           |   |  |
| 15 | Applying and Finishing walls with 2 or more coats of Tractor emulsion paint of approved colour / shade on surfaces after preparation of base with sand paper. POP/ Putty wherever required over a coat of primer of approved brand. Make : Asian Paint , Dulux. | SQM       | 500         |   |  |