



**CIVIL WORK OF SBI NUAGAON
PRICE BID**

S.No	ITEM SPECIFICATION	QTY	UNIT
1	Vitrified Tiles Flooring	-	-
	Providing and laying 600mm x 600mm nano polished double charged vitrified shine tiles of Jonson/ Nitco/ Kajaria/RAK or equivalent make with water absorption less than 0.08% and confirming to IS: 15622 of approved make, in all colours and shades, laid on 20 mm thk. cement mortar 1;4 (1 Cement : 4 Coarse Sand), including grouting the joints with white cement and matching pigment etc. all complete, including cost of all materials, labour, T&P etc. required for the work.	175	Sqm
2	Painting Works		
A	Internal Wall Painting		
	Providing and applying two or more coats of Acrylic Emulsion paint to internal walls, columns, beams ceiling etc. Over a coat of primer as per manufacturer's specification including all labour and materials complete in all floors of approved make and shade.	700	SQM
B	Wall Putty on Internal Surfaces Only		
	Providing 2.0 mm thick of Birla white wall care putty (Water resistant white cement based putty for concrete mortar walls and ceiling) after removing all loosely adhering material from the wall surface of 1 mm thickness.	400	Sqm
C	Providing and applying two or more coats enamel paint to door and windows, MS works of approved shade and make	100	Sqm
3	Half Brick work using locally available good quality bricks for partition walls with cement mortar of 1:3 (cement: Coarse sand). At every 1m, two nos 6mm bars shall be laid. Rate shall include lifting of materials, curing etc complete	50	Sqm
4	Finishing the wall surface with 12 to 15mm thickness plaster in proportion 1:4 (cement: coarse sand) to make the surface truly line and level including scaffolding, curing etc complete. At any level and height)	100	Sqm
5	Providing and fixing 30mm thickness flush door of Sylvan/ Century finished with teak wood lipping on all edges , three hinges for each door, one door stopper, one door closer of godrej make, one mortise lock of godrej make per door etc complete. The both surface shall be finished with 1mm thick laminate of approved shade.	15	Sqm
6	Providing and fixing in position factory made precast RCC M-40 fixing with hold fast embedded in 1:3:6 concrete block for door frame(Size 125 mmx 60 mm) having excellent smooth finish as per IS: 6523 with reinforcement of 3 Nos, 6 mm dia main bars tied with 3 mm M.S stirrups placed @ 200 mm C/C and 6 numbers high strength polymer blocks of required size for fixing hinges including providing 6 no specially designed M.S. galvanised sleeves for accomodating 6 mm dia fully threaded bolts for fixing hold fast on vertical members, providing suitable arrangement for relieving sliding door bolts and tower bolt etc all complete, as per the direction of Engineer in charge. The frame shall be measured in running metre correct to two places of decimal	30	Meter

7	<p>Providing and fixing in position factory made precast RCC M-40 fixing with hold fast embedded in 1:3:6 concrete block for doors of Size frames having excellent smooth finish as per IS: 6523 with reinforcement of 3 Nos, 6 mm dia main bars tied with 3 mm M.S stirrups placed @ 200 mm C/C and 6 numbers high strength polymer blocks of required size for fixing hinges including providing 6 no specially designed M.S. galvanised sleeves for accomodating 6 mm dia fully threaded bolts for fixing hold fast on vertical members, providing suitable arrangement for recieving sliding door bolts and tower bolt etc all complete, as per the direction of Engineer in charge. The frame shall be measured in running metre correct to two places of decimal.</p>	1	Cum
8	Providing and fixing MS I Section for lintel	100	KG