



SBI INFRA MANagementsOLUTIONS PVT. LTD.
(SBIIMS)
(A Wholly Owned Subsidiary of SBI)

Circle Office:4th Floor ,SBI, Local Head Office, III/1,Pt.J N Marg,
Kharvelnagar,
Bhubaneswar-751001

Tender for Interior Furnishing works of
SBI RAJGANGPUR
(Price Bid)

Tender ID: BHU201909009
Date: 16.10.2019

Name of the Tenderer.....

Address:.....

.....

GSTIN:.....

(Eligible for doing business at Orissa)

**SBI RAJGANGPUR
INTERIOR FURNISHING WORK (BILL OF QUANTITIES)**

SI No	Item Description	Qty	Unit
1	<p>Single Window Counter (1500x900x750 mm) without Side Credenza : Providing and fixing in position 750 mm high single widnow counter without side credenza. Side Credenza shall be paid in separate item where ever required. SWC shall consist of:</p> <p>a) 19mm thick block board for Top (1500 x 900 mm), Front (1500x750 mm), Two sides and one middle member (each 900x750 mm)</p> <p>b) 400 mm wide Drawer unit having 3 drawers of equal sizes made of 12 mm thick BWP grade ply of approved make with Godrej autolocking push type locks and "C" type SS finish handles.</p> <p>c) Ebco/Godrej make telescopic sliding key board tray.</p> <p>d) All exposed surfaces shall be cladded with 1 mm thick high gloss laminate of approved make and shade except edges, which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge.</p> <p>e) All un-exposed surfaces shall be cladded with 0.8 mm thick s laminate of approved make and shade.</p> <p>f) Provisions to be made avilable for Corian solid surface work as per the design / direction of Engineer-in-Charge</p>	3	Each
2	<p>Heavy Cash Counter (1800x900x750 mm) without Side Credenza : Providing and fixing in position 750 mm high single widnow counter without side credenza. Side Credenza shall be paid in separate item where ever required. SWC shall consist of: a) 19mm thick block board for Top (1500 x 900 mm), Front (1500x750 mm), Two sides and one middle member (each 900x750 mm) b) 400 mm wide Drawer unit having 3 drawers of equal sizes made of 12 mm thick BWP grade ply of approved make with Godrej autolocking push type locks and "C" type SS finish handles. c) Ebco/Godrej make telescopic sliding key board tray. d) All exposed surfaces shall be cladded with 1 mm thick high gloss laminate of approved make and shade except edges, which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge. e) All un-exposed surfaces shall be cladded with 0.8 mm thick s laminate of approved make and shade. f) Provisions to be made avilable for Corian solid surface work as per the design / direction of Engineer-in-Charge</p>	2	Each
2	<p>Work station for CM (1800x750x750) without Side Credenza Providing and fixing work station for Branch Manager with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cupboard in place of three drwawers as mentioned in item 1(b). The drawer should be provided with auto locking Godrej key system.</p>	1	Each
3	<p>Work station for Dy. BM, Accountant & Back Office (1500x750x750) without Side Credenza work station for officer with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cupboard in place of three drwawers as mentioned in item 1(b). The drawer should be provided with auto locking Godrej key system.</p>	4	Each

3	Work station (1350x750x750) without Side Credenza work station for officer with same specification as item no. 1 above (Single Window Counter) but having only one drawer and one cupboard in place of three drawers as mentioned in item 1(b). The drawer should be provided with auto locking Godrej key system.	5	Each
4	Providing and fixing in position Side Credenza made of 19mm thick block board (Top: 900 mm x 450 mm) having 1 drawer unit (450 W x 150 H mm) at the top made of 12 mm thick BWP grade ply of approved make complete with Godrej multipurpose drawer locks and "C" type SS finish handles and one cupboard (450 W x 500 H mm) at bottom with telescopic sliding drawers as above with auto closing hinges for the shutters of the cupboards. The unit shall be complete with SS finish "C" type handles with locking arrangement. All exposed surfaces shall be cladded with 1 mm thick laminates of approved make and shade except edges and table top. Edges which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge and Table Top is to be provided with 6mm thick corian solid surface. All un-exposed surfaces shall be cladded with 0.8 mm thick laminate of approved make and shade complete in all respect as per the drawing and direction of Engineer-in-charge.	15	Each
5	Providing and fixing in position 12 mm thick clear float glass of Modi float / Indo asahi / Saint Gobin over Single Window Counter top up to 1200 / 1350 mm height in arch profile with wooden vertical supports with required etching of SBI emblem & border on the glass as directed and with machine polish finish edges and with teak wood beading and required hard ware fittings / bracket etc to complete the work in all respect. All glasses should be clean, beveled edges and machine cut and machine moulded with provision of half round opening in bottom middle portion of glass. No extra payment will be made on this account. Allowable tolerance for glass thickness is + 0.3 mm. The glass shall be clear float glass and should be approved by the Engineer in Charge. It shall be clear, float transparent and free from cracks, flaws, Bubbles or Vision defects. The float glass shall conform to the IS 14900.	10	Sqm
6	Supplying, fitting and fixing low height partly glazed double skin partition for specified enclosure, made out of 25 mmX 50 mm locally available Aluminium Metal Studs, in combination of 6mm BWP ply + 1mm matt/ mirror finish laminates on both sides and 8 mm glass with necessary beading as per the design and instruction of E-I-C, The bottom member shall be fixed to the R.C.C. floor with wedge bolt and rawl plugs at suitable intervals. All the wooden sections to be treated with anti fungal and anti termite chemical treatment before being used. The visible portion of the framework shall be French polish. The glass shall be fixed with required beading as per approved design and direction of Engineer-in-charge. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc. for complete work. The glass portion of the partition should be provided with deep etching as directed by the Engineer in charge.	20	Sqm

7	<p>Supplying, fitting and fixing full height partly glazed double skin partition for specified enclosure, made out of 50mm x 50mm size kiln seasoned Kasi/ Badam/ Tendra/ Gamhari /Giringa wood frame at 600 x 600mm c/c bothways. The bottom portion i.e. upto 1200mm 6mm BWP ply + 1mm matt finish laminates on both sides, from 1200mm up to 2100mm height 5.5 mm glass with necessary beading, from 2100 upto ceiling level & above same as per bottom portion. The vertical members shall go beyond the false ceiling level and fixed to the soffit of R.C.C. slab/beam along with one extra top member. The bottom member and top member shall be fixed to the R.C.C. floor/roof slab with wedge bolt and rawl plugs at suitable intervals. All the wooden sections to be treated with anti fungal and anti termite chemical treatment before being used. The visible portion of the framework shall be French polish. The glass shall be fixed with required beading as per approved design and direction of Engineer-in-charge. All materials are to be of approved make, shade and quality. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc. for complete work. The measurement shall be done upto false ceiling level and no extra payment shall be made for framework or for the ply or laminate above the ceiling level. The glass portion of the partition should be provided with deep etching as directed by the Engineer in charge.</p>	20	Sqm
8	<p>Providing and fixing partly glazed flush door matching with glazed wooden partition made out of 50mm x 150mm IInd class hard wood bottom & top rail, 50mm x 100mm styles, 50mm x 200mm lock rail with 1mm laminate cladding, all hardware of SS finish, hydraulic door closure, door stopper, 5.5 mm etched glass along with concealed locking arrangements. All materials to be of approved make, shade and quality. All fixing, fitting works to be done to the satisfaction of Architect/ Bank's Engineer. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc.</p>	5	Sqm
9	<p>Providing and fixing 750 mm high and depth of 450 storage cabinet having minimum 2 filing cabinets etc. made out of 19 mm thk. BWP block board. All exposed surfaces shall be cladded with 1 mm thick high gloss laminates of approved make and shade except edges and table top. Edges which shall be covered with teakwood round and halfround polished beading as directed by the Engineer-in-charge and Cabinet Top is to be provided with 6mm thick corian solid surface. All un-exposed surfaces shall be cladded with 0.8 mm thick laminate of approved make and shade storage cabinet should be complete in all respect as per the drawing and direction of Engineer-in-charge including all hardware and locking arrangements. The rate shall include cost of all materials, labour, taxes, T&P, transportation, royalties etc.</p>	20	Sqm
15	<p>Providing and fixing 12 mm thick frameless toughened glass door shutter of approved brand and manufacture, including providing and fixing top & bottom pivot & double action hydraulic floor spring type fixing arrangement and making necessary holes etc. for fixing required door fittings, all complete as per direction of Engineer-incharge (Door handle, lock and stopper etc.to be paid separately</p>	5.00	Sqm
16	<p>Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm long with SS screws etc .complete as per direction of Engineer-in-Charg : Powder coated minimum thickness 50 micron aluminium tubular handle bar</p>	2.00	Each

17	Providing and fixing double action hydraulic floor spring of approved brand and manufacture conforming to IS : 6315, having brand logo embossed on the body / plate with double spring mechanism and door weight upto 125 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover plates with brass pivot and single piece M.S. sheet outer box with slide plate etc. complete as per the direction of Engineer-in-charge : With brass cover plate minimum 1.25 mm thickness	2.00	Each
----	---	------	------