



NIT No.	BHO201904019
DATE	22.04.2019

SBI INFRA MANAGEMENT SOLUTIONS PVT. LTD., CIRCLE OFFICE, BHOPAL

**INVITES TENDERS ON BEHALF OF SBI, A.O., INDORE
THROUGH E-TENDERING PROCESS.**

For the work of :

PROPOSED WOODEN FLOORING & ALLIED WORKS TO BADMINTON COURT CUM AUDITORIUM AT 1ST FLOOR OF STATE BANK INSTITUTE OF HRD, PLOT NO. 8 – 9, SECTOR ‘A’ SLICE NO. 06, SCHEME NO. 78, ARANYA, VIJAY NAGAR, INDORE – 452010 (M.P.)

(Interior Contractors who are on the panel of SBI, A.O., Indore in Category Interior & Furnishing Works (IAM)- Above Rs. 5 lacs upto Rs. 10 lacs and with SBI, Bhopal LHO in Category IF – work value work value up to Rs. 10 lacs (Network 1); are only eligible).

Note : Contractor should possess valid Digital Signature for this E-Tender.

PART ‘B’ : PRICE BID

Last date for submission of **E- Tender** : 1500 hrs. (IST) on 22.04.2019.

Opening of **E –Tenders** : 1530 hrs. (IST) on 06.05.2019.

Tender Submitted By :

Name of Vendor : _____

Address of Vendor : _____

GST No. of Vendor : _____

Date : _____

Vice President & Circle Head,
SBI INFRA MANAGEMENT SOLUTIONS PVT. LTD.
(A Wholly Owned Subsidiary of State Bank of India)
 Circle Office,
 Mezzanine Floor, SBI LHO Building,
 Arera Hills, Hoshangabad Road,
 BHOPAL - 462011 (M.P.)

Proposed Wooden Flooring & Allied Works to Badminton Court cum Auditorium at 1st Floor of State Bank Institute of HRD, Plot No. 8 – 9, Sector 'A' Slice No. 06, Scheme No. 78, Aranya, Vijay Nagar, INDORE – 452010 (M.P.)					
				(In INR)	
S.No.	Description of Item	Unit	Qty	Rate	Amt
1	Note : i) The rate to be inclusive of all taxes, octroi, levies, etc. except GST. ii) The rate to be inclusive of all leads, lifts, etc. iii) The debris, unused material, etc. has to be disposed off as per Municipal norms, outside the SBIHRD premises. iv) The SBIHRD is a training centre, hence to avoid disturbance to classrooms, working hours may be restricted as follows : a) Monday to Friday : 6 am to 10 am & 6 pm to 11 pm; b) full day on Saturdays & Sundays. v) The contractor has to submit Labo Sports Test Certificate & EN 14904 Certificate for the said flooring. vi) Defect Liability Period is 1 Year.				
2	Badminton Court Flooring :	Sqm	220.00		
	Supply, installation & finishing of Imported Hard Teak Wood Sports Flooring of Apex, Asian, Sundek or equivalent make for Badminton Court as specified herewith :				
	Moisture Barrier : The existing floor to be treated with moisture barrier (plastic Sheet) to be laid/placed on the existing floor before laying the base frame. The runners with air cushion pads to be placed on the vapour barrier in perfect level at 325 - 400 mm in single direction.				
	Base Frame : To be made of seasoned pine wood runners of approx. size 70 mm x 45 mm, treated with anti termite solution and fixed to the bottom side with 19 mm thick EPDM air cushioned pads, stapled through the two wings at 350 mm x 350 mm.				
	Surface Board : The top surface of the court to be made up of 1st class hard teak wood as Maple wood floor, approx. 21 mm thick, 65 to 85 mm wide and in random length in tongue & groove shape. The edges of the boards will have a finger lock groove and the bottom side with air pass groove and treated with special anti termite and water resistant lacquer. The surface board, to be screwed to the runner through the tongue only and will lock the screwed tongue by the grooves of the adjoining board. The ends of the boards will be locked by inserting the wooden fingers through the edge grooves and fixed with suitable adhesives. Expansion gap between wall & board as per manufacturer specification.				
	Finishing : After installation, the floor is to be machine sanded in uniform line & level with Bona machine. To be finished with Bona Sportive Coatings or equivalent and the finish to be high resistance to wear and meets DIN standards for slip resistance (P.U. polishing, polyurethane lacquer). Line marking for court to be carried out in required colours before applying finish coat.				
	Measurement of Area : Finished top surface.				
3	Line Marking of the Badminton Court :	LS	1.00		

	Colour of lines: The lines shall be easily distinguishable, preferably white or yellow.				
	Line Width: 40mm.				
	External dimensions of court (13.40m x 6.10m) includes width of lines, other dimensions are measurements between lines.				
4	Provision of Indoor Net Posts :	Pair	1.00		
	STAG PORTABLE BADMINTON POLE : Providing & installing 'wheel-away' model of the net post. The net posts are to be of metallic uprights, T - shaped, (each stag weighing minimum 40 kgs.), with rubber floor pads for the protection of the floor. The posts to have net hooks, cleats and grooved tops for the fixing of the net are attached to the post. Also, they should come equipped with in-built weights so that the whole arrangement remains stable during play. The post shall be 1.55m in height from the surface of the court and shall remain vertical when the net is strained. Measurement : Per Pair of Posts.				
5	Provision of Net :	No.	1.00		
	Net to be of nylon with tapes on all four sides, of Cosco or equivalent make, approx. 6 m in length, in colour as directed by the Bank/SBIIMS. The net shall be made of fine cord of dark color and even thickness. If necessary, the full depth of the net should be tied at the ends.				
6	Removing & refixing of doors	No.	3.00		
	Removing & refixing of existing entrance door shutters of the entrances to the hall to suit the new flooring height, in workmanship like manner, by cutting, planing, finishing and polishing/painting them keeping the durability of the door. Refixing the doors to original door frame. The rates to be inclusive of all hardware's required as screws, hinges, refixing of hardware to suit new height of the door, labour, polish/paint, etc. complete. Measurement : Per entrance door opening comprising of pair of door shutters, to be counted as one unit.				
7	Total ₹ (Exclusive of GST)				
8	(Rupees plus GST extra as applicable)				only

Date :

Signature & Stamp of Contractor