

BOQ AND SPECIFICATIONS FOR PROPOSED CIVIL WORKS OF STORM WATER DRAINAGE SYSTEM AT SBI OFFICER'S COLONY, CHAR IMLI, BHOPAL					
S No	Description of Item	UoM	Qty	Rate	Amount
1	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material at all leads and lifts in nearest Municipal Dumping Zone as per direction of Engineer-in-charge.	Cum	23.00		
2	Demolishing stone masonry manually/ by mechanical means including stacking the same and to be used in reconstruction of stone masonry as per direction of Engineer - in- charge.	Cum	30.00		
3	Random rubble masonry with hard stone in superstructure and above plinth level including levelling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size). Stone shall be supplied by this department.	Cum	30.00		
4	Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including dressing of sides and ramming of bottom disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to be levelled and neatly dressed. (No extra lift is payable if work is done by mechanical means). All kinds of soil.	Cum	270.00		
5	Providing and laying in position cement concrete of specified grade including the cost of centering and shuttering with 20mm nominal size graded stone aggregate. Nominal Mix -1 Cement : 3 sand : 6 graded stone aggregate.	Cum	50.00		
6	Providing and laying in position cement concrete of specified grade including the cost of centering and shuttering with 20mm nominal size graded stone aggregate. Nominal Mix -1 Cement : 1.5 sand : 3 graded stone aggregate.	Cum	85.00		
7	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding including cost of binding wire up to floor two level including all wastage etc. complete. Thermo-Mechanically Treated bars(TMT).	MT	3.85		
8	Providing & Fixing of Precast RCC drain cover of size 750x600 x70mm (thickness) with 6 holes, manufactured by using M-30 grade of concrete reinforced with 8mm dia Tor Steel @100mm c/c both ways, manufactured by vibro compaction process using joint less FRP moulds, so as to achieve shuttering finish on five faces @top face will have broom finish etc complete.	Each	214.00		
	Amount in Rs. (excluding GST)*				

*GST shall be paid extra as applicable.

SEAL AND SIGNATURE OF THE FIRM