## TENDER FOR INTERIOR FURNISHING WORKS AT THE NEW PREMISES OF SBI REGIONAL BUSINESS OFFICE AT KOTTARKARA - PRICE BID

				Rate	Amount
-					
1	Low Height Partitions	40.00	Sq M		
	Providing and fixing in position of low height partitions of the height 1200 mm as per shape shown in the drawing.ie. (750mm solid partition and glass above)				
	Aluminium sections of size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure ,vertically at about 60 cm centers and 3 Nos Horizontally of the same size of frame at floor level, 750 mm and at 1200 mm level. same size at 370 mm level, fixed in position. 8 mm Plywood on both sides of framework finished with 1 mm laminate of approved color and shade with grooves on both sides., 8 mm Plywood of approved quality finished with 1mm Laminate with grooves on both sides of approved color and shade. Top of the partition finished with laminate and 12mm thick glass with etching is fixed over the partition with Dorma make (or) Equivalent make 'D' bracket of SS finish of 12mm thick. Alround the partition 75mm thick Dark color laminate is provided as show in the drawing and pattern.				

2	MODULAR PARTITION (120cm(H)) - 65 to 75 mm thick powder coated 1.2mm thick CRCA partitions (Manufactured by Godrej/Metafab/Featherlite/Methodex/any approved makes) with pre punchered cutouts to run electric & networking cables. Dual race ways with punch out to fix electrical & data modules for power & data modules for power & data at just below table and skirting level.Partitions are covered with 9mm tiles both sides prelaminated particle board/Fabric cladded Board/glass/soft board as required by using sliding panel method. Level adjusters and all the visible edges of partitions are covered with 2 mm thick powder coated aluminium trims & pvc joinery.	135.00	Sq M	
3	Full Height Partly Solid & Partly Glazed	50.00	Sq M	
3	Partition/non glazed partition:	30.00	Sq IVI	
	Providing and fixing in position of double skin partition, partly paneled and partly			
	glazed as per details shown in the drawing.			
	Frame Work Detail: Aluminium sections of			
	size 63.5 X 38.1X1.2 mm thk. of INDAL/JINDAL as internal frame structure			
	,vertically at about 60 cm centers and 3 Nos			
	Horizontally of the same size of frame at floor level, 750 mm and at 1200 mm level.			
	same size at 370 mm level, fixed in			
	positionHarwood section of thickness 50 X 50 mm, vertically at about 60 cm centers			
	varied along columns, wall ends, junctions			
	of walls, as necessary. Horizontally of the			
	same size of frame at floor level, 900 mm,2100 mm, and roof level. 50 X 25 mm at			
	450 mm level.			
	Lining Work: 8 mm plywood of approved make on both sides of framework from floor			
	level to 900 mm level and 2100 mm level to			
	6" above false ceiling level finished with 1 mm laminate of approved color and shade.			
	Between 900 mm and 2100 mm level, 8 mm			
	thick clear float glass with etching fixed with			
	necessary Dorma (or) equivalent make 'D' bracket of SS finish of 12mm thick. The			
	glass opening 'jamb' portion finished with			
	laminate.			

	Measurement for the partition area shall be considered from the floor level to false ceiling level only.			
4	Fully glazed Door	8.00	Sq M	
	Providing and fixing frameless fully glazed 12mm thk <b>toughened</b> float glass fixed with necessary patch fittings (Dorma make) including cutting, making holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits, jams including necessary fixtures, screws, sealant wherever required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking systems, 1 pair of 600mm long S. S. (H Shape) Handles of approved make, floor springs, and any necessary hardware items.(DORMA MAKE Top Pivot - <b>PT</b> 24, Top Patch Fittings - <b>PT</b> 20, Bottom Patch fittings - <b>PT</b> 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 32mm dia X 600mm length)			
5	Fully Glazed - Fixed Glass Partition -	27.00	Sq M	
	Patch Fitting		•	
	Providing and fixing of fixed glass partitions with 12mm thick toughened glass using PT Standard fittings like PT 90/PT 92 of Dorma make at the top and bottom including cutting, making holes in glass and fixing the fittings in floors, ceilings etc and making the same good with necessary screws, 3M Vinyl sticker as per approved, colour, design and pattern, sealants etc.complete.			
6	Partly Glazed And Partly Paneled Doors.	11.00	Sq M	

	II class T.W. frame of size 75 X 50 mm as per the shape and size given in the drawing.			
	35 mm thick (finished) flush shutter finished with 1mm laminate on both sides with			
	necessary grooves.8mm thick clear float glass of size 250 X 1400 mm fixed with			
	necessary steam beach beading and			
	etching. DORMA Make or equivalent make hardware fittings like locking			
	arragements,20 mm dia and 300 mm high SS brush steel finish handles, door closer,			
	hinges, tower bolts,etc,. Fixed to the shutters.			
7	FALSE CEILING:			
1	NOTE:The false ceiling area will be			
	measured in flat area only.			
7 (a)	Gypsum Board False Ceiling	500.00	Sq M	
	Providing and fixing of M/F suspended false ceiling as the detail given in the drawings. With G.I frame work and 12.5 mm tapered gypsum board panels to form grids of 45.7 X 122 cm as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprising			
	Frame work of intermediate channels (M.F.T) at 122 cm centers along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A) along walls alround perimeter side of the ceiling. The intermediate channels suspened from ceiling, through starp hangers 25 X 0.5 mm (MF 8) at 122 cm centers connected to soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional perimeter channels (MF 6A) for light fittings, Air conditioners Ducts, vertical drops, offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws to from grids with 2 coats of plastic emulsion paint of approved color and one coat of putty over a coat primer etc, complete.			

<b>Grid Ceiling -</b> with fissured mineral fits board tile 600X600X12mm thk (armstrong approved eqv.)secured with universal cli over suspended grid system with hot dipp precoated GI angle sections 24X24X0.9m size on walls/partitions,'T' section 24x38X0.7mm size 3600mm length in o	or ips ped pen
direction and cross 'T' section 600mm lo fixed into slots in the main 'T' to fo 600x600mm grid. Necessary cutouts lighting fixtures, air-conditioning grills to provided.	for
8 Tables	
The table top is 25mm thick post form prelaminated particle board havi underside covered with laminate, and oth exposed faces are made of 19 mm the marine plywood(IS 303 grade) finished we 1mm thick laminate. Ready made Keyboat tray made out of powder coated MS she exposed edges lipped with PVC edge ba 0.5mm thick mounted under the workt with telescopic sliding channelsEbco other approved is to be provided. A foot rewith country wood of 7.5x2.5cm also to provided. 12mm thick glass to be provided for table top and the edges of the glass be polished. The inner portion is finish with laminate finish. Drawers are made 12mm thick marine plywood and exposs faces are finished with 1 mm laminate a inner sides with enamel paint finish shown in the drawing. Necessary fittin such as telescopic steel slides, godrej lochandles etc. of approved make are to provided. One Drawer set contains the number of drawers (with 13-15cm indepth) are to be provided. One calmanager is to be provided as shown in the drawing. Supplying and installing CFTrolleys made out of powder coated 1.6 m thick MS sheet with adjustable width, from back open & provided with lockable casted. Ebco or other approved Necessary beedings and grooves in laminate to provided. Edges of plywood finished we PVC edge banding /teakwood lipping.	ing ner ick with ard eet and top or est be led to need of sed and as ngs ck, be ree ner ble the PU nm t & ors ary be

i	Table of size 200x90x75cm	1.00	Nos	
ii	Table of size 150x75x75cm	7.00	Nos	
9	Tables 150cm(L)X150 cm(L)X65cm (W) - Supplying and fixing L-shaped table made out of 25mm thick interior grade both side prelaminated particle board with exposed top edges lipped with 2mm thick PVC edgeband applied with hot melt glue and other edges with 0.5mm thick PVC edge band all round panel and gromet is provided for wire management. Modesty panel, hardwares like minifix powder coated clipboard screws PVC right angle block, level adjusters etc Footrest are made of 18mm prelaminate particle board with 0.5mm thick PVC edge band knok down type bottom bush etc.30cm wide and 15cm height at one and the other end is zero 50cm length fixed on the bottom side of the table etc. complete.	36.00	Nos	
9(a)	DRAWER UNIT - Supplying and fixing drawer unit made out of 19mm thick marine plywood edgebanded with 1mm laminate. 4 drawer pullouts mounted on sliders, with exposed edges lipped with PVC edge band 0.5mm thick central locking system for drawer pullouts (Ebco/equivalent), with bottom bush with necessary shutters to be provided.	36.00	Nos	
9(b)	KEYBOARD TRAYS - Supplying and installing keyboard tray made out of powder coated MS sheet exposed edges lipped with PVC edge band 0.5mm thick mounted under the worktop with lelescopic sliding channels. Ebco or other approved	36.00	Nos	
9( c)	CPU TROLLEYS - Supplying and installing CPU trolleys made out of powder coated 1.6mm thick MS sheet with adjustable width, front & back open & provided with lockable castors. Ebco or other approved.	36.00	Nos	
10	Side Tables			
	OINO INDIOS			

i ii	The side table top with 25mm thick postformed prelaminated particle board, and all other exposed faces are made of 19 mm marine plywood finished with 1mm thick laminate, and inside painted with 2 coats of enamel over a coat of putty and multiwood/teakwood beading on all exposed edges. Godrej metal body locks, all fixtures, nylon brushes etc complete,  Side table of size 120x45x75cm  Side table 90x45x75	9.00	Nos Nos	
11	Low Level Storage :	40.00	Sq M	
	Providing and fixing low level storage to detail as shown in the drg. Size about 450mm wide, 750mm high comprising. 18 mm Plywood for top, bottom, rear, sides and One intermediate with necessary TW reeper. The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness flexy laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.  Suitable door shutters with all fittings and fixtures to be provided. Exposed faces of Plywood at top and sides of unit to be finished with 1mm thick laminate of approved color and shade.		-	
	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.			
12	High Level Storages in Record Room :	65.00	Sq M	

	Providing and fixing high level storage to detail as shown in the drg. Size about 450mm wide, and upto ceiling height. 18 mm Plywood for top, bottom, rear, sides, horizontals and One intermediate with necessary TW reeper.The unit top shall be with 25mm thick Plywood Board of approved make with 1mm thickness laminate of approved color and brand with front side half rounded edge and all the edges and all the three sides with 3mm thick band strip.  Suitable door shutters with all fittings and fixtures to be provided. Exposed faces of Plywood at top and sides of unit to be			
	finished with 1mm thick laminate of approved color and shade.			
	All concealed faces of Plywood finished with one coat of wood preservative paint and exposed faces of Steam beach molding / beading polished to the satisfaction of the Bank. The inside faces of unit wax and finished with varnish of approved color and shade.			
12	Column Paneling	52.00	Sq M	
	Providing and fixing cladding around the columns to detail as per drawing comprising 18mm thick Plywood with necessary stiffner on both ways of required nos and finished with 1 mm thick laminate of approved colour and shade.			
13	Wall papaling	25.00	Sa M	
13	Wall paneling  Providing and fixing wall paneling to detail as shown in the drawing with 18mm thick Plywood finished with 1mm thick laminate	25.00	Sq M	
14	Providing and fixing Roller blinds for banks front glass partition Colour and materials selection by the EIC, Rates including material cost and labour charges etc. complete.	40.00	Sq M	
15	Painting - Painting the internal walls with 2 coats of plastic emulsion paint over putty finish and a coat of primer in the banking hall	500.00	Sq M	

16	Officers Chair - Medium back revolving chair with height adjustment facility, 5 legged nylon base 330mm with twin castor wheels, synchronized simple mechanism, TUV-class 4 gas spring:120mm, fully polyurethane fixed arms, seat with best quality mpulded PU foam and upholstery back with best quality black coloured soft foam imported fabrics complete. Back to full back without any gaps in between the seats and back cushions. back to be about 24 inches. To be tested as per BIFMA standards. Durotec, Bosq (Wlx 201)etc.	83	Each	
17	Visitors Chair - Low back non revolving chair with fixed low back, fully polyurethane fixed arms, seat with best quality moulded PU foam and upholstery back with best quality black coloured soft foam imported fabrics complete. Back to full back without any gaps in between the seats and back cushions. back to be about 21 inches and internal lumbar support belt .2.1mm thick, powder coated mild steel frame etc completeTo be tested as per BIFMA standardsDurotec, Bosq (Tqv 301) etc.	20	Each	
18	High Back Chair - High back revolving chair with height adjustment facility, 5 legged nylon base 330mm with twin castor wheels, synchronized simple mechanism, TUV-class 4 gas spring:120mm, fully polyurethane adjustable arms, seat with best quality mpulded PU foam and upholstery back with best quality black coloured soft foam imported fabrics complete. Back to full back without any gaps in between the seats and back cushions. back to be about 24 inches. To be tested as per BIFMA standards. Durotec, Bosq (WIx 101) etc.	2	Each	
40	Osfa Three sectors Oscillos of f			
19	Sofa Three seater - Supplying of sofa having either fabric or synthetic leather upholstery of make indroyal (Arta Make), durotecetc.	2	Each	
				ļ

20	Sofa Single Seater - Supplying of sofa having either fabric or synthetic leather upholstery of make indroyal (Arta make), Durotec etc.	4	Each	
21	Teapoy - Providing a teapoy of oval shape of size 100X75cm with 12mm glass at top with machine cut polished edges with teak wood frame work.Indroyal, Durotec, etc	2	Each	
22	Conference Table - Providing U-shaped Conference table of length 8m and leg width of 0.75m. A central well of width 1m to be provided. The table top is 25mm thick post formed prelaminated particle board having underside covered with laminate, and other exposed faces are made of 19 mm thick marine plywood(IS 303 grade) finished with 1mm thick laminate.	16	RM	
	Ready made Keyboard tray made out of powder coated MS sheet exposed edges lipped with PVC edge band 0.5mm thick mounted under the worktop with telescopic sliding channelsEbco or other approved is to be provided . A foot rest with country wood of 7.5x2.5cm also to be provided.The inner portion is finished with laminate finish . Necessary fittings such as telescopic steel slides, godrej lock , handles etc. of approved make are to be provided. cable managers to be provided at intermediates as shown in the drawing. Necessary beedings and grooves in laminate to be provided .Edges of plywood finished with PVC edge banding /teakwood lipping.			
	TOTAL CST 489/	100/		
	GST 18% GRAND TOTAL	18%		
	ONAID IOIAL			