

ESTIMATE

ADDITIONAL CIVIL WORKS AT FANCY BAZAR EVENING BRANCH

Sl.No	Particulars of Items	Unit	Quantity	Rate	Amount
1	<p>Providing polished ceramic wall tiles of approved quality, size, shape and thickness not less than 8mm on walls and skirtings over cement mortar bed 10 mm thick in prop. 1:3 (1 cement : 3 coarse sand) including cutting where necessary finished with flush pointing with Fix-A-Tile (Choksey / Sika / Pedelite / Rouf) /white cement slurry mixed with approved pigment to match shade of tiles complete at all levels as specified and directed. (Cement plastering to be measured and paid separately). (Coloured pigment should be in conformity with colour of tiles and as approved and directed by the Department). (Walls means both interior and exterior walls).</p> <p>a) Normal range Somany/ Orient/Nitco/Asian Make ii) Of size 200mmx300mm and above</p>	Sq.m	41		
2	<p>Providing VITRIFIED floor tiles of approved quality of specified size, shape and thickness not less than 18mm on floors, skirtings, risers and treads of steps over 15 mm thick base of cement mortar in prop. 1:3 (1 cement : 3 coarse sand) including cutting where necessary finished with flush pointing with Fix-A-Tile (Choksey/Sika/Pedelite/Rouf) / white cement slurry mixed with approved pigment to match shade of tiles, mixed with approved pigment to match the shade of the tiles, complete at all levels as specified and directed. (Coloured pigment should be in conformity with colour of tiles and as approved and directed by the Department)</p> <p>a) Normal range Somany/ Orient/Nitco /Varmora/VITA/ Marbito/ Make i) Of size 400mmx400mm and above</p>	Sq.m	20		
3	<p>1st class brick nogged wall in cement mortar including racking out joints and curing complete as directed in super structure above plinth up to 1st floor level (protruding M.S rod/Tor steel of column to be embedded in cement mortar and will be measured and paid separately)</p> <p>(A) 112mm thick brick wall (a) In cement mortar in proportion 1:4. (1 cement:4 sand)</p>	Sq.m	125		
4	<p>Providing 18mm thick Granite slab on vertical face of pedestal laid over 19mm thick waterproof plyboard for installation of wash basin at different wash room area .The rate shall also includes the supply,fitting and fixing of plyboard of 19mm thickness.The rate shall also includes fixing of 1mm thick laminate of approved make with proper adhesive in the external surface of the plyboard and the internal surface to be painted by enamel paint.</p>	Sq.m	14		

5	15 mm thick Cement plaster in single coat on single or half brick wall for interior plastering up to 1st floor level including arises, internal rounded angles, not exceeding 80mm girth and finished even and smooth including curing complete as directed.	Sqm	250		
	On rough side/fair side				
	a) In cement mortar 1:3				
6	Providing, fitting and fixing anodised aluminium sliding windows and ventilators of standard sections of approved brand without horizontal glazing bars, joints mitred and welded (manufactured to relevant IS specifications) and providing and fixing handles, angle cleat, rubber gasket, roller, bolting device, locking arrangements, screws etc as required complete as specified and directed for all levels.	Sqm	51		
	(a)2 Track sliding window				
	(iv) 5 mm clear glass				
7	Providing wood work in frame (chowkaths) of doors, windows, clerestory windows and other similar works wrought, framed and fixed in position in contact with C.C or brick masonry wall including supplying, fitting and fixing with M.S. hold fast (40mmx3mmx250mm) as per design embeded in cement concrete block in proportion 1:2:4 and with two coats of kiricide oiling to the timber faces in contact with C.C and masonry as directed and specified.	Cum	0.13		
	(b) With 1st class timber (Bonsum/ Sundi)				
8	Providing fitting and fixing 1/3 panelled 2/3 glazed wooden shutters for doors/windows including oxidised iron butt hinges (100mm x75 mm x3.55 mm) with necessary screws including glass panes (other fittings to be measured and paid separately)	Sq.m.	11.76		
	A) With 1st class wood				
	(iii) 30 mm thick.				
9	Repairing work i.e closing of locker room window with R.C.C and blocking of wash room window by using reinforcement and concreting	L/S	1		
10	Supply and Fitting fixing of Table top Wash Basin with necessary fittings complete in all respect of jaquar make or equivalent to be used in Branch Manager Chamber	nos	1		
	Supply and Fitting fixing of Table top Wash Basin with necessary fittings complete in all respect of jaquar make or equivalent.	nos	5		

Rate are exclusive of GST