

## PRICE BID

BILL OF QUANTITIES FOR INTERIOR FURNISHING WORKS AT STATE BANK OF INDIA, ANWAL BRANCH (Hr)					
S.NO.	SPECIFICATIONS	QNTY.	UNITS	RATE	AMOUNT
1	<b>SINGLE LEVEL SWO COUNTERS:</b>				
	Providing and fixing at site SWO counters each upto 5'0" long, 2'-6" high and 3'-0" wide, as per design and drawing. SWO counters to be made of 19 mm thick commercial ply with 1.0 mm thick laminate on outer visible surfaces excluding table curvilinear top (single color on horizontal surface & two colors on vertical surfaces), with 40 mm X 12 mm thick teak wood/MDF beading required all around, as per drawing. Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the counter. The top with Curvilinear profile shall be made out of 19mm thk. commer block board and finished with 6mm thk. flexi ply as base for polyacrylic sheet or approved laminate as/design with provision for LED Light in bottom. Teak wood/MDF lipping will be provided on all the remaining edges of the counter, including bottom touching the floor and the drawers. The counter shall have a keyboard tray of size 600 X 270 with both side laminated board with back support, , of EBCO make fixed on channels, as per manufacturer's instructions / specifications.	8.30	mtr		
	Three drawers with autolock running on both sides mounting Telescopic (channels) of EBCO make, made of 19 mm thick commercial ply with 1 mm thick laminate on front face and drawer locks to be provided on one side of the counter as per layout. The sides of the drawers shall be made of 12 mm thick plywood, bottom of 6 mm thick plywood & front of 19 mm thick commercial ply. Non Visible/Inside surface i.e. inside leg-space of table, inside drawers shall be finsihed with 1mm thk. white/off white laminate. All exposed Teak wood edges / teak wood lipping /MDF beading shall be Spray painted Satin Enamel paint or spirit (natural) polish as required. The drawers shall have partitions for keeping currency notes & the counter should also includes foot rest , Space for CPU as per drawing, complete in all respects. The provision of swaping machine of green channel size 9"x 6" with lid shall be provided at right side of each counter while facing from front.				
2	<b>POLYACRYLIC SURFACE HARD TOP ON SWO COUNTER TOP:</b>				
	Providing and fixing (12mm thick) white polyacrylic stone (non-absorbent, non-porous solid surface composite material, belonging to the solid surface category) as per drawings/design.providing by the Architects complete in all respect including adhesives, buffing and wastage.	8.50	sq.m.		
3	<b>FIXED TOUGHNED GLASS IN PARTITIONS:</b>				

	Providing & Fixing 12mm thk. Toughned Glass Panels with SS glass connectors of 304 Grade, fixed in position, as per interior details/instruction of the Achitect/Engineer in charge.	1.75	sq.m.		
4	<b>12MM THK. TOUGHENED GLASS FOR BANKING/SWO COUNTERS WITH ETCHING -FRONT &amp; SIDES:</b>				
	Providing and fixing 12 mm thick, clear plain toughend glass of fixed in vertical position at counter level & to side partitions as per drawing, the counter top glass fixed on both sides to toughned glass partitions & side partitions fixed to wooden partition with superior quality stainless steel L - shaped clamps / glass holders 2 no. on both sides. A 6" dia. semi circular hole at the bottom for transaction shall be provided. All the edges of the glass shall be grinded polished and left free. Superior quality stainless steel L - shaped clamps / glass holders 2 no. on both sides to holding the front glass partition to S.W. Counter.	5.90	sq.m.		
5	<b>12MM THICK TOUGHNED GLASS DOORS WITH PATCH FITTINGS:</b>				
	Providing & Fixing Openable 12mm thk. Toughned Glass Door,holded with Patch fitting ( i.e. bottom & top patch,L-Patch, floor machine & Door lock) of (Dorma/Ozone)make,fixed in position as per manufacturers guidelines. The Job also includes providing & fixing of 24" long SS handle & provisions of holes/cuts in glass panel to facilitate fixing of Patch fitting & Handle. The job shall be complete in all respects,including necessary hardware, complete in all respects as per the instruction of the Architect / Engineer in charge.	9.70	sq.m.		
6	<b>FIRE RESISITANT DOOR (UPS ROOM)</b>				
	Providing & fixing Fire resistant door (GMC, Baddi/ Kutty, Paonta), including door frame 100x50x1.2mm GPST steel/ 16SWG GI sheet, duly powder coated, with hold fasts to be embedded in brick wall in cement concrete 1:2:4. Door shutter will be 46mm thick, made of powder coated 0.8mm thick GPST sheet, fire rating of 120 minutes, as per IS 3614 (Part 2). Fire rated wired glass of 300x200 mm size to be provided. Rates include all necessary hardware like pull handle, steel hinges, dead lock, hilty fasteners, complete in all respect.	1.00	no.		
7	<b>WOODEN PARTITION WITH LAMINATE (LOW HEIGHT):</b>				
	Providing & fixing partition made of 44 mm X 44 mm X 16 Gauge aluminium extruded sections frame @ 2'-0" to 2'-0" c/c vertically & horizontally. The frame shall be fixed rigidly at floor level as well as ceiling with rawl plugs. The frame work to be cladded with 8mm thick commercial ply and 1.0mm thick laminate APPROVED make in specified pattern as per interiors details on both sides. Also 3"x5/8" teak wood section shall be provided on the exposed edges of the partitions, including provideing grove	10.50	sq.m.		

	for 12mm thick glass wherever specified. The rate shall also include for providing grooves in laminate & wood.				
	Note: (i) All ply to be sprayed with anti termite and anti borer spray. (ii) Rates to include all necessary supports and as per details (iii) Measurements to be recorded up to finished false ceiling level.				
8	<b>PARTY GLAZED WOODEN PARTITION &amp; DOORS (FULL HEIGHT):</b>				
	Full Height partly Glazed (with etching) & partly both side laminated Partitions: Providing & fixing partition made of 44 mm X 44 mm X 16 Gauge aluminium extruded sections frame @ 2'-0" to 2'-0" c/c vertically & horizontally. The frame shall be fixed rigidly at floor level as well as ceiling with rawl plugs.	16.50	sq.m.		
	The frame work to be cladded with 8mm thick commercial ply and 1.0mm thick laminate APPROVED make in specified pattern as per interiors details on both sides. Also 1-1/2" x5/8" teak wood beading shall be provided on both sides of 8mm thk. glass with etching work as per interior details where ever specified. The rate shall also include for providing grooves in laminate & wood.				
	Note: (i) All ply to be sprayed with anti termite and anti borer spray. (ii) Rates to include all necessary supports and as per details (iii) Measurements to be recorded up to finished false ceiling level.				
9	<b>TABLES:</b>				
	Table made of 19 mm thk. Commercial ply with front and side visible vertical surfaces to be finished with laminate 1mm thick (of approved shade); Table Top to be cladded with additional 4mm thk MDF finished with Satin Enamel Spray Painted of approved shade, with 40 mm X 12 mm thick teak wood/MDF beading all around, as per drawing. The front of the table top shall be projected as per drawing. The modesty guard shall be finished with 12.0 mm thk. toughed glass with 4" wide .S.S. Spacer. Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the table. The wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers. The table shall have a keyboard tray of size 600 X 270 of EBCO make fixed on channels, as per manufacturers instructions / specifications. A full depth CPU shelf 15" wide shall be provided at left hand side of counter underneath the working top, at 4" above the floor level and 3" away (horizontally), from vertical end which will be made of 19mm thick commercial ply finished with laminate 1mm thk. and 3/4" x 1/2" teakwood/MDF lipping on two visible sides. three lockable drawer running on side mounting drawer slides (channels) of EBCO make made of 19 mm thick commercial ply with 1mm thick laminate on front face, handle / knob and magnetic catcher shall be				

	provided on one side of the table as per layout. The sides of the drawer shall be made of 12 mm thick plywood / 19 mm ply, bottom of 6 mm thick plywood & front of 19 mm thick bply. A full length foot rest made of hard wood 3" x 1½" section shall be provided at 4" above floor level. Non-Visible/inside surfaces i.e. inside / leg-space of table, inside of drawer / cupboard shall be finished in 1mm thk. laminate of white/off white shade and teak wood /MDF edges / lipping / beading shall be Spirit polished or Spray Painted as required.				
a)	Size 6'-0" X 3'-0" X 2'-6"	1	no.		
b)	Size 5'-0" X 2'-6" X 2'-6"	3	no.		
<b>10</b>	<b>SIDE CREDENZA:</b>				
	Providing & fixing Side credenza ( 15" to 18" deep ) made of 19 mm thick commercial ply and 6 mm thick plywood on back side & 1mm thick laminate of approved shade on top horizontal surface & vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have three drawers, horizontaly running on side mounting drawer slides (channels) of EBCO make. The remaining part of the credenza will have cupboard with shutters and one shelf. The shutters with handle / knob and magnetic catcher shall be provided beneath the drawers all non visible/inside surfaces shall be finished with white/off white laminate 1mm thk. and teak wood edges / lipping / beading shall be Spirit polished with matching pigment.				
	Officer's & Staff side credenzaas per Drawing & specification mention in item above. Size - (W X D X H)				
a)	B.M (3'-6" X 1'-6" X 2'-3")	1	no.		
b)	Officers (3'-0"x1'-3"x2'-3")	2	no.		
<b>11</b>	<b>BACK CREDENZA / LOW HEIGHT STORAGE :</b>				
	Providing & fixing back credenza 18" deep ( top surface 18" to 24" as per site) & 30" HT. made of 19 mm thick commercial ply board and 6 mm thick plywood on back side & 1mm thk laminate of approved shade on top horizontal surface & vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have drawers running on side mounting drawer slides (channels) of EBCO make & cupboard with shutters and one shelf as per drawings & details. The shutters with handle / knob and magnetic catcher shall be provided and non-visible/inside surfaces should be finished in enamel paint of white/off white shade. The teak wood edges / lipping / beading shall be Spirit polished with matching pigment.	10.00	mtr		
<b>12</b>	<b>WOODEN BOXING FOR ELECTRICAL PANEL</b>				
	Providing & fixing at site cabinet 8'-6"height having	7.60	sq.m.		

	overall depth of 2'-0".the carcase shall be made of 19mm thk commercial block board. The shutters shall be made of 19mm thk commercial blockboard, with 1.0mm thk laminate on outer surfaces. The shutters shall be mounted on SS piano hinges & provided with magnetic catches, lock & towerbolts as required with 5mm thk teak wood lipping, duly spirit polished. all internal surfaces, & back of shutters shall be painted white. the cabinet shall be complete with all necessary hardware like locks, handles, catchers, towerbolts etc.				
13	WRITING DESK/CUSTOMER VOUCHER STAND /FORMS STAND INCLUDING PASS BOOK,CHEQUE DROP & SUGGESTION BOX:				
	Providing and fixing forms stand of size 4'-0" X 1'-6" X 3'-9" with 3 nos. storage units of forms with 12 mm glass top fixed with 3" SS spacer. Space for housing vouchers of size 1'6" W, 1'-0" D & 9" H is also provided on the top and on side (L-shaped, wall hung) including provision of Pass Book, Cheque Drop & Suggestion Box as per drawings made of 19 mm thick commercial ply with 1.0 mm thick laminate to be fixed and 3/4" x 1/4" teak wood lipping on two visible sides on it All exposed Teak wood edges / teak wood lipping / beading shall be spirit polished with matching pigment. etc. & to be fixed on the wall.cost of spacers ect. all inclusive complete.	1	no.		
14	WALL PANELLING:				
	Providing and fixing paneling over the existing wall made out of framework of 50 mm X 25 mm - 18 gauge section un anodised Aluminium ( as per requirement) frame work @ 16" to 24" c/c vertically & horizontally.The frame work to be clad with 8.0 mm thick commercial ply and following finishigs as per drawing and instructions. All exposed surfaces to be clad with teakwood moulding of size 30 mm X 12.0 mm made to shape. The work should be complete in all respects including provisions of grooves duly designed & finished. All wood to be treated with wood preservatives of approved ISI quality. All exposed teak wood shall be spirit polished with matching pigment. The rate shall include for providing groves in laminate & wood. Payments shall be made only for exposed surfaces & actual measurement at site, no payment shall be made for paneling behind furniture such as tables, Credenza , storage etc.				
	Panelling with laminate (1.0mm thick)	85.00	sq.m.		
15	WOODEN BOXING ON COLUMNS				
	Providing & fixing wooden boxing on columns as per details, using 19mm thick commercial block board, finished with 1.0mm thick laminate fixed as per pattern, complete in all respects.	6.50	sq.m.		
16	NIGHT LATCH LOCK:				
	Providing & Fixing Night latch in cash cabin door -	1	no.		

	Providing and fixing night latch lock Godrej make in aluminium / wooden doors, complete in all respects.				
17	<b>FALSE CEILING -(MINERAL FIBRE TILE):</b>				
	Providing and fixing false ceiling at all heights, made of 600 mm X 600 mm X 16 mm Prima Dune / Sand Supreme, RH 99 & micro log edge with black lining, mineral fibre ceiling tiles of type - Fine Fissured micro lock with silhouetted grid (black reveal), Tegular edge, laid on Armstrong exposed grid systems. The framework comprises of main rubber spaced at 1200 mm c/c, securely fixed to the structural soffit by approved hangers of spacing not more than 1200 mm c/c. Hangers (G.I. wire of 4 mm dia.) to be fixed by approved rawl plugs, level adjusters & screws etc. The last hanger at end of each main runner should not be more than 450 mm from the adjacent wall. Flush fitting 1200 mm long Cross T's (with double stitching) to be interlocked between main runners at 600 mm c/c to form 1200 mm X 600 mm modules. Cut cross T's longer than 600 mm to be supported independ-ently. 600 mm X 600 mm modules to be formed by fitting 600 mm long flush fitting cross T's centrally between the 1200 mm Cross T's. The rates shall be inclusive of making opening with frame etc. for electrical / air conditioner & finishing of ceiling in all respect, the work includes provision of trap door if required.	70.60	sq.m.		
18	<b>GYPBOARD FALSE CEILING:</b>				
	Providing and fixing suspended false ceiling including steps as per design with 12.5mm tapered edge Gypsum Board to the grid comprising of cold rolled galvanized metal section to the required line and level.The grid consists of a perimeter channel (MF6a of dimensions 20mm x 27mm x 37mm x 3.5M) fixed round the perimeter to receive and of the ceiling section (MFS) and the outer edges to gypboard. The intermediate channel (MF7) of dimensions 15mm x 45mm x 0.9mm x 3.6M) at 1200mm c/c in the one direction and the ceiling section (MFS of dimensions 80mm x 26mm x 0.5mm x 3.6M) at 450mm c/c in the other direction are connected by a connecting clip (MF9). The grid is suspended with an adjustable strap hanger (MF9). The grid is suspended with an adjustable strap hanger (MF8) of dimensions 25mm x 0.5mm) at 1200mm c/c on both ways from the structural soffit using a soffit cleat and expandable bolts/fasteners Nut and bolts are used to connect strap hangers to soffit cleats and for joining ends of channel sections together. The gypsum board layers are screwed to the M/F ceiling sections with gypboard drywall screws. Jointing and screw spotting are then carried out as per manufacturer's standard recommendations. Perimeter Channels (MF7) to be used around the cut outs for light fittings. AIC ducting etc.The work includes painting with 2 coats of plastic emulsion to give an even & finished	110.00	sq.m.	600.00	66,000.00

	surface. The payment area will be the visible area only The work should be complete as per instructions of Architect or Engineer in charge.				
19	<b>ROLLER BLINDS OF VISTA / MAC MAKE</b>				
	Providing and fixing Rolling Roman blinds made of fabric of approved design and shade, as approved by the Architect, including rolling channels and other fitting complete in all respect, as per manufacturer's specifications. Make : FARRARI/ VISTA/ MARVEL.	20.10	sq.m.		
20	<b>ACP CLADDING / SHUTTER BOXING:</b>				
	Providing cutting, bending and fixing of aluminium Composite Panel cladding of approved make / manufacture on external façade of size as shown in drawings at all heights and elevation including necessary frame work, either curved or straight or circular in plan. The aluminium composite panel should consist of 3 mm thick thermoplastic core of anti - oxident LDPE + HDPE ( Virgin Core) sandwiched between two layers 0.5 mm thick aluminium alloy sheet ( alloy grade 3003 of ASTM B-209) making a total panel thickness of 4 mm.The surface finish shall be PVDFcoat of 30 micron over a base polyester coat on top and service coat on the reverse with chrome /alkyd of 6 - 7 microns coating shall confirm to ASTM D 2244-93 and ASTM D 523 - 89 for color retention and chalk resistance.ACP shall be fixed on especially designed aluminium frame work with horizontal and vertical members of extruded aluminium made out of AA 6063 T, 6 - 20 microns anodizing shall be done on the aluminium section. The aluminium frame work shall be of 50 x 25 x 1.6 Sheet to be supplied in width of 1220 mm. The color shade and texture of the ACP to be as per the approved Bank color design and pattern.	44.00	sq.m.		
21	<b>ACP BANK LOGO 2' DIA:</b>				
	Providing , making to shape and size ( as per the design provided) and fixing to position SBI bank logo made out of ACP sheet of bank blue color ( pre approved) fixed to position with aluminium framework with required screws, nuts bolts and hooks etc. of size 2' x 2'	1.00	no.		
22	<b>PAINT WORK:</b>				
a)	Applying three or more coats of Oil Bound Distemper (ASIAN/ NEROLAC) of approved shade including making of ground, rubbing, filling of putty base preparation with BIRLA/ JK Putty, applying a coat of cement primer, complete. In case where the surface has been earlier white/colour washed, the old white/colour wash shall be entirely removed and surface broomed/scrapped down before preparing the surface for applying paint as described above. Rates include cleaning of splashes, stains on floor, window panes etc and scaffolding, if required and for all heights.	320.00	sq.m.		

b)	Exterior Paint: Applying three or more coats of Exterior Pain(APEX or equivalent) of approved shade including making of ground, rubbing, filling of putty base preparation primer with BIRLA/ JK Putty, applying a coat of cement primer, complete for all heights.	90.00	sq.m.		
23	<b>TEXTURE WORK:</b>				
	Providing & applying a coat of RUSTIC textured finish in white color (ASIAN) on walls and columns. The rate shall include scrapping, leveling & preparing the surface with JK/ ASIAN/ BIRLA WHITE putty. Applying 1 coat of texture over a coat of primer & applying 2 or more coats of plastic emulsion paint of approved shade to give even & uniform surface, including cleaning of floor, surface etc. complete.	40.00	sq.m.		
	<i>NOTE: For items nos. 6 to 7, flat area of doors &amp; windows will be measured &amp; paid. No separate measurements will be made for door jambs, chauhats etc. In case of enamel painting of windows &amp; ventilators, flat measurement will be taken of window area (one side) and no separate measurement will be taken for steel grills.</i>				
24	<b>VITRIFIED TILE FLOORING:</b>				
	Providing and laying 1st quality vitrified tiles (Marble series Double charged- JOHNSON/ KAJARIA/ RAK- as approved by Bank's Engineer/Architect) of following sizes, as per design pattern on floor & skirting with chemical or adhesive/ cement as directed and joints to be filled with grout of approved colour, including dismantling existing floor tiles and disposal of malba from site, cutting wooden/ aluminum doors to match new floor level, preparing of surface & disposal of malba from site.				
i)	24"x24" Vitrified tiles Double Charged- marble series.	215.00	sq.m.		
25	<b>CERAMIC TILE FLOORING IN TOILET (ANTI SKID TILES):</b>				
	Providing and laying Anti- skid ceramic floor tiles, of 12"x12" or 16"x16" size (KAJARIA/ JOHNSON/ NITCO), shade & pattern as directed by Bank's Engineer/ Architect, as per design pattern on floor with chemical or adhesive/ cement as directed and joints to be filled with grout of approved colour, including dismantling existing floor tiles and disposal of malba from site, filling depressions in floor, cutting wooden/ aluminum doors to match new floor level, preparing of surface, dismantling of tiles & disposal of malba from site.	9.00	sq.m.		
26	<b>WALL TILES :</b>				
i)	Providing & fixing 1st quality vitrified wall tiles 12"x24" size as approved by Architect/ Bank's Engineer, of approved shade & pattern (KAJARIA/ JOHNSON/ NITCO), fixed with Cement plaster 1:4 (1cement: 4 fine sand) & neat cement as per specifications, including dismantling existing tiles/	43.00	sq.m.		



	dado/ plaster & disposal of malba from site, laying 12mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) complete, including all types of leads/ lift, scaffolding, pads, racking joints, filling of joints with white cement grout, curing, etc. complete.				
27	<b>GI PIPE WORK / PLUMBING</b>				
	Providing & fixing GI Pipes medium class conforming to IS-1239 (JINDAL/ TATA), including necessary fittings like nipples, tee, socket, union (SNW/ UNIQUE make) etc., complete. Rates to include cutting/ chasing walls, floor, fixing pipe & making good the damages with cement mortar, complete in all respect.				
a)	15mm dia nominal bore	5	mtr.		
b)	20mm dia nominal bore	5	mtr.		
28	<b>SOIL WASTE DRAINAGE PIPE WORK</b>				
	Providing & fixing PVC(SWR) Pipes Type B, heavy class conforming to S13592-1992. (PRINCE / SUPREME / DIPLAST/ ASTRAL), including necessary fittings like bend, offset, collars etc., complete. Rates to include cutting/ chasing walls, floor, fixing pipe & making good the damages with cement mortar, complete in all respect.				
a)	75 mm dia	8	mtr.		
b)	100 mm dia	8	mtr.		
29	<b>SANITARY FITTINGS</b>				
a)	Providing & fixing 1st quality vitrous china white coloured wall mounted European Water Closet (JAQUAR-SLS-WHT-6751P180PP + SLS-WHT-6201) mounted on MS brackets, CP overflow with mosquito proof coupling, with black seat cover & lid, CP brass hinges, CP bend, WC fixed with brass screws, including connecting with existing CI pipe with CI/ PVC pipe with including dismantling existing fixtures & stacking the material at site, complete in all respect.	2.00	nos.		
b)	Providing & fixing 1st quality vitrous china white coloured Thin Rim Table Top Basin Wash basin 50x42x12 cm size (model - ARS-WHT-39901 Aria), 32mm CP waste, CP bottle trap, CP brass chain & rubber plug, fixing wash basin on granite top of 3'x2' size or as instructed; granite top to be fixed on top of RCC shelf 3" thick, including reinforcement steel, shuttering, scaffoldings, props, curing etc, complete, cutting & making good RCC shelf/ floor/ walls, wherever required, complete in all respect.	2.00	nos.		
c)	Providing & fixing 1st quality vitrous china white coloured urinal with Fixing Accessories of size Size: 370x315x620mm (model URS-WHT-13261of Jaquar) complete in all respect.	1.00			
30	<b>CP FITTINGS &amp; ACCESSORIES</b>				
a)	Providing & fixing 15mm dia CP short body Bibcock (JAQUAR OPAL- Cat no. 15037 ), with CP wall flange, complete.	2	nos.		

b)	Providing & fixing 15mm dia CP Angle valve (JAQUAR - Cat no. OPAL- Cat no. 15053), with CP wall flange, complete.	10	nos.		
c)	Providing & fixing 15mm dia CP CONCEALED valve (JAQUAR - Cat no. OPAL-), with CP wall flange, complete.	3	nos.		
d)	Providing & fixing 15mm dia CP Pillar cock (JAQUAR PRS-CHR-031), auto closing type, complete.	3	nos.		
e)	Providing & fixing CP Health Faucet ABS (JAQUAR-ALD-769L250X190), with 120cm SS flexible tube (VIKING) & ABS wall hook, complete.	2	nos.		
f)	Providing & fixing 15mm dia CP Water jet for WC with connecting CP pipe, complete in all respect.	2	nos.		
g)	Providing & fixing 15mm dia Urinal Valve Auto Closing System with Built-in Control Cock with Wall Flange PRODUCT CODE: PRS-CHR-077 of Jaquar, complete in all respects	1	nos.		
h)	Providing & fixing CP jali (heavy duty) with CP outer ring, complete.	5	nos.		
i)	Providing & fixing CP Towel RING(JAQUAR )- 6" dia, heavy duty, complete.	2	nos.		
J)	Providing & fixing CP liquid soap container(JAQUAR ), complete.	2	nos.		
31	<b>MIRROR</b>				
	Providing & fixing 600x450 mm or as directed, beveled edge mirror 5.5 mm superior glass (ATUL/ SAINT GOBBIN) complete with 6 mm thick hard board ground fixed to wooden cleats & CP brass screws, washers & clips etc. complete.	2	No.		
32	<b>DISMANTLING</b>				
	Dismantling brick & shifting of doors (steel or wood) shutter including chowkhats, architrave, holdfasts etc.	1	job		
	<b>TOTAL (Item No. 1 - 32)</b>				

Amount in Words: \_\_\_\_\_

Signatures of Contractor / Firm with Seal