	PRICE BID FOR RENOVATION WORKS AT VALAKUZHY (EXISTING PREMISES		CH AS PE	R UNIFORM LA	YOUT
SI.No	DESCRIPTION OF WORK	Qty	Unit	Rate	Amount
	SINGLE WINDOW SYSTEM : LAMINATION TOP				
1		4	RM		
	snown in the drawing. All the internal and external exposed surfaces including inside of drawers to be finished with 1 mm thick				
	laminate . All exposed edges of plywood to be fixed with 2 mm				
2	thick matching edge banding.  SINGLE WINDOW SYSTEM (With Out Front Glass).	2	RM		
_	Specification same as im no.(1) but without front glass.	-			
3	LOW HEIGHT PARTITION FOR SINGLE WINDOW SYSTEM:Providing and fixing of Low height partitions for Single window system of 1350 mm height from finished floor level, as per the drawing. Aluminium sections of size 50 x 50 x 1 mm thick of INDAL/ JINDAL make as internal frame structure vertically at about 60 cm centres and 3 nos horizontally of the same size of frame at floor level, 750 mm and at 1350 mm level fixed in position. 8 mm plywood both sides of frame work finished with 1 mm laminate of approved color and shade with grooves on both sides upto 800 mm height. top of the partition finished with laminate of 1 mm thick. Clear float glass of 12 mm thickn ofapproved band with etching shall be fixed with SS D Brackets for a height of 500 mm above the solid partition. Partition on rear similar to side partition, but solid partition. One door shutter for each cabin for 680 mm width and 1350 mm height, similar to door shutter item, fitted with Godrej night latch at 500 mm from floor level, openable inside the cubicle shall be provided.	43	Sq.M		
4	Custom Made Low Height Partition: for CO cabin: Providing and fixing in position of custom made low height partitions of the height 1500 mm (900mm solid partition and 600mm glass above) as per drawing attached. Aluminium sections of size 50 x 50 x 1 mm thick of INDAL / JINDAL as internal frame structure vertically and 3 nos horizontally of the same section at floor level 900 mm level and at 1500 mm level. 8 mm plywood of approved quality finished with 1 mm laminate with grooves on both sides of frame work. Top of the partition finished with laminate and 10 mm thick glass with etching is fixed over the partition with SS D brackets including a door as per the specification for door shutter item with Godrej or equivalent mortice lock, tower bolt hinges etc. complete.	22	Sq.M		

5	Custom Made Full Height Solid Partition:Supply and set in position of custom made double skin full height partitions as	22	Sq.M	
	per shape and size shown in the drawing. Anodised			
	aluminium frame work with sections of size $50 \times 50 \times 1$ mm thick of JINDAL/ INDAL @ 60 cm c/c vertically and			
	horizontally at columns & wall ends and false ceiling level.			
	Alternate vertical frames to be fixed firmly to the roof ceiling slab. 8 mm plywood on both sides of frame work from the			
	floor level to false ceiling level finished with 1 mm laminate			
	on both sides including necessary grooves . Measurement for the partition area shall be considered from floor level to			
	false ceiling level only.			
6	Partly solid and partly glazed door:- Providing and fixing door	6	Sq.M	
	shutter using 35 mm thick solid block board finished with 1 mm thick laminate on both sides with grooves fixed with 8			
	mm glass 600 x900 mm fixed with beech wood beadings			
	above 900 mm . Each door shutter to be provided with 4 nos. 150 mm SS hinges, a pair of 300 mm long SS handles,			
	tower bolts, hydraulic door closer mortice lock etc of Dorma			
	or equivalent make.			
7	Fully glazed Door- Providing and fixing frameless fully glazed 12mm thk toughened glass door fixed with necessary patch	6.5	Sq.M	
	fittings (Dorma or equivalent make) including cutting, making			
	holes, cutouts in the glass of required shape and size to accommodate fittings and fixing the fittings in floors, soffits,			
	jambs including necessary fixtures, screws, sealant wherever			
	required and SS cover over patch fittings. Rate shall include necessary etching film / LOGO, approved patch fitting locking			
	systems, 1 pair of 600mm long S. S. (H Shape) Handles of			
	approved make, floor springs, and any necessary hardware items.( DORMA MAKE Top Pivot - PT 24, Top Patch Fittings -			
	PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V,			
	Corner lock with strike plate and Euro Profile Cylinder - US 10, Handle - TG DIH600 - 600mm length) Measurement will			
	be taken only upto solid partition level above.			
8	Providing and fixing of fixed glass partitions with 12mm thick	22	Sq.M	
	toughened glass using PT Standard fittings like PT 90/PT 92 of Dorma or equivalent make at the top and bottom including			
	cutting, making holes in glass and fixing the fittings in floors,			
	ceilings etc and making the same good with necessary screws including etching as per approved patterns.			
9	Gypsum Board False CeilingProviding and fixing of M/F suspended false ceiling with G.I frame work and 12.5 mm	150	Sq.M	
	tapered gypsum board panels to form grids of 45.7 X 122 cm			
	as per manufactures specification including provision for stepped shaped ceiling for lighting trough comprisingFrame			
	work of intermediate channels (M.F.T) at 122 cm centers			
	along one direction M/F ceiling section MF5 at 45.7 cm center along other direction. Perimeter channels (MF 6A)			
	along walls alround perimeter side of the ceiling. The			
	intermediate channels suspended from ceiling,through strap hangers 25 X 0.5 mm (MF 8)at 122 cm centers connected to			
	soffit cleats p534 (27 X 37 X 25 X 1.6mm) the cleats			
	connected to ceiling through metal expansion rawl plugs 1/2" dia and 17/16" long with additional channels (MF			
	6A)for light fittings, air conditioners Ducts,vertical drops,			
	offset etc. 12.5mm thick gyp board with tapered edges fixed to underside of suspended grid with 25 mm screws including			
	2 coats of plastic emulsion paint of approved color and over			
	a coat of putty and a coat primer etc, complete.			
10	BM Table	1	No.	

	Providing and fixing Branch Manager's table of size 1800 x			
	800 X 750 mm high to detail as shown in drg. Comprising			
	table top out of 18mm thick Plywood finished with 1mm			
	thick laminate of approved color and brand and side edges			
	with 2mm thick band strip.12 mm glass with polished			
	bevelled edges to be provided for the table top with			
	necessary wire manager. Foot rest cum CPU stand with 18			
	mm plywood finished with 1 mm laminate. All the internal			
	and external exposed face of plywood to be finished with 1			
	mm laminate and all the exposed edges of ply to be provided			
	with 2 mm matching edge band. Keyboard tray 600 x 350			
	mm made of 18 mm thick plywood finished with 1 mm			
	laminate and 50 mm dia MS wire manager of approved			
	quality. One set of 3 drawers of equal height, inside a			
	drawer box of 450 mm width 712.5 mm height and 600 mm			
	deep made of 18 mm thick plywood at bottom, sides rear			
	with necessary lipping telescopic drawer slides, locking			
	arrangements, 100 mm long SS handles etc. complete.			
11	Cido Toblos Fox DMDroviding and fining at the att for Ad	4	N1 -	
''	Side Tables For BMProviding and fixing side unit for Manager	1	No.	
	/ BM table to detail as per drg. of size 1200mm x 600 mm			
	made of 18 mm Plywood finished with 1 mm laminate			
	having covered with 2 mm matching edge band Two			
	shutters fixed with Box Type hinges, Locking arrangement,			
	100 mm long S.S brush finish handles, tower bolt, ball catch			
	etc,.complete. 12 mm glass with polished edges to be			
	provided for the table top. All external internal exposed			
	faces of Plywood to be finished with 1 mm laminate and the			
	exposed edges of ply to be provided with 2 mm thick			
	matching edge band.			
40		_		
12	Providing and fixing Officer's table of size 1500 x 750 X 750	2	No.	
	mm high to detail as shown in drg. as per specification in			
	item no.11 above. 12 mm thick glass with polished edges to			
40	be provided on table top.	_		
13	Providing and fixing cash officer's table of size 2000 x 800 X	1	No.	
	750 mm high to detail as shown in drg. as per specification in			
	item no.11 above. 12 mm thick glass with polished edges to			
	be provided on table top.			
14	Side Tables For OFFICER - Providing and fixing side unit for	3	No.	
	Officer table to detail as per drg. of size 120 x 45 cm as per			
	specification in item no.11 above			
15		2	NIA	
15	Side table for counters - providing and fixing side unit of size	3	No.	
	1500 x 450 mm for counters as per spcification in item no.11			
	above			
16	Low Level Storage :Providing and fixing low level storage to	8	Sq.M	
	detail as shown in the drg. Size about 450mm wide, 750mm			
	1200 mm high with openable shutters in front approx 450			
	mm wide fixed with box type hinges, locking arrangements			
	150 mm SS handles and tower bolts made of 18 mm Plywood			
	<u> </u>			
	for top, bottom, rear sides and One intermediate member			
	finished with 1 mm laminate of approved colour and brand			
	and all the edges and sides fixed with matching 2 mm thick			
	pvc band strip. All the exp[osed internal and external faces			
	of plywood to be finished with 1 mm thick laminate of			
	approved colour and shade. Measurement shall be taken for			
	the front elevation area.			
17	Providing and fixing columns/ wall panelling to detail as	20.00	Sq.M	
	shown in the drawing with 18 mm thick plywood finished			
	with 1 mm thick laminate.			
18	<u> </u>	1	No	
10	Providing and fixing wall mounted writing desk of 1200 x 350	1	No.	
	mm in 19 mm plywood with 1 mm laminate on all exposed			
	surfaces. Top portion is to be provided with 12 mm clear			
	glass with polished edges, with shelves to keep slip books			
1	including frosting of approved design and exposed edges to			
	II CO I SIL TERRALI IN THE I I I IN			
	be fixed with TW beeding with melamine polish. A provision			
	to be made for keeping Banks printed Broachers for public			
10	to be made for keeping Banks printed Broachers for public	45	C	
19	to be made for keeping Banks printed Broachers for public Providing and Fixing 100 mm wide Vertical Blinds of Vista	15	Sq.M	
19	to be made for keeping Banks printed Broachers for public	15	Sq.M	

1					
20	Painting the walls/ ceiling with two coats of plastic emulsion paint of approved make and shade including cleaning the surface.	250	Sq.M		
21	Painting the walls/ ceiling with two coats of plastic emulsion paint of approved make and shadeover a coat of putty including cleaning the surface.	200	Sq.M		
22	Painting - Painting the new wall for UPS room with 2 coats of plastic emulsion paint over putty finish and a coat of primer	200	Sq.M		
23	Do fiving of existing counters	1.0			
24	Re-fixing of existing counters  Vitrified Flooring in Banking Hall - Flooring with best quality vitrified flooring tiles, fixed over existing flooring with , 60x60cm (Kajaria or equivalent approved) as per the design, colour and make asper the instruction of the engineer in CM 1:3,12 mm thick including providing borders, buttons etc and pointing with approved quality compound which match the colour of the tiles cleaning after laying including labour charges, cost and conveyence of materials etc. complete.Base price of the tile should be Rs. 65 per sqft.		Sq M		
25	Removing the existing aluminium partition and providing and AAC block partition blocks(auto claved aeorated concrete) of size 600x200x200mm jointed with webar lock set etc complete.Rate should be inclusive of materials,labour, transportation etc		sqm		
26	UPS ROOM DOOR - Fabricating and installing metal door (in UPS room and record room) of size 0.9mX 2.1m , double skin using 1" square tubes for frame work and two horizontal members at equidistant and a central vertical member of same section. 18 gauge sheet to be welded on both sides of framework. proper hinges and padocking system to be provided. Suitable metal cutla to be provided.		No.		
27	Removal of existing entrance wooden door shutters with frame work , making good the surface with plastering etc. and stacking the door and frame at location identified by Branch.	1	No.		
28	Rolling shutter - Providing and fixing Rolling shutter for main entrance of size approx. 2.00mx2.1m (Pull & Push Type) made out of 1.00 mm x 75mm Mild Steel or Galvanised steel laths of convex corrugation, complete with side guide & bottom rails made out of 2.5/2.0 mm M. S. Sheets with interlocking arrangements for the steel lath by means of alternative end clips, brackets, strong suspensions shaft made out of pipes, loaded with high tension coil type spring made out of spring steel wire. Central Locking arrangement, pulling hooks handles with all fitting accessories in best workmanship with one coat of Red-Oxide Primer. and two coats of synthetic paint. For better smooth working Ball Bearing should be provided. Rate including the material cost and labour charges, including locks, handles etc. complete.		Sq.M		
29	Provide/fix kitchen counter with 18 mm thick jet black granite (with polished / rounded edges) over a box of marine plywood of 19 mm thick with openable shutters		Sq.M		
30	Providing and fixing stainless steel sink with drain board of size about 36" x 18" including all connection/ fittings such as tap water/ waste line connections etc. complete.		No.		
31	Painting the windows/ doors/ ventilators with two coats of synthetic enamel paint of approved make and shade including cleaning the surface.		Sq.M		
32	Providing RCC lintel works 1:1.5:3 above the UPS room , Record room doors  TOTAL	Ls			
1	· · · · · -			l	1