	PRICE BID FOR ELECTRICAL WORKS AT STATE BANK OF KHERA.(HR.)	INDIA,	BRANCI	HAT BAW	ANI
DAD	T-I : COMPUTER POINTS & DISTRIBUTION				
-	Supply all material, storing, handling, fixing of computer points computer points in suitable size of GI/PVC box including providing 3 nos 5 amps 3 pin modular sockets to be provided under table top and controlled by 1 no 15 A moduler type switch and indicator (to be provided above the table top in partition) with moduler cover plate etc complete as required including 3X2.5 sq. mm copper armored cable Note: Maximum two computer points are to be provided on one circuit. (Switches : Make: Anchor/Crabtree/North-West/MK		each		
2	Supply all material, storing, handling, fixing of computer points computer points in suitable size of GI/PVC box including providing 1 nos 15 amps 6 pin modular power sockets to be provided controlled by 1 no 15 A moduler type switch and indicator with moduler cover plate etc complete as required including 3X2.5 sq. mm copper armored cable. Note: One power points are to be provided on one circuit and dirctly to be connected on Power DB. (Switches : Make: Anchor/Crabtree/North-West/MK		each		
3	Supply, installation, testing and commissioning of factory fabricated distribution board rust inhibited powder coated sheet fabricated comprising of incoming and outgoing isolator & MCBs neutral link or neutral bus, top and bottom detachable entry earthing bolts interconnection and grouting bolts etc complete as required as per details below. Make: Havells/HPL/Standard/ Legrand/L&T				
a)	8 way SPN MCBDB Double Door comprising of 1 No 63 Amp DP Isolator and 6 No SPMCB 10/16 Amp. (UPS output)	1	no.		
	6 way SPN MCBDB comprising of 1 No 63 Amp DP Isolator and 4 No SPMCB 10/16 Amp.(Branch)	1	No		
c)	4 Way TP MCBDB Double Door in recessed wall including cutting of wall and making good the damages comprising 1 no 100 A FP TPN and 6 Nos.32 A DPMCBS etc complete as required. (for Air conditioning only).		no.		
d)	4 WayTP MCBDB Double Door in recessed wall including cutting of wall and making good the damages comprising 1 no 63 A FP MCB and 12 Nos. 6/10 Amp SPMCBS etc complete as required. (for Light, Fan point, Raw power points).		no.		

				1	
4	Supply, installation, testing and commissioning of following				
	capacity 3 pin metal clad industrial type plug and socket				
	arrangement with plug top, cap and chain controlled by				
	under noted capacity: (Make:				
	Havells/HPL/Standard/Legrand/L&T)				
a)	20 Amp with 20 Amp. C Curve SP MCB. (for 1.5 TR High	3	no.		
	wall split AC's)				
b)	30 Amp with 32 Amp. DP MCB for Acs (for 2.0 TR Cassette	3	no.		
	AC's & 2.0 TR High wall split AC'S)				
5	Providing and fixing of suitable size MS box fabricated with	1	job		
	16 G MS sheet either in recess wall or on surface to				
	accommodate dedicated earth from earth electrode and				
	further distribution of earth to computer points including				
	providing of 5 mm bakelite on base connector strip and				
	painting of box etc as required.				
6	Basic electrical Wiring of light points, plug points & power				
	points				
	Wiring for light point/ ceiling fan point/ exhaust fan point				
	with 1.5 sq.mm FRLS PVC insulated copper conductor single				
	core cable in surface / recessed medium class PVC conduit				
	ISI Mark, with 6Amp modular switch, modular plate,				
	suitable GI junction & switch boxes & clip and earthing the				
	point with 1.5 sq.mm FRLS PVC insulated copper conductor				
	single core cable etc. as required.(Wires Make: Havells/ RR				
	Kable / KEI/Finolex) (Switches : Make:				
	Anchor/Crabtree/North-West/MK)				
	(Rate includes 3 x 2.5 sq.mm FRLS copper conductor, single				
	core cable in PVC conduit for circuit/sub main wiring along				
	with earth wire)				
a)	single 6 Amp Switch controlling 1 light point for T-5, Wall	35	no.		
	Fans, exhaust Fans , Ceiling fan and other seprate room				
	supply only				
b)	single 6 Amp Switch controlling 4 no. downlights / 4 no.	20	no.		
	LED downlight / 2 no. 2'- 0"x 2'-0" 36 watt light fittings				
	Note: Lihgts/fans points to be calculated by numbers of				
1	lights and no extra cost shall be paid for dummy switch.)				

PAI	RT-II : PANELS , KIT KATS & CABLES			
7	Providing and fixing of 03 no 200 Amps KITKAT with 1 no	1	job	
	neutral link on suitable size of Bakelite sheet of thickness			
	not less than 12 mm complete as required			

	<u> </u>			
8	Supply at site installation testing and commissioning of			
	panel fabricated with 16 G MS sheet. The panel shall be			
	free standing type totally enclosed dust and vermin proof			
	construction with rubber gaskets. The floor mounting panel			
	shall have ISMC mounting channels, GI earth busbar,			
	busbar chamber ,cable alleys interconnection with solid			
	bar/PVC insulated copper conductor as per requirement,			
	and suitable supports of busbars. The panel shall be			
	painted with two coats of enamel paint (Grey shade) over			
	primer and shall also be provided with designation of			
	Incoming and outgoing feeder as details below:			
	INCOMING			
	1 no MCCB Breaking Capacity 25 KA 160 Amp 4P , Model-			
	DU250 Series, L&T make			
	1 no 0 -500V digital Voltmeter in separate compartment			
	and digital Amp meter and one set of CTs (3 Nos) with CT			
	Ratio 200/5 A with LED type phase Indication Lamps with			
	protection fuses in a separate compartment			
	200 Amps capacity 4 strips Aluminium bus bars.			
	OUTGOING			
	2 nos MCCB Breaking Capacity 10 KA 100 Amp 3P and 4	1	set	
	nos MCCB Breaking Capacity 10 KA 63 Amp 3P with		500	
	seprate neutral Link, DU Series, L&T make.		<u> </u>	
9	Supply, Installation, testing & commissioning of PVC			
	insulated PVC sheathed armoured cable of 1100 V (\ensuremath{IS}			
	;1554 Part 1) and fixing of cable on wall with suitable size			
	of clamps /saddles or laid in floor/recess wall including			
	cutting of wall /floor and making good the damages etc			
	complete as required of following sizes (ISI marked).			
	(Make: Havells/ RR Kable / KEI/Finolex/Pymen)			
a)	3.5X50 sq. mm aluminum conductors armoured cable with	20	mtr.	
	two Nos. 8 SWG GI wire			
c)	3.5X25 sq. mm aluminum conductors armoured cable with	35	mtr.	
	two Nos. 8 SWG GI wire			
d)	3X6 sq. mm copper conductors armored cable with one	30	mtr.	
	Nos. 8 SWG GI wire			
10	Supplying and making end termination with brass			
	compression gland and aluminium lugs for following size of			
	PVC insulated and PVC sheathed / XLPE aluminium/Copper			
	conductor cable of 1.1 kV grade as required.			
	Conductor capie of 1.1 KV grade as required.			
a)	3.5X50 sq.mm aluminum conductor	2	no.	
	3.5X 25 sq.mm aluminum conductor	8	no.	
-	3X6 sq. mm Copper cable gland.	6	no.	
	Supplying and providing 3 x 2.5 sq.mm FRLS copper		mtr.	
			mu.	
	conductor wires with earth wire for the connection from			
14	AC DB to metal clads UPS DISTRIBUTION BOARD			

			1	
	supply, installation, testing and commissioning of factory fabricated distribution board rust inhibited, powder coated sheet fabricated comprising of incoming and outgoing isolator and MCB's neutral link or neutral bus, top and bottom detachable entry earthing bolts interconnection and grouting bolts etc complete as requd. Make: Havells/HPL/Standard/Legrand/L&T as per details below :-			
а	4 way DB comprising of 2 no. 63 amp DPMCB (UPS out put)	2	each	
b	4 way TPNDB Double Door comprising of 1 no. incoming 63 amp MCB & 3 no. 32 DPMCB (UPS input)	1	each	
12	Providing and laying following sizes of PVC insulated copper			
	conductor cable of 1100 V in flexible/ PVC conduit pipe			
	with accessories such as glands bends etc (as per			
	requirement) including making necessary interconnection			
	etc complete as required.			
	2 X 6 Sq mm with 1 no suitable insulated 2.5 sq mm multi	25	mtr.	
	stranded copper wire in PVC flexible pipe. (Make: Havells/			
12	RR Kable / KEI/Finolex) Supplying & fixing the 1 no.4 pole 200 Amps capacity	1		
12	change over switch and complete connection with		no.	
	Electrical Panels as required .Make:			
	Havells/HPL/Standard/ Legrand/L&T			
14	EARTHING			
	a)Supply and fix copper plate earth station with		Sets	
		1	Sets	
	600X600X3mm copper plate including all accessories such	1	Sets	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry	1	Sets	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit,	1	3013	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc	1	Sets	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage	1	3612	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc	1	3613	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage	2	Sets	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch)			
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover			
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt			
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS			
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987.	2	Sets	
15	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip			
15	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987.	2	Sets	
15	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip with earth station below ground level etc as required.	2	Sets	
15	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip	2	Sets	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip with earth station below ground level etc as required. b)Supply fixing and termination of 20X3 mm G.I strip with	2	Sets	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip with earth station below ground level etc as required.	2 5 10	Sets Meter Meter	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip with earth station below ground level etc as required. b)Supply fixing and termination of 20X3 mm G.I strip with earth station below ground level etc as required. a)Providing and fixing of 8 SWG copper earth wire in the recess for loop earthing etc. as required. b)Providing and fixing of 8 SWG GI earth wire in the recess	2 5 10	Sets Meter Meter	
	600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. (Branch) b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. a)Supply fixing and termination of 20X3 mm copper strip with earth station below ground level etc as required. b)Supply fixing and termination of 20X3 mm G.I strip with earth station below ground level etc as required. a)Providing and fixing of 8 SWG copper earth wire in the recess for loop earthing etc. as required.	2 5 10 20	Sets Meter Meter Meter	

17	Supply and Joying following dia 2 mm in thiskness ISI Mark				
	Supply and laying following dia 2 mm in thickness ISI Mark				
	PVC pipe under floor or in recessed walls from earth				
	electrode to UPS room for computer dedicated earthing				
	25 mm diameter	50	Meter		
		- 50	WELEI		
PAR	T IV - TELPHONE & DATA CABLE				
-	Wiring for telephone points with 0.6 mm dia 2 pair	7	no.		
	insulated annealed tinned electrolatic copper conductor in		_		
	2 mm thick 25 mm dia ISI marked PVC conduit complete				
	with accessories such as bends, junction boxes etc. with				
	suitable size of G.I./PVC box modular plate and cover in				
	front on surface or in recess including providing and fixing				
	modular type telephone socket outlet and making				
	necessary connections etc. complete as reqd. (Make:				
	Dglink/KEI/Finolex)				
	Supply, installation and testing & commissioning of Tag	1	no.		
	Block 20 pair for telephone connections Make: krone				
20	Providing , Laying, testing & commisioning of 10 pair	20	mtr.		
	telephone cable from outside govt. / bsnl DB to Rack for				
	lease line, ISDN of Make: Delton, finolex, polycab.				
	Data cabling work for computer networking starting	10	no.		
	from mounting rack at system room with UTP CAT-6e				
	LAN Data cable in 2mm thick 25 mm dia ISI mark PVC				
	conduit with accessories such as bends, Tees,				
	junction boxes including providing and fixing cat-6 I/O				
	plates and SMB complete with all networking				
	accessories etc complete as reqd. (Make: D- LinK/MOLEX/AMP/COMMSCOPE).				
	Note: Only One Data Points to be provided in One				
	Table/Counter. Extra points not to be provided in One				
	Maximum 6 no. data cable must be run in one pvc				
	pipe.				
	supply, installation, testing and commissioning of 24-port	1	no.		
	Patch Panel				
	Supply and installation, testing and commissioning of	1	no.		
	mounted rack 15" hight made of powder coated MS sheet				
24	supply, installation, testing and commissioning of factory				
	manufactured CAT-6e patch chord complete with 2 no.				
	connectors etc. complete as reqd.				
a)	1 mtr. long	10	no.		
	2 mtr. long	10	no.		
	PART-V : SUPPLY, INSTALLATION TESTING & COMMISSION	ING OF F	ANS & I	FIXTURES	

25	SITC of 2"x2" Celing grid 33-36 watt LED panel fixtures with	17	no.	
	essential driver in false ceiling including making necessary			
	arrangement for mounting the fixtures and connection			
	with 2 x 1.5 sq.mm insulated copper cable from adjacent			
	point in PVC flexible pipe etc Complete as reqd. Make			
	Philips cat. RC 380 B- LED-30-6500PSE OD WH or			
	equivalent of Wipro / Bajaj.			
26	SITC of 15 watt LED fixtures /dowlighters with essential	20	no.	
	driver in false ceiling including making necessary			
	arrangement for mounting the fixtures and connection			
	with 2×1.5 sq.mm insulated copper cable from adjacent			
	point in PVC flexible pipe etc complete as reqd. Make			
	Phillips cat no. DN - 192 - 1000 or equivalent of Wipro /			
	Bajaj.			
27	SITC of 5 watt recess mounted LED down light with			
	assembly complete with including making necessary			
	connections etc. Complete as reqd. (M/s Crompton Cat		no.	
	No. Or equivalent of Philips/Wipro/ Bajaj)			
28	SITC of 18 watt of T5 LED fixtures directly on ceiling / wall	8	no.	
20	including making necessary connections with 2x1.5 sq.mm		110.	
	insulated copper cable conductor wire etc. complete as			
	reqd Make Phillips cat no. DN - 192 - 1000 or equivalent of			
20	Wipro / Bajaj.	1 5		
29	SITC of 400 mm sweep High Flow Crompton Greaves (or		no.	
	equivalent) wall fan with high flow model with 3 pin plug			
	complete as required. (M/s Crompton or equivalent of			
	Khaitan / Bajaj.)			
30	LED Strip light (4.5/5 watt)for cove (M/s Phillips /Wipro /	50	MTR.	
	Bajaj Complete in all respects with suitable drivers			
	complete as required.			
31	SITC of 1200 mm CEILING fans complete as reqd. (M/s	3	no.	
	Crompton High Breeze or equivalent of USHA / Bajaj).			
32	SITC of 200 mm exhaust fans complete with self opening		no.	
	louvers / shutters including necessary frame etc, complete			
	as reqd. (M/s Crompton High Breeze or equivalent of USHA			
	/ Bajaj)			
33	SITC of 30 watt Street light /Flood light for lighting the front			
	side of the branch(M/s Crompton Cat No. LSTS-30-CDL or	4	no.	
	equivalent of Philips/Wipro .			
34	SITC of Automatic Programmable Time Switch 24 Hour for			
	Glow sign board and ATM AC's (Make: L&T or equivelent to	2	no.	
	Legrand/Havells/Seimens)			
	PART-VI : AIR CONDITIONING WORKS			

35	Supply, erection, testing and commissioning following Wall			
	Mounted/Roof Mounted Cassette units with cordless			
	remote complete with all necessary firring duly insulated			
	with 9mm thk. Nitrite rubber pipe insulation with (
	evaporate coil-copper only_ fan and fan motor, machine			
	control panel improved refringent joints, Air conditioners			
	shall be fitted with hermetically sealed type suction			
	reciprocating or discharge cooled rotary compressor or			
	scroll compressor, compressor unit operating on			
	R22/R410. All complete as per drawing and Instructions of			
	the Architect/employer (rates are to be inclusive of copper			
	refringent pipe and supply cable with insulation and drain			
	pipe up to 3mtr. length & powder coated MS Stand)			
	Copper only (Make : Hitachi/Daikin/Carrier/Voltas/Blue			
	star)			
a)	1.0 TR wall mounted split unit (Minimum 5 star rating			
	invertor type) including all necessary fitting amd mounting			
	as specified by the manufacturer	1	no.	
	Note: Warrenty certificates of Airconditioning units to be			
	submitted by the vendor with the bill.			
36	Providing and fixing stablizer inputvoltage range of 140-			
	280V and output to be 230V Make : Blue Bir/Logic state/			
	Inline/V-guard (Copper winding)			
	4 KVA (for 1TR to 1.5 TR Split AC)	1	no.	
37	Supplying & Laying of following COPPER REFRIGERANT			
	PIPING Thickness 22 SWG For Hiwall Split AC complete with			
	fittings Suction / Discharge line insulated with 12 mm			
	SUPERLON / ARMAFLEX suction line. Multi-runs between			
	Indoor & Outdoor units shall be considered as ONE length			
	for the purpose of measurement. (Make: Total			
	Line/Armacell)			
<u> </u>	1/4" + 1/2" Refrigerant piping - For Hiwall Split AC's	35	mtr.	
h)				
~/	HWS/Cassette AC (2.0 Tr & 3.0 Tr) Copper pipe size (5/8"	80	mtr.	
	& 3/8")			
	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain	60	mtr. mtr	
	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. &	60		
	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor	60		
	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls,	60		
	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever	60		
	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls,	60		
38	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme)	60	mtr	
38	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme) Supplying and providing FRLS Eletrical flexible cable of	60 230		
38	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme) Supplying and providing FRLS Eletrical flexible cable of 3x2.5sq.mm multi strand suitable for 1.5 Tr H.W Split &	60 230	mtr	
38	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme) Supplying and providing FRLS Eletrical flexible cable of 3x2.5sq.mm multi strand suitable for 1.5 Tr H.W Split & 2.00 Tr Cassette Multi-runs between Indoor & Outdoor	60 230	mtr	
38	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme) Supplying and providing FRLS Eletrical flexible cable of 3x2.5sq.mm multi strand suitable for 1.5 Tr H.W Split & 2.00 Tr Cassette Multi-runs between Indoor & Outdoor units and between Metal Clads to Out door for electrical	60 230	mtr	
38	& 3/8") Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme) Supplying and providing FRLS Eletrical flexible cable of 3x2.5sq.mm multi strand suitable for 1.5 Tr H.W Split & 2.00 Tr Cassette Multi-runs between Indoor & Outdoor	60 230	mtr	

40	Taking down & Re-fixing of Existing 2.0 Tr.& 1.5 Tr Split A.C	4.00	Nos		
	including filling of Gas complete in all respect upto the				
	satisfaction of consultant / engineer in-charge.				
	TOTAL AMOUNT				
	DISCOUNT(IF ANY)				
	GRAND TOTAL				
	Add GST @ 18% on Total as applicable				
Not	e: the vendor have to provide LAN diagram after completion	of the w	ork alon	g with the b	ill, without it

(IN WORDS) RS

SIGNATURE OF CONTRACTOR:

NAME OF CONTRACTOR:

ADDRESS OF CONRACTOR: