

**PRICE BID**

**UPVC WINDOWS AT LHO BUILDING AT PATNA**

<b>Sl. No</b>	<b>Particulars of Items</b>	<b>Unit</b>	<b>Quantity</b>	<b>Rate (Rs.)</b>	<b>Amount</b>
<b>1.</b>	Removal of old window and disposal and stacking the same within the LHO premises as directed by Bank including the cost of labour, mechanical tools and transportation, mending good the damages with all job of removal, disposal and transportation complete as directed.	<b>No.</b>	<b>742</b>		
<b>2.</b>	Providing and fixing factory made UPVC white/colour Sliding/Openable single shutter glazed window up to 1.50 m in height dimension comprising of uPVC multi-chambered frame with in built roller track OR upvc frame and sash extruded profiles duly reinforced with 1.60+/- 0.2 mm thick galvanized mild steel section made from roll forming process of required length(shape & size according to uPVC profile), appropriate dimension of uPVC extruded glazing beads and uPVC extruded interlocks. EPDM gasket, wool pile, zinc alloy(white powder coated) touch locks with hook, zinc alloy body with single nylon rollers(weight bearing capacity to be 40 kg), G.I. fasteners 100x8 mm size for fixing frame to finished wall and necessary stainless steel screws etc. Profile of frame & sash shall be mitred cut and fushion welded at all corners, including drilling of holes for fixing hardwares and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with with weather proff silicon sealant over backer rod of required size and approved quality, all complete as per approved drawing & direction of Engineer-in-charge. (Toughen glass of 8 mm thickness used for glazed part with silicon sealant AND AS PER REQUIREMENT). Note : For uPVC frame and sash extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Variation in profile dimension in higher side shall be accepted	<b>Sq.m</b>	<b>1242.00</b>		

<p>but no extra payment on this account shall be made.  Two tracks two panels sliding window OR  openable one shutter made of (big series) frame  67x50 mm &amp; sash 46x62 mm both having wall  thickness of 2.3+/- 0.2 mm and single glazing  bead/double glazing bead of appropriate dimension.  (Area of window above 1.75 sqm upto 2.50 sqm)  with all complete job including all types of cost and  fixture and as directed by the Bank.  Brands : Velvet Finestra, Aster, Finesta, JB Venture,  TSS or equivalent as approved by Bank.  Bank will finalize the brand and Vendor to arrange  accordingly.</p>				
---	--	--	--	--

**Total :**

GST Will be paid extra as applicable