## Schedule of Quantities for Internal Electrical and other allied Work of SBI civil line Branch Sagar

S.N	Description of items	Qty	Unit	Rate	Amount
1	ELECTRICAL WIRING				
	Providing, fixing, testing and commissioning of POINT WIRING of any length for light point/Wall fan point/Exhaust fan point/ Call bell point/ including call bell/ including fan box( if required), 'S' type fan hook etc with 3 X 1.5 Sq.mm(P/N/E) PVC 650V/1100V Grade FRLS WIRE insulated copper conductor single core multi strended wire in 16 SWG(Medium Gauge) stove enamelled rigid steel conduit 20mm/25mm with conduit accessories like bend, junction box etc in concealed/surface manner as per site requirment with suitable Modular Switches/Sockets with plate and Metal/PVC box,Scaddle, angle bracket (if required), 3 plate ceiling rose/bulb holder etc. The floor/roof/wall junction box shuold be of MS(heavy duty) box of suitable size and covered with Steel finish Steel cover sheet by screw tight and gasket to avoid water/dust insertion. The item includes Circuit wiring from DB to the switch board with 3x2.5 Sq.MM. The above wiring carried				
	out surface or recess in wall/floor/roof should be cutting by cutter/chiesling, replastering, curing, painting with uniform and smooth finish by specilised workman ship and making the surface neat afterwards complete in all respect as per direction of Bank Engg. (EACH Circuit to take NOT MORE than 7-8 points) The conduit/ Flexible conduit/junction box/metal modular box etc must be joined by gland and check nut at both ends. (each circuit to be controlled by one MCB). The colour code of wire are as under: Phase- Red, Neutral- Black, Earth-Green Make of Material for items of BOQ:- (i) Modular Type Switch/socket/step electronic fan regulator, plate, box, TV/telephone, bulb holder/3 pin ceiling rose with all accessories:-Lergand/ Anchor(Roma)/MK/ Crabtree (ii) MS conduit/PVC conduit with all accessories:-BEC/AKG/NIC/Precision (iii) PVC insulated copper wire(FR) 650V/1100 V grade:- Finolex/RR cable/ Havells				
а	Providing and fixing of point wiring with above specifications. One light point controlled by one switch.	98	Nos.		
b	Providing and fixing of point wiring with same above specifications. Two light points to be controlled by one switch.	30	Nos		
С	Providing and fixing of ceiling fan point controlled as under (i) one 6 amp switch (ii) one no stepped electronic regulator of two module type.	36	Nos.		
d	providing and fixing 6 Amps Plug Points with same specs as above and install along with same light switchboard	20	Nos		
e.	Master switch of 16 Amps( Only Grey/Golden/Wooden colour other than white colour) to install alongwith same light switch board to control all light as a master switch ON/OFF in each switch board	10	Nos		
2	6 AMP. POINTS ON SEPARATE BOARD :Supply,fixing,testing and commissioning of 1 No 6 A Multi Socket with 1No. 6 A switch (Modular type) with cover plate, sheet steel box / PVC modular box etc on surface / concealed manner I/c electrical connections and making good all the damages, painting, cleaning the site etc complete including all accessories as per site requirement and as directed.  (Minimum two and Maximum three points are loop with one circuit as mentioned beolw)	26	Nos		

				T	
3	Power Wring (6 / 16 AMP. POWER POINTS). Supply, fixing, testing and commissioning of 1 No 16 A switch & 1 No.six pin 6/16 Amp. Multi Socket (Modular Type) with cover plate, sheet steel box etc on surface / concealed manner I/c electrical connections and making good all the damages, painting, cleaning the site etc complete including all accessories as per site requirement and as directed. (Maximum two points are loop with one circuit as mentioned below)	26	Nos		
4	SPECIAL POINTS: (For Computers). Supply, fixing, testing and commissioning of following Modular type switch socket with cover plate, PVC modular box on Surface / sheet steel box in concealed manner I/c electrical connections and making good all the damages, painting, cleaning the site etc complete including all accessories as per site requirement and as directed.  2 Nos. 6 A Switch + 3 Nos. 6 A, 3 pin Socket (Minimum two and Maximum three points are loop with one circuit as mentioned beolw)	48	Nos		
5	AC/Geyser Point (Single Phase). Supply, Installation, Testing and commissioning of the surface / recess mounting A.C. / GEYSER power point with the followings:  Metra Plug and Socket DBs with one Nos 20 Amp SP MCB, 20 Amp plug and socket with complete Enclosur plate and box 1 set i/c electrical connections and making good all the damages, painting, cleaning the site etc complete including all accessories as required as per site requirement and as directed by Bank Engineer.  OR Modular 32A DP 1 way switch with plate & box 1 set. + 25A & 10A twin socket  (Only one point is connected with one circuit as mentioned below)		Nos		
6	AC Point (Three Phase). Supply, Installation, Testing and commissioning of the surface / recess mounting A.C. Cassette power point with the followings:  Metal enclose Four way with one Nos 32 Amp FP MCB with complete Enclosur plate and box 1 set i/c electrical connections and making good all the damages, painting, cleaning the site etc complete as required as per site requirement and as directed. (Only one point is connected with one circuit as mentioned below)	7	Nos		
7	CIRCUIT WIRING:(FR LS WIRE) Supply, installation, testing & commissioning of FRLS circuit wiring measured in numbers with suitable size of MS conduit 1.6 mm thick and 25mm dia. The wiring in MS conduit is as per IS code. The average length of wiring around between(25-30) Mtr.				
7.a	3 X 2.5 sqmm (For UPS Circuit/6 amp Separate Board) in suitable size of 16 SWG (MMS) steel conduit as per IS code.	32	Nos		
7.b	3 X 4.0 sqmm ( For AC/Power Circuit ) in suitable size of 16 SWG (MMS) steel conduit as per IS code.	26	Nos		
8	UPS OUTGOING & OTHER FR WIRING, As Per Requirment.				
8.a	3 X 1.5 Sqmm copper multistreand FRLS wire in suitable size of 16 SWG (MMS) steel conduit.	5	R.Mtr		
8.b	3 X 2.5 Sqmm copper multistreand FRLS wire in suitable size of 16 SWG (MMS) steel conduit.	5	R.Mtr		
8.c	3 X 4 Sqmm copper multistreand FRLS wire in suitable size of 16 SWG (MMS) steel conduit.	5	R.Mtr		
8.d	3 X 6 Sqmm copper multistreand FRLS wire in suitable size of 16 SWG (MMS) steel conduit.	120	R.Mtr		

	5 X 4 Samm, Conner multistrend ERI S wire in suitable size of 16			
8.e	5 X 4 Sqmm. Copper multistrend FRLS wire in suitable size of 16 SWG (MMS) steel conduit ( For Cassettee AC)	160	R.Mtr	
9	Supplying, installation, testing and commissioning of indoor type, sectionalised, compartmentalized, MV Panel board of suitable size fabricated from CRCA sheet of 2 mm thick for frame work,enclosure and doors, 3 mm thick for gland plates with stiffers where required, having vibration free structure chemically treated with seven tank process before painting for surface treatment and powder coated,with aluminum busbar with DMC / SMC busbar supports suitable for 3 Phase 415 V 50 Hz AC supply i/c providing and fixing the following switchgear mounted thereon complete with gaskets and interconnections, connection as per specification complete as required.  ( The board shall be dust & vermin proof with suitable degree of IP protection ) NOTE: All switchgears Ics shall be equal to 100% Icu. Sheet 14 swg: panel sides,upper,lower,and Ft.doors Sheet 16 swg: back side and compartments.  Glande plates: 3 mm thick.  Cable entry: Provision at bottom and upper sides.  The above panel belongs following as under:			
1	A. 4 Nos. 600 Amp. Electrolytic grade Aluminum Bus Bars insulated with colored Heat Shrinkable PVC Sleeves & duly supported on SMC/DMC molded supports with Antitracking barriers.  B.INCOMING SWITCHGEARS:  (i) 1 No. FP 400 Amp, 36 KA MCCB with thermal magenetic trip unit., 4 Nos 600 amp Al. Bus Bars with all necessary accessories.  3 Nos 250V, LED RYB indicating lamp, Digital Energy meter, Digital Voltmeter & Digital Ammeter sutiable size of CTS, selector switches etc.  C. OUTGOING SWITCHGEARS:  (i) 1 Nos- 250 Amp, MCCB 25 KA with Al Bas Bars of 400 amp capacity with all accessories, LED indicators etc.(Main MS compartment.) & 3 Nos125 amp three pole MCCB (Other MS compartment.)  (ii) 1 Nos 250 amp onload changeover with incommer of 1 Nos- 250 Amp, 4 pole MCCB 25 KA with Al Bas Bars of 300 amp capacity with all accessories, LED indicators etc(Main MS compartment.)  (iii) Alu Bas Bars of 400 amp capacity with all accessories, LED indicators etc with direct from cos.  ( IV) 1 no. space for 250 A COS seprate compartment ( Note:- Before Placing the Panel order, firstly it Passed by The Bank Authority, otherwise it will not considered)		Nos	
10	Supply, installation, testing and commissioning of totally enclosed cubical Power Factor Correction Panel board fabricated with 14/16 swg M.S.sheet powder coated, hardware, all interconnections of suitable size of pvc insulated cu.leads with lugs, two earthing terminal on both end of panel, control wiring etc complete as required, comprising with the followings- 70 KVAR 1 No 200 A, T.P. MCCB 35 KA (As Incomer) following capacities Mix Di-electric Three phase Power Capacitor-1 Set - 20 KVAr with 60 A TP MCB.(Fixed) 3 Set - 10 KVAr with AC3 -20 A Power Contactor & 20 A TP MCB 4 Set - 5 KVAr with AC3 -60 A Power Contactor & 63 A TP MCB 1 No 12 stage Automatic power factor Correction Controller with suitable size C.T. for operation.  1 Set - VAF meter with suitable size of 3 nos C.T.'s.  4 Nos - Al. Bus Bar of 500 A 1 Set - 3 Nos. LED type RYB Indicating Lamps through SP MCB.	1	Nos	

11	Supply & Installation of SDP(Surge Protector Devicve) for general protection of main Distribution Board Legrad Make Cat No. 412247 (3P+N), 40 KA, T2- Imax 40KA/pole with complete wiring.		Nos	
11.a	Providing & fixing 6 way vertical load line double door D.B for AC with 125 Amp. TP MCCB incomer and outgoing to be 4 Nos 32 amp TP MCB, 6 Nos 32 amp SP MCB FOR AC	2	Nos	
11.b	Providing and fixing 6 way TPN double door DB for LIGHT /POWER POINTS with 63 Amp TPN , controlling 18 Nos. 10/16/32 Amps SPMCBs. & Complete.	2	Nos.	
11.c	Providing and fixing 4 way TPN double door DB for LIGHT /POWER POINTS with 63 Amp TPN , controlling 12 Nos. 16/32 Amps SPMCBs. & Complete.	2	Nos	
11.d	Providing and fixing (12) way SPDB double door type For UPS points with 1x32 Amps DP, controlling 10 Nos, 10 AMP SPMCB for <b>ups output</b>	2	Nos.	
11.e	Providing and fixing (8) way SPDB double door type For Light DB only for Emergency Lights like glow sign etc with 1x32 Amps DP, controlling 6 NO.10 A./16 AMP SPMCB For Branch, ATM & street light	3	Nos.	
11.f	Providing and fixing (4) way TPN double door type For UPS INPUT with 1x 63 Amps TPNand 63 amp DP MCB- 3 Nos & 3 Nos, 32 amp SP MCB complete (E-lobby/UPS Output)	1	Nos.	
12	CABLES			
	Supplying, unloading, storage, laying, testing and commissioning of PVC/XLPE insulated (Heavy Duty) Al/Cu conductor armoured cable suitable for working voltage upto and including 1100 V grade, laid and tied on existing overhead cable trays, or laid and tied over MS supports in masonry trenches with copper/al cable lugs, single compression brass cable glands, tapping, crimping etc. as required and all cables run with double run( 2 No.) of GI wire of 8 SWG size. The size of cables are as under:- Make of Material:- (i) PVC/XLPC Armoured cable:- Finolex, Havells, RR cable, CCI(Cable Corp. of India) (ii) Cable Termination:- Dowells, Comet			
12.a	3.5 X 185 Sq.mm XLPE. Al. armoured Cable (Main cable) <b>2 nos</b> .  One cable stand by	100	Mtr	
12.b	3.5 X 95 Sq.mm XLPE. Al. armoured Cable D.G. Set	40	Mtr	
12.c	3.5 X 50 Sq.mm XLPE. Al. armoured Cable(AC VTPN & BUS BARS)/Main cable	60	Mtr	
12.d	3.5 X 25 Sq.mm XLPE.Al.armoured Cable (POWER/LIGHT/UPS)	80	Mtr	
12.e	4X 16 Sq.mm XLPE.Al.armoured Cable (LIGHT/UPS)	60	Mtr	
12.f)	3x1.5 Sq.mm XLPE.Cu.armoured Cable (Street Light)	160	Mtr	
12.g	Excavation of cable trench below ground & back filling of trench with sand, bricks protection after laying of cable.	100	Mtr	
13	EARTHING			

	T			Γ	
(i)	COPPER PLATE EARTH STATION: Preparation of the Plate Earth Station: (As per IS:3043)  (a) Excavation of hard rocky earth, soft murrum, hard murrum etc and back filling with black cotton soil for the earth station, the earth pit size is 1000 mm X 1000 mm X 2500 mm.  (b) Supply and fixing of Copper Plate of Size 600 mm X 600 mm X 3.0 mm thick.  (c) Fixing of 50 mm X 6 mm, 3 Mtrs copper strips from Copper Plate to earth terminal including brazing/welding at plate etc.  (d) Supply and laying in position 19 mm, 2 Mtrs G.I "B" Class pipe for watering with reducer/funnel with mesh.  (e) Supply and Fixing of the following in the earth station.  (i) 75 Kg. Charcoal.  (ii) 15 Kg. Original Salt.  (iii) Black Cotton soil of adequate amount.  (f) Construction of earth pit chamber including necessary brick work concrete, plastering, S/F of C.I Cover of size 12" X 12" complete as per site requirment.	2	Nos		
(ii)	G.I.PLATE EARTH STATION:  Preparation of the Plate Earth Station: (as per IS:3043)  (a) Excavation of rocky earth, soft murrum, hard murrum etc and back filling with black cotton soil for the earth station, the earth pit size is 1000 mm x 1000 mm x 2500 mm deep.  (b) S/F of G.I. plate of size 600 x 600 x 6.0 mm thick.  (c) S/F fixing 50 mm x 6 mm, 3 mtrs G.I, strips from G.I.plate to earth terminal including brazing / welding at plate etc.  (d) Supplying and laying in position 19 mm, 2 mtrs G.I. `B' class pipe for watering.with reducer/funnel with mesh.  (e) S/F of the following in the earth station.  75 Kg. Charcoal, 15 Kg. Original Salt. and Black Cotton soil of adequate amount.  (f) Construction of earth pit chamber including necessary brick work concrete, plastering, S/F of C.I. Cover of size 12" x 12" complete as per site req.and marking its value and identification etc.	4	Nos		
(iii)	Providing and fixing Copper/GI strip as per specification compete including connection to earth electrode revetting/sweating/soldering, burying 15 cms below in all types of soil/rocks etc complete as required. (a) 25 x3 mm Cu Strip	5	Mtr.		
	(b) G.I.Strip 25 X 5 mm	80	Mtr		
(iv)	Supply and laying of 10 Sq.mm 650V/1100 V PVC grade insulated copper wire in 15 mm G.I. Pipe ISI grade including all	70	Mtr.		
	accessories complete as required.  OCCUPANCY SENSORS:-				
14	Supply, installation, testing and commissioning of occupancy sensor surface/recess mounted as per site condition complete with all wiring/conduit/Switch etc complete in all respect as per site condition as required Honeywell Make K5015/16, Siemens/Johnson Control OR Equivalent as per Bank's approved.	6	Nos		
15	TELEPHONE POINT				

(i)	Two pair, 0.61 mm dla. telephone cable tinned copper conductor, P.V.C. insulated and sheathed, fire retarding, anti termite, colour coded twisted pairs and rip cord, Double outlet The length of telephone cable upto 35 meter length or less as per site condition with shutter modular type Telephone Outlets (RJ — 11) wth suitable size MS / PVC modular boxes and it laying, fixing, testing and commissioning in suitable size 20/25 mm dia,16 SWG (Medium Gauge) thickness rigid PVC conduit with conduit accessories like bend/junction box/cover plate/sheet steel/PVC box on surface/concealed manner i/c electrical connections and making goods all the damages,replastering, painting, cleaning the site etc complete as required as per site condition. The floor/roof/wall junction box shuold be of MS(heavy duty) box of suitable size and covered with Steel finish Steel cover sheet by screw tight and gasket to avoid water/dust insertion.	20	Nos	
(ii)	Make of Material:- Delton/Finolex/RR cable Supplying and fixing of krone telephone tag block on surface/ recess mounted with its accessories suitable for the multi core telephone cable and shall accommodate tin-plated phosphor bronze connectors, the connectors shall splice unskinned cables up to 0.61 mm dia and shall be terminate both incoming and out going lines, the tag blocks shall be mounted inside, water proof box and locking arrangement and shall be fully accessible.  (A) 30 Pair tag block	1	Nos	
16	DATA CABLING FOR LAN  Droviding fiving testing and commissioning of all nodes of four pair.			
а	Providing, fixing, testing and commissioning of all nodes of four pair UTP CAT 6 LAN cables length upto 30 meter length or less as per site conditionin suitable size 20/25 mm dia, 16 SWG wall thickness rigid PVC conduit with conduit accessories like bend/junction box/ fan box etc on surface/recessed manner and making good all the damages, painting, cleaning the site etc complete as required as per site condition and as directed as required. Junction box shuld be covered with Stainless steel plate with screw with gasket for protection of water/dust. Providing, fixing, testing and commissioning of modular type Information Outlets with suitable size of MS/PVC modular boxes complete, all accessories with insulation displacement connectors etc suitable for CAT 6 UTP cabling with RJ-45 socket with testing and commissioning of STP cabling with scanner for all the nodes/switches/jack panel complete (Each point/circuit/cable from both load and source end to be marked with ferrules.)  Make of Material:- (i) Data Cable, Cat 6 cable, Switch, Jack panel, Rack, Patch cords & Other accessories:- D-Link, Legrand	44	Nos	
b	Providing and fixing Patch Panels 24 port (100 base TX) CAT 6 patch/jack panel with connector, out lets and necessary connectivity complete as required & (D-Link make)	2	Nos	
С	Providing, assembling, fixing, testing and commissioning Floor/Wall mounted RACKS for gig switches, patch panels etc including cooling DUAL fan trays, a 10 Point PDU, Fixed Trays as necessarycomplete.  9 U wall mounted RACK	2	Nos	
d	Providing and fixing of flowing factory fabricated Patch cords.			
	(UTP/CAT 6 complete with connector on both side.) for 1 Mt. long	44	NI -	
i		41	Nos.	
ii	for 2 Mt. long	40	Nos	
е	Providing, fixing,testing and commissioning of four pair CAT 6 LAN cable in suitable size of 20/25mm PVC medium gauge 16SWG conduit including all accessories	100	Mtr	

	TV POINT:-Supply, installation, testing and commissionig of TV			
	TV POINT:-Supply, installation, testing and commissioning of TV			
17	point(Modular) with RG-6 cable in the Medimum Gauge 1.6	1	Nos	
	mm PVC Conduit with all accessories complete in all respect			
	Supply and installation of Vinyl sticker for on Electrical DBs			
18	like, "Switch Off at Night", Switch Off For Safety, etc	20	Nos	
	Making & Providing of 3 sets of Asbuilt Drawing with coloured print			
19	for entier Electrical work (Power/UPS/Light/Data/Telephone/AC etc.)	1	Lum	
'3	To entier Electrical work (i ower/or o/Eight/Data/Telephone/AC etc.)	'	sum	
	as advised by the Bank's Authority.			
	Description of light /fan fixture			
	LED LUMINARES:- 2' x2' (FULL GLOW TYPE)			
	LED light fittings (600 X600mm) dimension suitable for grid/gypsum			
00	ceiling complete with its electrionic driver as required per instruction		Niss	
20	of Bank's Model No are as under:- PHILIPS:- RC380B G2 LED 35S-	60	Nos	
	6500 PSU OD WH LED (FULLGLOW)			
	WIPRO:- CRCO1ORO 38 HP57			
	HAVELLS:- LHECDIL7IL1W036 (Edge- Lit) LED DOWNLIGHTER:			
	15 Watt, recessed mounted circular down lighter , 6" dimension with			
	complete its electronic driver are as under:-			
21	PHILIPS:- GREENLED-DN193B LED-12S-6500 PSU	50	Nos	
	WIPRO:- IRIS LED LD 71-121-XXX-50-XX			
	HAVELLS:- LHEBJNP ZPZ 1W 015(ENDURA LOW DEPTH)			
	CG:- LC DD-15-CDL,  External Street LED Light- Providing & Fixing of 45 watt LED light			
	fixture, pressure die cast aluminium housing, heat resistant glass, IP			
22	65 protection & better optics for uniform distribution. PHILIPS,	4	Nos	
	WIPRO, HAVELLS, CG			
	External Street LED Light- Providing & Fixing of 30 watt LED light			
23	fixture, pressure die cast aluminium housing, heat resistant glass, IP	8	Nos	
	65 protection & better optics for uniform distribution. PHILIPS, WIPRO, HAVELLS, CG			
	LED Spot Light, 3 Watt, 2/3"(Inches) size as per site requirment.			
24		6	Nos	
	PHILIPS, WIPRO, HAVELLS, CG			
	LED COVE/ STRIP LIGHT WITH ITS ELECTRONIC			
25	DRIVER( BLUE COLOUR):- Supply, installation, testing and	150	N/I+r	
25	commissioning of bright LED strip light with its electronic driver complete as required.	130	Mtr	
	PHILIPS, WIPRO, HAVELLS, CG			
	Providing & fixing of "Digital Clock" /Digital Panel indicating Time,			
26	Day, Date, Temperature at outside of big size, as suitable over the	2	Nos	
	facade as advised by the Bank with standard power back up. Make:-	_	1100	
	Ajanta, Titan BOX TYPE LUMINAIRES: LED TUBE FITTINGS,			
27		22	Nos	
	1200mm, 18/20 Watt PHILIPS/WIPRO/HAVELLS/CG CEILING FAN:			
	Single phase heavy duty grease filled double ball bearing,			
	aerodynamically designed heavy gauge aluminium blades, copper			
28	wounded and impregnated silicon stamping motors etc	36	Nos	
	1200 mm sweep, brilliant white			
	l ·			
	CG/USHA/ ORIENT/HAVELLS  EXHAUST FAN:-			
	Single phase, 300mm sweep, 900 rpm, metallic exhaust fan of the			
	following single phase Exhaust fan continuously rated, capacitor start			
	and run type, totally enclosed and ruggedly built, pre lubricated			
29	double ball bearing, copper wounded, A & E class insulation,	6	Nos	
	dynamically balanced, below 40 db sound level etc, front cover with			
	grill/gravity louver for protection purpose with 12 mm plywood			
	complete in all respect make as under: CG/USHA/			
	ORIENT/HAVELLS/ALMONARD/ALSTOM			
30	Charges for servicing of L.T. Panel including , cleaning, oiling ,	1	nos.	
	greacing etc. complete.			
	19			

				-
31	Charges for servicing of H.T. Yard including cleaning, oiling, tightning of jumpher, clamp etc, including taking shut down.	1	nos.	
32	Supply, fixing & Replacement of LED Indicator (RYB)	18	nos.	
33	Supply, fixing & replacement of 11 K.V. A.B. Switch complete set	1	set	
34	Supply, fixing & replacement of 11 K.V.D.O.set complete set	1	set	
35	Charges for painting of H.T.Yard including painting with Aluminium paints in pole,chanel etc. complete as per site	1	nos.	
36	Supply, fixing & filling of transformer oil in transformer for toping	60	ltr	
37	Painting of Transformer base with exterior emulsion paints.	1	nos.	
38	painting of chain link fencing with Aluminium paints & brick wall paints with exterior emulsion paints. Fencing wall	1	nos.	
39	Supply & laying of ACSR conductor for jumpher as site req	15	mtr	
40	charges for repairing of H.T. yard earth station with painting of chambers & nomination with paints of earth station etc.	1	job.	
41	Supply, fixing & repalacement of 22 KV post insulator	2	nos.	
42	Supply, fixing & replacement of 11 KV D.O. barrel with H.T. Fuse	3	nos.	
43	Supply, fixing & replacement of RYB Colour Sleave in jumpher	60	mtr	
44	Charges for cleaning of green grass in yard	1	job.	
45	Repairing of earthing chamber with namination etc.	1	job.	
46	Supply, fixing & replacement of 11 K.V. Lightning Arrestor set	1	set	
47	Supply, fixing & fixing of coper flexible cable in A.B. Handle	1	set	
48	Supply, fixing & replacement of breather with Silica gel	1	nos.	
49	Making/ Provision of interlocking conection with A.B. switch & switch gear	1	job.	
50	Supply, fixing & speading of 40mm gitti in H.T. Yard	300	cuft	
51	Removal and dismentalling of all existing old wiring, switchgears, DBs, changeover, main switch, old casing capping, old wooden	1	job.	
53	BuyBack of old Electrical Main Panel with Light fixtures as avilable at site/as directed by Bank official	1	Job	
54	Grand Total (Excluding GST)			

A 1 // 1	<b>,</b>
	)