

PRICE BID	
STATE BANK OF INDIA	
TENDER FOR PROPOSED INTERIOR FURNISHING WORK OF SBI TALOJA MIDC BRANCH, P21, MIDC TALOJA, TAL. PANVE, DIST. RAIGAD - 410208	

ABSTRACT					
Sr. No	Items of Work	QTY.	Rate	Unit	Amount
	<u>FURNITURE</u>				
{A}	<u>COUNTERS</u>				
A01	<p>SINGLE WINDOW COUNTER WITH SIDE TABLE & FRONT GLASS PARTITION</p> <p>Table Size - 5'-0" X 3'-0" X 2'-6" Side Table - 3'-6" X 1'-6" X 2'-6"</p> <p>Providing and Fixing cash counter with side table in made of 18 mm thk. BWR (ISI 303) ply frame work for top, stiffner, verticals, shelves, apron, sides, drawer unit, shutters, customer Top, foot rest, 12mm thick BWR (ISI 303) ply for drawer sides, sliding shutters, front Apron and 6mm thick BWR (ISI 303) ply for side table back, drawer bottom, drawer unit back along with matching color PVC laminate edge bidding & teak wood supports for fixing of top. Cash counter shall have 900 mm in Depth and 750 mm in height or as per Bank's Requirement.</p> <p>The Cash counter writing top and side table top and 1.00mm thk. appd. color solid core laminate along with 12mm thick PLAIN Glass partition fixed above Table top upto 7'-0" in ht.</p> <p>The glass fixed with "D" type Stainless Steel bracket. The Cash counter shall have 1 No. of drawer unit having pencil drawer 4" deep & 3 Nos. of equal drawers below pencil drawer or as per the Bank requirements and side table shall have 2 Nos. of drawers at top and sliding shutters below the drawers.</p> <p>All the external surfaces i.e. counter & side table, drawer side etc. shall have approved make/ colour 1.0mm thick full core Solid core laminate finish and 0.8mm thick white laminate for internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE/DORMA make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles, Stainless Steel Grommet (wire manager), 2" dia S.S. Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S. Drawer chanel Powder Coated CPU Hanger etc. complete as per detail drawing and instructions of the Architect/Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Per Number</p>	15.00	Rft		
A02	<p>Branch Manager Table With Side Table - Veneer laminate finish</p> <p>Table Size - 7'-0" X 3'-0" X 2'-6" Side Table - 3'-6" X 1'-6" X 2'-6"</p> <p>Providing & Fixing Branch Manager Table with side table made out of 18mm thick BWR (ISI 303) ply frame work for table and side table tops, sides, apron, shelves, drawer units, shutters, drawers front, stiffeners, borders, 12mm thick BWR (ISI 303) ply for drawer sides, keyboard, borders, foot rest and 6mm thick BWR (ISI 303) ply for drawer unit back, drawer bottom, side unit back, grooves etc. with matching color PVC laminate edge beading.</p> <p>The table shall have one drawer unit with one tea tray, one pencil tray 100 MM deep & 3 Nos. of equal drawers below.</p> <p>The side table shall have drawers at top & sliding shutters below along with provision for C.P.U. Hanger.</p> <p>The table shall have 750 mm in height and side table shall have 750 mm in height. table top & side table top shall finished with 3 mm thk. Appd. Veneer with 10 mm thk. Glass on table top.</p>				

Cont...2

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
2					
	<p>All the external surfaces i.e.counter & side table, drawer side etc. shall have approved make/ colour 1.0mm thick approved solid core laminate finish and 0.8mm thick white laminate for internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE/DORMA make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles,Stainless Steel Grommet (wire manager), 2" dia M.S.Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S.Drawer chanel Powder Coated CPU Hanger including supply & fixing flat screen holder - single arm (ebco make)etc. complete as per detail drawing and instructions of the Architect/Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Per Number</p>	1.00	NOS.		
A03	<p>Officer Table With Side Table -Laminate <u>Table Size</u> - 5'-0" X 2'-6" X 2'-6" <u>Side Table</u> - 3'-6" X 1'-6" X 2'-6"</p> <p>Providing & Fixing Officer's Table With Side Table made out of 18mm thick BWR (ISI 303) ply frame work for table, side table, sides, top, front apron, shutters, unit sides, 12mm thk BWR (ISI 303)ply for drawer sides, key board sides, sliding shutters, foot rest,6mm thick BWR (ISI 303) ply for back, drawer unit back, drawer bottom etc. with matching color PVC laminate edge bidding etc. complete.</p> <p>The table front shall have 12mm thick BWR (ISI 303) ply panels with 4" X 12mm thk. Border along with one drawer unit with one drawer for pencil tray, three Nos. of equal drawers, key board drawer, CPU Hanger & side table shall have 3" deep 2 Nos. drawer at top & sliding shutter below the drawers etc. complete.</p> <p>All the external surfaces i.e.counter & side table, drawer side etc. shall have approved make/ colour 1.0mm thick full core Solid core laminate finish and 0.8mm thick white laminate for internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE/DORMA make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles,Stainless Steel Grommet (wire manager), 2" dia M.S.Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S.Drawer chanel Powder Coated CPU Hanger including supply & fixing flat screen holder - single arm (ebco make)etc. complete as per detail drawing and instructions of the Architect/Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Per Number</p>	3.00	NOS.		
A04	<p>GM & CR.Seller Table -Laminate <u>Table Size</u> - 5'-0" X 2'-6" X 2'-6"</p> <p>Providing & Fixing Officer's Table made out of 18mm thick BWR (ISI 303) ply frame work for table, sides, top, front apron, shutters, unit sides, 12mm thk BWR (ISI 303)ply for drawer sides, key board sides, , foot rest,6mm thick BWR (ISI 303) ply for back, drawer unit back, drawer bottom etc. with matching color PVC laminate edge bidding etc. complete.</p> <p>The table front shall have 12mm thick BWR (ISI 303) ply panels with 4" X 12mm thk. Border along with one drawer unit with one drawer for pencil tray, three Nos. of equal drawers, key board drawer, CPU Hanger etc. complete.</p> <p>All the external surfaces i.e.counter , drawer side etc. shall have approved make/ colour 1.0mm thick full core Solid core laminate finish and 0.8mm thick white laminate for internal surfaces including necessary hardware of HETTICH /KICH /HAFFLE/DORMA make i.e. Stainless Steel Hinges, Ball Catches, Stainless Steel Locks, approved design Stainless Steel Handles,Stainless Steel Grommet (wire manager), 2" dia M.S.Pipe for footrest, teak wood 3" deep drawer for key board, Twin telescopic S.S.Drawer chanel Powder Coated CPU Hanger including supply & fixing flat screen holder - single arm (ebco make)etc. complete as per detail drawing and instructions of the Architect/Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Per Number</p>	2.00	NOS.		

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
3					
A05	<p>Cheque Writing Desk</p> <p>Dimensions :- 3'0" x 1'0" x 3'0"</p> <p>Providing & Fixing Cheque writing desk made out of 18mm Thk. BWR (ISI 303) ply Framework for verticle , Sides, Bottom, Back & 10mm Thk. Glass top in one piece with 8mm thk. Glass verticle at 4" c/c. or as per bank requirement. All external & internal surfaces shall have 1mm. Thk approved color laminate including edges etc. complete as per the detail drawing & instructions of Architect/ Engineer</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Per Number</p>	1.00	NOS.		
A TOTAL OF TABLE					
{B} B01	<p>FULL HEIGHT PARTITION</p> <p>BOTH SIDE LAMINATE FINISH PARTITION</p> <p>Providing and Erecting in position approximate 9'-0" to 9'-6" in height partitions to be made out of 2" X 2" X 1.5mm thick Aluminum Tubular section frame work 2'-0" c/c bothways (Vertical & Horizontal) fixed with 2" X 2" X 2.5mm thick Aluminum Angle Cleats with Pan Headed Screws covered with 12 mm thk. BWR Plywood from both sides fixed with Flat Headed Metal Screws. The aluminum members of partition shall rigidly fixed to the existing Ceiling / Floors / Beams & Side Walls, whichever is applicable & as directed, the alternate members and corner members fixed upto existing Slab, Beams, whichever applicable.</p> <p>All exposed surfaces of the partition shall have approved make / color 1.0 mm thick laminate from both sides or as per site requirements etc. complete. The necessary openings in the partitions shall be provided for A.C. Grill, Electrical Conduits, Electrical Switches, etc. complete as per requirements / instructions of Architect/ Bank's Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	100.00	SFT		
B02	<p>12 MM THK. TOUGHENED GLASS PARTITION</p> <p>Do as above Item No. B01 along with Providing & Fixing Saint Gobain / Asahi India or equivalent make 12 mm thk. TOUGHENED float glass for full height partition in single piece or 2 or 3 pieces (minimum 2400mm in length) with computerised diamond cut & diamond edge polish. The TOUGHEN Glass fixed with Brush finished Stainless Steel Runner for top, bottom, sides or as per site requirements including making required cutouts/ holes for Locks, Handles, "V" cut grooves etc. along with Sunk Headed Metal Screws, adhesive, nails etc. complete as per the site requirements, detail drawing and instructions of Architect / Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	145.00	SFT		
B03	<p>LOW HEIGHT PARTITIONS</p> <p>BOTH SIDE LAMINATE PARTLY 10MM THK. GLASS WITH WICKET GATE</p> <p>Do as above ITEM NO.B01 (Both Side Laminate), but low height partition shall have 4'-6" in height or as per the site requirements low height partition shall have both side approved make / color 1.0mm thick solid core laminate long with 10mm thk. Plain glass fixed above 3'-0" in height or as per detail drawing. Glass to be fixed with Brush finished Stainless Steel Runner for Bottom & Side etc. complete as per the site requirements, detail drawing and instructions of Architect / Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	145.00	SFT		
B TOTAL OF PARTITIONS					

Cont...4

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
4					
C	DOOR				
C01	12MM THK. TOUGHENED GLASS DOOR WITH DOOR FRAME - MAIN DOOR Providing & Fixing cabin glass door made out of Saint Gobain/Asahi India make 10mm thick toughened glass in single piece with computerised diamond cut & diamond edge polish for cabin doors including making required cutouts, holes for locks, handles, pivot, patch fittings, inclusive of providing & fixing DORMA /Haffle/ Hettich / Kich Floor Spring, Top Pivot, patch fittings, Hinges, Handles, Locks, Metal Screws, Nails, Fevicol, carting away debris out of compound, cleaning the site etc. complete as per instructions of Architect / Engineer. <u>Mode Of Measurement</u> - Length X Height	25.00		SFT	
C02	SOLID CORE DOOR WITH DOOR FRAME (Both side Laminate finish) Door Size :- 1 m x 2.1 m Providing & Fixing solid core flush door with door frame made out of 100 mm X 63 mm IMPORTED teak wood frame work in required shape and shutters made out of 32mm thick approved make Solid Core Flush Door along with approved make/color 1.00 mm thick appd. Color/ design laminate from both side , 6mm thick imported teak wood edge beading. The edge of the Doors / Shutters frame at edge finish with melamine polish of laminate matching shade along with approved make / design hardware i.e. Dorma / Haffle / Hettich / Kich Door Closure,S.S. Hinges, Stainless Steel Handles, Locks, Signage's, Name Plate with necesary hardware i.e. Sheet Metal Screws, Nails, Fevicol etc. complete as per detail drawing & instructions of the Architect/ Engineer. <u>Mode Of Measurement</u> - Per Number	1.00		No.s	
C03	FIRE DOOR FOR SERVER DOOR (2 HOURS FIRE RATED) Providing & Fixing G.I. fire door single leaf as per below specifications: Frame: GI 1.60 mm Shuter: GI 1.20 mm shutter width / active shutter width :984 mm Frame Profile (D x H): 105 mm x 57 mm Frame Joint Type: Butt Type Frame Rebate: Single Under Cut: 9.00 mm Infill Material: Rockwool / HONEYCOMB Vision Panel Active (VPW x VPH) : 300 mm x 300 mm , 6mm Glass(Fire Shutter Thickness: 46 mm Finish : Powder coating Ball bearing: Butt Hinges Lock: Mortise Dead Lock with 70 mm cylinderl, Handle: S.S. Finish Surface door closure with standard Arm <u>Mode Of Measurement</u> - Length X Height	25.00		SFT	
C04	TRAP DOOR FOR ROLLING SHUTTER Providing & Fixing trap door for Rolling Shutter made out of 50mm X 50mm Class II C.P.T.Wood frame work covered with 9 mm thk. BWR Ply (ISI 303) from one side for shutters & 50mm X 75mm II class C.P.T.W. outer frame with vertical supports upto RCC slab. All the exposed surfaces shall be finish with approved make 1.0mm thick appd. color laminate on outer side & 3 coats of enamel paint on internal side including necessary approved make/design S.S. Hinges, Concealed Handle, S.S. Stopper, S.S.Lockes etc. complete as per detail drawing & instructions of the Architect/ Engineer. <u>Mode Of Measurement</u> - Length X Width	85.00		SFT	
c TOTAL OF DOORS					
{D}	PANELLING/ WALL CLADDING				
D01	LAMINATE PANELLING Providing and Fixing laminate finish paneling for walls, columns etc. made out of 2"X 1" X 1.5 mm thick Aluminum Tubular frame work at every 1'-6" c/c (Vertical /Horizontal) both ways, covered with 12 mm thk. BWR Ply (ISI 303) upto ceiling height etc. complete.				

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
5	All the exposed surfaces of the paneling shall be finish with approved make/color 1.00mm thk. laminate upto ceiling height along with groove at junction of laminate etc. complete as per site requirements, detail drawing and the instructions of the Architect/Engineer. Mode Of Measurement - Length X Height	875.00	SFT		
D02	CALCIUM SILICATE PANELLING Providing and Fixing calcium silicate finish paneling for walls, columns etc. made out of 2"X 1" X 1.2mm thick Aluminum Tubular frame work at every 1'-6" c/c (Vertical /Horizontal) both ways, covered with 8 mm thk. calcium silicate board upto ceiling height with Sunk Headed Metal Screws as per the site requirements in required shape. All the exposed surfaces of the paneling shall be finish with approved make/color three cost Plastic Emulsion paint etc. complete as per site requirements, detail drawing and the instructions of the Architect/Engineer. Mode Of Measurement - Length X Height	325.00	SFT		
D03	Aluminium Composite Panel Cladding Providing,applying,fabricating and fixing panel of aluminium composite panel cladding in approved shape made out of 4 mm thick ACP sheet material consisting of 3mm thick FR grade mineral core following NBC part IV Fire and life safety (having 2 hours fire resistance in accordance to ASTM E119-12 and BS476 part 6 and 7 class O) sandwiched between two aluminium sheets (each 0.5 mm thick of AA 5005/AA3105 grade) The aluminium composite panel cladding sheet shall be coil coated with kynar 500 based PVDF/Lumiflon based fluopolymer resin (having 70:30 ratio of PVDF and acrylic) coating of approved colour and sg=hade on top face and polymer (service) coating of bottom face as specified using stainless steel screws,nuts,bolts,washers,cleats,weather silicon sealent,backer rods etc .overall weight of the ACP shall not be less than 7.5 Kilogram/ One Square Metre) Mode Of Measurement - Length X Height	325.00	SFT		
D04	Toughned Glass Partition Between ATM Machines Providing & Fixing 12 mm thk. Toughned glass partition as per Bank's approved design with patch filling of approved make/brand at top to a support directly from wall with heavy duty S. S. brackets with profile 'C' shape approved design brush finished. All exposed edges of glass to be machine polished. Complete as per design and instructions by Architect/Engineer. Mode Of Measurement - Per Number	3.00	No.s		
D	TOTAL OF PANELLING				
{E}	FALSE CEILING & PAINTING				
E01	GYPSUM FALSE CEILING P/Fixing Gypsum Board false ceiling of Gypsum India or equivalent make. <u>METALLIC GRID</u> (conforming to IS:2095:1982): - The metallic grid shall consists of GI Perimeter channels of size 27mm X 0.5mm thick having one flange of 20mm & another flange of 30mm, GI Intermediate channel of size 45mm X 0.9mm thick with two flange of 15mm each at 1200mm center to center, GI hanger of size 25mm X 10mm X 0.5mm thick at 1200mm center to center distance along with GI Cleat & Steel Expansion Fasteners The Ceiling section of 0.5mm thickness having curled wedge of 51.5mm and two flanges of 26mm each with lips of 10.5mm at 450mm c/c. along with connecting clips of 12.5mm drive fixed with sheet metal screws at 230mm c/c. METAL GRID INSTALLATION: - Perimeter channel fixed to all side of walls, partitions, beams, columns, whichever applicable fixed with sheet metal screws with raw alplugs at 225mm center to center & intermediate channels at 1200mm center to center including GI steel hangers fixed to the slab, beams soffit, whichever with GI cleats & steel expansion fastners.soffit, whichever with GI cleats & steel expansion fastners. The ceiling section placed in a direction perpendicular to the intermediate channel at 450mm c/c. fixed to the intermediate channel with the help of connecting clips & 12.5mm dry wall Sheet Metal Screws at 230mm c/c. Distance.				

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
6					
	<p><u>COVERING</u>: - Fixed 12.5mm thick gypsum board to the metal frames in required shape in taper / square edges of the gypsum board shall be finish with filling the joints with fibre tape finish the surfaces in one level & line finish with three coats of approved make / shade Plastic Emulsion paint including making grooves, cutouts for Light Fittings, AC Grills, AC Diffusers, Smoke Detectors, Sprinklers System, Security System etc. as per the other vendors requirements along with additional frame for Light Fittings & AC Grills, scaffolding etc. complete as per instructions of Architect. <u>OR</u> do as per Manufacturer's Specification. Cutouts will not be deducted while measuring the ceiling area.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Width</p>	1000.00	SFT		
E02	<p>MINERAL FIBRE FALSE CEILING</p> <p>Providing & Fixing mineral fibre board false ceiling of AMF / ARMSTRONG or equivalent false ceiling system (THERMATEX FEINSTRATOS MICRO PERFORATED with FINELINE of 15mm GRID with Black GRID REVEAL) of grid size 600mm X 600mm with G.I. ceiling frame work as per Manufacturer's specifications including filling of Acoustic ceiling tiles 15mm thick of size 600mm X 600mm microlook having 0.55 NRC, 38dB & 95% RH and 90% Light Reflector.</p> <p>Smoke Development - 0% Fire Resistance - 120 Minutes A2-s1, d0 & DIN EN 13501-1 The cost of include the cost of frame work for fixing light fixtures. The light fixtures shall not be fixed directly on to the tiles. Complete in all respects as per detail drawings and instructions of Architect. Cutouts will not be deducted while measuring the ceiling area.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Width</p>	1100.00	SFT		
E03	<p>PLASTIC EMULSION PAINT</p> <p>Removing the existing color wash/distemper/oil bond distemper / plastic/ luster etc. paint by scrapping, washing and scrubbing. The surface shall then be allowed to dry for atleast 24 hours. It shall be then sand papered to give a smooth & even surface. Holes shall be filled with BIRLA putty made of plaster of paris. Then first coat of primer to be applied. After this necessary leveling shall be done with putty and second primer coat shall be applied. The plastic emulsion paint of approved shade and make shall be applied in minimum 3 coats (finishing paint) including scaffolding, cleaning the floors, fittings, furniture's, ladders, glasses, removing of debris out of the compound etc. complete as per the instructions of the Architect / Engineer.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	2650.00	SFT		
E04	<p>Texture Paint</p> <p>Preparation of surface including scrapping wherever required to remove all loosely adhered particles followed by washing with water using wire brush to ensure thorough cleaning.</p> <p>Providing and applying one coat (water proofing Coat) of fibre reinforced membrane paint, having crack bridging ability up to 2.00 mm, superior ant carbonation & water proofing property with life of 5 years.</p> <p>Providing & applying 1.5-2.0 mm thick Synthetic Texture by mixing the product with clean water thoroughly with an electrical mixer for 3-5 minutes until the desired homogeneous paste is achieved so as to ensure that the mixture is free from lumps before use.</p> <p>Applying minimum thickness of 1.5-2.0 mm of homogeneous paste those prepared on the plastered surface with a steel trowel so as to have the desired texture finish and design. If necessary, a second layer may be applied.</p> <p>The entire work should be carried out strictly in accordance with the manufacturers' specifications including necessary scaffolding etc. and execution of work at all heights and locations complete as per the Direction of Engineer / In-Charge.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	50.00	SFT		

Cont...7

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
7					
E05	<p>Enamel Paint</p> <p>Providing and applying Synthetic Enamel Paint on doors / windows frame, shutters, railing, grills, gates etc. in two or more coat of approved brand and shade including a priming coat as per manufacturs' specifications, after necessary preparation of surface with scrapping, sand paper rubbing, applying putty, including necessary scaffolding etc.complete as directed by the Engineer-incharge. Paint: Asian, Nerolac, Berger, Dulux</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	200.00	SFT		
E05	<p>Wall Paper</p> <p>(Basic Cost: Rs. 120/sqft)</p> <p>Providing & fixing wall paper as approved by Architect/Bank's Engineer-in-charge. The wall paper is to be fixed on one coat of primer and one coat of fine finish surface/wall/false ceiling as per approved design with necessary glue and to be finished without stains, bubble, etc. Complete as per design, pattern & directions of the Architect/Bank's Engineer-in-charge. Make-D'decor/Gold Leaf/Marshalls or any approved make.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	50.00	SFT		
E TOTAL OF FALSE CEILING & PAINTING					
{F}	STORAGES				
F01	<p>FULL HEIGHT STORAGE - LAMI. (450 MM DEEP)</p> <p>Providing & Fixing full height storage 450mm deep made out of 25 mm thick</p> <p>BWR (ISI 303) ply frame work for sides, bottom, shelves, top, shutters, verticals & 100mm wide X 12mm thick BWR (ISI 303)ply border for shutters fixed vertically, horizontally, 6mm thick BWR (ISI 303) ply for backside of storage along with teak wood edge bedding, 40mm X 25mm laminate matching color edge moulding & stainless steel pin for adjustable shelves fixing etc. complete.</p> <p>All exposed surfaces shall have approved make/color 1.0mm thick laminate including edges, grooves and 0.8mm thick white colour laminate</p> <p>to all internal surfaces along with necessary approved make/design hardware i.e. Stainless Steel Hinges with Stainless Steel Bearing (AISI 316 Grade) & Stainless Steel Pin (AISI 316 Grade),Stainless Steel Brush Finished Handles, 150mm Stainless Steel Tower bolts at top and Bottom Magnetic Ball Catches, Apporved make locks etc. complete as per detaildrawing and instructions of Architect / Engineer.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	180.00	SFT		

Cont...8

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
8					
F02	<p>LOW HEIGHT STORAGE - LAMINATE</p> <p>Providing & Fixing low height storage 450mm deep made out of 19mm thick BWR (ISI 303) IS 303 ply frame work for sides, bottom, shelves, top, shutters, 6mm thick BWR (ISI 303) ply for backside of storage along with matching color PVC laminate edge bidding.</p> <p>All exposed surfaces shall have approved make/color 1.0mm thick laminate including edges, grooves & 0.8 mm thick white color laminate to internal surfaces along with necessary approved make hardware i.e. Stainless Steel Hinges with Stainless Steel Bearing (AISI 316 Grade) & Stainless Steel Pin (AISI 316 Grade), Stainless Steel Brush Finished Handles, 150mm Stainless Steel Tower Bolts at top & bottom, Magnetic Ball Catches, Locks, carting away debris out of compound, cleaning the site etc. complete as per site requirements, detail drawing and instructions of the Architect.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	90.00	SFT		
F03	<p>SHUTTER FOR ELECTRICAL PANEL</p> <p>Providing and Fixing shutters for electrical panel made out of 50mm X 40mm C.P.T. Wood frame work for sides and shutters made out of 25 mm thick BWR (ISI 303) ply with edge beading.</p> <p>All exposes surfaces shall have approved make/color 1.0mm thick laminate and 0.8mm thk. approved color laminate from inside along with 150mm wide Aluminum powder coating A.C.grill at top and bottom for exhaust including approved make/design hardware i.e. S. S. Hinges with S.Steel Bearing (AISI 316 Grade) & Stainless Steel Pin (AISI 316 Grade), Stainless Steel Brush Finish Handles, 150mm Stainless Steel Tower Bolts at top and bottom, Magnetic Ball Catches, Locks, etc. complete as per site requirements, detail drawings and instructions of the Architect / Engineer.</p> <p style="text-align: right;">Mode Of Measurement - Length X Height</p>	55.00	SFT		
F	TOTAL OF STORAGES				
{G}	<p>SUNDRIES</p> <p>G01 VERTICAL BLIND</p> <p><u>Headrail</u> :- is extruded anodized high strength. Aluminum alloy section with wall thickness of 1.2mm. The section shall have provision of approved fabric balance matching with louver fabric.</p> <p><u>Control Unit</u>:- Providing reduction gear box having the reduction ratio 3:5:1 for a very smooth operation of the blinds. This unit should consists of the planetary gear in the outer housing, 4 small transmission gear fitted in the middle assembly and a gear attached to central sprocket unit.</p> <p><u>Chain Tilter</u>:- Shall be made of plastic bead of diameter 4.5mm through which 2mm thick polyester cord should pass. The patch of the beads shall be 6mm. The chain should drives the sprocket fixed in the end control unit to rotate the louver by 180 Degree.</p> <p><u>Carriers</u>:- Are moulded should have anti friction additive.</p> <p>It should have a housing with wheels, having a gear and worm mechanism driven by tilt rod fixed to end control unit, which should rotates vertical worm and fixed with a PVC stem to hold the vertical louvers.</p> <p><u>Tilt Rod</u>:- Should be of extruded aluminum having 3 key ways.</p> <p>The tilt rod should be fixed at the end control unit & should drives the carrier gear mechanism for rotting the louvers with the Aug diameter of 5.8mm.</p> <p><u>Installation Bracket</u>:- Should be of galvanized steel fitted with pressure clips made out of spring steel to hold the head rail.</p> <p><u>Spacers</u>:- Should be of moulded plastic, for proper spacing of the runners on Tilt Rod as per actual site size with the width of the louvers.</p> <p><u>Louvers</u>:- Made of fabric in varying widths of 125mm fabric (select) with fast color & possess protective Scotchguard.</p>				

Cont...9

Sr. No	Items of Work	QTY.	Rate	Unit	Amount
9	<p><u>Bottom Mechanism</u>:-It should have bottom weight made of powder coated galvanized steel for maximum corrosion resistance. It should be of 100mm on the width of the louvers & fitted in the bottom pocket of louvers. The bottom weight should attached with bottom chain of PVC balls of 2mm Diameter & equally spaced.</p> <p>"Clear Clips" should be fitted on the chain for clipping the bottom weight ends for the louvers in straight position.</p> <p><u>Cord</u>:- Should be of ABS material and consists of ABS cover steel weight.The length of the cord weight should be of 110mm weight.</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Length X Height</p>	200.00	SFT		
G	TOTAL OF SUNDRIES				
{H} H01	<p>MISCELLEANOUS FURNITURE</p> <p>DINING TABLE - LAMINATE FINISH (1500MM LONG X 1200MM WIDE X 750MM HT.)</p> <p>Providing and fixing table 1500mm long x 1200mm wide x 750mm high made out of 38mm thk. Pine flush. Provide and finish with 0.8mm thk. Laminate for below table area and provide 4.0mm thk. Veneer in 2 to 3 colour worth 140/- sft for top as approved by Architect/Bank's Engineer with 1 3/4" x 1" half round BTC moulding to be finished in PU finish. Complete as per design and direction of Architect/Bank's Engineer</p> <p style="text-align: right;"><u>Mode Of Measurement</u> - Per Number</p>	1.00	No.		
H	TOTAL OF MISCELLEANOUS FURNITURE				
i. TOTAL OF "A" TO "H"					
ii. DISCOUNT (% of i)			%		
iii. GRAND TOTAL (i-ii)					
GST WILL BE EXTRA					