

**STATE BANK OF INDIA**  
**ADMINISTRATIVE OFFICE, BHAGALPUR**  
**PRICE BID FOR CIVIL WORKS AT UDAKISHUNGANJ BRANCH**

**BRANCH : UDAKISHUNGANJ**

**UNDER RBO : MADHEPURA**

S.No	Item Description	Unit	Quantity	Rate (Rs.)	Amount (Rs.)
1	<b>BRICKWORK (FULL BRICK)</b> Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	26		
2	<b>BRICKWORK (HALF BRICK)</b> Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. Cement mortar 1:4 (1 cement :4 coarse sand)	Sqm.	20		
3	<b>PLASTER</b> 12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand)	Sqm.	240		
4	<b>REINFORCED CEMENT CONCRETE</b> Providing and laying in position ready mixed or site batched M-20 grade cement concrete for reinforced cement concrete work; using coarse aggregate and fine aggregate derived from natural sources, Ordinary Portland cement, admixtures in recommended proportions as per IS: 9103 to accelerate / retard setting of concrete, to improve durability and workability without impairing strength; including pumping of concrete to site of laying, curing, carriage for all leads; but excluding the cost of centering, shuttering, finishing and reinforcement as per direction of the engineer-in-charge. All works above plinth level upto floor V level Concrete of M20grade with minimum cement content of 330 kg /cum	cum	20		
5	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	cum	6		
6	<b>STEEL REINFORCEMENT</b> Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete. Thermo-Mechanically Treated bars of grade Fe-500D or more.	Kg	1100		
7	<b>SHUTTERING</b> Centering and shuttering including strutting, propping etc. and removal of form for Walls (any thickness) including attached pilasters, butteresses, plinth and string courses etc.	Sqm.	90		
8	<b>PUTTY</b> Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm.	350		
9	<b>PAINTING</b> Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	Sqm.	350		

10	<b><u>RAILING</u></b> Providing and fixing stainless steel ( Grade 304) railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners , stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-in charge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).	Kg	210		
11	<b><u>EUROPEAN TYPE W.C. PAN</u></b> Providing and fixing first quality European water closet of approved make EWC Constellation in white in colour including providing and fixing cistern height 80cm, width 36 cm with necessary porcelain, P/ S trap heavy duty plastic seats of approved manufacturer in approved colour, CP brass hinges, buffers etc., all complete including fixing in position with necessary holes, providing and fixing CP brass screws and connecting the outlet to the soll stack including testing the joints all complete as per specifications and as approved by the Engineer-in-charge.	Nos.	1		
12	<b><u>URINAL</u></b> Providing and fixing wall hang urinal of approved make flat back large and size of 58 cm x 38 cm x 35 cm white in colour fixed with the help of angle brackets including providing water spreader, domb, waste pipe and all complete as per the directions of the Engineer-in-charge.	Nos.	1		
13	Providing and fixing brass stop cock of approved quality of 15 mm nominal bore.	Nos.	3		
14	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. Brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: White Vitreous China Wash basin size 630x450 mm with a single 15 mm C.P. brass pillar tap.	Nos.	1		
15	Supplying and filling with sand including watering, ramming, consolidating and dressing complete.	cum	15		
16	Chequered precast cement concrete tiles 22 mm thick, jointed with neat cement slurry mixed with pigment to match the shade of tiles, including rubbing and cleaning etc. complete, on 20 mm thick bed of cement mortar 1:4 (1 cement: 4 coarse sand).	Sqm.	40		
17	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2 mm and braced with flat iron diagonals 20x5 mm size, with top and bottom rail of T-iron 40x40x6 mm, with 40 mm dia steel pulleys, complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer.	Sqm.	15		
18	Supplying and fixing rolling shutters of approved make, made of 80x1.25 mm M.S. laths with 1.25 mm thick top cover, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength conforming to IS: 4454 - part 1 and M.S. top cover of required thickness for rolling shutters.	Sqm.	17.5		
19	Providing Sal wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length all complete.	cum	0.05		
20	Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws, locking arrangement, door stopper etc.	Sqm.	2		
21	Supply and fixing of Aluminium door with chowkhats of approved make and thickness 25 mm or more for washroom including cost of tower bolt, side bolt, door handle and all other fixtures and with all complete job as directed by EIC.	Sqm.	2		

22	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. 15 mm nominal dia Pipes	metre	10		
23	Providing and fixing Ist quality ceramic glazed wall tiles 300mmx450mm conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete (make as per approved by Bank like JOHNSON, SOMANY, KAJARIA) with all complete job.	Sqm.	10		
<b>TOTAL</b>					
<b>#GST will be paid extra as per applicable</b>					