ESTIMATE FOR TILING AND SANITARY AND PAINTING WORK							
	AT OFFICER'S RESIDENTIAL COMPLEX, BHANGAGARH C3 42						
SN	Description of items	Unit	Qnty	Rate(Rs.)	Amount(Rs.)		
CATE	Dismantling tile work in floors/wall tiles etc laid in cement mortar including stacking material within 50 metres lead. For thickness of tiles 10 mm to 25 mm	sqm	30				
2	Providing and laying Vitrified tiles in different sizes (thickness to be specified by manufacturer), with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joint with white cement & matching pigments etc. complete.(Nitco/Kajaria/Johnson or equivalent)						
	Size of Tile 600x600 mm	sqm	76				
	SUB-TOTAL A						
CATE	GORY - B /PLUMBING AND PAINTING WORK						
1	Providing fitting and fixing vitreous china pedestal type water closet (European type W.C pan 400mm high) with seat and lead ,CP brass hinges and rubber buffers , CI/MS brackets , 40 mm dia flush band with fittings including painting of fittings and brackets, required. (Flushing Cistern to be paid separately) (White)		1				
	Hindware/parryware/Cera or equivalent)						
2	Supplying, fiting and fixing PVC flushing cistern with all internal fittings with CI brackets including fitting and fixing standard size CP flush pipe, union clamps etc. compete as directed and specified (pipes will be measured separately) 10 litre capacity.		1				
	Hindware/parryware/Cera or equivalent)	•					
3	Providing, fitting and fixing CP soap tray / soap dish complete as directed and specified. (Hindware/parryware/Cera or equivalent)	Each	1				
4	Providing, fitting and fixing CP towel rail complete as directed and specified.(600 mm and higher)	Each	1				
	i) General Purpose brandss(Hindware/parryware/Cera or equivalent)						
5	Providing, fitting and fixing Chrome Plated towel ring complete as directed and specified. i) General Purpose brandss(Hindware/parryware/Cera or equivalent)	Each	1				
6	Providing, fitting and fixing Chrome Plated waste coupling complete as directed and specified. i) General Purpose brandss (Hindware/parryware/Cera or equivalent)	Each	1				
7	Supplying, fitting and fixing Chrome Plated (C.P.) basin pillar tape complete as directed. Hindware/parryware brand or equivalent	Each	1				
8	Supplying, fitting and fixing Chrome Plated (C.P.) wall mixer complete as directed. Hindware/parryware brand or equivalent (a) General type	Each	1				
9	Supplying fitting and fixing Chrome Plated (C.P.) shower 15mm dia. Of approved brand as directed and specified. Hindware/parryware brand or equivalent	Each	1				
	minaware/panyware brana or equivalent						

10		Supplying fitting and fixing C.P. bib cock 15mm dia of approved brand			
III Bibbook Rong Triffeed Park	1.0	Hindware/parryware brand or equivalent			
Supplying fitting and fixing chrome plated (C.P.) stop-cock of approved brand and see as mentioned below as directed and specified. (G.I. & C.P. plios will be measured and poid separately) 11 Hindware/parayware brand or equivalent (9) Sirm dia(Angular stop cock with long thread.) (1) Supplying and fitting fixing C.P. pillar cock of 15mm dia of approved brand as specified and directed. Hindware/parayware brand or equivalent Supplying fitting and fixing Telephonic Chrome Plated (C.P.) shower of approved brand as directed and specified, (Pipes will be measured and poid separately) Hindware/Parayware brand (3) General type Providing two coats of Bild White Wall Care / J.K. Wall Putty (Water Resistant White Cement based putly for concrete/mortar walls and ceiling both internal and external) after removing all loosely achiering material from the wall surface with the help of emery stone, putly blade or wire brash and moistening the wall with sufficient quantity of clean or wire brash and moistening the wall with sufficient quantity of clean water as specified and directed by the department, (flotal thickness of two coats is maximum 1.smm), the rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on newfold (wall /cleling etc) surface after throughly browing the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand paperad smooth. Wall painting flwo coats with acrylic emulsion paint approved brand and manufacture (Asian point) 8 erger paint // CI paint/ J. & N point/ Nerolac.) Fainting two coats (excluding priming coat) on old wood based surface with enamel point of approved brand and manufacture (Asian point) 8 erger paint // CI paint/ J. & N point/ Nerolac.) Painting two coats (excluding priming coat) on old wood based surface with enamel point of approved brand and manufacture (Asian point) 8 erger paint // CI paint/ J. & N point/ Nerolac.) Painting two coats (ex	10	(i) Bibcock long thread	Each	2	
broand and size as mentioned below as directed and specified.(G.I. & C.P pipes will be measured and pold separateley) Hindware/parnyware brand or equivalent (iii) 15mm dia(Appelar stop cock with long thread) Each 2 Supplying and filting filting C.P. piller cock of 15mm dia of approved brand as specified and directed. Hindware/parnyware brand or equivalent Supplying Itting and Islang Telephonic Chrome Plated (C.P.) shower of approved brand as directed and specified, (Pipes will be measured and poid separately) Hindware/Parnyware brand (a) General type Providing two coats of Biblic White Wall Care / J.K. Wall Putry (Water Resistant While Cemen based putry for concrete/ morter walls and ceiling both internal and external) after removing all lossely adhering material from the wall surface with the help of emery stone, putry loade or wire brush and moistering the wall with officient quantity of clean water as specified and directed by the eleparatem, forth thickness of two coats is maximum. ISmm). The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on new/old (wall / Celeing etc), surface of ther throughly brooming the surfaces fee from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall painting fliwa coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICL paint/ J. & N paint/ Nerolac). Wall painting fliwa coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger point/ ICL paint/ J. & N paint/ Nerolac). Painting two coats ferom and an analysature (Asian paint/ Berger paint/ ICL paint/ J. & N paint/ Nerolac). Painting two coats ferom paint approved brand and manufacture (Asian paint/ Berger paint/ ICL paint/ J. & N paint/ Nerolac). Painting two coats fincluding appropiete priming coat) old steel and other metal surface with ename paint of approved brand and manufacture (Asian paint/		(i)2-Way bib cock	Each	2	
(ii) Isrim dia(Angular stop cock with long thread.) (iii) Isrim dia(Concelled stop cock.) Supplying and fitting fising C.P., pillar cock of Isrim dia of approved brand as specified and diffected. Hindware/parryware brand are equivalent Supplying fitting and fitting Telephonic Chrome Plated (C.P.) shower of approved brand as directed and specified. (Pipes will be measured and paid separately) Flindware/Parryware brand (a) General type Providing two coats of Birla White Wall Care /J.K. Wall Putly, Water Resistant White Cement based putly for concrete/ martar walls and colling both internal and externally after removing all loosely adhering marteral from the wall surface with the help of emery stone, putly blade or wire busis and moistening the wall with sufficient quantity of clean water as specified and directed by the department, florid hitckness of two costs is maximum. Jamm). The rote shall also included scrapping of damaged paint with sand paper Applying one cost of cement primer of approved brand and manufacture on newfold. (wall /cleling etc) surface after throughly brooming the surfaces free from martar droppings and other foreign marter and including preparing the surface even and sand papered smooth. Wall painting five costs with acrylic emulsion paint approved brand and manufacture /Asian paint / Berger paintif (Cl paint / J & N paint/ Nerolac) on new surface to give an even shade after throughly busing the surfaces free from martar droppings and other foreign marter and isound papered smooth. [a) Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac). Painting two coats (seuding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac). Painting two coats (seuding priming coat) old steel and other foreign matter. The rate shall also includes cost of primer and its application after cleaning the wooden surface of all dirt, dust and other fo	11	brand and size as mentioned below as directed and specified.(G.I. & C.P			
III) Ismm diaj(Concealed stop cack) Each 2		Hindware/parryware brand or equivalent			
Supplying and fitting fixing C.P. pillar cock of 15mm dia of approved brand as specified and directed. Supplying fitting and twing Telephonic Chrome Plated (C.P.) shower of approved brand as directed and specified. (Pipes will be measured and poid separately) Hindware/Parryware brand (a) General type Providing two coats of Birla White Wall Care / J.K. Wall Purtly (Water Resistant White Cement based purtly for concrete/ montar walls and ceiling both internal can destrenal) after removing all lossoes y adhering material from the wall surface with the help of emery stone, putly blade or wire brush and moistening the wall with sufficient quantity of clean of wire brush and moistening the wall with sufficient quantity of clean of wire brush and moistening the wall variety as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on new/old wall /cleiling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall painting (two coats) with acrytic emulsion paint approved brand and manufacture (Jakian paint) Berger painty (Cl painty J. & N painty Nerolac) on new surfaces the from mortar droppings and other foreign matter and sand papered smooth. (a) Acrytic Emulsion Paint approved brand and manufacture (Asian paint) Berger painty (Cl painty J. & N painty Nerolac). Pointing two coats (excluding priming coat) on old wood based surface with enamely paint of approved brand and manufacture (Asian paint) Elegent painty (Cl painty J. & N painty Nerolac). Pointing two coats (excluding appropriate priming coat) old steel and other mortal surface with enamely paint of approved brand and the foreign matter and papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface. ((ii) 15mm dia(Angular stop cock with long thread)	Each	2	
Indivare/parryware brand or equivolent Supplying fitting and fixing Telephonic Chrome Plated (C.P.) shower of approved brand as directed and specified. (Pipes will be measured and paid separately) Hindware/Parryware brand Gold Separately) Gold Separately Hindware/Parryware brand Gold Separately Gold Separ		(iii) 15mm dia(Concealed stop cock)	Each	2	
Supplying litting and fixing Telephonic Chrome Plated (C.P.) shower of approved brand as directed and specified. (Pipes will be measured and paid separately) Hindware/Paryware brand (a) General type Providing two coats of Birla White Wall Care / J.K. Wall Putty (Water Resistant White Cement based putty for concrete/ mortar walls and ceiling both infernal and external) after removing all loosely achieving material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department, (fotal thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on new/old (wall /cielling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign mafter and including preparing the surface even and sand papered smooth. Wall pointing (two coats) with acrylic emulsion point approved brand and manufacture (Asian point) Regree point/ ICI paint/ J & N point/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign mafter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian point/ Berger paint/ ICI paint/ J & N point/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel point of approved brand and manufacture (Asian point/ Berger paint/ ICI paint/ J & N point/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel point of approved brand and manufacture (Asian point/ Berger paint/ ICI paint/ J & N point/ Nerolac). Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel point of approved brand and manufacture (Asian point/ Berger paint/ ICI point/ J & N point/ Nerolac). Painting two coats (including appropiate priming coat) old s	12	brand as specified and directed.		2	
approved brand as directed and specified. (Pipes will be measured and paid separately) Findware/Parnyware brand [a] General type Providing two coats of Birla White Wall Care / J.K. Wall Putty (Water Resistant White Cement based putly for concrete/ mortar walls and ceiling both internal and external) after removing all loosely achering material from the wall surface with the help of emery stone, putly blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on newfold (wall /cleling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian point/ Berger paint/ 101 paint/ 1 & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian point/ Berger paint/ 101 paint/ 1 & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ 101 paint/ 1 & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ 101 paint/ 1 & N paint/ Nerolac). Painting two coats (excluding appropriate priming coat) old steel and other foreign matter and the metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ 101 paint/ 1 & N paint/ Nerolac). Painting two coats (including appropriate priming coat) old steel and other foreign matter. The rate shall		Hindware/parryware brand or equivalent			
[a] General type Providing two coats of Birla White Wall Care / J.K. Wall Putty (Water Resistant White Cement based putty for concrete/ mortar walls and celling both internal and external) after removing all losely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm), The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on newfold (wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian point/ Berger paint/ ICI paint/ J & N point/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel point of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel point of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding appropiate paint) (cl paint/ Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel point of approved brand and manufacture/ sain paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel point of approved brand	13	approved brand as directed and specified. (Pipes will be measured and paid separately)		ch 1	
Providing two coats of Birla White Wall Care / J.K. Wall Puthy (Water Resistant White Cement based puthy for concrete/ mortor walls and celling both internal and external) after removing all loosely adhering material from the wall surface with the help of emery stone, puthy blade or wire brush and moisterning the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on newfold (wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall pointing (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint) Regrep paint) (Cl paint) J & N paint) Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and and papered smooth. [a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint) Regrep paint) (Cl paint) J & N paint) Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint) Regrep paint) (Cl paint) J & N paint) Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint) Regrep paint) (Cl paint) J & N paint) Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint) Regrep paint) (Cl paint) J & N paint) Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint) Regrep paint) (Cl paint) J & N paint) Nerolac). Painting two coats (including appropriate priming coat)					
Resistant White Cement based putty for concrete/ mortar walls and ceiling both internal and external) after removing all loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department, (flotal thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of damaged paint with sand paper Applying one coat of cement primer of approved brand and manufacture on new/old (wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved bra		, ,			
manufacture on new/old (wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth. Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sond papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface. (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface	14	Resistant White Cement based putty for concrete/ mortar walls and ceiling both internal and external) after removing all loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of	Sqm	100	
and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sand papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface. Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface	15	manufacture on new/old (wall/cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered	Sqm	282	
Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sand papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface. [Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface	16	and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian	Sqm	282	
with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sand papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface. [Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac). Painting two coats (including appropriate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface	<u> </u>				
Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface	17	with enamel paint of approved brand and manufacture (Asian paint/Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sand papering and stopping. The rate shall also includes cost of primer	Sqm	12	
other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface					
(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).	18	other metal surface with enamel paint of approved brand and manufacture(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer	Sqm	12	
<u>. </u>		(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).			

19	Supply an fitting of Godrej lock	Nos	1	
20	Repairing of wooden /chowkath of door/window as per direction of EIC	sqm	6	
21	Providing, fitting and fixing 40mm x 48mm wood reinforced PVC chowkhats fixed to the columns / stiffeners / walls with necessary holdfast / sleeves etc. as specified and directed at all levels.		8	
22	Providing, fitting and fixing 24mm/ 29mm thick polymer reinforced moulded PVC door shutters fixed to the chowkath with necessary hinges, screws, bolts etc. as specified and directed at all levels (Door fixtures and fittings to be measured and paid seperately)		3.5	
	a) 24mm thick			
	SUB-TOTAL B			
TOTAL (A+B)				

Rates are exclusive of GST