Shot Immediated Dumping and demandring to include certifing and disposing of the abotic outside the after at Management of the abotic outside the after at Management of the abotic outside the abotic outside the after at Management of the abotic outside the after at Management of the abotic outside disposing and underprinning shall be prouded for the stativy of the adjoining work or popularly, which is to be with in fact, below distantition and demonstrating and demonstrating is a stativity of the adjoining and the work shall be provided for the stativity of the adjoining work or property, which is to be with in fact, below and demonstrating and demonstrating of the static and advisoring or seneroteside material and disclosed. Blanch static of the advisoring of the static of another abotic and static outside the abotic outside the about of the best propert outside outside the abotic outside the abotic outside the abotic outside the abotic outside about outside the about of the best property outside outside the about outsid		PRICE BID FOR THE CIVIL WORKS OF STATE BANK OF INDIA MAI	N BRAN	CH AT	внатти к	ALAN
DISMATCHING  The rate for all demolshing and dismannling to include carring and disposing of the debte outside the site at Municipal Dampsera parands.  Nonoseasary proposition, shrong and underprinting shall be provided for the safety of the adjoining work or compared to the state of the safety of saf	S.No.		Quantity	Units	Rate	Amount
Note: The rate for all demolishing and disminishing to include carting and disposing of the debts outside the sit at National Committee and Co		CIVIL WORKS				
Manisoda Dimominis quantity of the desired printing shall be proseded for the stabley of the adjoining sent or opportry, which is to be left in tack, before demanding and demonstrating in table in upon the work shall be control of in such as way that not demange is caused to the adjoining water or property.  1.1 DISMARTILING WORKS: Demanding of brick wall of all thickness in comment mortar, including glarned ties, comment placets, node insets, ducing and disposed of unerviceble materials to nesessed manifoling of interview the materials to nesessed manifoling duringing ground. Dismanding of existing particles with close in the control of the stable apport frame in CR Wood of the conflictors of the work of the conflictors of the comment of the stable of the comment of the comm	1	DISMANTLING				
Mescale Demonstra comunities.  Necessary peoplery, which is to be biff in task, before decembing and demokaling is taken up and the work shall be provided for the safety of the adjorning work or peoplery, which is to be biff in task, before decembing and demokaling is taken up and the work shall be provided for the safety of the safety						
Necessary prophes, shoring and underprinning shall be provided for the safety or the stoping with or property with is to be eith rate, probe demanding and denolating is steen up and the work shall be provided to the steen up and the work shall be a steen up and the work shall be steen up and the work shall be a steen up and the work shall be a steen up and the work shall be a steen up and the steen or placed or under content or the steen of shutters, fixed glaring and stacking of serviceable material in or design and objects of underviceable material and disposal of unserviceable material in order an immicroble dumping counce. Demanding of existing short in claim of council or complete with glass and disposal of unserviceable material to the doses dumping ground. Dismardling and Removal of existing electrical installations, wing, switches, sockets, condusts, light flutures, stabilities of existing placed installations, wing, switches, sockets, condusts, light flutures, substitute of the consistent installations, wing, switches, sockets, condusts, light flutures, substitutes of the consistent installations, wing, switches, sockets, condusts, light flutures, substitutes of the consistent installations, wing, switches, sockets, condusts, light flutures, and inspects and making size ready for nonground. Dismardling and Removal of the copper planty ground. Dismardling and Removal of existing flutures, who is the steep of the consistent installations, wing, switches, sockets, condusts, and inspects and making size ready for non-interest installations. The lien involveds disposal of unservicable materials to the discuss distinct plant of the consistent planty and removal or existing size ready for non-interest installations and planty an						
comined out in such a way that no damage is caused to the adjoining work or poparty.  1. DISAMATINEN WORK: Demonstrating of trick was in ord all thickness in creent mortar, including glazed titles, comment plates, door finites, ducts and disposal of unserviceable material as directed. Chemamiling of existing false ceiling including removing base support frame in GV Wood etc. and disposal of unserviceable material to the obsert dumping ground. Dismanting of existing false ceiling including ground in the provided material to response the provided in the provided of the provided of unserviceable material to the object of unserviceable material to the object dumping ground. Dismanting of existing false support fame in GV Wood etc. complete in all resports and making it is ready for new interior installations. The fame included objected of unserviceable material to the object of the complete in all resports and making site ready for new interior installations. The stem includes disposal of unserviceable material to the object of the complete in all resports and preparation of the surface to take new boring The cost to include the disposal of device to the nemeral provision of the surface to take new boring The cost to include the disposal of device to the nemeral provision of the surface to take new boring The cost to include the disposal of device to the nemeral provision of the surface to take new boring The cost to include the disposal of device to the nemeral provision of the surface to the new boring The cost of the borner of the provision of the surface to the new boring Takes. We start this cost of the borner provision of the surface to the surfa						
1.1 DISMANTLING WORK:- Dismanstrilling of broke wall of all thickness in cement mortar, including glazed lites, cement places, door lines, ducies and disposed or uneventeether materials and cidenced. Demanting of existing door window travers and shutters, fixed glazing and stanking of serviceshite material and disposed or formation of the places and control of the places and shutters, and the places of uneventeether materials and disposed or formation of the places also control of the places also control of the places and otherwise of the places and control of the copper piping, dating places, condusts, light factors, and the places and control of the copper piping, dating places, condusts, light factors, and the places and complete in all respects and making site ready for new interior installations. The term includes disposed of unserviceable material to the obsert dumping ground. Demanting of filled up error insend floors concrete fillings, PCC. Format concrete it. from the existing floor, Including places, complete in all respects and control price approved from the branch materials places. Low & full H. Storages. Side racks, pin up toxicity. Well parameter governed in all respects and makings gite ready for new interior installations. The fleen includes disposal of unserviceable material to the obsert dumping ground. Before taking any material to the other branch materials of the floor price in the second price in all respects and makings gite ready to new interior installations. The fleen includes disposal of the price of the places of the plac						
comment plaster, door intrides, ducts and disposal of unserviceable material as directed. Dismantling of existing door window fames and shatters, flood glasting and staking of seventuable material to the classed durping ground. Dismantling of existing takes ceiling including removing beau apport times in Oil Wood ceil. and oil good of unserviceable material to the classed durping ground. Dismantling and Removal or desting destination is adopted of unserviceable material to the clossed durping ground. Dismantling and Removal or desting destination is adopted of unserviceable materials to the clossed durping ground. Dismantling and Removal or desting active complete in all respects and making site ready for new interior installations. The item includes disposal of unserviceable material to the clossed durping ground. Dismantling destinations are included disposal of derive and the second of unserviceable materials to the clossed durping ground. Dismantling delice up area? ireade force: converted filing, PCC, Fears concrete etc. from the existing floor, foliate, pathy etc. complete in all respects and preparation of the surface to the closest durping ground. Dismantling delice up area? ireade force: converted filing, PCC, Fears concrete etc. from the existing floor, foliate, pathy etc. complete in all respects and preparation of the surface to the closest durping ground. Dismantling and floor of the surface to the closest durping ground. Dismantling delice up area? ireade floor ground and unserviceable material to the closest durping ground. Eleven the ground is the existence of the surface of the closest durping ground. Eleven the ground is the existence of the existence of the surface of	11					
1.2 MAKING CUT OUT IN MASONRY WALL (for Ventilator 2:0" X 2:0") : Making openings in walls for ventilator windows, AC ducting etc. without damaging the surroundings and making good the affected areas with smooth plaster in mix proportion 1¼ finished in paint , inclusive of lintel support in Cuddapah stone of thickness 25mm to be provided where over required. Cost to be inclusive of fling the excess opening with brick bats and finishing the same in smooth plaster in cement mortar 1:4, proper curing, giving supports to walls etc., complete.  2. MASONRY AND PLASTER  2.1 Casting RCC 230mm x 230 mm RCC lintel beam comporising of 12mm dia steel bars (4 NOS), with 8mm dia strutups in 1:24 cement concrete. The work includes shutering/farmework/curing and floor screed complete in all respects to the satisfaction of the Architect and Bank Engineer.  2.1 CEMENT CONCRETE SCREEDING :- Providing and Isying IPS (Indian Patent Stone) for flooring to a maximum 75mm TO 88Mm links using cement concrete 1:24 (froament 2: Carase sand 4: apraded stone aggregate 20mm and down gauge) for flooring bands and other similar locations, tamped, spaded, trowelled and top finished neat, smooth with floating coat of cement as directed laid in alternate panels of area not more than 2 sgm and laid to water levels or proper slopes as directed with necessary shuttering, hacking the existing surface, curing etc., complete at all heights and levels as per site condition, (Toilest and Partry)  2.2 115mm to 230mm BRICK WALL TO EXISTING SLAB :- Providing and laying half brick partition wall with will burnt good quality of first class designation 75 in cement mortar 1:4 (1 cement: 4 coarse sand) including providing 2 Nos of form dia MRS round bars at every IV Thick course, including scafdiding, curing rubbing the surface, carding out joint set., complete as directed and specified for walls, at all floor and levels.  Make :- ACC / LUTRATECH / BINANI  2.4 (SeMENT PLASTER :- Providing and laying 12 mm thick cear that plaster (Single coat) of mix 1:4:2 (1 c	1.1	cement plaster, door lintels , ducts and disposal of unserviceable material as directed. Dismantling of existing door/ window frames and shutters, fixed glazing and stacking of serviceable material and disposal of unserviceable material to nearest municipal dumping ground. Dismantling of existing false ceiling including removing base support frame in GI/ Wood etc. and disposal of unserviceable material to the closest dumping ground. Dismantling of existing partitions with doors in wood/ gypsum including removing base support frame in GI/ Wood etc. complete with glass and disposal of unserviceable material to the closest dumping ground. Dismantling and Removal of existing electrical installations, wiring, switches, sockets, conduits, light fixtures, stabilizers etc. complete in all respects and making site ready for new interior installations. The item includes disposal of unserviceable material to the closest dumping ground. Dismantling and Removal of existing AC units (indoor & outdoor) including the removal of the copper piping, drain pipe, interconnecting cables etc. complete in all respects and making site ready for new interior installations. The item includes disposal of unserviceable material to the closest dumping ground. Dismantling of filled up area/ raised floors/ concrete filling, PCC, Foam concrete etc. from the existing floor, toilets, paltry etc. complete in all respects and preparation of the surface to take new flooring The cost to include the disposal of debris to the nearest municipal grounds. Dismantling and Removal of existing Tables, low & full Ht. Storages, Side racks, pin up boards, Wall paneling complete in all respects and making site ready for new interior installations. The item includes disposal of unserviceable material to the closest dumping ground. Before taking any material to the	1.00	job		
2.1 Casting RCC 230mm x 230 mm RCC lintel beam comproising of 12mm dia stel bars (4 NOS.) with 8mm dia striupps in 1:24 cement concrete. The work includes subtreting/framework/curing and floor screed complete in all respects to the satisfaction of the Architect and Bank Engineer.  2.1 CEMENT CONCRETE SCREEDING: Providing and laying IPS (Indian Patent Stone) for filororing to a maximum 75mm TO 85MM thick using cement concrete 1:2:4 (1cement : 2 Coarse sand : 4 graded stone aggregate 20mm and down gauge) for flooring bands and other similar locations, tamped, spaded, trowelled and top finished neat, smooth with floating coal of cement as directed laid in alternate panels of area not more than 2 sgm and laid to water levels or proper slopes as directed with necessary shuttering, hacking the existing surface, curing etc, complete at all heights and levels as per site condition, (Tollets and Pantry)  2.2 I15mm to 230mm BRICK WALL TO EXISTING SLAB: Providing and laying half brick partition wall with well burnt good quality of first class designation 75 in cement mortar 1:4 (1 cement : 4 coarse sand) including providing 2 Nos of 6 mm dia MS round bars at every IV thick course, including scalfolding, curing rubbing the surface, racking out joints etc., complete as directed and specified for walls, at all floor and levels.  Make: ACC / ULTRATECH / BINANI  2.3 CEMENT PLASTER: Providing and laying 12 mm thick cement plaster (Single coat) of mix 1:4:2 (1 cement : 4 fine sand : 2 coarse sand) to all type of RCC/ Brick work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.  4 Wooden windows with 12mm ms square grill 4" c/c fixed outside : Providing & fixing Wooden windows Size (5:0" X 6:0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam b	1.2	MAKING CUT OUT IN MASONRY WALL (for Ventilator 2'-0" X 2'-0"):- Making openings in walls for ventilator windows, AC ducting etc. without damaging the surroundings and making good the affected areas with smooth plaster in mix proportion 1:4 finished in paint, inclusive of lintel support in Cuddapah stone of thickness 25mm to be provided where ever required. Cost to be inclusive of filling the excess opening with brick bats and finishing the same in smooth plaster in cement mortar 1:4, proper curing, giving supports to		Nos.		
striupps in 12.4 cement concrete. The work includes shutering/framework/curing and floor screed complete in all respects to the satisfaction of the Architect and Bank Engineer.  2.1 CEMENT CONCRETE SCREEDING: Providing and laying IPS (Indian Patent Stone) for flooring to a maximum 75mm TO 85MM thick using cement concrete 1:2:4 (1cement: 2 Coarse sand: 4 graded stone aggregate 20mm and down gauge) for flooring bands and other similar locations, tamped, spaded, trowelled and top finished near, smooth with floating coat of cement as directed laid in alternate panels of area not more than 2 sqm and laid to water levels or proper slopes as directed with necessary shuttering, hacking the existing surface, curing etc., complete at all heights and levels as per site condition. (Tollets and Pantry)  2.2 115mm to 230mm BRICK WALL TO EXISTING SLAB: Providing and laying half brick partition wall with well burnt good quality of first class designation 75 in cement mortar 1:4 (1 cement: 4 coarse sand) including providing 2 Nos of 6mm dia MS round bars at every IV thick course, including scaffolding, curing rubbing the surface, racking out prints etc., complete as directed and specified for walls, at all floor and levels.  2.3 CEMENT PLASTER: Providing and laying 12 mm thick cement plaster (Single coat) of mix 1:4:2 (1 cement: 4 fine sand: 2 coarse sand) to all type of RCC' Brick work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.  2.4 Wooden windows with 12mm ms square grill 4" c/c fixed outside: Providing & fixing Wooden windows Size (5-0" X 6-0") with wooden chowkhat 6" X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8 mm thick clear float glass with edge polishing & round smoothenend exposed edges A						
maximum 75mm TO 85MM thick using cement concrete 1:2:4 (1cement : 2 Coarse sand : 4 graded stone aggregate 20mm and down gauge) for flooring bands and other similar locations, tamped, spaded, trowelled and top finished neat, smooth with floating coat of cement as directed laid in alternate panels of area not more than 2 sqm and laid to water levels or proper slopes as directed with necessary shuttering, hacking the existing surface, curing etc, complete at all heights and levels as per site condition.(Toilets and Pantry)  2.2 115mm to 230mm BRICK WALL TO EXISTING SLAB :- Providing and laying half brick partition wall with well burnt good quality of first class designation 75 in cement mortar 1:4 (1 cement : 4 coarse sand) including providing 2 Nos of 6mm dia MS round bars at every IV thick course, including scaffolding, curing rubbing the surface, racking out joints etc., complete as directed and specified for walls, at all floor and levels.  CEMENT PLASTER:- Providing and laying 12 mm thick cement plaster (Single coat) of mix 1:4:2 (1cement : 4 fine sand : 2 coarse sand) to all type of RCC/ Brick work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.  Make :- ACC / ULTRATECH / BINANI  2.4 Moden windows with 12mm ms square grill 4" c/c fixed outside :- Providing & fixing Wooden windows Size (5:0" X 6:0") with wooden chrowkhat 6"X 2:5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothnened exposed edges All accessories like the stopper, heavy duty brass hinges, lack, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc.		striupps in 1:2:4 cement concrete. The work includes shutering/framework/curing and floor screed complete in	0.00	CUM		
well burnt good quality of first class designation 75 in cement mortar 1:4 (1 cement : 4 coarse sand) including providing 2 Nos of 6mm dia MS round bars at every IV thick course, including scaffolding, curing rubbing the surface, racking out joints etc., complete as directed and specified for walls, at all floor and levels.  Make :- ACC / ULTRATECH / BINANI  2.3 CEMENT PLASTER :- Providing and laying 12 mm thick cement plaster (Single coat) of mix 1:4:2 (1cement : 4 fine sand : 2 coarse sand) to all type of RCC/ Birck work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.  Make :- ACC / ULTRATECH / BINANI  2.4 Wooden windows with 12mm ms square grill 4" c/c fixed outside :- Providing & fixing Wooden windows Size (5'-0" X 6'-0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list.  a Ventilator of size (2'-0" X 2'-0")  1 Nos.  Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed in existing walls . complete in all respects.	2.1	maximum 75mm TO 85MM thick using cement concrete 1:2:4 (1cement : 2 Coarse sand : 4 graded stone aggregate 20mm and down gauge) for flooring bands and other similar locations, tamped, spaded, trowelled and top finished neat, smooth with floating coat of cement as directed laid in alternate panels of area not more than 2 sqm and laid to water levels or proper slopes as directed with necessary shuttering, hacking the	6.17	SQM		
2.3 CEMENT PLASTER: - Providing and laying 12 mm thick cement plaster (Single coat) of mix 1:4:2 (1cement: 4 fine sand : 2 coarse sand) to all type of RCC/ Brick work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.  Make: ACC / ULTRATECH / BINANI  2.4 Wooden windows with 12mm ms square grill 4" c/c fixed outside: - Providing & fixing Wooden windows Size (5'-0" X 6'-0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list.  a Ventilator of size (2'-0" X 2'-0")  1 Nos.  b Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed in existing walls . complete in all respects.	2.2	well burnt good quality of first class designation 75 in cement mortar 1:4 (1 cement : 4 coarse sand) including providing 2 Nos of 6mm dia MS round bars at every IV thick course, including scaffolding, curing rubbing the		СПМ		
4 fine sand : 2 coarse sand) to all type of RCC/ Brick work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.  Make:-ACC / ULTRATECH / BINANI  2.4 Wooden windows with 12mm ms square grill 4" c/c fixed outside:- Providing & fixing Wooden windows Size (5-0" X 6'-0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list.  a Ventilator of size (2'-0" X 2'-0")  b Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed in existing walls. complete in all respects.  74.35  SQM		Make :- ACC / ULTRATECH / BINANI				
Wooden windows with 12mm ms square grill 4" c/c fixed outside :- Providing & fixing Wooden windows Size (5'-0" X 6'-0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list.    Ventilator of size (2'-0" X 2'-0")	2.3	4 fine sand : 2 coarse sand) to all type of RCC/ Brick work in line, level and plumb including smooth cement finish as directed including providing necessary bands, drip molds groove and wire mesh at all junction of walls and ceiling including racking the joints or roughening the RCC surfaces, necessary curing scaffolding etc., complete as directed and specified.	74.35	SQM		
(5'-0" X 6'-0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list.  Nos.  Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed in existing walls . complete in all respects.  SQM						
b Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed in existing walls . complete in all respects.  1.45 SQM	2.4	(5'-0" X 6'-0") with wooden chowkhat 6"X 2.5" thick. Windows shall be finished with 35 x 5mm steam beach wood beading on edges of window. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost	0	Nos.		
b Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed in existing walls . complete in all respects.  1.45 SQM	а	Ventilator of size ( 2'-0" X 2'-0")	1	Noe		
3 PAVING AND WET WORKS		Providing and fixing M.S. Grills made with 16 mm sq. bars @ 4"c/c bothways(Horizontally and vertically) fixed				
3 PAVING AND WET WORKS						
	3	PAVING AND WET WORKS				

3.1	TILE DADO: Providing and laying mirror polished 300x600mm vitrified tile dado at Pantry laid over adequate thickness of cement mortar 1:4 (1cement: 4 coarse sand) using chemical grouting aquamix/laticrete grout. Tile adhesive unitile make. The rate shall be inclusive of necessary preparation, cleaning etc., complete.  Makes: Somany / Johnson / RAK	30.25	SQM	
3.2	VITRIFIED TILE FLOORING: Providing and laying flooring with Vitrified tiles of size 600mm x 600mm x 10mm of approved make and sample in pattern as per detailed drawings on up to 25mm thick bed of cement mortar 1:6, including surface preparation, neat cement float, giving necessary slopes, cleaning joints and grouting them in neat white cement paste with pigmented additives to match shade of the tile etc complete. With Spacers of 4mm filled with Laticrete Epoxy Grout. Note:- The job includes dismantling of existing flooring (Tile/ Terrazo/ Vinyl/ Screeding)/ Wall Tiles including removing base in cement mortar of any depth etc. and disposal of unserviceable material to the closest dumping ground.	197.28	SQM	
3.3	Makes: Somany / Johnson / RAK  ANTI SKID TILES (VITRIFIED TILE): Providing and laying flooring with Vitrified tiles of size 300mm x 300mm x 10mm of approved make and sample in pattern as per detailed drawings on up to 25mm thick bed of cement mortar 1:6 including surface preparation, neat cement float, giving necessary slopes, cleaning joints and grouting them in neat white cement paste with pigmented additives to match shade of the tile etc complete. With Spacers of 4mm filled with Laticrete Epoxy Grout. Base Rate of Tile: Rs 650/- per sqm.	10.58	SQM	
3.4	Makes:-Somany / Johnson / RAK  KITCHEN/ PANTRY SLAB:- Providing and fixing M20 RCC pantry slab with 12 mm dia bars @ 6"c/c bothways(Horizontally and vertically) of Width 2'-0" and thckiness of 100mm with Granite stone top including moulding. The cost to include fixing of the counter using MS angles with proper anchoring in the wall to take washbasin/sink	2.23	SQM	
3.5	Semi glazed wooden doors with frame: WIDTH (2'-6" TO 3'-6")  Providing & fixing of 32mm thick semi glazed flush type doors. Doors shall be finished with 1mm thick laminate of approved colour & make with 35 x 5mm steam beach wood beading on edges of door. The glass shall be 8mm thick clear float glass with edge polishing & round smoothenend exposed edges All accessories like the door stopper, heavy duty brass hinges, latch, handle, lock etc shall be part of the job. All teak wood members to have melamine spray polish finish. Rate to include cost of conveyance of all materials, labour charges etc. complete as directed. As per approved hardware list. Make: Duro/Green Panel/Merino	3.00	Nos	
4.1	Providing and fixing Chlorinated Poly Vinyl Chloride (CPVC) pipes 1.5" / 3/4"/ 1" dia nominal OD pipes conforming to IS 15778, having thermal stability for hot and cold water supply including all CPVC plain and brass threaded fittings including fixing the pipe with clamp at 1.00 mtr spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement & the cost of cutting chases and good the same including testing of joints complete.(Concealed work including cutting chases and good the walls etc (NOTE: The job includes removing and shifting existing plumbing pipes and fixing new pipes and proper installation including complete job.)  MAKES-Prince, Supreme, Astral	80.00	Rmtr	
4.2	Providing, fixing, testing and commissioning of UPVC pipe (upto 6" /4"/ 3" /2" diameter as per site) SWR type 'B' conforms to IS: 13592-1992 with all fittings such as bends, tees, elbow, 'Y', offset, cleaning pipe door, clamps and steel structural supports etc. including cutting the floors, walls & making floor trap, making good the same in cement concrete 1:2:4 & cement mortar 1:4. The wall thickness of pipe and technical characteristic conforms to IS: 13592-1992 type 'B'. The fitting dimension conforming to IS: 14735-1999. The jointing to be completed with rubber ring joint/solvent weld joint.(NOTE:- The job includes removing and shifting existing plumbing pipes and fixing new pipes and proper installation including complete job.) Makes- Prince, Supreme, Astral	70.00	R.Mt.	
4.3	WC:- Providing & Fixing in position Extended Floor Mounted type water-closet suite (as approved by the Architect/Engineer-In-Charge), Extended Floor Mounted type consisting of:    Viterous Chinaware CLEO COUPLED CLOSET Extended Floor Mounted with 2/4 liters capacity matching Chineware cistern and complete fittings with 'S' trap, as approved. (Griha Certified)    Viterous Chinaware CLEO COUPLED CLOSET Extended Floor Mounted with 2/4 liters capacity matching Chineware cistern and complete fittings with 'S' trap, as approved. (Griha Certified)    Viterous Chinaware Cleor mounted with concealed trap in circular design (to the approval of Architect/Engineer-In-Charge)    Color :WHITE.Make:- (HINDWARE- CLEO COUPLED CLOSET Cat. No. 20050 (S - 19/22) Cistern :-21033/34). (GRIHA CERTIFIED)    Viterous Chinaware Cleor Couple Close Couple With Close C	3.00	Nos	
4.4	Set of Flora Health Faucet , Angular Stop Cock with wall Flange etc from Hindware/ Kohler/Jaquar for	3.00	sets	
4.5	each toilet.  WASHBASIN: Providing and installing wall hung Washbasin (Hindware PURE Cat No. :- 10127 or equivalent. Complete with bottle trap 32mm with 125mm & 175mm with Wall Connection Pipe & Wall Flange The cost to be inclusive of all MS angles, G.I. reducer (Snw/ Unique) for floor drain, complete 75 x 50mm size, Including C.P Bottle Trap " (Hindware - Cat No. :- F850015),, 32mm C.P. Brass waste of standard pattern., C.I. Brackfast for building into wall including painting etc. required for the fixing.  Make: Hindware/Kohler/Jaquar	3.00	Nos	
4.6	15mm C.P. Flora Brass Pillar Cock from Hindware/ Kohler/Jaquar for each toilet.	3.00	Nos	
4.7	Providing & Fixing in position white viterous China flat back lipped front URINAL, Consisting of:- a) Flat back large urinal basin of viterous chinaware. COLOR- WHITE. HINDWARE: 60002 ( 59CM X 39CM X 37.5CM) b) C.P. Brass Spreaders with brass unions & G.I. Clamps, complete including cutting & making good the walls & floors and painting of fitting etc. (as required by Architect/Engineer-In-Charge). Make: Hindware/ Kohler/Jaquar.	1.00	Nos	
4.8	Providing & Installation of <b>Pressmatic EON Urinal Flush Valve</b> System similar to (Hindware Cat No. :-F310016) for urinal complete with all accessories.	1.00	Nos	

	Plumbing accessories for kitchen and toilets:-  Providing & fixing C.P brass bib cock with wall flange of approved make conforming to isi 8931 (15mm nominal bore) Make:(Element / Flora / Aspiro Series of Hindware)  II) Providing & fixing Angle valve of approved make conforming to isi 8931 (15mm nominal bore) Make:(Element / Flora / Aspiro Series of Hindware)  III) Providing & fixing stainless steel floor trap jali of approved make conforming to isi:8931Make:(Element / Flora / Aspiro Series of Hindware)  IV)  Providing and fixing all the fittings such as bends, tees, elbow, "Y", offset, cleaning pipe door, clamps and steel structural supports etc. required for the normal functioning of the kichten and toilet. Make: Hindware/  Kohler/Jaguar	4.00	Nos.	
	Kitchen Sink for Pantry (size 24 X 18X 8) (Hindware Single Bowl (Classic SB - 513525) or equivalent). The cost to be inclusive of all MS angles etc. required for the fixing. Make: Hindware / Neelkanth.	1.00	Nos	
	GRANITE:-Providing and fixing 18 mm thick mirror polished, machine cut, Granite Stone slab for door threshholds, sills or Similar location of required size of approved shade, colour and pattern laid over 20mm thick base in cement mortar 1:3 (1 cement: 3 coarse sand) with joints treated with matching pigment, epoxy touch-ups including rubbing, polishsing where as required, curing etc. The Nosing of the treads to be finished using Flat Edge/ Eased Edge Nosing. Complete in all respect at all floors as per direction of Engineer-In-Charge.	5.00	SQM	
	Water Cooler Connection including all accessories and fitting material as required. Complete job as per architect satisfaction.	1.00	Nos.	
4.13	Mirror SIZE (3'-0"X3'-0") :- Providing and fixing in position best indian make bevelled edge 5.5mm thick mirror mounted on asbestos sheet ground fixed in position by means of 4.no Chromium plated brass screws & washers over rubber washers & rawl plug embedded in the wall or Chromium plated brass clamps with c.p. brass screws (as required by the Architect/Engineer-In-Charge) complete including cutting & making good walls etc. Size(600x910mm)	3.00	Nos.	
	Providing, Fixing & Supplying Water Tank 1000 ltrs. Triple layerd including all necessary accessories.( Make Sintex)	0.00	Nos.	
	Collapsible Grill Gate: Collapsible gate with 40mm x 40mm x 6mm Tee as top and bottom guide rail, 20mm x 10mm x 2mm vertical channels 100mm apart in fully stretched position 20mm x 5mm M.S. flats as collapsible bracings properly rivetted and washered including 38mm steel rollers including locking arrangements, fitted and fixed in position with lugs set in cement concrete and including cutting necessary	8.50	SQM	
	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor.Grill weighing above 16 KG./sq. mtr and above.	6.50	JQW	
	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and	32.00	SQM	
4.16	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S., W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.			
4.16	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S., W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width			
4.16	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S., W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance &			
4.16	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)			
4.16	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings			
4.16 5 5.2	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.			
4.16 5 5.2	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval)	32.00	SQM	
4.16 5 5.2	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.	32.00	SQM	
4.16 5 5.2	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.	32.00	SQM	
4.16 5 5.2	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in	180.00	SQM	
4.16 5 5.2	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.	180.00	SQM	
4.16 5 5.2 5.3	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor.Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft,with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site . all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.	180.00	SQM	
5 5.2 5.3 5.4	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor.Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  External Apex paint  Providing and applying external Apex paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval)	180.00	SQM	
4.16 5 5.2 5.3	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S. W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor. Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  External Apex paint  Providing and applying external Apex paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  External Apex paint  Providing and applying external Apex paint three coats to give an even shade after preparation of surface for	180.00 80.00	SQM SQM SQM	
5 5.2 5.3 5.4	holes, chasing etc. in walls, floors etc. and making good damages complete. M.S. or W.I. Ornamental grill of approved design joints continuously welded with M.S, W.I. Flats and bars of windows, railing etc. fitted and fixed with necessary screws and lugs in ground floor.Grill weighing above 16 KG./sq. mtr and above.  Rolling Shutter  Supplying and fixing rolling shutters of approved make made of 80 mm X 1.25mm M.S laths interlocked together through their entire length and joined together at the end by end locks mounted on specially designed pipe shaft, with brackets side guides and arrangements for inside and outside locking with push pull operation complete with center locks but excluding the cost of the top cover and spring. Shutters having width below as per site. all leads and lifts.  Providing and fixing 27.5 centimeter long wire spring grade No.2 for rolling shutters. (for Front entrance & ATM)  Providing and fixing top cover for rolling shutters. Shutters having width as per drawings  PAINT  Plastic Emulsion paint  Providing and applying Plastic Emulsion paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  Enamel paint  Providing and applying enamel paint three coats to give an even shade after preparation of surface for painting by scrapping on shutter, doors, windows and grill etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  Make: Nerolac, Asian, Berger.  External Apex paint  Providing and applying external Apex paint three coats to give an even shade after preparation of surface for painting by scrapping etc. & filling including one primer coat, complete in all respects (Colour to approval) applicable to old or new.  BUY BACK: ( All the old grid/false ceiling, Alumunium partition, wooden partition, tables and low height/full height storage, are to be i	180.00 80.00	SQM SQM SQM	