

TENDER & SPECIFICATIONS FOR PROPOSED INTERIOR WORKS AT SBI RACC KHANDWA (FIRST FLOOR) BRANCH (M.P) (RBO- 04 KHANDWA)					
S.NO	ITEM AND SPECIFICATION	QTY	UNIT	RATE	AMOUNT
A.	INTERIOR WORK'S				
1	Main Door + CM CABIN DOOR – Toughened Glass :				
	Providing, making and fixing Toughend Glass Door:- 12mm thk single/double shutter toughened glass doors, Including Floor springs make Hardwvn/ozone/Dorma or equivalent set, Upper patch, lower patch, lock key plate, provision of locking system, etc. One set of 25 mm dia S. S. brush finish pull handles (approx. 300mm length) "C" shaped, of appoved make Including Etching pattern, Note- Including, labour, transport, material, delivered and placed in position at site of work.	7.5	SQM		
2	Toughened Glass Fixed Glazing				
	Providing, making and fixing Toughened Glass :- a. 12mm thick toughened clear float glass b. Fixed with " D " brackets/ SS fittings as required. c. Etching film to be done as directed Note-The cost to include all materials, labour, hardware etc.,	3	SQM		
3	Full Height Partly Glazed/ Solid Wooden Partitions : With Door				
	Providing and fixing full height partly wooden, partly glazed, Solid partitions- specifications (Measurement shall be taken up to finished partition level & not of frame work and sal wood member shall go up to slab/beam soffit) A. Aluminium Frame Size -50mm X 50mm X 1.60 mm thick 450/600 mm c/c both ways B. 8 mm thk. Bwp plywood from both the sides C. 1.0mm thick approved shades of laminate D. 5 mm thick float glass (for Partly Glazed Partitions) E. Eitching as per approved design F - A 32 mm thk flush door with 1 mm lamination on both sides, 8 mm plain glass, (for partly Glazed Doors) Frame of 2nd class BTC/ Teak wood Frame of 100mm x 50 mm, all fitting like Mortice lock with 2 nos Handels , S.S. 125Mm Heavy duty Hinges 3 Nos. Door stoppers, 2 Nos Tower Bolts 200mm Note- Including all materials, labou Note -Including all fittings,material, screw, labour etc. Complete.	32	SQM		
4	Low Height partitions With / Without Glass				
	Providing and fixing Half Height (approx-1200 mm ht.) partitions. Aluminium Frame Size -50mm X 50mm X 1.60 mm thick 450/600 mm c/c both ways(Horizontal/Vertical) 8 mm thk. Bwp plywood Termite & Borer Proof from both the sides 1.0mm thick approved shades of laminate 12.00 mm thick float glass Eitching as per approved design wicket gate wherever required with Godrej Night latch Note -Including all fittings,material, SS hinges, SS tower bolts screw, labour etc. Complete..	15	SQM.		

<u>S.NO</u>	<u>ITEM AND SPECIFICATION</u>	<u>QTY</u>	<u>UNIT</u>	<u>RATE</u>	<u>AMOUNT</u>
5	Gypsum Board False Ceiling : Providing, making and fixing Gypsum Board False Ceiling :- 12.5 mm thick G.I. Perimeter Channels of size 0.55mm thick. G.I. intermediate channels of size 45mm from the soffit at 900mm centres with ceiling angle of width 25mm X 10mm X 0.55mm thick intermediate channel at 450-600 mm c/c Two coats of primer + two or more coats of plastic emulsion paint Note -Including all fittings,material, labour,cut outs required for light fixtures, Speakers, screws and joint paper/fibre tape etc. complete.	155.00	SQM		
6	Cove in ceiling : Providing, making and fixing Cove in Gypsum Ceiling Inside height 150 - 200 mm and border 75 mm to hide strip/cove light in ceiling	#REF!	RM		
7	Mineral Fibre Grid Tile Ceiling : Providing, & Fixing Mineral Fibre Grid Tile Ceiling System- A. Black T Junctions. The tiles should have black strip combination with White edges, B. Module size of 600mm x 600mm x 12mm. C. 24 mm wide T-section flanges D Main Runner, 1200 mm & 600 mm Cross Tees with a web height of 32 mm and 27mm ,25 mm respectively Note-The cost shall include all fittings, labour and materials etc complete including proper installation and provisioning etc	55	SQM		
8	Full/Half Height Storage : (Measurement area = Length x Height). Providing, making and placing Full/Half Height Storage:- A. 450 mm deep full/Half ht. storage units B. 18mm thk BWP grade plywood at sides & at top.& shutter ,Shelves C. Back to be of 12 mm thk BWP grade plywood. D external surfaces 1.0mm thick laminated finish and internal surfaces to have 0.8mm white lamimated finish Note- ss 100mm Hinge, SS handles, magnetic catchers Godrej or ebco lock & brass handles all approved make etc.	26	SQM		
9	Wall Hung Storage (0.75 m HIGH) P/ F Wall Hung Storage made out of 18 mm thk MR Ply, 35-45 cm deep, 6mm thk BWP Ply for the back, openable shutters in 18 mm thk BWP Ply, with hinges as recommended, 18 mm thk removable shelf with 1 mm laminate finish on both sides, edges shall be provided with 2 mm thk PVC strips on all sides. All hinges, tower bolts, S.S Brush finish handles, ball-catches shall be of brass heavy duty, approved make Locks etc. complete as per design/ instructions.	1.20	SQM		

<u>S.NO</u>	<u>ITEM AND SPECIFICATION</u>	<u>QTY</u>	<u>UNIT</u>	<u>RATE</u>	<u>AMOUNT</u>
10	Wall/Column Panelling				
	Providing, making and fixing single skin paneling:- A. Using 8 mm thick BWP plywood on walls B. Made out of 50 x 25 x 1.0 mm thk weighing 0.467 kg/rmt aluminum frame 450 mm c/c both ways C. Finished with 1mm thick decorative laminate of approved make and shade D Teak wood decorative beading of 35mm x 20 mm finished with polish/painting as directed. Note -Including all fittings,material, labour etc. Complete..	105	SQM		
11	Vertical Blinds :				
	Providing & installing Vertical Blinds of Trac / Vista or equivalent,- Size 100 mm wide, in two colours, Including all material. Labour etc complete	8	Sqm		
12	FURNITURE WORKS				
A.	Tables :-				
	Providing and supplying table detailed below : A. 2.-18 mm thick BWP Plywood B. 3.- 1 mm thick laminate on external surfaces and 0.7 mm thick lamination on internal surfaces of approved make C. 4.- TW half round beading of sect 20 x 12 mm duly polished D 5.- Drawer unit of width 350mm (clear internal), consisting of set of 3 nos. of drawer. E 6.-Drawer made of 18 mm thk. MR Ply wood for the front and rear 12 mm BWP Plywood for sides and 6mm thk MR ply for the bottom sliding & teak wood beading of sect. 20 x 6 mm F 7- EBCO Sliding Telescopic Rail +M S powder coated keyboard tray with mouse tray. Note all fittings, fixtures, locking arrangement, handles, etc. Complete.				
	Providing multidrawer Godrej or Ebco single lock and approved brass handle for each drawer. Providing circular holes in table top for cables with PVC cable managers of 65 mm dia and cap.				
	On the left side platform at bottom for CPU.The bottom compartment made up of 18mm thick. MR plywood. The exposed edges of the plywood to be provided with TW lipping of size 20x6 mm duly polished.				
	One M S powder coated keyboard tray with mouse tray as manufactured by ebco (KBTM 45) or EGL (KBT-M-001) including sliding channel as per manufacturers specification to be provided below the working platform.				
a	CM CABIN Tables :				
	Size 1.80 m x 0.90 m x 0.75 m ht.	1	Nos.		
B.	Officer Tables :				
	Size 1.50 m x 0.75 m x 0.75 m ht.	11	Nos.		
13	TABLE TOP 10.0 mm Glass :				
	Providing and Fixing of table Top Glass :- a. 8mm Thick Bevell edge Glass Make- Modi, Saint Gobain, ASAHI etc.	2	Sqm		

<u>S.NO</u>	<u>ITEM AND SPECIFICATION</u>	<u>QTY</u>	<u>UNIT</u>	<u>RATE</u>	<u>AMOUNT</u>
14	Sofa set :				
	Providing, making and fixing in position sofa set with side arms :- A. 12 mm thick commercial ply B. 8mm thick commercial ply back side C. 150 mm thick high density foam rubber of approved quality to seat of zigzag spring D approved Shade Leatherite E 50 mm thick foam rubber of approved quality, density mini. 32 to back covered Note-Rate inclusive of cost of material, transportation, loading/unloading, labour tools & tackles up to any lead and lift etc. Measurement : no. of seats	9.00	Per seat		
15	CENTRE TABLE FOR WAITING HALL				
	Providing at site Center table of Size- 4' x2' Made up of 18 mm thick MR Ply 12.0mm thick Top Glass 1.0 mm thick laminate. Including All material , Labour etc Complete.	1.0	NOS.		
16	Hardwares :				
	Providing and fixing Door closers on doors of make Everite/Ozone/ Hardwyn or equivalent upon approval including all packing, levelling, etc. as required.	3.00	Nos.		
17	NOTICE BOARD :				
	Providing & fixing at site notice board :- a. Size 3' x 4' b. Wood frame of size 2" x1" wooden section with 5.0mm plain glass c. 19.0mm soft board lining at back with approved shade of cloth,	1	Nos.		
18	ACP Panelling Works :				
	Providing and fixing in position Aluminium Composite Panel (ACP) on wall, boxing, shutter panelling with & ATM with framing:- 1.-M.S. Tube sections of min. 50 mm x 25 mm and 16 gauge, @ 600 mm c/c or less. 2.- thickness of 3 mm minimum. Alubond / Eurobond / Fujibond / Alcobond or equivalent Note- The cost shall include all fittings, scaffoldings, chase making, lifting, cutting, on site adjustments, plaster repairing, etc. complete.	10	SQM		

S.NO	ITEM AND SPECIFICATION	QTY	UNIT	RATE	AMOUNT
19	Plastic Emulsion Paint :				
	Providing & applying Plastic emulsion paint on walls, ceiling, etc. Removing, scrapping & cleaning the existing color wash/distemper/oil bond distemper / plastic/ luster etc. paint by scrapping, washing and scrubbing and applying Birla putty nor equivalent. The surface shall then be allowed to dry for atleast 24 hours. It shall be then sand papered to give a smooth & even surface. Holes shall be filled with BIRLA putty, made with plaster of paris. Then first coat of primer to be applied. After this necessary leveling shall be done with putty and second primer coat shall be applied. The plastic emulsion paint of approved shade and make shall be applied in minimum 2 coats (finishing paint) including scaffolding, cleaning the floors, fittings, furniture's, ladders, glasses, removing of debris out of the compound etc. complete as per the instructions of the Bank / SBI.	65	SQM		
20	Enamel Paints to Doors, Windows, Grills, Metallic Surfaces, Walls :				
	Providing & applying Enamel Paints to Doors, Windows, Grills, Metallic Surfaces, walls, etc. Removing, scrapping & cleaning the existing enamel paint on doors, windows, grills, metallic surfaces, etc. paint by scrapping, sand papering and scrubbing. Then first coat of primer to be applied. After this necessary leveling shall be done with putty & second primer coat shall be applied. The enamel paint of approved shade shall be applied in minimum 3coats (finishing paint) including scaffolding, cleaning the floors, fittings, furniture's, ladders, glasses, removing of debris out of the compound etc. complete as per the instructions of the SBI. (The grills, metallic surfaces, etc. shall be finished with after scrapping, applying red oxide & finish with minimum 2 coats of enamel paint in two different shade).	40	SQM		
B.	CHAIRS				
21	High back, revolving chair FOR CM with cushioned seat and back and molded PVC hand rest, hydraulic vertical movement, swivel type chair with castors, as per quality and design approved,	1	Nos.		
22	Medium back, revolving executive chair with cushioned seat and back and molded PVC hand rest, hydraulic vertical movement, swivel type chair with castors, as per quality and design approved,	11	Nos.		
23	Medium back fixed type chairs with cushioned seat and back and molded PVC hand rest Godrej, S-frame type, as per quality and design approved,	25	Nos.		
	Note- Makes viz. Godrej Bravo/Featherite/ Wipro/ make or equivalent as approved				
TOTAL AMOUNT FOR INTERIOR WORK'S					