ir. No	Repair and upgradation of ISD seatin Description	Quantity	Unit	Rate	Amount
	Description	Quantity	onic	nate	
1	Buyback: Removing carefully and shifting the existing removed workstation, furniture, 28 no. of old modular workstations out of Banks premises at contractors cost and risk without any damage to banks property	20000	dol		
3	Providing and fixing double charged vitrified tiles of Kajaria, Johnson, etc. make (size 600mm x 600mm) flooring matching with existing flooring in cement sand mortar (1:4) bedding including removal of existing damaged flooring, debris etc. from site as per directions of the Bank	100	sqm		
4	Providing and applying one or more coat plastic paint to walls and ceiling after suitable surface preperation Putty, POP etc. complete the work as per site conditions & instructions of the Bank	500	sqm		
5	Repair of damaged gypsum false ceiling wherever required while removing the partition complete	15	sqm		
6	Removing old damaged laminate as per approved, providing and fixing new veneer (if required) to matchched with existing shade complete the finished work as per site conditions & instructions of Bank.	40	sqm		
7	Providing and applying PU polish to top of existing table and side storage unit complete the work as per instruction of the Bank	25	sqm		
8	Providing and applying melamine polish complete the work as per instruction of the Bank	25	sqm		
	Modular work station works:	60	Nos		
	Linear workstation work supplying and installing (Sharing and non - sharing type) Size : 1200W x 600D x 750H-1050 H Type : DESKING SYSTEM Desking System : Linear(Sharing & Non-sharing) Flip up: 450mm Access flipup Above table top main screen: 8mm Thick Sandwich glass panel mounted on bracket size of 1050W X 450 mm Ht ABOVE TABLE TOP END RETURN SCREEN PASSAGE SIDE: 8mm Thick Sandwich glass panel mounted on bracket size of 1050W X 450 mm Ht (White / Blue colour as approved by Bank) Wire Management: : MS Powder coated cable tray mounted below the table top height of 150mm to have the provision for DATA, POWDER Sockets& cables. Table top: Table top 25mm thick prelaminated particle board with flipup cutout Leg: legs are made of MS powder coated 50sq tube leg with ms powder coated perforated modesty at passage side Alcemy leg The legs adopts white fine powder-coated technique to make the color match with other components perfectly, so there is no color difference. Cable riser: Ms-Powder coated junction box Non sharing WS as The thickness of metal plate is 0.8mm, the thickness of the Powder coating is 60~100µm pass the wire from floor level to WS. Beams : Horizontal beams below table top will be with 40mm x 20mm rectangular tube CRCA Powder coated. Modesty: ms powder coated perforted modesty below the table top (for front between shared workstation & aisle for non shared workstation)				
	,	I		I	
	Total :				

* GST will be paid extra as applicable