

N.O.W. - FURNISHING OF STATE BANK OF INDIA**AO PANCHKULA (6TH FLOOR)****ESTIMATE FOR THE INTERIOR WORKS**

S.No.	DSR REF.	Item	Quantity	Units	Rate	Amount
		PANELING/PARTITON				
		Note: For the Paneling, Full height partitions and low height partitons the work measuremnt for costing shall be only of the plain visible surface, no extra cost for extrusions or extra frame work required as per drawing will be made. The work done above ceiling, below floor finish level or not directly visible shall not be measured.				
1		WALL PANELING				
		Providing and fixing panelling on column/wall. Framing shall consist of Heavy duty Aluminium Box Sections 50mmx25 mm with maximum spacing of @ 600mm c/c Both ways horizontally and vertically on the column/wall. This framing would be covered by 8mm thk. ISI Marked Ply finished in approved 1.0mm Th. Laminate of desired shade, design and gloss. Wooden molding, lipping etc. shall be provided wherever required as per drawing and deco painted in desired shade. The paneling shall have skirting and intermediate bands finished with laminate of desired shade, design and gloss. The work shall also include the cost of making cut-outs for the electrical switches, lights, switch boxes etc. and provision for laying conduit for electrical/telephone/Data cabling etc.	126.16	SQ.M		
		The work shall include making provisions for the shutters for the existing niches with 18mm thick ply finished with 1mm thick mica of desired shade/texture/finish with modular hinges, lock, magnet stopper and handle complete including painting/polishing the edges as per the direction of the engineer-in-charge.				
		MAKES:				
		ALUMINIUM: JINDAL, HINDALCO, NALCO OR EQUIVALENT				
		PLY: CENTURY/GREEN/DURO OR EQUIVALENT				
		MICA: GREEN/SUNMICA/MARINO OR EQUIVALENT				
		ADHESIVE: FEVICOL SH/ VAMICOL/JIVANJOR OR EQUIVALENT				
2		FULL HEIGHT PARTITIONS:				
		Providing and fixing wooden full height partition with following specifications:	6.83	SQ.M		
		(a) Supporting system comprising of Dry wall Frame Work Boral/Rondo/Gyp. of 50mm x 50mm (18 Gauge) square section@ max. 600mm c/c both horizontally and vertically. The frame shall be fixed rigidly at floor level and ceiling level wherever possible. The rate should also include necessary strengthening with additional members at doors and other openings.				
		(b) The partition shall have 8mm Plywood fixed on both sides with screws for the entire height of the partition and finished with approved 1.0mm Th. Laminate of desired shade, design and gloss on both sides. Wooden molding, lipping etc. as directed by Bank / architect shall be provided wherever required. The partition shall have skirting and intermediate bands finished with metallic laminate of desired shade, design and gloss.				
		(c) The full height partition shall be WITH OR WITHOUT 8mm clear float glass with etching fixed as per drawing with 75mm x 12mm Teak wood jamb/chaowkhat around glass opening and 12mm x 12mm teak wood beading for fixing of glass on both sides. As per the direction of Engineer-in-charge and design.				

	(d) The work to include providing and fixing of partly glazed wooden door shutters using 35mm readymade ISI flush door shutter with 1.0mm thick laminate of desired shade/textures and gloss as per drawing with teak wood frame of 75mm x 40mm. The door shall have 6mm thick teak wood lipping all around the edges. The door shall have vision panels with 8mm thick clear float glass with etching fixed with double 14mmx25mm thick teak wood moulding as per design. The exposed surface of wood shall be deco painted in desired shade. The door shall be complete in all respect with hardware handles, godrej 6-lever lock/night latch lock, door stoppers, 8" tower bolts, hinges etc all in brass.				
	MAKES:				
	ALUMINIUM: JINDAL, HINDALCO, NALCO OR EQUIVALENT				
	PLY: CENTURY/GREEN/DURO OR EQUIVALENT				
	MICA: GREEN/SUNMICA/MARINO OR EQUIVALENT				
	ADHESIVE: FEVICOL SH/ VAMICOL/JIVANJOR OR EQUIVALENT				
	GLASS: SAIN GOBAIN/MODI GLASS/ASAHI FLOAT GLASS				
	LIPPING/MOULDING: CP TEAK FIRST CLASS				
	HARDWARE: OZONE/DORMA/GODREJ				
	Note: The measurement for the costing of the ceiling will be done for the plain surface and no extra cost shall be paid for the steps or cope lighting. No extra cost shall be made for cutting the board for fixing of lights/airconditioner diffusers or return air grills/provision for conduits for cabling/ adjustment of the suspended grid as per the layout of the air-conditioners/ air-conditioning ducts or other fittings.				
3	GYPSUM BOARD FALSE CEILING WITH STEPS:				
	Providing and fixing suspended false ceiling including steps and provision of cope lighting as per design with 12.5mm tapered edge Gypboard / 12mm thick Elephant Gypsum Board to the grid comprising of cold rolled galvanized metal section to the required line and level. The grid consisting of a perimeter channel fixed round the perimeter. The intermediate channel at 1200mm c/c in the one direction and the ceiling section at 450mm c/c in the other direction to be connected by a connecting clip. The grid to be suspended with an adjustable strap hanger.	151.12	SQ.M		
	The grid to be suspended with an adjustable strap hanger at 1200mm c/c on both ways from the structural soffit using a soffit cleat and expandable bolts/fasteners Nut and bolts to be used to connect strap hangers to soffit cleats and for joining ends of channel sections together. The gypsum board layers to be screwed to the M/F ceiling sections with gypboard drywall screws. Jointing and screw spotting are then carried out as per manufacturer's standard recommendations. Perimeter Channels to be used around the cut outs for light fittings. A/C ducting etc. The work should be complete as per instructions of Architect or Engineer in charge including 2-3 coats of oil bound distemper , over a coat of primer.				
	MAKES:				
	GYPSUM BOARD: SAINT GOBAIN/USG BORAL/GYPSUM INDIA				
	CEILING SECTIONS: SAINT GOBAIN/USG BORAL/GYPSUM INDIA				
4	OFFICER'S TABLES WITHOUT SIDE CREDENZA				

	(a) Providing and fixing at site Officer's table made of 18mm th. commercial ply board with 1mm thick laminate of desired shade, design and gloss on outer visible surfaces; single color on horizontal surface & two color on vertical surfaces. . The front of the table top shall be projected and curved as per drawing. Provision for 3" dia. Round/3" square stainless steel of grade 304 cable manager for computer / electrical cables at appropriate place, will be made in the top surface of the table. Esteem Biege wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers.				
	The counter shall have a wooden keyboard rest of size 600mm x 270mm made with 18mm ply fixed with sliding telescopic channels of ebco/godrej/hettich make. The work shall also include provision of foot rest made with wooden member of section 3" x 5" along the leg space.				
	(b) There shall be provision of one storage cabinet 1'3" wide. The frame shall be made with 18mm thick ply board. The cabinet shall have one lockable drawer running on side mounting drawer slides (channels) of EBCO make & one cupboard with shutter beneath the drawer, made of 18mm thick commercial ply board with 1mm thick laminate of desired shade, design and gloss on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12mm thick plywood, bottom of 6mm thick plywood & front of 18mm thick ply board.				
	All other surfaces i.e. inside / legsapce of table, inside of drawer / cupboard shall be provided with 0.8mm thick laminate of desired shade/design and gloss, and wood lipping / beading shall be PU polished with matching pigment/deco painted in desired colour. The table shall have a CPU ledge made of 18mm thick ply board on one side, complete as per drawing.				
	MAKES:				
	PLY: CENTURY/GREEN/DURO OR EQUIVALENT				
	MICA: GREEN/SUNMICA/MARINO OR EQUIVALENT				
	ADHESIVE: FEVICOL SH/ VAMICOL/JIVANJOR OR EQUIVALENT				
	LIPPING/MOULDING: CP TEAK FIRST CLASS				
	HARDWARE: OZONE/DORMA/GODREJ				
a)	2.13 X 0.91 X 0.76	1.00	no.		
b)	1.68 X 0.76 X 0.76	4.00	no.		
5	<u>LOW HEIGHT STORAGE CABINETS/BACK STORAGE: (2'6" HIGH)</u>				
	(a) Providing and fixing storage cabinets of size 2'6" (High) x 18" (Deep) along the walls/partitions, as per interior drawings, using 18mm board for carcass, shutters, vertical and horizontal partitions, 6mm ply for the back and 1mm High Gloss laminate of approved shade on vertical and horizontal visible surfaces. The shutters shall be overlapped on the carcass and shall be provided with EBCO hinges. The width of the shutter shall be between 12" to 15" as per the site conditions. All the exposed edges of the board shall be provided with wooden lipping 18mm x 3mm, duly PU poished/deco painted in desired shade. The inner surface shall be provided with 0.8mm thick laminate of desired shade, design and gloss. The cabinet shall be complete with handles, knobs, locks and magnet catchers etc. to the satisfaction of the Architect/Engineer.	9.30	RMT		
	MAKES:				
	PLY: CENTURY/GREEN/DURO OR EQUIVALENT				
	MICA: GREEN/SUNMICA/MARINO OR EQUIVALENT				

		ADHESIVE: FEVICOL SH/ VAMICOL/JIVANJOR OR EQUIVALENT			
		LIPPING/MOULDING: CP TEAK FIRST CLASS			
		HARDWARE: OZONE/DORMA/GODREJ			
6		LOW HEIGHT STORAGE CABINETS/BACK STORAGE: (2'0" TO 2'3" HIGH)			
		(a) Providing and fixing storage cabinets of size 2'6" (High) x 18" (Deep) along the walls/partitions, as per interior drawings, using 18mm board for carcass, shutters, vertical and horizontal partitions, 6mm ply for the back and 1mm High Gloss laminate of approved shade on vertical and horizontal visible surfaces. The shutters shall be overlapped on the carcass and shall be provided with EBCO hinges. The width of the shutter shall be between 12" to 15" as per the site conditions. All the exposed edges of the board shall be provided with wooden lipping 18mm x 3mm, duly PU polished/deco painted in desired shade. The inner surface shall be provided with 0.8mm thick laminate of desired shade, design and gloss. The cabinet shall be complete with handles, knobs, locks and magnet catchers etc. to the satisfaction of the Architect/Engineer.	12.04	RMT	
		MAKES:			
		PLY: CENTURY/GREEN/DURO OR EQUIVALENT			
		MICA: GREEN/SUNMICA/MARINO OR EQUIVALENT			
		ADHESIVE: FEVICOL SH/ VAMICOL/JIVANJOR OR EQUIVALENT			
		LIPPING/MOULDING: CP TEAK FIRST CLASS			
		HARDWARE: OZONE/DORMA/GODREJ			
7		TEXTURE PAINT:- (Spectrum Finish)			
		Providing & applying spectrum surface texture finish of approved shade & colour on walls as per requirement & manufacturers recommendations.	147.47	SQ.M	
		MAKES:			
		TEXTURE PAINT: SPECTRUM/ASIAN/ALTEC OR EQUIVALENT			
8		HYDRAULIC DOOR CLOSER:			
		Providing and fixing silver color (or matching with color scheme as per site) hydraulic door closer Godrej/dorma/ozone/Hyper / Everrite ISI marked make, to doors complete in all respects.	3.00	NOS	
		MAKES:			
		HARDWARE: OZONE/DORMA/GODREJ			
9		VITRIFIED TILE FLOORING 600MM X 1200MM			
	11.41	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 50mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including providing 3mm thick joints with required spacers and filling the joints with epoxy of desired colour as per the manufacturer's specifications.. (Italian Marble Shade Digital Tiles from Johnson and Johnson, Kajaria, Somany etc)	137.33	SQM	
	11.41.2	Size 600mm x 1200mm			
		MAKES:			
		TILES: Italian Marble Shade Digital Tiles from Johnson and Johnson, Kajaria, Somany etc			
9		DISMANTLING			

	Dismantling of the existing furniture, false ceiling, storages, partitions or any of the interior or civil work for the execution of the above said works as per the specifications and the approved plans. The works shall also include the disposal of the unwanted material to the suitable location as per the MC and stacking of the usable material to a location as per the direction of the engineer-in-charge.	1.00	LS		
	Total Value of Works				
	NOTE: THE BUY- BACK OF THE EXISTING FURNITURE SHALL BE DECIDED AS PER THE INSTRUCTIONS OF THE BANK.				