## Price bid for SITC of Down comer system (Hose Reel/Terrace Pump & Accessories) at CPPC, **Bhopal building** S.No **Item Description** Quantity Unit Rate per unit Amount (Rs.) SITC of Fire Bridage Inlet (2 way) with 63 mm dia intstaneous inlet 2 complete with all necessary fittings and Stainless Steel NRV. Nos (MAKE – NEW AGE/ GEI /AAAG or other equivalent ISI Mark) SITC of Cast iron body Non-Return valves (NRV) PN1.6 dual plate with matching flanges, rubber insertion, nuts, bolts and washer etc. of 2 following sizes complete as regd. (Make:Sant /Kartar/New Age/Audco/other equivalent ISI Mark) 100 mm dia 3 Nos 80 mm dia 2 Nos b Supply, fixing, testing commissioning of butterfly valve PN 1.6, with Bronze/ Gunmetal seat duly ISI marked complete with Nuts, Bolts, washers, gaskets, conforming to IS 13095, of following sizes as required. (MAKE – NEW AGE/ SWATI/Lifeguard /Kartar/other equivalent ISI Mark) 8 а 100 mm dia Nos Providing, fixing, testing and commissioning of Above Ground M.S. ERW Black C Class Heavy duty pipes as per IS: 1239 including cutting, screwing, welding etc. and providing all fittings like flanges, bends, tees, elbows, reducers, clamps, hangers etc. with painting of one coat of primer and 2 or more coats of synthetic enamel paint of approved make / shade complete as per specification (MAKE TATA/ JINDAL/ Nezone/other equivalent ISI Mark) 100 mm dia 158 RMT 80 mm dia RMT 20 25 mm dia 10 RMT SITC of Fire Aid Hose Reel Drum with 30mtrs long thermoplastic hose type 2 as per IS:12585 and GM shut off nozzle 25 mm dia Gate Valve, 5 Nos Union pipe complete set confirming to IS: 884 (MAKE – NEW AGE/ AAAG/ SWATI /Lifeguard / other equivalent ISI Mark) Providing, fixing, testing & Commissioning of Single headed ISI Marker Oblique pattern Stainless steel Hydrant Landing valve with 80 mm dia, flanged inlet & 63 mm dia instantaneous type female outlet complete with cap and chain twist release lug and all accessories as per IS: 5290-Nos 1983 (Type -'A') and specifications complete as required. (MAKE – NEW AGE/SWATI/ Lifeguard/Shah Bhogilal/ Ghosh Engg/ New Age/ Safex or other ISI Mark) Providing & Fixing of weather proof hose cabinets fabricated from 18 S.W.G M.S Sheet with Centre opening full front glass door and locking arrangement suitable to accommodate 2nos 15M Long hoses and 1 no. Branch Pipe with nozzle. The cabinet shall be painted with one coat of 5 Nos primer and 2 or more coats of synthetic enamel paint of approved make & shade and shall be suitably mounted on a raised masonry platform

complete as reqd.(Make - Self Fabricated) 750 X 600X 250 MM

| 9  | Providing RRL Hose with ISI Marked (IS:636) 63 mm dia X15 M long complete with instantaneous type Stainless Steel 63 mm dia ISI Marked male & female couplings (IS: 903) bound & riveted to hose pipes with SS rivets and SS wire complete as required. (MAKE: Shah bhogilal/Newage/Lifeguard/BRG or equivalent ISI Mark)  Providing & Fixing of Stainless Steel 63 mm dia Short Branch Pipe 20 mm dia nozzle, ISI marked (IS: 903) complete as required. (MAKE– Shah Bhogilal/ Ghosh Engg/ New Age/Lifegaurd/ SWATI/TULSI/ or other equivalent ISI Mark)  Supply & fixing of 100mm dia bourden type glycerin filled, Stainless steel dial type pressure gauge(0 - 16 Kg) range, 3 / 8 " BSP bottom entry on Pump Delivery Line complete with Ball valve (Wikai/ Waree/ baumar   | 5 2 | Nos |  |
|----|--|-----|-----|--|
| 11 | /Guru/other equivalent ISI Mark) Supply & fixing of Pressure switches for automatic operation of pumps, including necessary wiring upto control panel and Ball valve. (Make Potter/Indfos or other equivalent ISI Mark)  | 2   | Nos |  |
| 12 | Supply, Installation, Testing & Commissioning of Electric Driven Terrace pump for Hydrant applications suitable for automatic operation and consisting of following details given as A, B, C, D, E, F, G. (Make-KIRLOSKAR / Mather & platt /ABB/Siemens/Lubi/other equivalent ISI Mark)  A. Horizontal Single stage Centrifugal End suction, back pull type pump complete for delivery of below mentioned discharge, with necessary accessories the suction side ( all items to be matching with the suction side dia of the pump) including bypass arrangement for Testing of pump B. Material of construction: Pump Casing - Cast Iron, Impellor - Bronze, Shaft - SS 410, Packing - Mechanical Seal  C. Pump shall be capable of furnishing not less than 150 % of rated capacity at a head not less than 65 % of the rated head. The shut off head shall not exceed 120 % of rated head  D. Squirrel cage induction motor suitable for 3 phase, 415 V, 50 HZ, Ac supply T.E.F.C confirming to IP:55, of required HP suitable for the above pump, along with flexible coupling, coupling guard complete in all respect E. Common bed plate fabricated from mild steel channel for installation of pump and Motor  F. Pump technical sheet which confirming required specifications issued by manufacturer to be submitted.  G. Suitable cement concreat foundation duly plastered with anti vibration pads. |     |     |  |
| а  | 450 LPM suitable for 24 Mtr Head, single stage   | 1   | Nos |  |
| 13 | SITC of Starter Panel, Fabricated for capable of Operation of 450 / 900 LPM Terrace Pump or capable of start up to 10 HP pump and having provision for automatic starting by pressure switches, control mounting shall include necessary lamps indications, ammeters for motor full load circuit with CTs and selector switch, auto/manual selector switch voltmeter with selector switch controlling push button etc. The panel shall be duly painted with protective anticorrosive and shall be foot mounted/wall mounted type including all accessories. (Make- L&T/ ABB/ Siemens/other equivalent ISI Mark)  | 1   | Nos |  |

| 14                          | SITC of 4C X 16sq mm, Copper PVC Shielded Cable suitable to run 7.5 HP/5.0 HP pump on maximum load (Fire Panel to Terrace PUMP) (Make-Polycab/ Finolex/ RR Kable/ KEI/other equivalent ISI Mark)  | 50 | RMT |  |  |  |
|-----------------------------|---|----|-----|--|--|--|
| 15                          | Supplying, fixing and placing plastic cylindrical vertical closed top three layers (PVC) tank at the terrace over the staging with manhole cover with locking and cleaning arrangement including arrangements of overflow (Flot valve e.t.c), water filling from existing arrangements availabe at branch and also providing adequate thickness/ capacity MS fabricated stand for placing 5000 and 2000 litre capacity PVC Tank on the terrace, and others connection etc. if required. (Make: Sintex / Polycon or equivalent ISI mark) |    |     |  |  |  |
| а                           | 5000 ltr  | 1  | Nos |  |  |  |
| b                           | 2000 ltr  | 3  | Nos |  |  |  |
| 16                          | Providing and fixing gunmetal of single acting air release valve with screwed inlet 25 mm dia. (Make: Zoloto/ Karter/ Kitz/ other equivalent ISI Mark)  | 1  | Nos |  |  |  |
| 17                          | Miscellaneous Civil work including core cutting, repairing and any other civil work etc.  | 1  | Nos |  |  |  |
| Grand Total (Excluding GST) |   |    |     |  |  |  |