Sr. No.	Description	Quantity	Unit	Rate	Amount
1	MANAGER TABLE- Size 1800mm x 900mm x 750mm	1.00	NOS		
	Supplying and installation of Table as per the following description				
	and as designed by the Architect:				
	Table Top: Providing and fixing 19 mm thick IS 303 BWR grade				
	plywood with 1.0mm thick laminate finish with necessary				
	intermediate support. Table top shall be supported by 18 mm thick				
	BWR grade ply wood with plywood framing. The top of the table				
	shall be provided with equal sized 12mm thick toughened glass				
	with polished edges. The top level of the glass shall be 750mm.				
	Apron (Modesty Panel) made from 18mm thick BWR grade				
	plywood finished with 1mm laminate.				
	Table sides, back & intermediate panels (at 500mm from each				
	side) made from 18 mm thick MR ply wood finished with 1mm laminate for exposed surfaces (4 faces) and 0.8 mm thick laminate				
	for inner surfaces shall be provided as per drawing. Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be				
	provided using 18 mm thick BWR grade plywood. Each Drawer				
	Fascia made out of 18 mm thick plywood and all sides of drawers				
	be made of 12 mm thick plywood & bottom of drawers shall be of 8				
	mm thick BWR grade plywood. The drawer unit box and individual				
	drawers to be fixed with 1mm laminate on all exposed sides and all				
	the internal surfaces shall be finished with 0.80 mm thick balancing				
	laminate. The drawers to be fitted with Telescopic sliding channel				
	with SS Group locks of approved make and 100 mm long brush				
	finish Stainless Steel handles C-type for each drawer. The front ply				
	of the drawers to be overlapping the frame.				
	Computer Keyboard (550 x 375 mm) of metal / PVC of approved				
	make shall be provided. Footrest of 38 x 76 MM T.W members				
	shall be provided. All internal surface will have min. 0.80 mm thick				
	balancing laminate. Table shall have stand of 18 mm ply finish with				
	1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and				
	PVC cable Manager shall be provided in the cutouts on the tabletop.				
	All edges to be provided & fixed with teak wood lipping patti				
	finished with melamine polish. All the surface without laminate /				
	balancing laminate shall be lacquered polished of approved				
	shade.As per drawing and instruction of Architect/Bank, work to be completed.				
	Plywood Make: Greenply, Century, Duro or equivalent approved by				
	the Bank.				
2	OFFICER'S TABLE- Size 1500mm x 750mm x 750mm	10.00	NOS		
	Same as above but the size of table shall be 1500mm x 750mm x 750mm				

Sr. No.	Description	Quantity	Unit	Rate	Amount
3	MEETING ROOM TABLE - Size 1200mm x 750mm x 750mm	2.00	NOS		-
	Providing & Fixing Conference Table of shape as per design made from 50mm X 40mm T. W. Wood framework 450mm center to center both ways for tabletop covered with 12mm thick BWR ply for bottom, 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. All exposed surfaces shall be finish with approved color 1.0mm thk. laminate. All internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be inclusive of Brush Finish Stainless Steel Tray with POP UP Flap for electrical switches including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound,cleaning the site etc. complete as per the detail drawing and instruction of Engineer. Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
	SIDE/ REAR CREDENZA- For officer and clerical staff table				
4 4A	Low Height Cupboard with Laminate Finish: Providing & fixing Low Height Storage Cupboard of 750 height and 450mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 25 mm thk BWR Ply and shelves to be made with 19 mm thk.BWR ply.	28.20	SQMT		-
	approved laminate. All the other internal and external surfaces to be finished with 1.0mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffele), SS towerbolts etc. All shutters to be made overlapping the frame only front elevation will be considered for area calculation. As per drawing and instruction of Architect/Bank, work to be Completed				
	Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
5	WALL/ COLUMN PANELING WITH LAMINATE FINISH.	41.80	SQMT		-
	Wall paneling made from 25 x 25 x 1.00 mm thick hollow aluminum sections, over which BWR grade ply of 10 mm shall be fixed and additional 6-8mm ply in layers to create grooves as per the design in the drawing or as directed by Architect, with decorative molding patty on the edges. Providing and fixing in position wooden paneling to column / walls				
	<ul> <li>finished with laminate comprising as under:-</li> <li>(i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columnns in perfect line, level and plumb.</li> </ul>				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	(ii) Panel Finishing:- Providing & fixing 10 mm thick approved make BWR plywood and additional 6-8mm ply in layers to create grooves as per the design to Aluminum framework finished with 1.00mm thick approved quality and shade laminate, using approved adhesive, in approved pattern & design, including providing grooves, decorative moldings etc. as per Architectural drawings and as directed at site by the Engineer-in-charge.				
	(iii) Providing approved quality, seasoned, full length, Teak Wood molding 15 mm thick with adequate width as required at site, to all openings, cutouts etc duly polished with melamine polish complete as directed by the Engineer-in-charge at site.				
	(iv) The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in- charge at site.				
	(v) Applying 2 or more coats of melamine polish to exposed edges of paneling, moulded beadings etc. including preparation of surface, sealer coats etc. complete including wastage of material, if any, scaffolding for execution of work at all heights and locations etc. complete.				
	<ul> <li>Approved make:-</li> <li>(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.</li> <li>(b) Plywood:- Greenply, Century, Duro or equivalent approved by the Bank.</li> <li>(c) Laminate:- Dorby Mica, Greenlam/Century/Archid / Aerolam or equivalent approved by the Bank.</li> <li>(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.</li> </ul>				
	Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.				
6	MDF FLUTED WOODEN PANELLING	18.40	SQMT		
-	Wall paneling made from framework of 25 x 25 x 1.20 mm thick hollow aluminum sections spaced 600mm c/c, over which MDF fluted wooden panel of 10mm +/- 2mm shall be fixed as per the design in the drawing or as directed by Architect.				
	(i) Framework:- Made out of 25 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columnns in perfect line, level and plumb.				
	(ii) Panel Finishing:- Providing & fixing 10mm +/- 2mm thick approved MDF Wooden Panelling fixed on the aluminum sections with tongue and groove joints in line and level including PU paint.				

	BOQ OF FURNISHING WORK (LOOSE & FIXED FURNITURE) FOR STATE BANK OF INDIA - EMERALD BRANCH, SHAHIBAUG								
	Rate should be inclusive of material,labour,tools, machinery, scaf e etc. all taxes, transportation etc. complete. (Excluding GST) GST	folding, fin	al dispos						
Sr. No.	Description	Quantity	Unit	Rate	Amount				
	(iii) The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in- charge at site.								
7	FULLY GLAZED DOOR Size 900mm x 2400mm	11.00	SQMT						
	Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed / solid / gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures & hardwares.								
	Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank.								
	Mode of Measurement: Door opening size shall be measured.								
8	FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED GLASS UPTO 8' LEVEL WITH SOLID PARTITION ABOVE 8' LEVEL	72.00	SQMT		-				
	Providing & fixing full height glazed partition with 12mm Toughened glass of approved make up to 8' level height with solid partition above 8'-0" level up to false ceiling bottom.								
	The glazed panels shall be fixed to the existing floor and false ceiling with all necessary SS brackets (D, C or U type) Vertical joints between the glass panels shall be sealed with suitable transparent sealant.								
	The solid partition above 8'-0" level shall be made with aluminium framework of size 63mm X38.10mm X1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 6mm BWR ply finished with 1.0mm thick laminate as per direction.								
	Providing, placing in position & erecting full height partition in desired shape, framework shall be of 50 x 50 x 1.5 mm thick aluminum square section placed at 500 mm c/c both ways or as directed.								
9	FULL HEIGHT SOLID WOODEN PARTITION WITH BOTH SIDES	60.30	SQMT		-				
	LAMINATE Providing & fixing in position 70mm thick +/- 2mm full height solid/opaque wooden partitions finished with laminate on both sides comprising as under:-								

Sr. No.	Description	Quantity	Unit	Rate	Amount
	(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm (may slightly vary as per unavoidable site conditions) both ways (horizontal and vertical) fixed rigidly on floor, wall / column &				
	ceiling. (ii) Plywood skin:- Providing & fixing 12 mm thick MDF boards on both sides of the framework.				
	(iii) Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approve quality adhesive complete.				
	(iv) Making suitable cutouts/ openings/ channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.				
	(v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.				
	(vi) Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.				
	(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
	<ul> <li>Approved make:-</li> <li>(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.</li> <li>(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank.</li> <li>(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.</li> <li>(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.</li> </ul>				
10	FULL HEIGHT SOLID / PARTLY GLAZED WOODEN PARTITION WITH BOTH SIDES LAMINATE	15.30	SQMT		
	Providing & fixing in position 70mm thick +/- 2mm solid / opaque partly glazed full height wooden partitions with 1200 mm high glass middle panels finished with laminate on both sides comprising as under:-				
	(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium sections not exceeding 600 mm c/c bothways (horizontal and vertical) except in glazed portion of partition, fixed rigidly on floor, wall / column & ceiling. Spacing of frame members may vary to the nearest possible extent as per site conditions.				
	(ii) Plywood skin:- Providing & fixing 12mm thick MDF boards on both sides of the framework.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
110.	(iii) Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approve qualityadhesive complete.				
	(iv) Providing and fixing 12mm thick approved make 1200 mm high toughened Glass panels in the middle panels of partitions using second class seasoned teak wood moulding of finished sectional size 75mmx12/15 mm all-round, complete as per drawing and as directed at site.				
	(iv) Making suitable cutouts/openings/channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.				
	(v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.				
	(vi) Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.				
	(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
	<ul> <li>Approved make:-</li> <li>(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.</li> <li>(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank.</li> <li>(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.</li> <li>(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the</li> </ul>				
	Bank. Mode of measurement:- Though aluminium frame shall extend up to RCC slab/Beam bottom level above false ceiling, clear partition area below false ceiling shall be measured including deductions for Doors and openings above 0.50 Sqm.				
11	Providing & Supplying Sofas, Sofa chairs of various types & categories (Single seater, Two seater & Three seater) etc complete as per the manufacturers specifications as mentioned below. The rights to select & approve the sofas & seating shall vest with the clients. The contractor shall submit brochures of manufacturer at the time of quoting for this item etc complete as per layout. The consultants reserve the right to select the sofas in line with the technical specifications envisaged & meeting the specifications standards expected.				
	(Approved makes: Godrej / Durian / Featherlite)				
11A	Two seater sofa	1.00	NOS		-
11B	Three seater sofa	3.00	NOS		
40		00.00	0017		-
11B 12	FALSE CEILING FINISHED WITH LAMINATE	26.90	SQMT		

## BOQ OF FURNISHING WORK (LOOSE & FIXED FURNITURE) FOR STATE BANK OF INDIA - EMERALD BRANCH, SHAHIBAUG Note : Rate should be inclusive of material, labour, tools, machinery, scaffolding, final disposal of debris , cleaning cutting wastage etc. all taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills. Sr. Quantity Unit Description Rate Amount No. Same as Gypsum false ceiling but instead gypsum boards providing, making, and fixing 12 mm thick. BWR Grade ply, and additional 6-8mm ply in layers with molding of approved design shall be fixed as per drawing or as directed by Architect, with decorative molding patty. The plywood should be finished with 1 mm thick. Laminate of approved colour(wooden finish) and quality.

Sr. No.	Description	Quantity	Unit	Rate	Amount
13	CENTER TABLE (900mm X 600mm OVAL / RECTANGULAR)	3.00	NOS		-
	Providing and supplying in position oval or rectangular centre table to be made out of 2" X 2" teakwood frame including 12mm thk clear glass top with bevelled edges including bottom glass shelf with etching etc complete. The rate shall also include SS lining design to the teakwood frames including all the necessary hardware, fittings, fixtures as per manufactursrs specifications complete.				
14	BACK PAINTED GLASS				
15A	Back painted glass (Lacquer Glass) paneling: Providing and fixing in position wooden paneling to column / walls finished with Back painted (Lacquer Glass) comprising as under:-	29.90	SQMT		-
	(i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed upto 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columnns in perfect line, level and plumb.				
	(ii) Panel Finishing:- Providing & fixing 12 mm thick approved make BWR plywood to Aluminum framework finished with 8 mm thick approved quality and make back painted Lacquer Glass panels of required size, rigidly fixed using 3M adhesive / double side self- adhesive tape complete as directed by the Engineer-in-charge.				
	(iii) The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards etc., including providing necessary wooden/aluminum section members support at cutouts, providing scaffolding for execution of work at all heights, complete as per drawings and as directed by the Engineer-in-charge at site.				
15		1.80	RMT		
15	Providing and placing in position Reception Table of approx. size depth 600 mm and 750 mm height. (length should be specified as per site condition) Made from 18 mm BWR grade ply as per design given by the Architect, additional 8/12 mm ply in multiple layers to be used as per drawing. All drawers shall be made in 12 mm thick BWR grade ply fixed on soft closing slides, with approved quality locks. All external faces to be finished with 1 mm thick. Laminate of approved color and quality and internal faces with 0.8 mm thick. Laminate in the color white.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
16	SINGLE WINDOW COUNTER / CASH COUNTER Size - 1500 mm X 900 x 750 mm with White acrylic solid surface & blue lacquered glass finishing	7.50	RMT		-
	Supplying & fixing single window counter as per design and drawing made out of 18 mm thick IS 303 BWR grade ply wood boxing of approved make, complete with 18 X 6 mm Teak wood beading on all edges wherever required. Tabletop made from 12mm thick ISI 303 BWR-grade flexi ply. The countertop to be finished with 6mm thk. sparkle white Corian sheet with 1.5" Thk. Bull Nose Moulding from inside and Curved Machine polished edge from outside dropped down to form light pelmet on front Apron as per detail drawing. The vertical surface below the apron to be finished with blue lacquered glass. Working table top and edges shall be finished with 6 mm thick sparkle white acrylic solid surface (corian of DUPONT/ Merino/ REHAU or equivalent approved make ) as per drawing and direction with all labour and material.				
	The cost shall be inclusive of S & F of a drawer unit or drawer & shelf unit (in place of bottom 2 drawers) made of 18 mm thick MR grade plywood and with approved make multipurpose Auto Lock in drawer and group lock in shelf unit. Inner width of drawer box be 400mm, one side of box is leg panel, upper side of box is table top, back side modesty panel and Bottom of Box is of 18 mm thick ply. 4 Nos drawers shall be 525 mm deep (inner dimension), First (Top) drawer 100mm height (facia) & rest 3 of equal size. Top two drawers shall be Cash drawer having 6 equal compartments for currency notes.				
	Foot rest of 75 mm X 38 mm (3" x 1.5") in Teak wood and CPU stand of 18 mm ply finished with 1 mm thick laminate of size 400 mm X 375 mm. Key board tray of approved make of size 450 mm X 375 mm to be fixed.				
	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade. All fittings like 75 mm long S.S. handle, Auto Lock to each drawer and cabinet doors, piano / auto hinges, ball catcher, stopper, metal cable manager etc. should be fixed of approved make. Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers.				
	All the internal surface (non-visible surface) shall be provided with 0.80 mm thick balancing laminate of approved shade etc. complete. Counter shall be made independent in Length of 1600 mm and properly placed between two partitions. Counter will be measured in RMtr between two partition and paid.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
	FINISHING DETAILS:				
	1) Table Top: 6 mm thick white acrylic solid surface				
	2) Front Appron: Round 6 mm thick white acrylic solid surface and				
	6 mm thick blue lacquered glass fixed with Natural Silicon				
	3) Facing of Drawers: 1.00 mm thick laminate finish				
	4) All the internal surface (non-visible surface) shall be provided				
	with 0.80 mm thick balancing laminate				
	Brief list of make are as under or any equivalent make will be				
	permitted by the Engineer:				
	MR grade Ply wood ( IS :303) - Green / Century / Anchor / Archid /				
	Mayur / Kit / Samrat / Croma				
	Acrylic solid surface (Corain) - Dupont/ Merino/ REHAU or				
	equivalent approved				
	Laminate- Green / Formica / Sunmica / Century /Marino / Aica				
	Multipurpose group Lock - Ebco / EG / Godrej				
	Telescopic channels - Ebco / Everite				
	Keyboard tray - Ebco / Hettich / Innofit / Featherlite				
	Auto lock- Ebco / Dorma / Ozone				
	Cable Manager (60mm) - Metal - Ebco or equivalent				
	Adhesive- Fevicol / Pedilite / Araldite / Royal Bond				
	LOW HEIGHT WOODEN PARTITIONS (LHP) WITH LAMINATE				
17	FINISH	22.60	SQMT		-
	Providing & fixing in position 70 mm +/- 2mm thick Low height				
	wooden partitions with 450mm high glass panel finished with				
	laminate on both sides comprising as under:-				
	(i) Total Height of the partitions shall be from 1200 mm to be 1350				
	mm including 300 to 450 mm high 12 mm clear glass panel as per				
	approved drawing.				
	(ii) Framing : Made out of 50mm x 50mm, 1.2 mm thick hollow				
	aluminium sections placed bothways (horizontal and vertical) not				
	exceeding 450 mm c/c rigidly fixed to floor, wall / columns etc				
	including extending end/intermediate vertical members not				
	exceeding 1500 mm c/c for total finished height of LHP.				
	(ii) Skin : Providing & fixing 12 mm thick MDF plywood on both				
	sides of the framework and all-round vertical posts extending up to				
	total height of LHP.				
	(iii) Finishing :- Providing and fixing 1.00mm thick approved quality				
	and shade laminates using approve quality adhesive, over ply as				
	per approved design & pattern including providing grooves as per				
	Architectural drawing and as directed by the Engineer-in-charge.				
	(iv) Glazing :- Providing and fixing 12mm thick approved make				
	clear float glass panels (not exceeding 1.50 m in length) with				
	polished edges on all sides, fixed using suitable CP Brass /SS 'D'				
	brackets placed not exceeding 450mm c/c on horizontal surface of				
	partition and at both ends on vertical posts to rigidly hold the glass				
	panels.				
	(v) Providing finished section size 70/75 x 8mm thick seasoned				
	second class Teak wood moulding to all exposed edges of partition				
	including applying 2 or more coats of melamine polish / Duco paint				
	including necessary preparatory work for surface preparation with				
	putty, priming coat, sealer coat etc. complete as per sample				
	approved by the Bank.				1

Sr. No.	Description	Quantity	Unit	Rate	Amount
110.	(vi) Making necessary cutouts for electrical conduits / cables & switchboard etc., including providing additional supports wherever required complete as per drawings and as directed by Engineer.				
	(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
	<ul> <li>Approved make:-</li> <li>(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.</li> <li>(b) MDF: - Greenply, Century, Samrat or equivalent approved by the Bank.</li> <li>(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.</li> <li>(d) Adhesive: Fevicol SH/Vamicol or equivalant approved by the</li> </ul>				
	<ul> <li>(e) Enamel Paint/polish: Asian/Nerolac/Berger or equivalent approved by the Bank.</li> <li>(d) Glass: Saint Gobain, Asahi Float, Modi Guard.</li> </ul>				
18	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS PARTITION ON COUNTER TOP, FRONT SIDE AS FOLLOWS.	3.40	SQMT		-
	Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. Two cutouts to be made one half round of 150mm dia and another for mouth piece rectangular size of 75mm wide 450mm long. All edges of glass shall have Diamond cut polished edges as directed. Brief list of make are as under or any equivalent make will be permitted by the Engineer Glass- Asaahi/ Tata / Modi guard / Saint gobain Square bracket (50 mm x 12.5 mm ) S S finish - Oswal / Riddhi / Swift or equivalent				
19	PROVIDING AND FIXING 12 MM THICK TOUGHENED FLOAT GLASS PARTITION TOWARDS FRONT SIDE OF SINGLE WINDOW COUNTERS TOWARDS PUBLIC SPACE AS FOLLOWS.	1 40	SQMT		-
	12 mm thick Toughened clear float glass of required shape with bevelled edges on top portion shall be fixed with SS brackets with flat back on wooden partition and counter top as directed. All edges of glass shall be Diamond cut polished edges as directed complete. Maximum length and height will be measured for payment purpose. Brief list of makes are as under or any equivalent make will be permitted by the Engineer Glass- Asaahi/ Tata / Modi guard / Saint gobain Square / D bracket S S finish of required size - Oswal / Riddhi / Swift or equivalent				
	approved make				
20	WAITING AREA SEATING	4.00	NOS		-

	BOQ OF FURNISHING WORK (LOOSE & FIXE			R	
Noto :	STATE BANK OF INDIA - EMERALD BRAI Rate should be inclusive of material,labour,tools, machinery, scaf			al of dobria	alconing outting
	e etc. all taxes, transportation etc. complete. (Excluding GST) GST				
of Bills		nii so pai	a ao np		s and of payment
Sr.					
No.	Description	Quantity	Unit	Rate	Amount
110.	3seater polypropylene chairs in approved color of approx. single				
	seat size 530 x 560 x 850 mm height (including back rest) Make:				
	Godrej, Featherlite, WIPRO.				
21	POLYESTER FILM OVER GLAZED PARTITIONS:	43.60	SQMT		-
	Providing and fixing in position high impact resistant Polyester				
	Films of approved design & pattern, which once installed on glass, give additional strength to glass, reduce glare & prevent glass from				
	splintering on impact. thickness not less than 4 Mil (100 mic.) or 7				
	Mil (175 mic.)				
22	ROLLER BLINDS	17.10	SQMT		-
	Providing, fabricating and fixing vertical roller blinds of approved				
	make preferably of "Vista Levelor" with a woven made acrylic	1			
	coated fabric of 100% polyester of thickness $0.50 - 0.60$ mm (+/- 5% tolerance) with the main properties like resistance to Cracking				
	& Fraying, dust repellence, UV proof and virtually maintenance free				
	along with the Vista accessories of like Head rail, Roller tube Idler,				
	Bottom rail, chain, matching colour installation brackets etc.				
	including all fixtures and fittings of Vista like Rainbow curtain rods				
	with electric resistance welded MS pipe having a corrugated virgin	1			
	PVC extrusions reinforced to minimize friction, finials and along				
	with standard anchoring arrangements etc. all complete done in				
	workmanlike manner as per the approved design, colour and including necessary scaffolding as directed.				
	Providing and fixing 1.0mm thick laminate on any existing laminate				
	surface by fixing 4mm / 6mm thick MDF baord. Rate includes				
23	applying lacquer polish on all existing exposed wooden member etc. complete. Only laminate finished surface area shall be		SQMT		-
	measured for payment.				
24	DINING TABLE SIZE: 1200 X 750 X 750 HT.	1.00	NOS		-
	Supplying and Providing Dining Table, T.W beading shall be fixed				
	on border .Top shall be made of 18mm thick commercial plywood				
	with additional 18mm thick Ply wood patta of required width on				
	edges with 1.0mm thick laminate on top of approved shade brand and. supports of the Table shall be made of 2" x 2" T.W. members				
	in a Design as directed. All surfaces not laminated shall be lacquer				
	polished.				
	Exposed edges of Table Top shall be made 36mm thick by				
	providing additional 18 mm thick ply wood patta of required width.				
25	ELECTRIC CUB BOARD	4.70	SQMT		
		L 4.70			-

Sr. No.	Description	Quantity	Unit	Rate	Amount
	Providing and fixing Electric cupboard using 18mm thick bision panel for verticale and shelves and aluminium framing of 50 x 25 x 1.20mm thick with 6mm thick bision panel on both side for shutter with 1.0 mm thick laminate on all exposed surface and polishing/ synthetic enamal paint on all internal surface. shutter with approved make lock handle, hinges,ball catches P & fixing S.S Perforated jali shall be provided in shutter etc.complete as directed, depth of cup board 1'-3". Shutter height up to 7'-0"/8'-0" and above fixed Type up to false ceilling bottom.				

Sr. No.	Description	Quantity	Unit	Rate	Amount
26	SHUTTER FOR UNDER PANTRY PLATFORM	1.40	SQMT		_
	Providing and fixing cupboard shutters below pantry platform using 1 1/2" x 2 1/2" T.W members for frame, 18mm Tk plywood with 1.0mm lamiante for shutters. Providing 1/2" th T.W beading all around shutter. Providing S.S hinges, Handles, stoppers and magnetic catch as directed. All the surface shall be polished/ synthetic enamal paint as directed complete.Providing and fixing 0.60mm thick balancing laminate on internal shutter surface				
27	12MM THICK TOUGHENED GLASS DIAPHARM FOR SEPARATING TWO M/C FOR E-LOOBY	4.40	SQMT		-
	Providing and fixing 12mm thick Toughened glass Diapharm for Separating of between two M/C with etching and frosting Films complete as directed. Glass edges shall be round moulded and polish as per direction complete.Glass shall be fixed in wall and floor with necessary suitable patch fittings as directed. (Area based on outer diameters shall be measured and paid).				
28	ISOLATED FLUSH DOOR SHUTTER (Partly Glazed and Partly Laminate) WITH FRAME	6.10	SQMT		-
	Providing and fixing 4"x2" steam beach member for frame and Flush door shutter made out of 31mm thick flush door with 6mm thick clear float glass vision panel secured with 12mm thick steam beach beading, 31x 12 mm thick steam beach periphery patti around shutter edges, 1mm thick laminate on both sides, 35x12mm thick steam beach stopper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Aprroved make Ded Lock, S.S Handles, 150mm long Door stoppers, doorstop of approved make etc. all exposed surface /edges not laminated be provided with lacquer polish. As per drawing and instruction of Architect/Bank Complete				
29	ISOLATED FLUSH DOOR SHUTTER (Partly Glazed and Partly	2.00	SQMT		_
	Laminate) WITH FRAME FOR UPS ROOM Providing and fixing aluminium frame of 65mm x 38mm x 1.5 mm thick and door shutter made out of 50x25x1.5mm thick framing at maximum 1'-6" C/C both way with 8mm thick Hilux Board on both side with painting.Providing 6mm thick clear float glass vision panel secured with 12mm thick steam beach beading, 31x 12 mm thick steam beach periphery patti around shutter edges, aluminium stoper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Aprroved make Ded Lock, S.S Handles,Door stoppers, doorstop of approved make etc. complete as per drawing & instructions				
20	WICKET CATE	0.00	00147		
30	WICKET GATE	2.20	SQMT		-

BOQ OF FURNISHING WORK (LOOSE & FIXED FURNITURE) FOR							
STATE BANK OF INDIA - EMERALD BRANCH, SHAHIBAUG							
Note :	Note : Rate should be inclusive of material, labour, tools, machinery, scaffolding, final disposal of debris , cleaning cutting						
wastage etc. all taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment							
of Bills.							
Sr.							
No.	Description	Quantity	Unit	Rate	Amount		
	Same as above but 30mm thick flush shutter with both side						
	laminate including SS hinges with countersunk SS screws,						
	Aprroved make Night latch Lock, S.S Handles, Door stoppers,						
	doorstop etc complete as directed.						

Sr. No.	Description	Quantity	Unit	Rate	Amount
04		4.40	OONT		
31	<b>SOFT BOARD</b> Providing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6mm thick commercial plywood on back side and 12mm th soft board on front. Fixing cloth of selected design of Basic rate of Rs. 150 per mt.steam beach member shall have lacquer polish as directed complete.		SQMT		-
32	SLIP COUNTER size: 900mm x 350mm x 1050mm Providing and fixing writing desk size: 900mm x 350mm x 1050mm ht. Verticle Sides and bottom shall be made out of 36 mm (2X18) thick Commercial plywood and back side 12mm thick ply wood		NOS		
	with Laminate on Top and Edges on all sides including inside divisions. Top shall be made from 12mm th Thoughend glass with polished edges making diff divisions by 18mm thick plywwod with laminate on both side for slips or forms as per detail drawing and inststruction complete. (Drawing as enclosed herewith) Laminate to be provided on all visible surface.				
33	DRESSING UNIT WITH PUFFY size: 450mm x 1200mm	1.00	NOS		
	Dressing Table shall have 450mm x 1200mm, 5mm thick mirror with 1 1/2" x 3" T.W frame and 6mm thick BWR plywood 2'-0" x 6" size having polished edges supported by brass bracket 2 Nos. as directed.				
	Puffy shall be made of using TW member size 2"x2" and 18mm th.plywood for seat support. Seat shall be padded with 4" foam covered with hession cloth and upholstered with Approved shade and quantity fabric. Basic price of fabric shall be Rs.400 per Rmt. Visible wooden support shall be polished,Size of Puffy shall be 1'6"x1'6".				
34	ACP SHEET PANELING (e Lobby) Providing and fixing 3 mm thick aluminium composite panel of Flexi Bond / Euro Bond with 0.25 mm foil with 2" x 1" x 1.20 mm thick aluminium hollow section tray system with minimum 20 mm bending with silicon Dow Coming of GE seal proof - ACP of approved indian make complete as per selection and direction of Architect for front facade for the building This item will be carried out as per manufacturer specifications. Rate also including trap door shutter including hinges stopers etc complete as directed. Design as per Bank standered Drawing and Architects instruction		SQMT		-
	TOTAL COST "A"		RS.		-
			πэ.		-