

S.I.T.C. OF ONE NO 8 PASSENGER / 544.0 Kgs, ELEVATOR AT STATE BANK OF INDIA, GWALIOR, MP.						
PASSENGER LIFT :						
Sl. No.	DESCRIPTION OF ITEMS	QTY	UNIT	RATES	AMOUNT	
	PART-A					
1	Supplying Installation ,Testing and Commissioning of Passenger elevator of capacity of 8 persons /544.0 Kg with Machine room complete with Specifications and Following requirements :					
	i Load and Speed @ 1.00 MPS.					
	ii Travel : Ground + 2 Floors. (Total Three Floors) excluding machine room					
	iii Stop and Openings : 3 Stops, 3 Openings (All opening on same side). Single Entrance car					
	iv Power supply : 415 Volts 3 Phase 50 cycle AC supply Light supply : 230 volts, 1 phase ,50 cycles, A.C.					
	v Main Drive for Car : AC variable voltage, variable frequency (VVVF)					
	vi Drive for Car door : AC variable voltage, variable frequency (VVVF)					
	vii Controls : ACV3F, 32 bit Microprocessor integated serial communication control system with RMS (Remote monitoring system)/ BMS (Building monitoring system) supporting software					
	viii Operation : Simplex, fully collective selective operation with/ without attendant					
	ix Machine : Permanent magnetic synchronous gearless motor					
	x Car Dimensions : 1000-1100 mm wide x 1300-1400 mm deep x 2200 mm hight (Car inside Dimensions)					
	xi Car Enclosure :					
	a. Panels – Return , side and Rear : shall be fully Stainless steel body,hair line finished with a distinctive style and elegance to provide a luxurious appearance. Including rear side(Back wall) Mirror 6mm thk. Mirror glass(width of car, Ht.1200mm) (Stainless steel Moonrock finish to match the car interior at the time of execution)					

SI.	DESCRIPTION OF ITEMS	QTY	UNIT	RATES	AMOUNT
	Car Door : Stainless steel Moonrock finish to match the car interior at the time of execution				
b.					
c.	Flooring : Grey Vinyl Tiles.				
d.	Ceiling & Ventilation : Sheet steel with Milky white acrylic covers,				
	2 nos indirect fluorescent lights, Forced Car ventilation (with fan switchin service cabinet and autocut off)				
xii	Landing Doors : Stainless steel hair line finished landing doors with provision for emergency key opening at all landings.				
xiii	Door Operation : Automatic central opening with electronic door detector.				
xiv	Car operating panel 1 Full Height Stainless Steel Face Plate Silver brushed StSt Segmented LCD display Square flush mounted KDS90				
xv	Landing Signalization Stainless Steel 7 segment display Flush Mounted Silver brushed StSt Square,flush mounted KDS90				
xvi	Signal Fixtures :				
a.	Digital Hall Button.				
b.	Position indicator and Car direction Indication (CDI).				
c.	Interphone for communication to Car.				
xvii	Other features :				
a.	Attendant Operation.				
b.	Hall Call Detection.				
c.	Automatic car return device.				
d.	Non stop button in car (Available with Attendant operation),				
e.	Inter Communication Unit				
f.	Serial Communication				
g.	Radio Interference filter.				
h.	Hall Call cut out (By software).				
i.	Door Open & Close button.				
j.	Over current protection ,				
k.	Overload and Load Non stop Device.				
l.	Battery operated Alarm Bell and Emergency Light with battery charger.				
m.	Light Ray device.				
n.	Full Car Operating Panel with digital clock & temp. display,				
o.	Voice synthesizer.				
p	Accurate releveilling, Automatic, closed door				
q	Fireman's switch etc.				
r	Car failure Operation (safe landing)				
s	Over load Warning.				
t	Infrared curtain door operation.				
u	Provision for Lighting in Lift well and Car top for maintenance and other safety features complete in all respect as per the specifications.				
v	ARD System with suitable battery , battery charger and other equipment etc complete as required./Emergency rescue device with audio announcer				

SI.	DESCRIPTION OF ITEMS	QTY	UNIT	RATES	AMOUNT
	xviii Standard				
	Correction drive to next level Emergency Alarm @ Main Floor Car Call backwards Overload function, constant indication/Buzzer Bypass load Function Auto Cut off Fan and Light Manual Rescue Operation Centralized Hoisting for lesser vibration and smooth travel Pit Ladder Micro movement Led Based Buttons L.W.D. (Load Weighing Device) Direction & Position Indicator In Car & Landing Advanced Car Position Indication Automatic Brake Test function every 11hours Every run brake supervision Phase reversal functioning Signal Fixtures +10% to -10% Voltage Fluctuation Withstanding Capacity Door Close Button Door Open Button Car Emergency Light Fireman Drive Curtain of Light 169 Beams Accurate Releveling, Automatic, Closed Door				
	xix Additional				
	Yes, Adavnced Door Opening selected Emergency Rescue Device with audio announcer 2 Way Dedicated Intercom Nudging service Attendant Service Lift Announcer BMS Square Spot Light LED Access Control Provision Interface only Continuous, Priority call in car B, 2 Hours Fire rated Yes Elec surge protection selected				
	Standard Limits for Lifts :				
	a. Rate of ACC / DEC : 1.0 M/Sec sq (Max.)				
	b. Jerk : 1.2 M/Sec Cu (Max.)				
	c. Car Vibration (Vertical / Horizontal) :20 / 6 mg (Max.)				
	d. Noice Level :				
	i. Car : 56 db (From 1 Meter distance)				
	ii. M/C Room : 75 db (From 1 Meter distance)				
	e. Level Accuracy : +/- 8 mm (Max)				
	f. Flight Time (For 3.0 Meter) : 7.0 Sec.				
	TOTAL AMOUNT FOR LIFT WORKS AS PER ABOVE	1	No.		
	GST as Applicable				
	PART-B (AMC WORK'S)				

design home

Architects, Interior Designers Landscaping Consultants,
455/3 Shakti Nagar Bhopal.

SI.	DESCRIPTION OF ITEMS	QTY	UNIT	RATES	AMOUNT
SI.		Amt. of Part-'A' +% Yearly AMC			
		Amount (AMC as per Yearly)			
1	For 1st Year @ 5.0% of Part-'A'. without GST , Elevator after the Defect liability period or One year				
2	For 2nd Year @ 5.6% (B)				
3	For 3rd Year @ 6.16% (C)				
4	For 4th Year @ 6.7 % (D)				
5	For 5th Year @ 7.5.% (E)				
	TOTAL AMOUNT OF AMC PART-B 2 TO 6)				
	Note:- The Amount are excluding the GST				