	BOQ FOR INTERIOR & FURNITURE WORK WITH PAINTING WORK OF							
SI.No	RAJNAGARH NEW BRANCH Description of items	Unit	Qnty	Rate(Rs.)	Amount(Rs.)			
1	<b>SWO COUNTER</b> : Supply and installing new <b>SWO Counters</b> of overall size 1680 mm X 1830 mm X 750 mm, including cost of side credenza (1200mm x 450 mm x 750 mm) made up of 19 mm thick Block board of approved brand all around and finished with laminate of not less than 0.8 mm thick of approve colour, brand and shade. The cost to include three drawers of 375 mm wide made up of 6mm/12mm ply of approved brand on right hand side of the table on telescopic slider with partitions for keeping of notes of different denominations, a keyboard tray 250 mm wide, CPU stand, foot rest as design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to be finished with laminate. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved make. Locks to be of single control type. Design and detail of the counters shall be as per Bank's new uniform colour, layout & elevation policy, with curvature on front with flexi ply. <b>Counter &amp; Credenza top to be provided with 8mm thick glass</b> duly finished on edges and necessary cut to accommodate wires, edges to be IIC and placement as per layout given.	Each	3					
	Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/Kitply or equivalent. Laminate Make: Greenlam/Centurylam/Archidlam/Merinolam or equivalent.							
2	Providing & fixing <b>counter Front 12 mm thick float glass</b> with polished edges,fixed with necessary S.S Brush finish brackets support on wooden partition as directed. Rate shalll includes fixing of frost film as per design & directed, cost of studs, making cut-outs for transaction and voice hole.	SQM	3.5					
3	Providing & Fixing <b>12 mm thick float glass</b> of size 320mm (width) x 1100mm (height) & tapering towards bottom as per the design and shape as shown in Bank's new uniform colour, layout & elevation policy, fixed with silicon and T.W beading support on wooden partition as directed, on either sides of SWO as per design. Rate shall includes etching of glass as directed by bank. All edges of glass shall be duly bevelled & polished as directed complete. Make: Saintgobin/ Modiguard or equivalent.	SQM	2					
4	Supply and installing of size- 2130 mm x 1830 mm x 750 mm <b>including cost of side</b> <b>credenza (1080mm x 600mm x 750 mm) for Chief Manager</b> made up of 19mm thick Block board all around, finshed with not less than 0.8 mm thick laminate of colour, shade & brand as approved. The table cost to include (pedestal), three drawers of 450 mm wide made with 6mm/12mm ply on right hand side on telescopic slider and a keyboard tray 250mm wide, CPU stand, foot rest as per design and direction by bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to finished with approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks, handles etc. of Godrej or approved brand. Locks to be of single control type. Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish & <b>8mm thick glass duly finished to be placed on top of table &amp;</b> <b>credenza</b> and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.		1					

				1	,
5	Supplying and installing <b>Tables</b> for <b>Grahak Mitra and cross selling staff table</b> of Overall size - 1680 mm X 600 mm x 750 mm made up of 19mm thick block board of approved brand all around and finished with not less than 0.8 mm thick laminate colour, brand and shade as approved by the Bank. The table cost to include (pedestal) three drawers of 375 mm wide made with 6mm/12mm ply on right hand side on telescopic slider, a keyboard tray 250mm wide with CPU stand and foot rest as per design and direction by Bank. The credenza unit should have openable/sliding shutter cupboard and intermediate horizontal shelves made in 12 mm thick plywood. All exposed edges to have to match the desk and finished with laminate . All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, fully extendable drawer slides, auto locks , handles etc. of Godrej or approved make. Locks to be of single control type.Design and detail of the table shall be as per direction of EIC. All the surfaces to be in laminate finish & 8mm thick glass duly finished to be placed on top of table & credenza and necessary cut-out to accommodate wires, edges to be m/c polished, with ms powder coated wire manager complete as per Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent.		1		
6	Providing and fixing floor mounted <b>writing desk</b> of size 1200mm x 300mm x 900mm(H) made of 19 mm/ 12 mm ply finish with not less than 0.8 mm thick laminate and with 12 mm thick float glass on top and voucher pigeon holes as per design & direction of bank, with laminated boards support.	Each	1		
7	Low ht storage unit: Providing and fixing storage units of size 450 mm x 750 mm, made up of 19 mm thick block board of approved brand on top & vertical support and finished with not less than 0.8 mm thick laminate of approved brand on side and top. The storage units shall have openable/sliding shutters made up of 19mm thick plywood and finished in 1 mm thick laminate of approved shade. The storage units shall have intermediate horizontal and vertical shelves made in 12 mm thick plywood. All exposed edges to be finished with 0.8mm thick laminate. All inner surface to be finished with mat finish enamel paint of approve brand. The works to include all hardwares such as: castors, brass hinges, ball catchers, locks , handles etc. of Godrej or approved make. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	RM	9		
8	Fabricating and fixing <b>column/wall paneling</b> with 8 mm thick ply finished with not less than 0.8 mm thick laminate of approved shade & brand over framework at spacing not exceeding 600 mm both ways (horizontal and vertical). Panelling framework to be secured to wall surface / column surface. Design and detail shall be as per direction of EIC and Bank's new uniform colour, layout & elevation policy. Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or		40		
	equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.				
9	Fabricating and fixing <b>full height solid partition</b> , made of 6 mm ply approved brand both side and to be finished with not less than 0.8 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) aluminium section framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. All exposed edge shall be covered with wood bidding/lipping of required size with polishing complete in all respect. <b>Payment will be made for the area upto false ceiling only.</b>		30		
	Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.				

10	Fabricating and fixing <b>full height semi glazed partition</b> , made of 6 mm ply of approved brand in both side and to be finished with not less than 0.8 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm ( thickness not less than 1.5 mm) aluminium section framework at spacing not exceeding 600 mm both ways (horizontal and vertical). Frame should be firmly fixed to the ceiling. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick teak wood moulding duly polished. All exposed edge shall be covered with wood lipping/bidding with polishing complete in all respect. Payment will be made for the area upto false ceiling only. <b>Rate shall include etching of glass as required by bank</b> . Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	37	
11	Providing and fixing <b>low height semi glazed wooden partitions</b> made of 6 mm ply of approved brand in both side and to be finished with not less than 0.8 mm thick laminate of approved brand, colour and shade over 50 mm x 50 mm (thickness not less than 1.5 mm) framework of approved brand at spacing not exceeding 600 mm both ways (horizontal and vertical). Top portion from 900 mm to 1500 mm height shall have 12 mm thick plain float glass (Make: Saintgobin/Modigurd) fixed with 10 mm thick wood moulding duly polished as per designe and direction by bank. All exposed edge shall be covered with teakwood lipping with polishing complete in all respect. Rate shall include making provision for fixing of counter top 12 mm glass on its edges with neccessary fixing arrangment as directed. <b>Rate shall include etching of glass as required by bank</b> . Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent.	SQM	11	
12	Providing and fixing Solid <b>doors shutter</b> made up of 38 mm thick block board of approved brand and quality, finshed both side with not less than 0.8 mm thick laminate of approved brand, colour and shade. Door shall include Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stopper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with wood lipping with polishing complete all respect. <b>Rate shall include etching of glass as required by bank</b> . Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.	SQM	11	
13	Providing and fixing <b>Semi glazed doors shutter</b> made up of 38 mm thick block board of approved brand and quality, finshed both side with not less than 0.8 mm thick laminate of approved brand, colour and shade. Middile portion at 900 mm to 2100 mm height shall have 6 mm thick plain float glass (Make Saintgobin/Modigurd) fixed with 10 mm thick teak wood bidding duly polished N C lacquer as per design and direction by bank. Door shall includes Godrej Mortise lock, two nos of 125 mm brass handle, 250 mm long tower bolt, brass door stoper, three nos 125 mm brass heavy hinge, hydraulic door closer of Godrej or approve make. All exposed edge shall be covered with wood lipping with polishing complete all respect. <b>Rate shall include etching of glass as required by bank.</b> Ply/Block Board Make: MR Grade of Century/ Green/Archidply/Gattani/kitply or equivalent. Laminate Make: Greenlam/Centurylam/Merinolam/Archidlam or equivalent.		12	
14	Providing & fixing in position Aluminium Composite Panel (ACP) / Shutter boxing Panelling with framing in 600 mm C/C both ways. Minimum 3 mm thick ACP to be fixed over the freamwork with 3M or equivalent adhesive and mirror screw in 600 width panels or distributed equally. Joints to be finished with Silicon based sealant. The shade /colour will be as per the direction of bank. Make: Alubond, Eurobond, Fujibond, Alcobond or equivalent ISO certified or	SQM	10	

Folse celling : Providing and fixing superhead false celling with 400x400 mm size at       50         15       Superhead: frome work or per monufactures' specifications. The item to include decision by bonk.       50         16       Specifications of India Cytume Constitution of Inghts/ori-conditioning gills as per design decision by bonk.       50         16       Specifications of India Cytume Co. The rate to include painting with laster point and specifications of India Cytum Co. The rate to include painting with laster point and specifications of India Cytum Co. The rate to include painting with laster point and specifications of India Cytum Co. The rate to include an ecasary fitting.       70         17       Providing & fixing inplace 100 mm. Verifical blinds with soche gured of approved make, quality and colour shade & pointing with laster point and specifications of India Cytum Co. The rate to include an ecasary fitting.       70         18       Becifications of India Gytum Co. The rate of the provide of approved make, quality and colour shade & pointical mail and side side of phywood framework as acequate:       70         19       Reviding and fitting glaced door made of 12 mm thick float glass with thost climits and in behave acids that design pattern with lass as the shall includes of blandweans such as the one SS. Shifts handle, lock, door stoper, hinge.       50         19       Supplying, praviding and fitting Godie Cylindical night latch lock at cash enclosur doors       6c       3         20       Moviding work coals of Bird While Wall Care JJJ. Wall Puthy Wale Resistant While Createry stope, puth (Wall Care					
beard false ceiling with Cd tramework of standard gauge and as per the specific dations of india Gyspum Co. The rate to hald/usite point and SAM       70         16       specific dations of india Gyspum Co. The rate to hald/usite point and SAM       70         17       make, quality and colour shade & pattern. State shall include necessary fittings scatch quard teatment on both sides etc. complete. The overlaps should be uniform & adequate.       SQM       12         18       MAIN GATE : Providing and fixing glazed door made of 12 mm thick float glass with frosted film fixed in between top & bothom rail and side site of phywood framework of size 125 mm x 50 mm. The framework to be finished with not less than 0.8 mm thick load all hardweens used as: Uncove acid etcheed design pattern with logo as SQM       5         18       Main GATE : Providing and fixing Godrej Cylindrical night latch lock at cash enclosure does all hardweens as to as to no so SJ. finish handle, lock, door stoper, hinge.       SQM       5         19       Supplying, providing and fixing Godrej Cylindrical night latch lock at cash enclosure does are deal with equination and mostering the wall with sufficient quarity of clean wolfer as specified and directed by the department. Ifortal thackness of two coats is flaid White Wall Care /JJK Wail Puthy [Water Resistant White Sequence with the pol energy state, puthy blace or wire bush and envirted with the suffice end water and including preparing the sufface from many state and papered smooth.       Sqm       450         20       hep of energy state, puthy blace or wire bruth and mostering the suffaces from from motor dropping and other foreign matter and including preparing the su	15	<b>12mm thick</b> mineral fiber ceiling tiles of Armstrong dune or approved make. Suspender, frame work as per manufacturer's specifications. The item to include cost of making necessary cut-outs for lights/air-conditioning grills as per design	SQM	50	
17       make, quality and colour shade & pattern. Rate shall include necessary fiftings, SQM       12         18       MAIN GATE : Providing and fixing glazed door made of 12 mm thick float glass with frosted film fixed in between top & bottom roll and side sile of phywood framework of size 125 mm x 50 mm. The framework to be finished with not less than 0.8 mm       5         18       thick lominate on both side. Glass to have acid etched design pattern with logo as SQM directed. Doors to be mounted on heavy duty floor spring/door closer. Rate shall included all hardwears such as: Two nos 3.3. Inish handle, lock, door stoper, hinge, lower boil etc. of approved make.       5         19       Supplying, providing and fixing Godrej Cylindrical night latch lock at cash enclosure doors       Each       3         20       Edministration and the comparison of bothen roll and devising both internal and external of after removing all loosely odhening matterning the wall with structure on sufficient quantility of cloen water as specified and directed by the department. [Ifotal thickness of two coats is maximum 1.5mm].The rate shall also included scrapping of damaged paint with sond pager       Sqm       450         20       Applying one coat of clement primer of approved brand and manufacture on more droppings and other foreign matter and including preparing the surfaces free from more dropping and other foreign matter and including preparing the surface free from more droppings and other foreign matter and including preparing the surface free from more droppings and other foreign matter and including preparing the surface free from more droppings and other foreign matter and including preparing the surface free from more droppings and other forei	16	<b>board false ceiling</b> with GI framework of standard gauge and as per the specifications of India Gypsum Co. The rate to include painting with lustre paint and making necessary design, pattern & cut outs for light fittings, cove light etc.		70	
Instact lim bieween top & bottom rail and side silie of plywood framework of size 125 mm x 50 mm. The framework to be finished with not less than 0.8 mm thick laminate on both side. Glass to have acid etched design pattern with logs as directed. Doors to be mounted on heavy duty floor spring/door closer. Rate shall includes all hardwears such as: two nos 5.5. finish handle, lock, door stoper, hinge, tower bolt etc. of approved make.       5         19       Supplying, providing and fixing Godrej Cylindrical night latch lock at cash enclosure doors       Each       3         20       Providing two coats of Birla White Wall Care /J.K Wall Putty (Water Resistant White Cement based putty for concrete/ mortar walls and celling both internal and external) after removing all loosely adhering material from the wall surface with the help of emery stone, putty blade or wise brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm). The rate shall also included scrapping of damaged paint with sand paper       Sqm       450         21       new/old (wall /celling etc). surface dafter throughly brooming the surfaces fee from mortar droppings and other foreign matter and including preparing the surface.       Sqm       450         22       newload (wall /celling throughly brooming the surfaces free from mortar droppings and other foreign matter and sand papered smooth.       Sqm       450         23       Applying one cost of cement primer of approved brand and manufacture (Asian paint) Herger paint/ 1C paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly buryshing the surfaces free from mortar droppings and oth	17	make, quality and colour shade & pattern. Rate shall include necessary fittings, scotch guard treatment on both sides etc. complete. The overlaps should be		12	
19       doors       Each       3         20       Providing two coats of Birla White Wall Care /J.K. Wall Putty (Water Resistant White Carenet) based putty for concrete/ mortar walls and ceiling both internal and external) ofter removing all loosely achiering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. [Total thickness of two coats is maximum 1.5mm].The rate shall also included scrapping of damaged paint with sand paper       Sqm       450         21       Applying one coat of cement primer of approved brand and manufacture on new/old (wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth.       Sqm       450         22       Wall pointing (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth.       Sqm       450         22       Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).       Sqm       50         23       of all dift, dust and other foreign matter sand papering and stopping.The rate shall also includes cost of primer and is application after cleaning the woden surface.       Sqm	18	frosted film fixed in between top & bottom rail and side stile of plywood framework of size 125 mm x 50 mm. The framework to be finished with not less than 0.8 mm thick laminate on both side. Glass to have acid etched design pattern with logo as directed. Doors to be mounted on heavy duty floor spring/door closer. Rate shall inclueds all hardwears such as: Two nos S.S. finish handle, lock, door stoper, hinge,		5	
20Cement based putty for concrete/ mortar walls and ceiling both internal and external) after removing all locsely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. [Total thickness of two coats is maximum 1.5mm].The rate shall also included scrapping of damaged paint with sand paperSqm45021new/old (wall /cleing etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth.Sqm45022Nell (kiain painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly burshing the surfaces free from mortar droppings and other foreign matter and sand papered smooth.Sqm45022(a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Nerolac).Sqm45023rediting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac).Sqm5024Painting two coats (including papering and stopping.The rate shall also includes cost of primer and its application after cleaning the wooden surface.Sqm5023of all dirt, dust and other foreign matter and papering and stopping.The rate shall also includes cost of primer and its application after cleaning the wooden surface.Sqm5024cleaning the surface of all dirt, dust and other foreign matter cleaning the wooden	19		Each	3	
21       new/old ( wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth.       Sqm       450         Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth.       Sqm       450         (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).       Sqm       450         Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).       Sqm       50         23       of all dirt, dust and other foreign matter sand papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface.       Sqm       50         24       Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).       Sqm       50         23       of all dirt, dust and other foreign matter sand papering coat ) old steel and other metal surface with enamel paint of approved brand and manufacture(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).       Sqm       50         24       Painting two coats (including appropiate primin	20	Cement based putty for concrete/ mortar walls and ceiling both internal and external) after removing all loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and moistening the wall with sufficient quantity of clean water as specified and directed by the department. (Total thickness of two coats is maximum 1.5mm).The rate shall also included	Sqm	450	
Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth.       Sqm       450         (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac).       Sqm       450         Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sand papering and stopping. The rate shall also includes cost of primer and its application after cleaning the wooden surface.       Sqm       50         Painting two coats (including appropriate priming coat ) old steel and other metal surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac).       Sqm       50         23       Asian paint/ Berger paint/ ICl paint/ J & N paint/ Nerolac).       Sqm       50         24       Casian paint/ ICl paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also includes application of primer after cleaning the old steel surface       Sqm       50	21	new/old ( wall /cieling etc) surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface	Sqm	450	
Painting two coats (excluding priming coat) on old wood based surface with         enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI         paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces         of all dirt, dust and other foreign matter sand papering and stopping.The rate shall         also includes cost of primer and its application after cleaning the wooden surface.         (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).         Painting two coats (including appropiate priming coat ) old steel and other metal         surface with enamel paint of approved brand and manufacture(Asian paint/         Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including         cleaning the surface of all dirt, dust and other foreign matter.The rate shall also         includes application of primer after cleaning the old steel surface	22	Wall painting (two coats) with acrylic emulsion paint approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) on new surface to give an even shade after throughly brushing the surfaces free from mortar droppings and other foreign matter and sand papered smooth. (a).Acrylic Emulsion Paint approved brand and manufacture (Asian paint/ Berger	Sqm	450	
Painting two coats (including appropiate priming coat ) old steel and other metal surface with enamel paint of approved brand and manufacture(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter.The rate shall also includes application of primer after cleaning the old steel surface 50	23	Painting two coats (excluding priming coat) on old wood based surface with enamel paint of approved brand and manufacture (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surfaces of all dirt, dust and other foreign matter sand papering and stopping.The rate shall	Sqm	50	
(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).	24	Painting two coats (including appropiate priming coat) old steel and other metal surface with enamel paint of approved brand and manufacture(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter. The rate shall also	Sqm	50	
		(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).	<u> </u>		

TOTAL COST

Rates are exclusive of GST