

BOQ FOR WATERPROOFING OF TERRACE SURFACE, WALLS AND GROUND AT CGM RESIDENCE, SHYMALA HILLS, BHOPAL

Sr. No.	Description	Units	Qty	Rate	Amount
1	<b>Removal of Tiles area and clean the floor with with grinding machine and wash will hight jet pressure machine.</b>	sqm	139.41		
2	Waterproof treatment– Overall roof . Surface preparation Removal of Entire loose floor and dispose at given place. Surface preparation by air blower and then wash by water. Dust frees the surface, if lose Plaster/concrete found remove and repair with All visible creaks Open in “ V” shapes & filling by sikaflex pu sealant  Apply one coat of Polymer Based primer ratio 1:2 (1 part product and two part water)by Brush/roller, After curing then applying glass fiber mash reinforced with 2nd coat of Polymer based Primer.	sqm	139.41		
3	SLOPING TERRACE SLAB:- with material (apply & supply) After removal of existing concrete material apply RCC slab from 4 inches to 1.50 inches with (sand+churi+cement) and slope preparation.	sqm	139.41		
4	Waterproofing coating After slope installation and 14 days curing Application of one coat primer+2 topcoat of elastomeric pu water proofing coating.	sqm	139.41		
5	Water Proofing Treatment for Roof Concrete floor area- 1.floor grinding. 2.Wash with jet pressure machine. 3.remove loose particals and fill all cracks and joints with pu sealants 4.Apply Polymer based 2 coat primer coats. 5.Apply two topcoats of pu acrylic elastomeric liquid membrane coating.	sqm	185.87		
6	Floor Epoxy coving on roof topcoat area at all floor and wall corner junctions.(3 inchi coving with epoxy material)	rmt	243.84		

7	Floor cementitious coving with chemical on ground floor area at all floor and wall corner junctions.(3 inchi coving with epoxy material)	rmt	487.68		
8	Waterproofing treatment for all parapet walls:-(product name kleanseal) Surface preparation:- Remove lose plaster & hollow sound surface Surface preparation by air blower and then wash by water. Dust frees the surface, if lose Plaster/concrete found remove All visible cracks Open in " V" shapes & filling by sikaflex pu sealant Apply one coat of wallprime on treated walls. Then apply 2 coats of (Elastomeric Acrylic Exterior wall coating)	sqm	65.06		
9	Waterproofing treatment for all exterior walls:-(product name kleanseal) Surface preparation:- Remove lose plaster & hollow sound surface Surface preparation by air blower and then wash by water. Dust frees the surface, if lose Plaster/concrete found remove All visible cracks Open in " V" shapes & filling by sikaflex pu sealant Apply one coat of wallprime on treated walls. Then apply 2 coats of (Elastomeric Acrylic Exterior wall coating)	sqm	464.68		
				total	
	GST EXTRA AS APPLICABLE				