

PRICE BID					
ABSTRACT FOR SBI WEALTH AT first floor BORING ROAD MORE BRANCH					
S.NO	DESCRIPTION	UNIT	QTY.	RATE	AMOUNT
1	MEETING/ CONFERENCE ROOM TABLE 900mm dia	Nos	1		
	Providing and placing in position Meeting Room tables of approx. size 2100/ 2400 mm x 1200 mm or 900mm/ 1200mm in diameter (size to be considered based on site conditions).Providing & Fixing Meeting/ Conference Table of shape as per design made from50mm X 40mm T. W. Wood framework 450mm center to center both ways for tabletop covered with 12mm thick BWP 710 ply for bottom, 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. All exposed surfaces shall be finish with approved color 1 mm thk. laminate. All				
	internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be inclusive of Brush Finish Stainless Steel Tray with POP UP Flap for electrical switches including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound,cleaning the site etc. complete as per the detail drawing and instruction of Engineer. Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
2	Repairing Existing table and shifting as per layout if required as per colour scheme and specification of table top and side units as complete with hardware as given table specification	Nos	6		
3	Removing and replacing existing partition LOW /FULL HT partly or solid with finishing and hardware as per partition specification or instruction by Bank Engineer/Architect	Sqm	15		
4	Providing & Supplying Sofas, Sofa chairs of various types & categories (Single seater, Two seater & Three seater) etc complete as per the manufacturersspecifications as mentioned below. The rights to select & approve the sofas &seating shall vest with the clients. The contractor shall submit brochures ofmanufacturer at the time of quoting for this item etc complete as per layout. The consultants reserve the right to select the sofas in line with the technical specifications envisaged & meeting the specifications standards expected.(Approved makes: Godrej / Durian / Featherlite)				
a	Two seater sofa	Nos	0		
b	Three seater sofa	Nos	0		
5	Providing & Supplying CHAIRS FOR OFFICERS/VISITORS AND MEETING ROOMmake Godrej/wipro/Durian	Nos	0		
6	WALL/ COLUMN PANELING WITH LAMINATE FINISH.				
	Match laminate colour shade as per signature branch code specified by selection by Bank engineer /Architect on Existing panelled wall on 6mm/9mm ply BWP 1 mm laminate on existing panelling	Sqm	118.494		

	(ii) Panel Finishing:- Providing & fixing 9 mm thick approved make BWP plywood and additional 6-8mm ply in layers to create grooves as per the design to Aluminum framework finished with 1.00 mm thick approved quality and shade laminate, using approved adhesive, in approved pattern & design, including providing grooves, decorative moldings etc. as per Architectural drawings and as directed at site by the Engineer-in-charge.				
	(iii) Providing approved quality, seasoned, full length, Teak Wood molding 15 mm thick with adequate width as required at site, to all openings, cutouts etc duly polished with melamine polish complete as directed by the Engineer-in-charge at site.				
	(iv) The rate should include cost of necessary hardware, making cutouts /openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts,doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site.				
	(v) Applying 2 or more coats of melamine polish to exposed edges of paneling, moulded beadings etc. including preparation of surface, sealer coats etc.complete including wastage of material, if any, scaffolding for execution of workat all heights and locations etc complete. Approved make:-				
7	OFFICER'S TABLE- Size 1500mm x 750mm x 750mm				
	Supplying and installation of Table as per the following description and as designed by the Architect:	Each	4.00		
	Table Top: Providing and fixing 19 mm thick IS 710 BWP grade plywood with 4mm thick Teak veneer with melamine finish with necessary intermediate support. Table top shall be supported by 18 mm thick BWP grade plywood with plywood framing. The top of the table shall be provided with equal sized 12mm thick toughened glass with polished edges. The top level of the glass shall be 750mm. Apron (Modesty Panel) made from 18mm thick BWP grade plywood finished with Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick BWP plywood finished with 1mm laminate for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing				
	Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWP 710 grade plywood. Each Drawer Fascia made out of 18 mm thickBWRplywood and all sides of drawers be made of 12 mm thick plywood &bottom of drawers shall be of 8 mm thick BWP grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sidesand all the internal surfaces shall be finished with 0.80 mm thick balancinglaminate. The drawers to be fitted with Telescopic sliding channelwith SS Grouplocks of approved make and 100 mm long brush finish Stainless Steel handles				

	<p>C-type for each drawer. The front ply of the drawers to be overlapping the frame. Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop. All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade. As per drawing and instruction of Architect/Bank, work to be completed. Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.</p>				
8	CLERICAL STAFF TABLE- Size 1200mm x 750mm x 750mm	Each	5.00		
	<p>Supplying and installation of Table as per the following description: Table top shall be made from 19 mm thick IS 710 BWP grade plywood with 4mm thick Teak veneer with melamine polish with necessary Tabletop shall be supported by 19 mm thick BWP grade plywood with wooden intermediate support. framing. The top of the table shall be provided with equal sized 12mm thick toughened glass with polished edges. Apron (Modesty Panel) made from 19 mm thick BWP grade plywood finished with 1mm laminate & groove pattern as per drawing. Table sides & intermediate panels (at 50cm from each side) made from 19 mm thick BWP grade plywood finished with 1mm thick laminate for all surfaces shall be provided as per drawing. (Removed drawer cabinet in this version as there will be no space left for a person to sit) Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided.</p>				
	<p>All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in table top. All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. As per drawing and instruction of Architect/Bank, work to be Completed. Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.</p>				
9	SIDE/ REAR CREDENZA- For officer and clerical staff table	sqm	6.50		

A	Low Height Cupboard with Laminate Finish: Providing & fixing Low Height Storage Cupboard of 750 height and 450mm deep. Outer exposed structure with to be made with 19mm BWP ply as per IS 710 and back side using 8mm BWP grade ply.All shutters to be made from 25 mm thk BWP Ply and shelves to be made with 19 mm thk.BWP ply. The top portion of the side and rear credenza to be finished with approved veneer and finished with melamine polish. All the other internal and external surfaces to be finished				
	with 1mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish.Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffele), SS towerbolts etc. All shutters to be made overlapping the frame Only front elevation will be considered for area calculation. As per drawing and instruction of Architect/Bank, work to be Completed Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.				
10	LOW HEIGHT PARTLY GLAZED PARTITION WITH 12MM TOUGHENED				
	Providing & fixing low height partly glazed partition with 12mm Toughened glass of approved make 70mm thk +-2mm thk, 1200 mm height, solid partition up to 900 mm level from bottom. The glazed panels shall be fixed above 900 mm with all necessary SS brackets (D, C or U type)	Sqm	15		
	Vertical joints between the glass panels shall be sealed with suitable transparent sealant.				
	The solid partition 900 mm level shall be made with aluminium framework of size 63mm X38.10mm X1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 6mm IS 710 BWP ply finished with 1.0mm thick laminate as per direction.				
11	FULLY GLAZED DOOR				
	Providing and fixing position 12 mm fully glazed toughened glass door, single/double shutter, of approx. size 900/ 1500 x 2100/2400 mm.Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed / solid / gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary	Sqm	3.78		

	cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures & hardwares.Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and				
	Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank. Mode of Measurement: Door opening size shall be measured.				
12	FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED				
	GLASS UPTO 2100 mm LEVEL WITH SOLID PARTITION ABOVE 2100 mm level	Sqm	37.1747		
	Providing & fixing full height glazed partition with 12mm Toughened glass of approved make up to 2100mm level height with solid partition above 2100 mm level up to false ceiling bottom. The glazed panels shall be fixed to the existing floor and false ceiling with all necessary SS brackets (D, C or U type)				
	Vertical joints between the glass panels shall be sealed with suitable transparent sealant.				
	The solid partition above 2100 mm level shall be made with aluminium 2100 mm level shall be made with aluminium framework of size 63mm X38.10mm X1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 6mm BWR ply finished with 1.0mm thick laminate as per direction.				
13	FULL / LOW HEIGHT SOLID WOODEN PARTITION WITH BOTH SIDES LAMINATE				
	REPARING EXISTING PARTITION and REPLACING PARTITION as per drawing				
	Providing & fixing in position 70mm thick +/- 2mm full height solid/opaque wooden partitions finished with laminate on both sides comprising as under:-	Sqm	22.0725		
	(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm (may slightly vary as per unavoidable site conditions) both ways (horizontal and vertical) fixed rigidly on floor, wall / column & ceiling.				
	(ii) Plywood/ MDF skin:- Providing & fixing 8mm thk BWR grade ply/ 12 mm thick MDF boards on both sides of the framework.				
	(iii) Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approve quality adhesive complete.				

	(iv) Making suitable cutouts/ openings/ channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.				
	(v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.				
	(vi) Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.				
	(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete. Approved make:-				
	(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank				
	(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank				
	(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.				
	(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.				
14	GYPBOARD FALSE CEILING Repairing work and after shifting partition if required on existing frame				
	Providing and fixing false ceiling at all height including providing and fixing of frame work made galvanized M.S. sections as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the	Sqm	41.67		
	including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval. Fixing of gypsum board to ceiling section and				
15	Center Table (3'-0" X 2'-0" Oval / Rectangular)				
	Providing and supplying in position oval or rectangular centre table to be made out of 2" X 2" teakwood frame including 12mm thk clear glass top with bevelled edges including bottom glass shelf with etching etc complete. The rate shall also include SS lining design to the teakwood frames including all the necessary hardware, fittings, fixtures as per manufacturers specifications complete.	Nos	0		
16	BACK PAINTED GLASS + LOGO				
	Back painted glass (Lacquer Glass) paneling:				
	Providing and fixing in position wooden paneling to column / walls finished with Back painted (Lacquer Glass) comprising as under:-	Sqm	7.5		

	(i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed upto 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb.				
a.	(ii) Panel Finishing:- Providing & fixing 9 mm thick approved make BWR plywood to Aluminum framework finished with 8 mm thick approved quality and make back painted Lacquer Glass panels of required size, rigidly fixed using 3M adhesive / double side self-adhesive tape complete as directed by the Engineer- in-charge.				
	(iii) The rate should include cost of necessary hardware, making cutouts openings for electrical conduits / cables, Switch boards etc., including providing necessary wooden/aluminum section members support at cutouts, providing scaffolding for execution of work at all heights, complete as per drawings and as directed by the Engineer-in-charge at site. Logo:- Providing and fixing in position with SS studs or as directed laser cut Logo as per design made from 18 mm MDF board (exterior grade) and finished with enamel paint as directed complete.directed by the Engineer-in-charge at site.				
b	Logo:- Providing and fixing in position with SS studs or as directed laser cut Logo as per design made from 18 mm MDF board (exterior grade) and finished with enamel paint as directed complete.	EACH	9		
17	Low Height wooden Partitions (LHP) with laminate finish Providing & fixing in position 70 mm +/- 2mm thick Low height wooden partitions with 450mm high glass panel finished with laminate on both sides comprising as under:-	Sqm	7		
	(i) Total Height of the partitions shall be from 1200 mm to be 1350 mm including 300 to 450 mm high 12 mm clear glass panel as per approved drawing.				
	(ii) Framing Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium sections placed bothways (horizontal and vertical) not exceeding 450 mm c/c rigidly fixed to floor, wall / columns etc including extending end/intermediate vertical members not exceeding 1500 mm c/c for total finished height of LHP.				
	(ii) Plywood/ MDF Skin : Providing & fixing 8-10 mm BWR grade Plawood/12 mm thick MDF plywood on both sides of the framework and all-round vertical posts extending up to total height of LHP.				
	(iii) Finishing :- Providing and fixing 1.00mm thick approved quality and shade laminates using approve quality adhesive, over ply as per approved design & pattern including providing grooves as per Architectural drawing and as directed by the Engineer-in-charge.				

	(iv) Glazing :- Providing and fixing 12mm thick approved make clear float glass panels (not exceeding 1.50 m in length)& 300 mm in height, with polished edges on all sides, fixed using suitable CP Brass /SS 'D' brackets placed not exceeding 450mm c/c on horizontal surface of partition and at both ends on vertical posts to rigidly hold the glass panels.				
	(v) Providing finished section size 70/75 x 8mm thick seasoned second class Teak wood moulding to all exposed edges of partition including applying 2 or more coats of melamine polish / Duco paint including necessary preparatory work for surface preparation with putty, priming coat, sealer coat etc. complete as per sample approved by the Bank.				
	(vi) Making necessary cutouts for electrical conduits / cables & switchboard etc., including providing additional supports wherever required complete as per drawings and as directed by Engineer.				
	(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.				
	Approved make:-				
	(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank (b) MDF: - Greenply, Century, Samrat or equivalent approved by the Bank. (c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank. (d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank. (e) Enamel Paint/polish: Asian/Nerolac/Berger or equivalent approved by the Bank (d) Glass: Saint Gobain, Asahi Float, Modi Guard.				
	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade.				
	All fittings like 75 mm long S.S. handle, Auto Lock to each drawer and cabinet doors, piano / auto hinges, ball catcher, stopper, metal cable manager etc. should be fixed of approved make. should be fixed of approved make.Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers.All the internal surface (non-visible surface) shall be provided with 0.80 mm thickbalancing laminate of approved shade etc. complete. Counter shall be made independent in Length of 1600 mm and properly placed between two partitions. Counter will be measured in RMtr between two partition and paid				
	FINISHING DETAILS:				

	<p>1) Table Top: 6 mm thick white acrylic solid surface 2) Front Apron: Round 6 mm thick white acrylic solid surface and 6 mm thick Yellow lacquered glass fixed with Natural Silicon</p> <p>3) Facing of Drawers: 1.00 mm thick laminate finish 4) All the internal surface (non-visible surface) shall be provided with 0.80 mm thick balancing laminate</p> <p>Brief list of make are as under or any equivalent make will be permitted by the Engineer: MR grade Ply wood (IS :303) - Green / Century / Anchor / Archid / Mayur / Kit / Samrat / Croma Acrylic solid surface (Corain) - Dupont/ Merino/ REHAU or equivalent approved Laminate- Green / Formica / Sunmica / Century /Marino / Aica Multipurpose group Lock - Ebco / EG / Godrej Telescopic channels - Ebco / Everite Keyboard tray - Ebco / Hettich / Innofit / Featherlite Auto lock- Ebco / Dorma / Ozone Cable Manager (60mm) - Metal - Ebco or equivalent Adhesive- Fevicol / Pedilite / Araldite / Royal Bond</p>				
18	STORAGE CUPBOARDS BACK OF TABLE				
A	<p>Providing and placing in position storage cupboard of 450 mm depth, frame work to be made out of 18 mm thick BWR grade ply. Full Height Cupboard with Laminate Finish: Providing & fixing full Height Storage Cupboard of 2100mm height and 450mm deep. Outer exposed structure with tobe made with 19mm BWR ply as per IS 303 and back side using 8mm BWR</p>	Sqm	4.65		
	<p>grade ply. Shutters to be of 25 mm BWR plywood and shelves to be made with 19 mm thk. BWR plywood. All internal and external surfaces to be finished with 1mm laminate of approved shade and make.All edges of the cupboard should be edge banded using PVC edge banding tape of approved shade.Shutters tobe provided with S.S.</p>				
	<p>200mm handles, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffele), SS tower bolts etc. All shutters to to be hinges, locks (Godrej/ Hettich/Haffele), SS tower bolts etc. All shutters to to be made overlapping the frame. Only front elevation will be considered for area calculation.</p>				
	<p>Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.</p>				
B	<p>Same as above- but finished externally with approved quality veneer and PUcoating finish over melamine polish complete instead of 1mm laminate.</p>				
19	SINGLE WINDOW COUNTER / CASH COUNTER REPAIR EXISTING COUNTER ASPER SPECIFICATION				

	Size- 1600 mm X 900 x 750 mm with White acrylic solid surface & Yellow lacquered glass finishing Supplying & fixing single window counter as per design and drawing made out of 18 mm thick IS 710 BWP grade ply wood boxing of approved make, complete with 18 X 6 mm Teak wood beading on all edges wherever required. Tabletop made from 12mm thick ISI710 BWP-grade flexi ply. The countertop to be finished with 6mm thk. sparkle white Corian sheet with 1.5" Thk. Bull Nose	EACH	4		
20	PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS PARTITION ON COUNTER TOP, FRONT SIDE AS FOLLOWS.	Sqm	0		
	EXISTING GLASS TO BE USED IF APPLICABLE				
	Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. Two cutouts to be made one half round of 150mm dia and another for mouth piece rectangular size of 75mm wide 450mm long. All edges of glass shall have Diamond cut polished edges as directed. Brief list of make are as under or any equivalent make will be permitted by the Engineer				
	Glass- Asaahi/ Tata / Modi guard / Saint gobain Square bracket (50 mm x 12.5 mm) S S finish - Oswal / Riddhi / Swift or equivalent				
21	LAMINATION ON EXISTING DOOR				
	Providing and fixing 6 mm IS 710 BWP Grade Plywood or MDF of approved make Century/Greenpanel/Green /Astin or Equivalent on door panel and finished with 1.0 mm laminate on both side of approved make & shade and complete with hardware glue etc of approved make complete as per drawing and as directed by Bank / Architect.	Sqm	12.60		
22	Acrylic Emulsion Paint on new surface				
	Providing and applying 2 or more coats of approved colour Acrylic Emulsion paint with roller finish over a coat of primer on internal walls including applying Birla White putty, rubbing with sand paper, to ensure smooth surface, suitable to receive paint, including scaffolding etc. complete as per manufacturers'specifications. Make:- Asian / Nerolac / Berger / Dulex	Sqm	100		
23	Acrylic Emulsion Paint on old surface Preparing earlier treated surface by scraping, rubbing with sand paper, applying two coats of Birla white putty wherever required, to level the surface, and its rubbing with sand paper, to ensure smooth surface, suitable to receive paint and then applying 2 or more coats of approved colour and shade of Acrylic Emulsion Paint with low VOC content over a coat of approved primer complete as per manufacturers' specifications to internal walls/ceiling including necessary scaffolding etc. complete.	Sqm	20		
	Make:- Asian / Berger/ICI or approved equivalent make.				
24	Polyester Film over glazed partitions:	Sqm	10		

	Providing and fixing in position high impact resistant Polyester Films of approved design & pattern, which once installed on glass, give additional strength to glass, reduce glare & prevent glass from splintering on impact. thickness not less than 4 Mil (100 mic.) or 7 Mil (175 mic.) Roller Blinds				
25	Providing, fabricating and fixing vertical roller blinds of approved make preferably of "Vista Levelor" with a woven made acrylic coated fabric of 100% polyester of thickness 0.50 - 0.60 mm (+/- 5% tolerance) with the main properties like resistance to Cracking & Fraying, dust repellence, UV proof and virtually maintenance free along with the Vista accessories of like Head rail , Roller tube Idler, Bottom rail, chain, matching colour installation brackets etc. including all fixtures and fittings of Vista like Rainbow curtain rods with electric resistance welded MS pipe having a corrugated virgin PVC extrusions reinforced to minimize friction, finials and along with standard anchoring arrangements etc. all complete done in workmanlike manner as per the approved design, colour and including necessary scaffolding as directed.	Sqm	6		
	Total amount of work				
	Add GST Extra as per applicable				
	NOTE:-				