Subject	Proposed Interiors for State Bank of India Branch Office, S	under Ch	ak, Distt.	Pathankot (Pb).			
	Boq - Electrical Work -1						
	ITEM DETAILS	QTY.	UNIT	RATE	AMOUNT		
	PART- A:						
	PART- I : PANELS , KIT KATS & CABLES						
1	Providing and fixing of 03 no 200 Amps KITKAT with 1 no neutral link on suitable size of Bakelite sheet of thickness not less than 12 mm complete as required. (Make: Havells/standard/C&S)	1.00	job				
2	MAIN PANEL: Supply at site installation testing and commissioning of panel fabricated with 16 G MS sheet. The panel shall be free standing type totally enclosed dust and vermin proof construction with rubber gaskets. The floor mounting panel shall have ISMC mounting channels, GI earth busbar, busbar chamber ,cable alleys interconnection with solid bar/PVC insulated copper conductor as per requirement, and suitable supports of busbars. The panel shall be painted with two coats of enamel paint (Grey shade) over primer and shall also be provided with designation of Incoming and outgoing feeder as details below:						
	INCOMING						
	1 no MCCB Breaking Capacity 25 KA 160 Amp 4P , make L&T /ABB/Schneider						
	1 no 0 -500V digital Voltmeter in separate compartment and digital Amp meter and one set of CTs (3 Nos) with CT Ratio 200/5 A with LED type phase Indication Lamps with protection fuses in a separate compartment , make L&T /ABB/Schneider						
	200 Amps capacity 4 strips Aluminium bus bars.						
	OUTGOING						
	1 nos MCCB Breaking Capacity 10 KA 160 Amp 3P and 2 nos MCCB Breaking Capacity 10 KA 100 Amp 3P with seprate neutral Link, make L&T /ABB/Schneider	1.00	set				
3	EMERGENCY PANEL: Supply at site installation testing and commissioning of panel fabricated with 16 G MS sheet. The panel shall be free standing type totally enclosed dust and vermin proof construction with rubber gaskets. The floor mounting panel shall have ISMC mounting channels, GI earth busbar, busbar chamber, cable alleys interconnection with solid bar/PVC insulated copper conductor as per requirement, and suitable supports of busbars. The panel shall be painted with two coats of enamel paint (Grey shade) over primer and shall also be provided with designation of Incoming and outgoing feeder as details below:						
	1 no MCCB Breaking Capacity 25 KA 125 Amp 4P , make L&T						
	/ABB/Schneider						

	1 no 0 -500V digital Voltmeter in separate compartment and digital Amp meter and one set of CTs (3 Nos) with CT Ratio 200/5 A with LED type phase Indication Lamps with protection fuses in a separate compartment (make L&T /ABB/Schneider			
	200 Amps capacity 4 strips Aluminium bus bars.			
	OUTGOING			
	1 nos MCCB Breaking Capacity 10 KA 100 Amp 3P and 4 nos MCCB Breaking Capacity 10 KA 63 Amp 3P with seprate neutral Link, make L&T /ABB/Schneider	1	set	
4	Supply, Installation, testing & commissioning of PVC insulated PVC sheathed armoured cable of 1100 V (IS;1554 Part 1) and fixing of cable on wall with suitable size of clamps /saddles or laid in floor/recess wall including cutting of wall /floor and making good the damages etc complete as required of following sizes (ISI marked). (Make: Havells/ RR Kable/Finolex) to be laid as per drg.			
a)	3.5X50 sq. mm aluminum conductors armoured cable with two Nos. 8 SWG GI wire	40.00	mtr.	
b)	3.5X25 sq. mm aluminum conductors armoured cable with two Nos. 8 SWG GI wire	100.00	mtr.	
c)	3X6 sq. mm copper conductors armored cable with one Nos. 8 SWG GI wire (For UPS Supply only)	80.00	mtr.	
d)	3X2.5 sq. mm copper conductors armored cable	10.00	mtr.	
5	Supplying and making end termination with brass compression gland and aluminium lugs for following size of PVC insulated and PVC sheathed / XLPE aluminium/Copper conductor cable of 1.1 kV grade as required.			
a)	3.5X50 sq.mm aluminum conductor	4.00	no.	
b)	3.5X 25 sq.mm aluminum conductor	10.00	no.	
c)	3X6 sq. mm Copper cable gland.	6.00	no.	
d)	3X2.5 sq. mm Copper cable gland.	10.00	no.	
6	Supplying & fixing the 1 no.4 pole 200 Amps capacity change over switch and complete connection with Electrical Panels as required. Make: Havells/HPL/Standard/ Legrand/L&T	1.00	no.	

7	UPS DISTRIBUTION BOARD			
	supply, installation, testing and commissioning of factory fabricated distribution board rust inhibited, powder coated sheet fabricated comprising of incoming and outgoing isolator and MCB's neutral link or neutral bus, top and bottom detachable entry earthing bolts interconnection and grouting bolts etc complete as requd. Make: Havells/HPL/Standard/ Legrand/L&T. as per details below:-			
a	4 way DB comprising of 2 no. 63 amp DPMCB (UPS out put).	2.00	each	
b	4 way DB comprising of 1 no. 63 amp 4P MCB - 3 phase (UPS input).	1.00	each	
8	Supply, installation, testing and commissioning of 63 Amp MCB change over DP with 4 way DB boxes, complete as required: (Make: Havells/HPL/Standard/Legrand/L&T).	2.00	each	
9	Supply, installation, testing and commissioning of following capacity 3 pin metal clad industrial type plug and socket arrangement with plug top, cap and chain controlled by under noted capacity: (Make: Havells/HPL/Standard/Legrand/L&T)			
a)	32 Amp with 32 Amp. With DP MCB. (for ups panel)	3.00	no.	
b)	20 Amp with 20 Amp. with DP MCB. (for ups panel)	4.00	no.	
10	Providing and fixing 16 S.W.G. MS sheet and also base frame for installation of MCB DBs plug and socket arrangement and to cover cables in UPS room & ECP including painting etc. complete	1.00	sq. mtr.	
11	Providing and laying following sizes of PVC insulated copper conductor cable of 1100 V in flexible/ PVC conduit pipe with accessories such as glands bends etc (as per requirement) including making necessary interconnection etc complete as required.			
a	2 X 6 Sq mm with 1 no suitable insulated 2.5 sq mm multi stranded copper wire in PVC flexible pipe. (Make: Havells/ RR Kable/Finolex).	20.00	mtr.	
	PART-II : COMPUTER POINTS & DISTRIBUTION			
12 / i	UPS POINT - Supply all material, storing, handling, fixing of computer points computer points in suitable size of GI / PVC box including providing 3 nos 5 amps 3 pin modular sockets to be provided under table top and controlled by 1 no 15 A moduler type switch and indicator with moduler cover plate etc complete as required including 3X2.5 sq. mm copper armored cable. Note: Maximum two computer points are to be provided on one circuit. (Switches: Make: Anchor/Crabtree/North-West/MK. (BM -3 & SWO counter - 2 each, O.T. table, N. Rack & LED - 2 each).	24.00	each	
ii	UPS POINT - As per item above but with 2 Nos. 15 A 5 pin socket controlled by 1 no 15 A switch and indicator. (for E - corner - 2Nos, BM - Nos. etc.).	3.00	each	

13	Supply, installation, testing and commissioning of factory fabricated distribution board rust inhibited powder coated sheet fabricated comprising of incoming and outgoing isolator & MCBs neutral link or neutral bus, top and bottom detachable entry earthing bolts interconnection and grouting bolts etc complete as required as per details below. Make: Havells/HPL/Standard/ Legrand/L&T.			
a)	8 way SPN MCBDB Double Door comprising of 1 No 63 Amp DP Isolator and 6 No SPMCB 10/16 Amp. (UPS output)	2.00	no.	
b)	6 way SPN MCBDB comprising of 1 No 63 Amp DP Isolator and 4 No SPMCB 10/16 Amp. (UPS output)	1.00	No	
c)	4 Way TP MCBDB Double Door in recessed wall including cutting of wall and making good the damages comprising 1 no 100 A FP TPN and 6 Nos.32 A DPMCBS etc complete as required. (for Air conditioning only).	2.00	no.	
d)	4 WayTP MCBDB Double Door in recessed wall including cutting of wall and making good the damages comprising with 30mA ELCB and 12 Nos. 6/10 Amp SPMCBS etc complete as required. (for Light, Fan point only)	1.00	no.	
e)	4 WayTP MCBDB Double Door in recessed wall including cutting of wall and making good the damages comprising 1 no 100 A FP MCB and 12 Nos. 20/25 Amp SPMCBS etc complete as required. (for Raw Power Only)	1.00	no.	
14	RAW POWER: Supply all material, storing, handling, fixing of Raw power points in suitable size of GI/PVC box including providing 1 nos 15 amps 6 pin modular power sockets to be provided controlled by 1 no 15 A moduler type switch and indicator with moduler cover plate etc complete as required including 2X2.5 sq. mm FRLS copper wire + earth wire in dia 2 mm in thickness ISI Mark PVC pipe. Note: One RAW power points are to be provided on one circuit and dirctly to be connected on Power DB. (Switches: Make: Anchor/Crabtree/North-West/MK	10.00	each	
15	Supply, installation, testing and commissioning of following capacity 3 pin metal clad industrial type plug and socket arrangement with plug top, cap and chain controlled by under noted capacity: (Make: Havells/HPL/Standard/Legrand/L&T)			
a)	20 Amp with 20 Amp. C Curve SP MCB. (for 1.0Tr /1.5 Tr High wall split AC's and seprate connection of record room /safe room/lockers room etc 4 nos. & Ac - 8Nos as required.)	12.00	no.	
16	Providing and fixing of suitable size MS box fabricated with 16 G MS sheet either in recess wall or on surface to accommodate dedicated earth from earth electrode and further distribution of earth to computer points including providing of 5 mm bakelite on base connector strip and painting of box etc as required.	1.00	job	

17	Basic electrical Wiring of light points, plug points			
	Wiring for light point/ ceiling fan point/ exhaust fan point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit ISI Mark, with 6Amp modular switch, modular plate, suitable GI junction & switch boxes & clip and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.(Wires Make: Havells/ RR Kable / KEI/Finolex) (Switches: Make: Anchor/Crabtree/North-West/MK)			
	(Rate includes 3 x 2.5 sq.mm FRLS copper conductor, single core cable in PVC conduit for circuit/sub main wiring along with earth wire)			
a)	single 6 Amp Switch controlling 1 light point for T-5, Cove light, exhaust Fans, Ceiling fan and other seprate room supply only.	25.00	no.	
b)	single 6 Amp Switch controlling 4 no. downlights / 4 no. LED downlight / 2 no. 2'- 0"x 2'-0" 36 watt light fittings.	25.00	no.	
c)	single 6Amp socket controlling by 5Amp Modular switch in switch boards - 10 Nos. & Wall Fans points - 10 Nos with switch & socket in separate switch board etc complete as required.	15.00	no.	
	Note: Lihgts/fans points to be calculated by numbers of lights and no extra cost shall be paid for dummy switch.)			
18	PART III - EARTHING			
	a)Supply and fix copper plate earth station with 600X600X3mm copper plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. The voltage between neutral and earth must be below 1 V. The work includs supply, fixing and termination of 5M Length 20X3 mm size copper strip with earth station below ground level etc as required.	1.00	Sets	
	b)Supply and fix GI plate earth station with 600X600X6mm GI plate including all accessories such as watering pipe and funnel and providing masonry enclosure at top with cover plate i.e excavation of pit, supplying and filling of salt charcoal, refilling of pit etc complete as required as per IS 3043-1987. the work includes supply, fixing and termination of 5M Length 20X3 mm size G.I strip with earth station below ground level etc as required.	2.00	Sets	
19	a)Providing and fixing of 8 SWG copper earth wire in the recess for loop earthing etc. as required.	20.00	Meter	
	b)Providing and fixing of 8 SWG GI earth wire in the recess for loop earthing etc. as required.	40.00	Meter	

	·				
20	Supply and laying following dia 2 mm in thickness ISI Mark PVC pipe				
	under floor or in recessed walls from earth electrode to UPS room				
	for computer dedicated earthing.				
	25 mm diameter	40.00	Meter		
	PART IV - TELPHONE & DATA CABLE				
21	Wiring for telephone points with 0.6 mm dia 2 pair insulated	9.00	no.		
	annealed tinned electrolatic copper conductor in 2 mm thick 25 mm				
	dia ISI marked PVC conduit complete with accessories such as bends,				
	junction boxes etc. with suitable size of G.I./PVC box modular plate				
	and cover in front on surface or in recess including providing and				
	fixing modular type telephone socket outlet and making necessary				
	connections etc. complete as reqd.(Make: Dglink/KEI/Finolex)				
22	Supply, installation and testing & commissioning of Tag Block 20 pair	1.00	no.		
	for telephone connections Make: krone				
23	Data cabling work for computer networking starting from mounting	20.00	no.		
	rack at system room with UTP CAT-6e LAN Data cable in 2mm thick				
	25 mm dia ISI mark PVC conduit with accessories such as bends,				
	Tees, junction boxes including providing and fixing cat-6 I/O plates				
	and SMB complete with all networking accessories etc complete as				
	reqd.				
	(Make: D-LinK/MOLEX/AMP/COMMSCOPE)				
	Note: Only One Data Points to be provided in One Table/Counter.				
	Extra poitns not to be paid if provided. Maximum 6 no. data cable				
	must be run in one pvc pipe. (Extra Data points not to be provided as				
	per bank's guidlines)				
24	supply, installation, testing and commissioning of 24-port Patch	1.00	no.		
	Panel				
25	Supply and installation, testing and commissioning of mounted rack	1.00	no.		
	15" hight made of powder coated MS sheet				
26	supply, installation, testing and commissioning of factory				
	manufactured CAT- 6e patch chord complete with 2 no. connectors				
	etc. complete as reqd.				
a)	1 mtr. long	20.00	no.		
b)	2 mtr. long	10.00	no.		
<u> </u>	-				
1	1	l	1	1	I

	PART-V : AIR CONDITIONING REFRIGERATION/DRAIN WORKS			
27	Supplying & Laying of following COPPER REFRIGERANT PIPING Thickness 22 SWG For Air Conditioners units complete with fittings Suction / Discharge line insulated with 12 mm SUPERLON / ARMAFLEX suction line. Multi-runs between Indoor & Outdoor units shall be considered as ONE length for the purpose of measurement. the work includes all hardware & required henger to complete the job. (Make: Total Line/Armacell).			
a)	1/4" + 1/2" Refrigerant Copper piping - For Hiwall Split AC's (1.0Tr / 1.5Tr) to be provided as per drg.	100.00	mtr.	
28	Supplying & laying recessed in wall Rigid ISI Mark PVC drain pipe of size 20mm /25 mm / 32 mm dia complete with fittings, U traps etc. & as specified to the nearest toilet / drain point under floor or in recessed walls for AC drains including cutting of walls, bends & Tees. making good the damages etc. wherever required. (Make: Diplast/Supreme)	50.00	mtr	
29	Supplying and providing Eletrical flexible FRLS Copper cable of 3 x 2.5sq.mm multi strand suitable for 1.0Tr / 1.5 Tr H.W Split / 2.00 Tr Cassette Multi-runs between Indoor & Outdoor units and between Metal Clads to Out door / indoorunit for electrical supply etc complete as required (Make: Havells/ RR Kable / KEI/Finolex)	180.00	mtr	
	PART- B:			
	PART-VI: LIGHTS & FANS FIXTURES			
30	SITC of 2"x2" Celing grid 36-43 watt LED panel fixtures with essential driver in false ceiling including making necessary arrangement for mounting the fixtures and connection with 2 x 1.5 sq.mm insulated copper cable from adjacent point in PVC flexible pipe etc Complete as reqd. (Make: Cat. No. BZRSQL 43L LED GF of Bajaj or equivalent of Philips / Wipro. 120 Lumens per Watt. Color temperature 6000K.	20.00	no.	
31	SITC of 15 watt LED fixtures /dowlighters with essential driver in false ceiling including making necessary arrangement for mounting the fixtures and connection with 2 x 1.5 sq.mm insulated copper cable from adjacent point in PVC flexible pipe etc complete as reqd. (Make Phillips / Wipro / Bajaj.	48.00	no.	
32	SITC of 18 watt of T5 LED fixtures directly on ceiling / wall including making necessary connections with 2x1.5 sq.mm insulated copper cable conductor wire etc. complete as reqd (Make: Phillips / Wipro / Bajaj)	12.00	no.	
33	Supply of 400/450 mm sweep Metal Body and Metal Blades Crompton greaves (or equivalent) SDX BLCK GOLD wall fan etc. 1325 rpm High Flow Mode complete as required. (equivalent of Bajaj / Havells /Usha/ orient / polar / khatain)	8.00	no.	
34	SITC of 1200 mm CEILING fans complete as reqd. (M/s Crompton / USHA / Bajaj).	3.00	no.	

35	SITC of 200 mm exhaust fans complete with self opening louvers / shutters including necessary frame etc, complete as reqd. (M/s Crompton/ USHA / Bajaj)	5.00	no.				
36	LED Strip light (4.5/5 watt) of approved colour & shade - wharm white for cove (Make: M/s Phillips /Wipro / Bajaj Complete in all respects with suitable drivers.	80.00	MTR.				
37	SITC of 30 watt Street light /Flood light for lighting the front side of the branch (M/s Crompton Cat No. LSTS-30-CDL or equivalent of Philips/Wipro)		no.				
	TOTAL OF PART : I +II+III+IV+V (A)						
	TOTAL OF PART : VI (B)						
	TOTAL AMOUNT (A+B)						
	GST extra as per applicable						
	Note: the vendor have to provide LAN diagram after completion of the work along with the bill, without it payment will not be made.						