

*Ar. Manav Salhotra*

**B.ARCH, M.C.O.A. ,A.O.I.O.V**

Member Council of Architecture

Reg. No. –CA/2001/27498

Associate of Institute of Valuers

Reg. No.- F-16504

Registered with Ministry of Finance

Regd. No- 189/CCIT/ASR/ITO(T)/VALUER/  
2011-12/15



## **3D Vision Architects**

ARCHITECTS, ENGINEERS, INTERIOR  
DESIGNERS, VALUERS,  
LANDSCAPPERS  
& VASTU CONSULTANTS

329, Govt. College Road, GURDASPUR.

Mob. No. 098141-77578

E-mail: salhotra\_manav53@rediffmail.com

Ref. No .....

Dated: 22.11.2024

**To**  
**The Regional Manager,**  
**Regional Business office,**  
**Pathankot.**

### **SOQ FOR INTERIOR FURNISHING WORK OF SBI MADHOPUR BRANCH , IS SUCH AS .**

| <b>S.N<br/>o</b> | <b>ITEM</b>  | <b>UNIT</b> | <b>QTY</b> | <b>RATE</b> | <b>AMOUNT</b> |
|------------------|--|-------------|------------|-------------|---------------|
| <b>A</b>         | <b>INTERIORS / FURNISHING</b>  |             |            |             |               |
| <b>1.</b>        | <b>Single Level SWO Counters</b>   |             |            |             |               |
|                  | Providing and fixing at site SWO counters each upto 5'0" long, 2'6" high and 3'0" wide, as per design and drawing. SWO counters to be made of 19 mm thick ply (Ecotech/Green/century) with 1.0 mm thick laminate on outer visible surfaces (single color on horizontal surface & two colors on vertical surfaces), with 40 mm X 12 mm thick teak wood/MDF beading required all around, as per drawing. Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the counter. The top with Curvilinear profile shall be made out of 19mm thk. Commercial ply and finished with 6mm thk. flexi ply as base for acrylic sheet (laminate 1.0 mm thk) as/design with provision for LED Light in bottom. Teak wood/MDF lipping will be provided on all the remaining edges of the counter, including bottom touching the floor and the drawers. The counter shall have a keyboard tray of size 600 X 270 with both side laminated board with back support, of (EBCO/Hettich/Godrej) make fixed on channels, as per manufacturer's instructions / specifications. | Rft.        | 16'-0"     |             |               |

|    |  |       |        |  |  |
|----|--|-------|--------|--|--|
|    | <p>Three drawers with autolock running on both sides mounting Telescopic (channels) of (EBCO/Hettich/Godrej) make, made of 19 mm thick (Ecotech/Green/century) ply with 1 mm thick laminate on front face and drawer locks to be provided on one side of the counter as per layout. The sides of the drawers shall be made of 12 mm thick plywood, bottom of 6 mm thick plywood &amp; front of 19 mm thick ply (Ecotech/Green/century) Non Visible/Inside surface i.e. inside leg-space of table, inside drawers shall be finished with 1mm thk. white/off white laminate. All exposed Teak wood edges / teak wood lipping /MDF beading shall be Spray painted Satin Enamel paint or spirit (natural) polish as required. The drawers shall have partitions for keeping currency notes &amp; the counter should also includes foot rest , Space for CPU as per drawing, complete in all respects. The provision of swapping machine of green channel size 9"x 6" with lid shall be provided at right side of each counter while facing from front.</p> |       |        |  |  |
| 2  | <p><b>POLYACRYLIC SURFACE HARD TOP ON SWO COUNTER :</b></p>  |       |        |  |  |
|    | <p>Providing and fixing (12mm thick) white polyacrylic stone (Dupont corian) (non-absorbent, non-porous solid surface composite material, belonging to the solid surface category) as per drawings/design provided by the Architects complete in all respect including adhesives, buffing and wastage.</p>   | sft   | 64.00  |  |  |
| 3. | <p><b>12 MM thk. toughened glass for Banking / SWO Counters with Etching. - front &amp; Sides.</b></p>   |       |        |  |  |
|    | <p>Providing and fixing 12 mm thick, clear plain toughened glass of fixed in vertical position at counter level &amp; to side partitions as per drawing, the counter top glass fixed on both sides to toughened glass partitions &amp; side partitions fixed to wooden partition with superior quality stainless steel L - shaped clamps / glass holders 2 no. on both sides. A 6" dia. semi circular hole at the bottom for transaction shall be provided. All the edges of the glass shall be grinded polished and left free.</p>  | Sqft. | 232.34 |  |  |
| 4. | <p><b>Superior quality stainless steel L - shaped connectors/clamps / glass holders</b></p>  |       |        |  |  |
|    | <p>Superior quality stainless steel L - shaped connectors/clamps / glass holders 2 no. on</p>  | Nos.  | 92.00  |  |  |

|    |   |      |      |  |  |
|----|---|------|------|--|--|
|    | both sides to holding the front glass partition to S.W.Counter.   |      |      |  |  |
| 5. | <b>Providing and fixing S. lacquered glass</b>  |      |      |  |  |
|    | Providing and fixing S. lacquered glass in front of SWO counter of 6 mm thk of approved colour (aqua blue). Glass shall be pasted duo corning silicon neutral care(DC 816 white) over the front of counter as per item no.-01. All Edges of the galss is grinded, polished and left free, only glass area with maximum ht ( at center) shall be measured for the purpose of payment.  | sqft | 24.0 |  |  |
| 6. | <b>Officer's &amp; Staff Tables</b>   |      |      |  |  |
|    | Table made of 19 mm thk. ply (Ecotech/Green/century) with front and side visible vertical surfaces to be finsihed with laminate 1.0 mm thick; Table Top to be cladded with additional 4mm thk ply finished with laminate 1.0 mm thk , with 40 mm X 12 mm thick teak wood/MDF beading all around, as per drawing. The front of the table top shall be projected as per drawing. The modesty guard shall be finished with 12.0 mm thk. toughned glass with 4" wide S.S. Spacer. Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the table. The wood lipping will be provided on all the edges of the table, including bottom touching the floor and the drawers. The table shall have a keyboard tray of size 600 X 270 of (EBCO/hettich/Godrej) make fixed on channels, as per manufacturers instructions / specifications. |      |      |  |  |
|    | A full depth CPU shelf 15" wide shall be provided at left hand side of counter underneath the working top, at 4" above the floor level and 3" away (horizontally), from vertical end which will be made of 19mm thick ply (Ecotech)/ Green/ century) finished with 1.0 mm thk laminate(clour as approved by Architect/ bank engg concerned) and ¾" x ¼" teakwood/MDF lipping on two visible sides. three lockable drawer running on side mounting drawer slides (channels) of (EBCO/Hettich/Godrej) make made of 19 mm thick commercial ply with 1.0 mm thick laminate on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12 mm thick plywood   |      |      |  |  |

|           |  |       |       |  |  |
|-----------|--|-------|-------|--|--|
|           | / 19 mm ply, bottom of 6 mm thick plywood & front of 19 mm thick bply. A full length foot rest made of hard wood 3" x 1½" section shall be provided at 4" above floor level. Non-Visible/inside surfaces i.e. inside / leg-space of table, inside of drawer / cupboard shall be finished in 1mm thk. laminate of white/off white shade and teak wood /MDF edges / lipping / beading shall be Spirit polished or Spray Painted as required.   |       |       |  |  |
| a)        | Size- 5'-0" X 3'-0" X 2'-6"  | Nos.  | 2.00  |  |  |
| b)        | Size- 6'-0" X 3'-0" X 2'-6"  | Nos.  | 0.00  |  |  |
| c)        | Size- 7'-0" X 3'-0" X 2'-6"  | Nos.  | 1.00  |  |  |
| <b>7</b>  | <b>3m Vinyl Prints with acrylic sheets</b>   |       |       |  |  |
|           | Providing and fixing 3m Vinyl film sand witched with in 4mm thk acrylic sheets fixed with SS Studs over existing wall/panelling/partition complete in all respects to the entire satisfaction of the Engg./ Architect.   | Sqft. | 60.00 |  |  |
| <b>8</b>  | <b>8.0 MM thk glass on top of officers tables.</b>   |       |       |  |  |
|           | Providing & Fixing 8.0mm thk clear float glass for Officers' & BM table top with bevelling on edges all around & grinding including cutting for wire manager as per the instructions of the Achitect/Engineer in charge.   | Sqft. | 51.0  |  |  |
| <b>9.</b> | <b>Side Credenza</b>   |       |       |  |  |
|           | Providing & fixing Side credenza ( 15" to 18" deep ) made of 19 mm thick ply (ecotech/green/century) and 6 mm thick plywood on back side & 1.0 mm thick laminate on top horizontal surface & vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have three drawers, horizontally running on side mounting drawer slides (channels) of (EBCO/hettich/godrej) make. The remaining part of the credenza will have cupboard with shutters and one shelf. The shutters with handle / knob and magnetic catcher shall be provided beneath the drawers all non visible/inside surfaces shall be finished with white/off white laminate 1mm thk. and teak wood edges / lipping / beading shall be Spirit polished with matching pigment. (Teak Veneer Make: Green/Uniply.,Basic rate @ 80/-sq.ft incl.taxes) |       |       |  |  |
| a         | Officer's & Staff side credenza as per Drawing   | Sqft. | 25.0  |  |  |

|     |  |       |       |  |  |
|-----|--|-------|-------|--|--|
|     | & specification mention in item above. Size - 3'-0"/ 4'-0" X 1'-6" X 2'-6" (W X D X H)   |       |       |  |  |
| 10. | <b>Back credenza / Storage</b>   |       |       |  |  |
|     | Providing & fixing back credenza 18" deep ( top surface 18" to 24" as per site) & 36" HT. made of 19 mm thick commercial ply and 6 mm thick plywood on back side & 1.0 mm thick laminate (colour and specification as approved by Architect / bank engg concerned) horizontal surface & vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have cupboard with shutters and one shelf. The shutters with handle / knob and magnetic catcher shall be provided beneath the drawers and non-visible/inside surfaces should be finished in 1mm thk. laminate of white/off white shade and teak wood edges / lipping / beading shall be Spirit polished with matching pigment.  | sqft. | 87.60 |  |  |
| 11. | <b>Work Stations for System Room</b>   |       |       |  |  |
|     | Providing and fixing in position single level work station counter each to be divided at approx. 4 rft. In length, in system / swift room as per site conditions, 2'0" wide and 2'6" high, counter shall be made 19 mm thick ply (ecotech/green/century) with 1.0 mm thick laminate on vertical as well as horizontal surfaces with provision of cable management for computer cables and electrical switch board at appropriate place, with teakwood lipping 3/4" x 1/4" on all edges including bottom touching floor. The counter shall have a keyboard tray of size 600 X 270 with both side laminated board with back support, of (EBCO/hettich/godrej) make fixed on channels, as per manufacturer's instructions / specifications. A full depth CPU shelf 14" wide shall be provided at left hand side of counter underneath the working top, at 4" above the floor level and 3" away (horizontally), from vertical end which will be made of 19mm thick ply laminated with 1mm thick laminate on top and 3/4" x 1/4" teakwood lipping on two visible sides. | sqft. | 0.0   |  |  |
|     | A full length foot rest made of hard wood 3" x 1/2" section shall be provided at 4" above floor level. One drawer with lock and one cupboard with shutter made of 19 mm commercial ply with 1 mm laminate on front side of cupboard shutter with shutter having good quality locks, magnetic catcher, hinges, handle / knob etc. is to be provided. The shutters shall be provided   |       |       |  |  |

|     |  |       |        |  |  |
|-----|--|-------|--------|--|--|
|     | <p>beneath the drawers with each counter on its right / left hand side. All the three sides of the drawer will be made of 12 mm thk ply and front side of 19 mm thk ply (ecotech/green/century) with 1 mm thick laminate. The bottom of drawer shall be made of 6 mm thick commercial plywood. The drawer will be provided with handle / knob of good quality to be got approved before fixing with drawer channel of 18" length &amp; the counter should have provisions of foot rest , Space for CPU Non-laminated surface i.e. inside leg space of counter inside of drawer / cupboard / outside of drawers / footrest / lipping / moulding etc. to be enamel painted white and teak wood edges / lipping / beading shall be spirit (natural) polish.</p>                 |       |        |  |  |
| 12. | <p><b>False Ceiling With Steps. - Gypsum Board for Bank Hall, B.M Cabin etc.</b></p>   |       |        |  |  |
|     | <p>Providing and fixing suspended false ceiling (as per specification of manufacture) including steps as per design with 12.5 mm tapered edge Gyp-board / 12 mm thick Elephant Gypsum Board to the grid comprising of cold rolled galvanized metal section to the required line and level. The grid consists of a perimeter channel (MF6a of dimensions 20 mm X 27 mm X 37 mm X 3.5 M) fixed round the perimeter to receive and of the ceiling section (MF5) and the outer edges to gyp-board. The intermediate channel (MF7 of dimensions 15 mm X 45 mm X 0.9 mm X 3.6 M) at 1200 mm c/c in the one direction and the ceiling section (MF5 of dimensions 80 mm X 26 mm X 0.5 mm X 3.6 M) at 450 mm c/c in the other direction are connected by a connecting clip (MF9).</p> | Sqft. | 876.78 |  |  |
|     | <p>The grid is suspended with an adjustable strap hanger (MF8) of dimensions 25 mm X 0.5 mm at 1200 mm c/c on both ways from the structural soffit using a soffit cleat and expandable bolts / fasteners Nut and bolts are used to connect strap hangers to soffit cleats and for joining ends of channel sections together. The gypsum board layers are screwed to the M/F ceiling sections with gyp-board drywall screws. Jointing and screw spotting are then carried out as per manufacturer's standard recommendations. Perimeter Channels (MF7) to be used around the cut outs for light fittings. A/C ducting etc. The work should be complete as per instructions of Architect or Engineer in charge. The rates</p>  |       |        |  |  |

|     |   |       |         |  |
|-----|---|-------|---------|--|
|     | should be inclusive of two or more coats of plastic emulsion over a coat of primer to give an even shade.   |       |         |  |
|     | The rate should be inclusive of making opening with frame etc. for electrical / air conditioner, A.C. grills & trap door etc. if required & finishing of ceiling in all respect. Steps/ Vertical bands shall be measured in square feet. Payments shall be made only for exposed surfaces & actual measurement at site. The work includes cost and conveyance of materials and labour charges including. All operational charges, tools, lifts and all heights etc.   |       |         |  |
| 13. | <b>False Ceiling - (Mineral Fibre) for Bank Hall, B.M Cabin, SBI Wealth HUB Part etc.</b>   |       |         |  |
|     | Providing and fixing false ceiling at all heights, made of 600 mm X 600 mm X 16 mm Prima Dune / Sand Supreme, RH 99 & micro log edge with black lining, mineral fibre ceiling tiles of type – Fine Fissured micro lock with silhouetted grid (black reveal), Tegular edge, laid on Armstrong exposed grid systems. The framework comprises of main runner spaced at 1200 mm c/c, securely fixed to the structural soffit by approved hangers of spacing not more than 1200 mm c/c. Hangers (G.I. wire of 4 mm dia.) to be fixed by approved rawl plugs, level adjusters & screws etc. The last hanger at end of each main runner should not be more than 450 mm from the adjacent wall. | Sqft  | 1076.07 |  |
|     | Flush fitting 1200 mm long Cross T's (with double stitching) to be interlocked between main runners at 600 mm c/c to form 1200 mm X 600 mm modules. Cut cross T's longer than 600 mm to be supported independently. 600 mm X 600 mm modules to be formed by fitting 600 mm long flush fitting cross T's centrally between the 1200 mm Cross T's. The rates shall be inclusive of making opening with frame etc. for electrical / air conditioner & finishing of ceiling in all respect, the work includes provision of trap door if required.   |       |         |  |
| 14. | <b>Full Height Partitions with etching on glasses. - Solid / partly glazed.</b>   |       |         |  |
|     | Providing and fixing partition made of 44 mm X 44 mm X 16 Gauge aluminium extruded sections @ 2'0" to 2'6" c/c vertically & horizontally. The bottom member shall be aluminium extruded sections of size 65 mm X 44 mm X 16 Gauge. The aluminium extruded   | Sqft. | 362.64  |  |

|   |              |              |  |  |
|---|--------------|--------------|--|--|
| <p>sections frame shall be fixed rigidly at floor level as well as ceiling with rawl plugs / steel lugs. The frame work to be clad with 8.0 mm thick commercial ply and 1.0 mm thick laminate as per pattern on both sides upto 3'0" height and above 7'0" height and 5.00 mm thick glass with etching as per design fixed with teak wood moldings above 3'0" height and upto 7'0" height. The skirting shall be finished with 1.0 mm thk brushed steel finsih lamiante. Work also includes providing and fixing of door as per drawing and specifications. All ply / wood to be treated with wood preservatives of approved ISI quality. The doors should be 38 mm thick and also be of similar specification with bottom and top rail of 8" &amp; 6" respectively etched Glass including heavy duty brass hinges and 6 lever mort ice lock of (godrej/hettich make) and other hardware as per requirement. The work should be complete in all respect including requisite hardware.</p> |              |              |  |  |
| <p>All mouldings/ lipping shall be finished with high gloss Spirit polished of approved shade. The rate shall also include for providing groves in laminate . All job to be done to Architect's satisfaction / as per bank direction. Measurements to be taken upto false ceiling level &amp; Payments shell be made only for exposed surfaces &amp; actual measurement at site, no payment shell be made above false ceiling.</p>  |              |              |  |  |
| <p><i>Note: (i) All ply to be sprayed with anti termite and anti borer spray.<br/>(ii) Rates to include all necessary supports and as per details<br/>(iii) Measurements to be recorded up to finished false ceiling level.</i></p>   |              |              |  |  |
| <p>15. <b>Low Height Partition with Laminate ((film to be provided on glasses as per requirement) ( Height + 4'-0" ) )</b></p>  |              |              |  |  |
| <p>Providing and fixing Low Height Partition made of 44 mm X 44 mm X 16 Gauge aluminium extruded sections @ 16" c/c vertically &amp; horizontally. The bottom member shall be aluminium extruded sections of size 65 mm X 44 mm X 16 Gauge. The aluminium extruded sections frame shall be fixed rigidly at floor level with rawl plugs / steel lugs / screw. The frame work to be clad with 8.0 mm thick ply and 1.0 mm thick laminate (as per approved shade in two or more clours as specified by Architect/ bank engg. Concerned) as per pattern on both side's upto 4'0" height. The</p>   | <p>Sqft.</p> | <p>76.50</p> |  |  |



|     |  |      |      |  |  |
|-----|--|------|------|--|--|
|     | <p>skirting shall be finished with 1mm thk brushed steel finish laminate. All ply / wood to be treated with wood preservatives of approved ISI quality. All mouldings /lipping shall be finished with high gloss Spirit polished of approved shade. The doors should be 38 mm thick and also be of similar specification with bottom and top rail of 8" &amp; 6" respectively etched Glass including heavy duty brass hinges and 6 lever mortise lock of godrej make and other hardware. The work should be complete in all respect including requisite hardware.</p>  |      |      |  |  |
|     | <p><i>Note: (i) All ply to be sprayed with anti termite and antiborer spray.<br/>(ii) Rates to include all necessary supports and as per details<br/>(iii) Measurements to be recorded up to finished false ceiling level.</i></p>   |      |      |  |  |
| 16. | <p><b>Main Entrance Door for B.O , B.M. CABIN &amp; ATM- Toughened Glass 12.0 mm thk. with etching /Logo</b></p>   |      |      |  |  |
|     | <p>Providing and fixing in position 12mm clear float toughened Glass for naked glass door. The work to include making necessary template for all the glasses and then cutting the clear float glass to correct size, making all the necessary holes, cuts etc., and then toughening the same. The cost to include all hardware required viz., Ozone/ebco/godrej or approved equivalent make floor spring with its accessories, top pivot, center lock, 450mm glass door handles etc., along with etching with sand blasting as per design and drawing. The maximum size of each glass shall be as per the drawing or the direction of the Engineer-in-charge. The rate shall include necessary etching film / logo all inclusive, complete and the rate is for a finished item of work etc., complete as directed.</p> | Sqm. | 7.15 |  |  |
| 17. | <p><b>Wall Paneling Laminated (1.00 mm Thk Laminate (windows. B.M. cabin, columns, officers table)</b></p>   |      |      |  |  |
|     | <p>Providing and fixing paneling over the existing wall made out of framework of 50 mm X 25 mm - 18 gauge section un anodised Aluminium ( as per requirement) frame work @ 16" to 24" c/c vertically &amp; horizontally.The frame work to be clad with 8.0 mm thick commercial ply for vertical surface and 6.0 mm thk commercial ply provided above that for grooving of size 3/8"x 3/8" and finished with 1.0 mm thk laminate as per design.The paneling shall be closed at top with 2"x 3/4" teak</p>   |      |      |  |  |

|     |  |       |        |  |
|-----|--|-------|--------|--|
|     | <p>wood beading above upto 2'-0" level of back storage credenza along wall and inside managers room upto false ceiling level, teak wood lipping / beading shall be spirit polished. and following finishings as per drawing and instructions. All exposed surfaces to be clad with teakwood moulding of size 30 mm X 12.0 mm made to shape. The work should be complete in all respects including provisions of grooves duly designed &amp; finished. All wood to be treated with wood preservatives of approved ISI quality. All exposed teak wood shall be spirit polished with matching pigment. The rate shall include for providing grooves in laminate &amp; wood. Payments shall be made only for exposed surfaces &amp; actual measurement at site, no payment shall be made for paneling behind furniture such as tables, Credenza , storage etc.</p> |       |        |  |
| i.  | Vertical Paneling finished with laminate 1.0 mm thk (two clour) (as approved by Architect/bank engg.)  | Sqft. | 742.94 |  |
| 18. | <b>DECORATIVE PANELLING (LOUVERS PANELLING)(in B.M. Cabin)</b>   |       |        |  |
|     | Providing & fixing interlocking Charcoal wall panel of 2700mmx160mmx240mm fixed to the wall & partition with suitable glue. Complete design -138 of EURO PARATIK or equivalent.  | Sqft. | 115.47 |  |
| 19. | <b>LACQUERED GLASS PANELLING (for columns)</b>   |       |        |  |
|     | Panelling with 6mm lacquered glass (St. Gobain "Planileque" or equivalent), fixed to walls over a layer of 12mm thick commercial ply/mdf using clear silicone adhesive, complete in all respects   | Sqft. | 81.0   |  |
| 20. | <b>Writing desk / Customer Voucher Stand / Forms Stand including Pass Book, Cheque Drop &amp; Suggestion Box</b>   |       |        |  |
|     | Providing and fixing forms stand of size 4'-0" X 1'-6" X 3'-9" with 3 nos. storage units of forms with 12 mm glass top fixed with 3" SS spacer. Space for housing vouchers of size 1'6" W, 1'-0" D & 9" H is also provided on the top and on side (L-shaped, wall hung) including provision of Pass Book, Cheque Drop & Suggestion Box as per drawings made of 19 mm thick commercial ply with 1.0 mm thick laminate to be fixed and 3/4" x 1/4" teak wood lipping on two visible sides on it All exposed Teak wood edges / teak wood  | Nos.  | 1.00   |  |

|     |   |       |      |  |  |
|-----|---|-------|------|--|--|
|     | lipping / beading shall be spirit polished with matching pigment. etc. & to be fixed on the wall.cost of spacers ect. all inclusive complete.   |       |      |  |  |
| 21. | <b>Door Closer</b>  |       |      |  |  |
|     | Providing and fixing silver colour (or matching with colour scheme as per site) hydraulic door closer Godrej / Hyper / Everrite make, to Doors complete in all respects.  | Nos.  | 8.00 |  |  |
| 22. | <b>Mortice Lock</b>   |       |      |  |  |
|     | Providing and Fixing silver colour (or matching with colour scheme as per site) Godrej make mortice lock to doors complete in all respects.   | Nos.  | 5.00 |  |  |
| 23. | <b>Night latch Lock</b>   |       |      |  |  |
|     | Providing and fixing night latch lock in cash cabin door of Godrej make in aluminium / wooden doors, complete in all respects.  | Nos.  | 1.00 |  |  |
| 24. | <b>Colour Powder coated Aluminium Doors with Both Side Pre-laminated / PVC coated Board / 12.0 mm thk.Glass with etching &amp; frosted as per requirements.</b>   |       |      |  |  |
|     | Providing and fixing aluminium door made of approved colour powder coated, aluminium extruded sections of various sizes as given below to be fabricated as per approved pattern for doors fixed in position with butt hinges to frame & frame fixed in position with rawl plugs, wooden pegs, screws, aluminium angles / cleats, etc. The doors will be made of three horizontal members and two vertical members provided with 8" long aluminium tower bolt, door stopper, 4 – lever, Make- Plaza, Harrison, Godrej, built in dead lock and aluminium T section / angle at vertical side. Both sides pre-laminated board/ glass 12 mm thick shall be fixed in panels with tapered glazing clips. After fixing / embedding with walls & lintel, etc. the surface will be properly repaired / made good with existing specifications.<br>a). 65 X 38 X 16 Gauge - All horizontal and vertical members of Door Frame.<br>b). 114 X 44 X 16 Gauge - All bottom & lock / middle rail horizontal members of doors.<br>c). 83 X 38 X 16 Gauge - Door members - Top rail & Stiles.<br>The rate shall include all hardware to complete the job. | Sqft. | 0.0  |  |  |
| 25. | <b>Colour Powder coated Aluminium Doors with Both Side Pre-laminated / PVC coated Board / 5.50 mm thk. Board as per requirements.(for doors and internal partitions )</b>   |       |      |  |  |

|    |   |      |       |  |  |
|----|---|------|-------|--|--|
|    | <p>Providing and fixing aluminium door made of approved colour powder coated, aluminium extruded sections of various sizes as given below to be fabricated as per approved pattern for doors fixed in position with butt hinges to frame &amp; frame fixed in position with rawl plugs, wooden pegs, screws, aluminium angles / cleats, etc. The doors will be made of three horizontal members and two vertical members provided with 8" long aluminium tower bolt, door stopper, 4 – lever, Make- Plaza, Harrison, Godrej, built in dead lock and aluminium T section / angle at vertical side. Both sides pre-laminated board 12 mm thick shall be fixed in panels with tapered glazing clips. After fixing / embedding with walls &amp; lintel, etc. the surface will be properly repaired / made good with existing specifications.</p> <p>a). 65 X 38 X 16 Gauge - All horizontal and vertical members of Door Frame.<br/> b). 114 X 44 X 16 Gauge - All bottom &amp; lock / middle rail horizontal members of doors.<br/> c). 83 X 38 X 16 Gauge - Door members - Top rail &amp; Stiles.</p> <p>The rate shall include all hardware to complete the job.</p> | Sft. | 42.0  |  |  |
| 26 | <p><b>Door to System room - Fire rated steel door including frame - 2 (Two) Hrs Metal test certificate will be provided issued from GQMC.</b></p> <p>(Kutty flush doors &amp; furniture co. Pvt Ltd.paonta sahib, distt. Sirmour, H.P. &amp; GMT, Baddi)</p>  | Sft. | 21.00 |  |  |
| a) | <p>Frame - Providing and fixing fire resistant door frame of section 100 x 50 mm having built in rebate out made up of 1.2 mm GPSP Sheet duly powder coated / 16 SWG G.I. sheet (zinc coating not less than 120 gm / sqm ) duly filled with vermiculite based concrete mix, suitable for mounting 120 minutes fire rated door shutters. The frame is fitted with intumescent fire seal strip of size 10 x 4 mm (minimum) around the frame and fixing with dash fastener of approved size and make, including apply a coat of approved brand fire resistant primer etc. complete as per direction of Engineer – in charge (including Dash fastners).</p>   |      |       |  |  |

|     |   |      |        |  |  |
|-----|---|------|--------|--|--|
| b)  | Shutter - Providing and fixing Metal Door Shutter 46 mm thk.made up of 0.8mm thick GPSP Sheet. Glazed fire resistant door shutters of 120 minutes fire rating conforming to IS : 3614 (Part – II), tested and certified as per laboratory approved by Engineer – in – charge, with suitable mounting on door frame, the entire shutter filled insulation material / Honeycomb craft paper of 160gsm (zinc coating not less than 120 gm/m2) and fixing with necessary stainless steel ball bearing hinges of approved make, provision of Fire Rated Wired Glass size of glass 300 X 200 including applying a coat of approved fire resistant primer etc. all complete as per direction of Engineer – in charge (paneling to be paid for separately). |      |        |  |  |
| c   | Hardware for fixing - Fire rated steel door including frame<br>Providing and fixing following hardware for fixing fire rated steel door including frame, complete.<br>Hinges 4X3X3 ( Min. 3Nos), Pull Handle 19 X 250mm - Pair, Dead Lock, Fire Rated Wired Glass size - 300 X 200, Fastners Hilti 10 X 92mm - (Min - 10Nos.)   |      |        |  |  |
| 27. | <b>BOXING FOR ELECTRICAL PANEL (18mm FIBRE CEMENT BOARD)</b>  |      |        |  |  |
|     | Providing & fixing at site cabinet 8'-6"height having overall depth of 1'-6".the carcass shall be made of <b>18mm thk Fibre Cement Board</b> . The shutters shall be made of 18mm thk Fibre Cement Board. with 1.0mm thk laminate on outer surfaces using suitable adhesive. The shutters shall be mounted on <b>heavy duty overlap type SS hinges</b> & provided with magnetic catchers, lock & towerbolts as required with 5mm thk teak wood lipping on all the exposed edges, duly spirit polished. All internal surfaces, & back of shutters shall be painted white, complete in all respects. MAKE : <b>ZYKRON (Century Ply) / SHERA Board / Equivalent</b>  | sqft | 0.0    |  |  |
| 28. | <b>Glass films(B.M. Cabin and Enterance)</b>  |      |        |  |  |
|     | Providing and fixing 3 M make decorative film on glass of approved shade as per architect's instruction with grooves etc. all completed.<br>Note Actual area of film installed will be measured and paid . No wastage will be   | Sft. | 147.90 |  |  |

|     |  |      |        |  |  |
|-----|--|------|--------|--|--|
|     | considered   |      |        |  |  |
| 29. | <b>PLANTER BOX</b>   |      |        |  |  |
|     | Supplying Planter 15'x15"x15" made of 19mm comm. Ply with 1mm laminate and polished teak wood moulding 25 x 8 mm on top & lining of aluminum sheet.  | No.  | 8.0    |  |  |
| 30. | <b>BANK LOGO &amp; LETTERS</b>   |      |        |  |  |
|     | Providing , making to shape and size ( as per the design provided) and fixing to position SBI bank logo made out of ACP sheet of bank blue color ( pre approved) fixed to position with aluminium framework with required screws, nutts bolts and hooks etc. of size 2' x 2'   | 1.00 | no.    |  |  |
|     | SBI logo 10" dia (SS FINISH)   | 1.00 | no.    |  |  |
|     | English letters 10" high (SS FINISH)   | 3.00 | no.    |  |  |
| 31. | <b>ACP CLADDING</b>  |      |        |  |  |
|     | <p>Providing cutting, bending and fixing of aluminium Composite Panel cladding of approved make / manufacture on external façade of size as shown in drawings at all heights and elevation including necessary frame work, either curved or straight or circular in plan.</p> <p>The aluminium composite panel should consist of 3 mm thick thermoplastic core of anti - oxident LDPE + HDPE ( Virgin Core) sandwiched between two layers 0.5 mm thick aluminium alloy sheet ( alloy grade 3003 of ASTM B-209) making a total panel thickness of 4 mm.The surface finish shall be PVDFcoat of 30 micron over a base polyester coat on top and service coat on the reverse with chrome /alkyd of 6 - 7 microns coating shall confirm to ASTM D 2244-93 and ASTM D 523 - 89 for color retention and chalk resistance.ACP shall be fixed on especially designed aluminium frame work with horizontal and vertical members of extruded aluminium made out of AA 6063 T, 6 - 20 microns anodizing shall be done on the aluminium section. The aluminium frame work shall be of 50mm x 25mm and 1.6 mm thk sheet to be supplied in width of 1220 mm. The color shade and texture of the ACP to be as per the approved Bank color</p> | sqft | 521.79 |  |  |

|     |   |      |      |  |  |
|-----|---|------|------|--|--|
|     | design and pattern.   |      |      |  |  |
| 32. | <b>ROLLING WINDOW BLINDS:</b>   |      |      |  |  |
|     | Providing & Fixing Roller Blinds of Vista make-made of Translucent fibre glass fabric of approved shade including 32mm round channel and mechanism and other fitting fixed in position as per manufacture's specification, complete in all respects to the satisfaction of Architect/Engineer in Charge.(with base rate of 120/- per sqft)  | Sqft | 60.0 |  |  |
|     | <b>TOTAL AMOUNT (FURNISHING WORK)</b>   |      |      |  |  |
|     | LESS: credit for old material like aluminium partitions, tables, old counters etc   |      |      |  |  |
|     | <b>NET TOTAL (FURNISHING WORK) (A)</b>  |      |      |  |  |
|     | <b>(GST will be paid extra as applicable)</b>   |      |      |  |  |
|     |   |      |      |  |  |
|     |   |      |      |  |  |
|     |   |      |      |  |  |
|     | <b>SOQ FOR THE INTERIOR FURNISHING WORK SBI WEALTH HUB OF STATE BANK OF INDIA<br/>BRANCH AT MADHOPUR</b>  |      |      |  |  |
| 1   | <b>OFFICER'S TABLE- Size 1500mm x 750mm x 750mm</b>   |      |      |  |  |
|     | Supplying and installation of Table as per the following description and as designed by the Architect:<br>Table Top: Providing and fixing 19 mm thick IS 303 BWR grade plywood with 4mm thick Teak veneer with melamine finish with necessary intermediate support. Table top shall be supported by 18 mm thick BWR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick toughened glass with polished edges. The top level of the glass shall be 900mm. Apron (Modesty Panel) made from 18mm thick BWR grade plywood finished with 1mm laminate.<br>Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with 1mm laminate for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing. Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWR grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWR grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with | No.  | 2.0  |  |  |

|                 |  |            |            |  |  |
|-----------------|--|------------|------------|--|--|
|                 | <p>Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame. Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop. All edges to be provided &amp; fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade. As per drawing and instruction of Architect/Bank, work to be completed.</p>  |            |            |  |  |
| <p><b>2</b></p> | <p><b>CLERICAL STAFF TABLE- Size 1200mm x 750mm x 750mm</b></p>  |            |            |  |  |
|                 | <p>Supplying and installation of Table as per the following description: Tabletop shall be made from 19 mm thick IS 303 BWR grade plywood with 4mm thick Teak veneer with melamine polish with necessary intermediate support. Tabletop shall be supported by 19 mm thick BWR grade plywood with wooden framing. The top of the table shall be provided with equal sized 12mm thick toughened glass fixed. Apron (Modesty Panel) made from 19 mm thick BWR grade plywood finished with 1mm laminate &amp; groove pattern as per drawing. Table sides &amp; intermediate panels (at 50cm from each side) made from 19 mm thick BWR grade plywood finished with 1mm thick laminate for all surfaces shall be provided as per drawing. (Removed drawer cabinet in this version as there will be no space left for a person to sit ) Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in table top. All edges to be provided &amp; fixed with teak wood lipping patti finished with melamine polish. As per drawing and instruction of Architect/Bank, work to be Completed. Plywood Make: Greenply, Century, Duro or</p> | <p>No.</p> | <p>0.0</p> |  |  |



|          |   |     |      |  |  |
|----------|---|-----|------|--|--|
|          | equivalent approved by the Bank.  |     |      |  |  |
| <b>3</b> | <b>MEETING ROOM TABLE</b>   |     |      |  |  |
|          | <p>Providing and placing in position Meeting Room tables of approx. size 1200mm in diameter (size to be considered based on site conditions).</p> <p>Providing &amp; Fixing Conference Table of shape as per design made from 50mm X 40mm T. W. Wood framework 450mm center to center both ways for tabletop covered with 12mm thick BWR ply for bottom, 19mm thick BWR ply for top, table stand and base with necessary 50mm X 40mm vertical supports. All exposed surfaces shall be finish with approved color 1 mm thk. laminate. All internal surfaces to be finished with 0.8mm thick laminate. All edges to be provide with TW lipping patti finished with melamine polish. Rate shall be inclusive of Brush Finish Stainless Steel Tray with POP UP Flap for electrical switches including necessary openings for wire manager, mikes carting away unserviceable materials out of the compound, cleaning the site etc. complete as per the detail drawing and instruction of Engineer.</p> <p>Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.</p>                          | No. | 1    |  |  |
| <b>4</b> | <b>SIDE/ REAR CREDENZA- For officer and clerical staff table ( 450mm X 900 mmx 750 mm)</b>  |     |      |  |  |
| a        | <p>Low Height Cupboard with Laminate Finish: Providing &amp; fixing Low Height Storage Cupboard of 750 height and 450mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 25 mm thk BWR Ply and shelves to be made with 19 mm thk.BWR ply.The top potion of the side and rear credenza to be finished with approved veneer and finished with melamine polish. All the other internal and external surfaces to be finished with 1mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish. Shutters will have concealed handle with wooden groove finished with approved shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffele), SS towerbolts etc. All shutters to be made overlapping the frame Only front elevation will be considered for area calculation. As per drawing and instruction of Architect/Bank, work to be Completed</p> <p>Plywood Make: Greenply, Century, Duro or</p> | No. | 0.00 |  |  |

|          |  |     |      |  |  |
|----------|--|-----|------|--|--|
|          | equivalent approved by the Bank.   |     |      |  |  |
| b        | Same as above- but finished externally with approved <b>quality veneer with melamine polish</b> complete instead of 1mm laminate to match with design of tables.   | No. | 2.0  |  |  |
| <b>5</b> | <b>STORAGE CUPBOARDS</b>   |     |      |  |  |
|          | Providing and placing in position storage cupboard of 450 mm depth, made out of 18 mm thick BWR grade ply.   | No. | 0.00 |  |  |
| A        | Full Height Cupboard with Laminate Finish: Providing & fixing full Height Storage Cupboard of 2100mm height and 450mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply.All shutters and shelves to be made with 19 mm thk. BWR plywood. All internal and external surfaces to be finished with 1mm laminate of approved shade and make.All edges of the cupboard should be edge banded using PVC edge banding tape of approved shade.Shutters to be provided with S.S. 200mm handles, magnetic catchers, self-closing SS hinges, locks (Godrej/Hettich/Haffele), SS tower bolts etc. All shutters to to be made overlapping the frame. Only front elevation will be considered for area calculation.<br>Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank. |     |      |  |  |
| B        | Same as above- but finished externally with approved <b>quality veneer and PU coating finish over melamine polish</b> complete instead of 1mm laminate.  | SQM | 0.0  |  |  |
| <b>C</b> | <b>LOW HEIGHT STORAGE CABINETS/BACK STORAGE: (0.90 HIGH)</b>   |     |      |  |  |
|          | (a) Providing and fixing storage cabinets of size 2'6" (High) x 18" (Deep) along the walls/partitions, as per interior drawings, using 19mm ply for carcass, shutters, vertical and horizontal partitions, 6mm ply for the back and 4 mm veneer on top and 1mm laminate of approved shade on vertical and horizontal visible surfaces. The shutters shall be overlapped on the carcass and shall be provided with Hettich/Godrej/Ozone hinges. The width of the shutter shall be between 12" to 15" as per the site conditions. All the exposed edges of the board shall be provided with wooden lipping 19mm x 3mm, duly PU polished/deco painted in desired shade. The inner surface shall be provided with 0.8mm thick laminate of desired shade and design. The cabinet shall be complete with handles, knobs, locks and                         | SQM | 3.52 |  |  |

|    |   |     |      |  |
|----|---|-----|------|--|
|    | magnet catchers etc. to the satisfaction of the Architect/Engineer.   |     |      |  |
| 6. | <b>WALL/ COLUMN PANELING WITH LAMINATE FINISH.</b>  |     |      |  |
|    | <p>Wall paneling made from 25 x 25 x 1.00 mm thick hollow aluminum sections, over which BWR grade ply of 10 mm shall be fixed and additional 6-8mm ply in layers to create grooves as per the design in the drawing or as directed by Architect, with decorative molding patty on the edges.</p> <p>Providing and fixing in position wooden paneling to column / walls finished with laminate comprising as under:-</p> <p>(i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb.</p> <p>(ii) Panel Finishing:- Providing &amp; fixing 9 mm thick approved make BWR plywood and additional 6-8mm ply in layers to create grooves as per the design to Aluminum framework finished with 1.00 mm thick approved quality and shade laminate, using approved adhesive, in approved pattern &amp; design, including providing grooves, decorative moldings etc. as per Architectural drawings and as directed at site by the Engineer-in-charge.</p> <p>(iii) Providing approved quality, seasoned, full length, Teak Wood molding 15 mm thick with adequate width as required at site, to all openings, cutouts etc duly polished with melamine polish complete as directed by the Engineer-in-charge at site.</p> <p>(iv) The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site.</p> <p>(v) Applying 2 or more coats of melamine polish to exposed edges of paneling, moulded beadings etc. including preparation of surface, sealer coats etc. complete including wastage of material, if any, scaffolding for execution of work at all heights and locations etc. complete.</p> <p>Approved make:-</p> <p>(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.</p> <p>(b) Plywood:- Greenply, Century, Duro or</p> | SQM | 7.73 |  |

|          |   |     |       |  |  |
|----------|---|-----|-------|--|--|
|          | <p>equivalent approved by the Bank.</p> <p>(c) Laminate:- Dorby Mica, Greenlam/Century/Archid / Aerolam or equivalent approved by the Bank.</p> <p>d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.</p> <p>Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.</p>   |     |       |  |  |
| <b>7</b> | <b>FULLY GLAZED DOOR</b>  |     |       |  |  |
| a        | <p>Providing and fixing position 12 mm fully glazed toughened glass door, single/ double shutter, of approx. size 900/ 1500 x 2100/2400 mm. Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed / solid / gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures &amp; hardwares. Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank.</p> <p>Mode of Measurement: Door opening size shall be measured.</p> | SQM | 3.90  |  |  |
| b        | <p><b>Flush doors with frame :</b></p> <p>P/ F 60 mm thk exterior grade two Flush Door approved make finished with 1 mm thk laminate of approved make &amp; shade, including 1st Class CP Teak Wood Frame of size 100mm x 50 mm polished / painted. The door shall be provided with approved make lock, heavy duty door closer, 4 nos. of 5" brass oxidized hinges, SS Brush finish H handle of 9" etc. complete.</p>   | SQM | 0.00  |  |  |
| <b>8</b> | <b>FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED GLASS UPTO 7' LEVEL WITH SOLID PARTITION ABOVE 7'LEVEL</b>  |     |       |  |  |
|          | <p>Providing &amp; fixing full height glazed partition with 12mm Toughened glass of approved make up to 7' level height with solid partition above 7'-0" level up to false ceiling bottom. The glazed panels shall be fixed to the</p>  | SQM | 11.85 |  |  |

existing floor and false ceiling with all necessary SS brackets (D, C or U type) Vertical joints between the glass panels shall be sealed with suitable transparent sealant.

The solid partition above 7'-0" level shall be made with aluminium framework of size 63mm X 38.10mm X 1.47 mm (0.780Kg /mtr) box section. The spacing of the Horizontal and Vertical members are approximately 600mm c/c (maximum) and the top of the frame shall be fixed to the RCC slab bottom. The exposed surfaces on both sides of framework are covered with 6mm BWR ply finished with 1.0mm thick laminate as per direction.

Providing, placing in position & erecting full height partition in desired shape, framework shall be of 50 x 50 x 1.5 mm thick aluminum square section placed at 500 mm c/c both ways or as directed.

**9 FULL HEIGHT SOLID WOODEN PARTITION WITH BOTH SIDES LAMINATE**

Providing & fixing in position 70mm thick +/- 2mm full height solid/opaque wooden partitions finished with laminate on both sides comprising as under:-

- (i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium square sections at spacing not exceeding 600 mm (may slightly vary as per unavoidable site conditions) both ways (horizontal and vertical) fixed rigidly on floor, wall / column & ceiling.
- (ii) Plywood skin:- Providing & fixing 12 mm thick MDF boards on both sides of the framework.
- (iii) Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design & pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approved quality adhesive complete.
- (iv) Making suitable cutouts/ openings/ channels for Doors, electrical conduits, cables & switch boards, AC ducts etc including providing necessary wooden supports wherever required and directed at site.
- (v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.
- (vi) (vi) The door shall be provided with approved

SQM 22.51

make lock, heavy duty door closer, 4 nos. of 5" brass oxidized hinges, SS Brush finish H handle of 9" etc. complete.

(vii) Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.

(viii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.

Approved make:-

(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.

(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank.

(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.

**10 MDF FLUTED WOODEN PANELLING**

Wall paneling made from framework of 25 x 25 x 1.20 mm thick hollow aluminum sections spaced 600mm c/c, over which MDF fluted wooden panel of 10mm +/- 2mm shall be fixed as per the design in the drawing or as directed by Architect.

(i) Framework:- Made out of 25 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb.

(ii) Panel Finishing:- Providing & fixing 10mm +/- 2mm thick approved MDF Wooden Panelling fixed on the aluminum sections with tongue and groove joints in line and level.

(iii) The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site.

iv) The Duco paint shall be of approved make and shade. The surface to be painted shall be first prepared smooth by applying proper grade of sandpaper/water-paper and then if any pores are noticed the same shall be filled with approved quality synthetic filler agent. The complete surface shall be then applied an even coat of sealer putty and permitted to dry.

SQM

17.84

|    |   |     |       |  |  |
|----|---|-----|-------|--|--|
|    | <p>The surface shall be again grinded smooth and even using appropriate grade of water-paper. When the surface is properly smooth and leveled without any pores or cracks the same shall be spray painted with approved quality Duco paint. The adjoining surfaces which are not to be painted with this application shall be suitably masked using appropriate masking tape. The paint shall be permitted to dry at room temperature and attain smooth lustrous finish.</p>  |     |       |  |  |
| 11 | <p><b>FULL HEIGHT SOLID / PARTLY GLAZED WOODEN PARTITION WITH BOTH SIDES LAMINATE</b></p>   |     |       |  |  |
|    | <p>Providing &amp; fixing in position 70mm thick +/- 2mm solid / opaque partly glazed full height wooden partitions with 1200 mm high glass middle panels finished with laminate on both sides comprising as under:-</p> <p>(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium sections not exceeding 600 mm c/c bothways (horizontal and vertical) except in glazed portion of partition, fixed rigidly on floor, wall / column &amp; ceiling. Spacing of frame members may vary to the nearest possible extent as per site conditions.</p> <p>(ii) Plywood skin:- Providing &amp; fixing 8mm thick ply for base with 6.0 mm MDF boards on both sides of the framework. With grooves as specified by Bank engineer/Architect</p> <p>(iii) Finishing:- Providing 1.00 mm thick, approved quality and shade laminate, on both sides of partitions in approved design &amp; pattern including making grooves as per Architectural drawing or as directed by the Engineer-in-charge using approved quality adhesive complete.</p> <p>(iv) Providing and fixing 12mm thick approved make 1200 mm high toughened Glass panels in the middle panels of partitions using second class seasoned teak wood moulding of finished sectional size 75mmx12/15 mm all-round, complete as per drawing and as directed at site. (i</p> <p>(v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.</p> <p>(vi) Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutouts etc. complete.</p> <p>(vii) The rate shall include cost of required</p> | SQM | 10.03 |  |  |

hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.

Approved make:-

(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.

(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank.

12

**GYPBOARD FALSE CEILING**

Providing and fixing false ceiling with cove at all height including providing and fixing of frame work made galvanized M.S. sections as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval.

Fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of Engineer in charge including cost of painting the false ceiling with two coats of acrylic emulsion paint over a cost of putty 12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- (Part I) :2011 (Board with BIS certification marks) to be used Same as Gypsum false ceiling but providing, making, and fixing Gypsum cove (inside height 150 - 200 mm and border 75 mm) to hide strip/cove light in ceiling

SQM

11.34



|    |  |     |       |  |  |
|----|--|-----|-------|--|--|
|    | or to act as pelmet for roller blinds on windows or for projector screen, etc.   |     |       |  |  |
| b) | <b>FALSE CEILING FINISHED WITH LAMINATE</b><br>Same as Gypsum false ceiling but instead gypsum boards providing, making, and fixing 12 mm thick. BWR Grade ply, and additional 6-8mm ply in layers with molding of approved design shall be fixed as per drawing or as directed by Architect, with decorative molding patty. The plywood should be finished with 1 mm thick. Laminate of approved colour(wooden finish) and quality.   | SQM | 6.27  |  |  |
| 13 | <b>MINERAL FIBRE GRID TILE CEILING:</b><br>Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections ( galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. | SQM | 14.13 |  |  |
|    | Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge. GI Metal Ceiling Lay in perforated Tegular edge global white colour tiles of size 595x595 mm and 0.5 mm thick with 8 mm drop; made of GI sheet having galvanizing of 100 gms/sqm (both sides inclusive) and 20% perforation area with 1.8 mm dia holes and having NRC (Noise Reduction Coefficient ) of 0.5, electro statically polyester powder coated of thickness 60 microns   |     |       |  |  |

|           |   |     |      |  |  |
|-----------|---|-----|------|--|--|
|           | (minimum), including factory painted after bending and perforation, and backed with a black Glass fiber acoustical fleece.  |     |      |  |  |
| <b>14</b> | <b>Center Table (2'-6" X 2'-0" Oval / Rectangular)</b><br>Providing and supplying in position oval or rectangular centre table to be made out of 2" X 2" teakwood frame including 12mm thk clear glass top with bevelled edges including bottom glass shelf with etching etc complete. The rate shall also include SS lining design to the teakwood frames including all the necessary hardware, fittings, fixtures as per manufacturers specifications complete.   | No. | 1.0  |  |  |
| <b>15</b> | <b>BACK PAINTED GLASS + LOGO</b><br><b>Back painted glass (Lacquer Glass) paneling:</b><br>Providing and fixing in position wooden paneling to column / walls finished with Back painted (Lacquer Glass) comprising as under:-<br>a<br>(i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed upto 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb.<br>(ii) Panel Finishing:- Providing & fixing 9 mm thick approved make BWR plywood to Aluminum framework finished with 8 mm thick approved quality and make back painted Lacquer Glass panels of required size, rigidly fixed using 3M adhesive / double side self- adhesive tape complete as directed by the Engineer-in-charge.<br>(iii) The rate should include cost of necessary hardware, making cutouts / openings for electrical conduits / cables, Switch boards etc., including providing necessary wooden/aluminum section members support at cutouts, providing scaffolding for execution of work at all heights, complete as per drawings and as directed by the Engineer-in-charge at site. | SQM | 7.04 |  |  |
| <b>b.</b> | <b>Logo:-</b> Providing and fixing in position with SS studs or as directed laser cut Logo as per design made from 18 mm MDF board (exterior grade) and and 10 inch -12 inch high and finished with PU metallic paint as directed complete.(LOGO designed as SBI EMRald   | NO. | 1.0  |  |  |
| <b>16</b> | <b>VITRIFIED TILE FLOORING</b><br>Providing & laying in-position Vitrified tiles in floor and skirting of approved make and colour uniformly in line, level and in approved design, including laying avg. 20 to 25 mm thick bed of  | SQM | 0.00 |  |  |

|           |   |     |       |  |  |
|-----------|---|-----|-------|--|--|
|           | <p>CM 1:6 (1 cement : 6 coarse sand) and filling the joints with epoxy based joint filling compound of matching shade, curing the joints etc complete.</p> <p>Rates to include providing &amp; fixing 100 mm high skirting as per drawing flushed with finished surface of wall in line and level and 6 mm wide groove to be made in wall at the junction of skirting and finished surface of wall etc. complete matching to flooring as per direction of Engineer In-Charge.</p> <p>Make: Kajaria, Somany, Johnson, RAK, Nitco<br/>Size of Tile 800 x 800 mm</p>   |     |       |  |  |
| <b>17</b> | <b>WOODEN FLOORING + SKIRTING</b>   |     |       |  |  |
|           | <p>Providing and placing in position wooden laminate flooring with planks of size not less than 1200 mm X 190 mm (with unlinck panels / tongue-groove locking arrangement) having a 0.2 mm thick top abrasive layer followed by decorative layer upon HDF (high density fiberboard) substrate core over raisin saturated backing layer installed using tongue-groove system over 2 mm thick underlayer of polyurethane foam on 250-micron polythene sheet over a smooth, flat, hard and free from moisture floor surface complete in all respect with required accessories like end profile, transition profile, reducer 'T' profile etc. and preparation of base including all other incidental works as per direction &amp; satisfaction of Architect in charge. Cost of Laminate Floor Accessories, Skirting, End edge, T- molding, Reducer shall have to be added in the cost, wherever required.</p> <p><b>Grade :-Mikasa/Greenlam/Centuryply/Square foot/EGO flooring/Red floor</b></p> | SQM | 30.44 |  |  |
| <b>18</b> | <b>Low Height wooden Partitions (LHP) with laminate finish</b>  |     |       |  |  |
|           | <p>Providing &amp; fixing in position 70 mm +/- 2mm thick Low height wooden partitions with 450mm high glass panel finished with laminate on both sides comprising as under:-</p> <p>(i) Total Height of the partitions shall be from 1200 mm to be 1350 mm including 300 to 450 mm high 12 mm clear glass panel as per approved drawing.</p> <p>(ii) Framing : Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium sections placed bothways (horizontal and vertical) not exceeding 450 mm c/c rigidly fixed to floor, wall / columns etc including extending end/intermediate vertical members not</p>   | SQM | 0.00  |  |  |

exceeding 1500 mm c/c for total finished height of LHP.

(ii) Skin : Providing & fixing 12 mm thick MDF plywood on both sides of the framework and all-round vertical posts extending up to total height of LHP.

(iii) Finishing :- Providing and fixing 1.00mm thick approved quality and shade laminates using approved quality adhesive, over ply as per approved design & pattern including providing grooves as per Architectural drawing and as directed by the Engineer-in-charge.

(iv) Glazing :- Providing and fixing 12mm thick approved make clear float glass panels (not exceeding 1.50 m in length) with polished edges on all sides, fixed using suitable CP Brass /SS 'D' brackets placed not exceeding 450mm c/c on horizontal surface of partition and at both ends on vertical posts to rigidly hold the glass panels.

(v) Providing finished section size 70/75 x 8mm thick seasoned second class Teak wood moulding to all exposed edges of partition including applying 2 or more coats of melamine polish / Duco paint including necessary preparatory work for surface preparation with putty, priming coat, sealer coat etc. complete as per sample approved by the Bank.

(vi) Making necessary cutouts for electrical conduits / cables & switchboard etc., including providing additional supports wherever required complete as per drawings and as directed by Engineer.

(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.

Approved make:-

(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.

(b) MDF: - Greenply, Century, Samrat or equivalent approved by the Bank.

(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.

|    |   |     |      |  |  |
|----|---|-----|------|--|--|
| 19 | <b>PROVIDING AND FIXING 12 MM THICK TOUGHENED GLASS PARTITION ON COUNTER TOP, FRONT SIDE AS FOLLOWS.</b>  |     |      |  |  |
|    | Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. Two cutouts to be made one half round of 150mm dia and another for mouth piece rectangular size of 75mm wide 450mm | SQM | 0.00 |  |  |

|     |   |     |       |  |  |
|-----|---|-----|-------|--|--|
|     | <p>long. All edges of glass shall have Diamond cut polished edges as directed.</p> <p>Brief list of make are as under or any equivalent make will be permitted by the Engineer Glass-Asaahi/ Tata / Modi guard / Saint gobain</p> <p>Square bracket (50 mm x 12.5 mm ) S S finish - Oswal / Riddhi / Swift or equivalent</p>  |     |       |  |  |
| 20  | <p><b>PROVIDING AND FIXING 12 MM THICK TOUGHENED FLOAT GLASS PARTITION TOWARDS FRONT SIDE OF SINGLE WINDOW COUNTERS TOWARDS PUBLIC SPACE AS FOLLOWS.</b></p>  |     |       |  |  |
|     | <p>12 mm thick Toughened clear float glass of required shape with bevelled edges on top portion shall be fixed with SS brackets with flat back on wooden partition and counter top as directed. All edges of glass shall be Diamond cut polished edges as directed complete.</p> <p>Maximum length and height will be measured for payment purpose. Brief list of makes are as under or any equivalent make will be permitted by the Engineer Glass- Asaahi/ Tata / Modi guard / Saint gobain , Square / D bracket S S finish of required size - Oswal / Riddhi / Swift or equivalent approved make</p> | QM  | 0.00  |  |  |
| 21. | <p><b>Acrylic Emulsion Paint on new surface</b></p>   |     |       |  |  |
|     | <p>Providing and applying 2 or more coats of approved Acrylic Emulsion paint with roller finish over a coat of primer on internal walls/ceiling including necessary scaffolding etc. complete as per manufacturers' specifications. Make:- Asian / Nerolac / Berger / Dulex</p>   | SQM | 0.00  |  |  |
| 22. | <p><b>Acrylic Emulsion Paint on old surface</b></p>   |     |       |  |  |
|     | <p>Preparing earlier treated surface by scraping, rubbing with sand paper, applying two coats of Birla white putty wherever required, to level the surface, and its rubbing with sand paper, to ensure smooth surface, suitable to receive paint and then applying 2 or more coats of approved colour and shade of Acrylic Emulsion Paint with low VOC content over a coat of approved primer complete as per manufacturers' specifications to internal walls/ceiling including necessary scaffolding etc. complete.</p> <p>Make:- Asian / Berger/ICI or approved equivalent make.</p>                  | SQM | 0.00  |  |  |
| 23. | <p><b>Polyester Film over glazed partitions:</b></p>  |     |       |  |  |
|     | <p>Providing and fixing in position high impact resistant Polyester Films of approved design &amp; pattern, which once installed on glass, give additional strength to glass, reduce glare &amp; prevent glass from splintering on impact.</p>  | SQM | 18.32 |  |  |

|     |  |     |      |  |  |
|-----|--|-----|------|--|--|
|     | thickness not less than 4 Mil (100 mic.) or 7 Mil (175 mic.)   |     |      |  |  |
| 24. | <b>Roller Blinds</b>   |     |      |  |  |
|     | <p>Providing, fabricating and fixing vertical roller blinds of approved make preferably of "Vista Levelor" with a woven made acrylic coated fabric of 100% polyester of thickness 0.50 – 0.60 mm ( +/- 5% tolerance) with the main properties like resistance to Cracking &amp; Fraying, dust repellence, UV proof and virtually maintenance free along with the Vista accessories of like Head rail , Roller tube Idler, Bottom rail, chain, matching colour installation brackets etc. including all fixtures and fittings of Vista like Rainbow curtain rods with electric resistance welded MS pipe having a corrugated virgin PVC extrusions reinforced to minimize friction, finials and along with standard anchoring arrangements etc. all complete done in workmanlike manner as per the approved design, colour and including necessary scaffolding as directed.</p> | SQM | 0.00 |  |  |
|     | <b>TOTAL AMOUNT (FURNISHING WORK) (WEALTH HUB (B)</b>  |     |      |  |  |
|     | <b>TOTAL AMOUNT ((FURNISHING WORK INTERIOR) (A)+ (FURNISHING WORK) (WEALTH HUB (B) )</b>   |     |      |  |  |
|     | <b>GRAND TOTAL</b>   |     |      |  |  |
|     |  |     |      |  |  |
|     |  |     |      |  |  |
|     |  |     |      |  |  |
|     |  |     |      |  |  |

