

BOQ FOR FURNISHING WORK AT PRERNATIRTH DERASAR ROAD SBI EMERALD BRANCH, AHMEDABAD.

Sr. No.	Description	Quantity	Unite	Rate	Amount
---------	-------------	----------	-------	------	--------

Note : Rate should be inclusive of material,labour,tools, machinery, scaffolding, final disposal of debris, cleaning cutting wastage & removing of all existing furniture items and relocating the same as per instruction by bank etc. All taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills.

1 OFFICER'S TABLE- Size 1500mm x 750mm x 750mm x 1 no

Supplying and installation of Table as per the following description and as designed by the Architect:	1.00	No			
--	------	----	--	--	--

Table Top: Providing and fixing 19 mm thick IS 303 BWR grade plywood with 1 mm thick laminate with necessary intermediate support. Table top shall be supported by 18 mm thick BWR grade ply wood with plywood framing. The top of the table shall be provided with equal sized 12mm thick toughened glass with polished edges. The top level of the glass shall be 750mm. Apron (Modesty Panel) made from 18mm thick BWR grade plywood finished with 1mm laminate. Table sides, back & intermediate panels (at 500mm from each side) made from 18 mm thick MR ply wood finished with 1mm laminate for exposed surfaces (4 faces) and 0.8 mm thick laminate for inner surfaces shall be provided as per drawing. Drawer / Storage cabinet: Box of 400 X 750 X 720 mm shall be provided using 18 mm thick BWR grade plywood. Each Drawer Fascia made out of 18 mm thick plywood and all sides of drawers be made of 12 mm thick plywood & bottom of drawers shall be of 8 mm thick BWR grade plywood. The drawer unit box and individual drawers to be fixed with 1mm laminate on all exposed sides and all the internal surfaces shall be finished with 0.80 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles C-type for each drawer. The front ply of the drawers to be overlapping the frame. Computer Keyboard (550 x 375 mm) of metal / PVC of approved make shall be provided. Footrest of 38 x 76 MM T.W members shall be provided. All internal surface will have min. 0.80 mm thick balancing laminate. Table shall have stand of 18 mm ply finish with 1 mm thk. Laminate of size 400 x 375 mm for keeping CPU and PVC cable Manager shall be provided in the cutouts on the tabletop.

All edges to be provided & fixed with teak wood lipping patti finished with melamine polish. All the surface without teak veneer / laminate / balancing laminate shall be lacquered polished of approved shade.As per drawing and instruction of Architect/Bank, work to be completed.

Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.

4 SIDE/ REAR CREDENZA- For officer and clerical staff table

A Low Height Cupboard with Laminate Finish: Providing & fixing Low Height Storage Cupboard of 750 height and 450mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters to be made from 25 mm thk BWR Ply and shelves to be made with 19 mm thk. BWR ply.

The top portion of the side and rear credenza to be finished with approved veneer and finished with melamine polish. All the other internal and external surfaces to be finished with 1mm laminate of approved shade and All edges to be provide with TW lipping patti finished with melamine polish. Shutters will have concealed handle with wooden groove finished with approved

shade of melamine polish as per drawing, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffe), SS towerbolts etc. All shutters to be made overlapping the frame Only front elevation will be considered for area calculation. As per drawing and instruction of Architect/Bank, work to be Completed
Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.

soze : 3'-0" x 1'-6" x 2'-6" x 1 no

1.00

Nos

5 STORAGE CUPBOARDS

A Providing and placing in position storage cupboard of 450 mm depth, made out of 18 mm thick BWR grade ply.

Full Height Cupboard with Laminate Finish: Providing & fixing full Height Storage Cupboard of 2100mm height and 450mm deep. Outer exposed structure with to be made with 19mm BWR ply as per IS 303 and back side using 8mm BWR grade ply. All shutters and shelves to be made with 19 mm thk. BWR plywood. All internal and external surfaces to be finished with 1mm laminate of approved shade and make. All edges of the cupboard should be edge banded using PVC edge banding tape of approved shade. Shutters to be provided with S.S. 200mm handles, magnetic catchers, self-closing SS hinges, locks (Godrej/ Hettich/Haffe), SS tower bolts etc. All shutters to be made overlapping the frame. Only front elevation will be considered for area calculation.
Plywood Make: Greenply, Century, Duro or equivalent approved by the Bank.

Sizes : 4'-7" x 1'-4" x 2'-6" x 1no

1.06

smt

6.0 WALL/ COLUMN PANELING WITH LAMINATE FINISH.

Wall paneling made from 25 x 25 x 1.00 mm thick hollow aluminum sections, over which BWR grade ply of 10 mm shall be fixed and additional 6-8mm ply in layers to create grooves as per the design in the drawing or as directed by Architect, with decorative molding patty on the edges.

8.92

smt

Providing and fixing in position wooden paneling to column / walls finished with laminate comprising as under:-

(i) Framework:- Made out of 50 mm x 25 mm x 1.2mm thick extruded Aluminium hollow sections, placed not exceeding 600 mm centre to centre, bothways (horizontal and vertical), fixed rigidly on wall / columns in perfect line, level and plumb.

(ii) Panel Finishing:- Providing & fixing 9 mm thick approved make BWR plywood and additional 6-8mm ply in layers to create grooves as per the design to Aluminum framework finished with 1.00 mm thick approved quality and shade laminate, using approved adhesive, in approved pattern & design, including providing grooves, decorative moldings etc. as per Architectural drawings and as directed at site by the Engineer-in-charge.

(iii) Providing approved quality, seasoned, full length, Teak Wood molding 15 mm thick with adequate width as required at site, to all openings, cutouts etc duly polished with melamine polish complete as directed by the Engineer-in-charge at site.

(iv) The rate should include cost of necessary hardware, making cutouts /

openings for electrical conduits / cables, Switch boards, AC ducts etc., including providing necessary wooden/aluminum section members support at cutouts, doors/windows openings etc. complete as per drawings and as directed by the Engineer-in-charge at site.

(v) Applying 2 or more coats of melamine polish to exposed edges of paneling, moulded beadings etc. including preparation of surface, sealer coats etc. complete including wastage of material, if any, scaffolding for execution of work at all heights and locations etc. complete.

Approved make:-

(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.

(b) Plywood:- Greenply, Century, Duro or equivalent approved by the Bank.

(c) Laminate:- Dorby Mica, Greenlam/Century/Archid / Aerolam or equivalent approved by the Bank.

(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.

Mode of measurement:- Though, the aluminium frame may extend above false ceiling level, clear paneling area available below false ceiling shall only be measured after deduction for all openings above 0.50 Sqm.

Column size : 0'-9" + 2'-4" + 0'-9" = 3'-10" x 9'-0" x 1 no

1'-0" + 2'-4"+ 1'-0"+2'-4" = 6'-8" x 9'-0" x 1no

7 FULLY GLAZED DOOR

Providing and fixing position 12 mm fully glazed toughened glass door, single/ double shutter, of approx. size 900/ 1500 x 2100/2400 mm 1.63 smt

Providing and fixing in position frameless glass door shutter made using 12mm thick toughened glass fixed to the partition (glazed / solid / gypsum partitions) using heavy duty floor spring with pivot of approved make including necessary cutting of floor and making the surface good to its original position including all necessary Patch fittings of approved make and fixtures & hardware.

Approved make: DORMA Top Pivot - PT 24, Top Patch Fittings - PT 20, Bottom Patch fittings - PT 10, Floor Spring - BTS 75 V, Corner lock with strike plate and Handle - TG DIH600 - 600mm length) or equivalent brand fittings from Hettich / Hafele / as per sample approved by the Bank. Rate should also include providing film as per design/ instructions of Bank.

Mode of Measurement: Door opening size shall be measured.

Size : 2'-6" x 7'-0" x 1no

8 FULL HEIGHT FULLY GLAZED PARTITION WITH 12MM TOUGHENED GLASS UPTO 7' LEVEL WITH SOLID PARTITION ABOVE 7' LEVEL

Providing & fixing full height glazed partition with 12mm Toughened glass of approved make up to 7' level height with solid partition above 7'-0" level up to false ceiling bottom.

The glazed panels shall be fixed to the existing floor and false ceiling with all necessary SS brackets (D, C or U type) vertical joints between the glass panels shall be sealed with suitable transparent sealant.

The solid partition above 7'-0" level shall be made with aluminium framework of size 63mm X38.10mm X1.47 mm (0.780Kg /mtr) box section. The spacing of the

Providing, placing in position & erecting full height partition in desired shape, framework shall be of 50 x 50 x 1.5 mm thick aluminum square section placed at

Size : 10'-3" x 8'-3" x 1no Less door : 2'-6" x 7'-0" x1no 6.50 smt

11 FULL HEIGHT SOLID / PARTLY GLAZED WOODEN PARTITION WITH BOTH SIDES LAMINATE

Providing & fixing in position 70mm thick +/- 2mm solid / opaque partly glazed full height wooden partitions with 1200 mm high glass middle panels finished with laminate on both sides comprising as under:- 9.50 smt

(i) Framing- Made out of 50mm x 50mm, 1.2 mm thick hollow aluminium the framework.

both sides of partitions in approved design & pattern including making grooves as

(iv) Providing and fixing 12mm thick approved make 1200 mm high toughened

teakwood moulding of finished sectional size 75mmx12/15 mm all-round,

(iv) Making suitable cutouts/openings/channels for Doors, electrical conduits,

(v) Providing and making suitable door frame with rebate for door shutters using approved quality seasoned full-length Teak Wood having finished sectional size 75mm x 20mm to the door perimeter complete as per detailed Architectural drawing and as directed at site.

(vi) Applying 2 or more coats of approved matching shade and finish, melamine polish to all exposed edges of partitions including those in door openings, cutoutsetc. complete.

(vii) The rate shall include cost of required hardware, necessary transportation, execution of work at all heights and locations including all lead, lift, wastage, statutory liabilities etc. complete.

Approved make:-

(a) Aluminum extruded sections: Jindal, Hindalco or equivalent approved by the Bank.

(b) MDF Board:- Greenply, Century, Samrat or equivalent approved by the Bank.

(c) Laminate:- Greenlam/Century/Archid or equivalent approved by the Bank.

(d) Adhesive: Fevicol SH/Vamicol or equivalent approved by the Bank.

Mode of measurement:- Though aluminium frame shall extend up to RCC slab/Beam bottom level above false ceiling, clear partition area below false ceiling shall be measured including deductions for Doors and openings above 0.50 Sqm.

Partly glazed partition : 4'-7" x 8'-6" x 1 no , 7'-5" x 8'-6" x 1 no

- 12** Providing & Supplying Sofas, Sofa chairs of various types & categories (Single seater, Two seater & Three seater) etc complete as per the manufacturers specifications as mentioned below. The rights to select & approve the sofas & seating shall vest with the clients. The contractor shall submit brochures of manufacturer at the time of quoting for this item etc complete as per layout. The consultants reserve the right to select the sofas in line with the technical specifications envisaged & meeting the specifications standards expected.
(Approved makes: Godrej / Durian / Featherlite)

A Single seater sofa

B Two seater sofa

C Three seater sofa

1.00 no

13 CHAIRS FOR OFFICERS/VISITORS AND MEETING ROOM

Supplying & Installation of Office Chairs

a) The seat & back are made of 1.20 cm thick hot-pressed plywood upholstered with fabric and polyurethane foam together with moulded ABS seat & back covers. The back foam should be designed with contoured lumber support for extra comfort having seat size 51x47 cm and back size 48x68cm approx. Overall size of the chair Depth 70 cm x width 70 cm x height 106 - 123.5cm seat ht. -44 - 45 cm. The polyurethane foam should be moulded with density =45 ± 2 kg/m³ and hardness + 20 ± 2 kg on Hampden machine at 25% compression.

b) Chair should be provided with a synchro tilt mechanism which should offer features like forward tilt, self-regulating tilt tension + Manual override, 4 position tilt locking and anti-shock back mechanism which prevents the back rest from hitting the user when the lock should be released. The backrest consists of a drop lift mechanism, which can be adjusted in the range of 6.5 cm and can be locked in 5 steps for the better lumbar support.

c) Chair should be provided with a gas lift mechanism for height adjustments. The pedestal should be injection moulded in black 30% glass filled nylon. The pedestal should be 60 cm pitch centre dia (70 cm with castors). The twin wheel castors are injection moulded in black nylon. All metal components are epoxy polyester powder coated with dry film thickness of more than 45 microns, salt spray test to withstand more than 1000 hrs, pencil scratch hardness more than 2H, other tests conforming to Class D, IS:6005:1970. Polyurethane arm rest & 5 twin wheel extra smooth castors.

A	Chair for Officers (Godrej model- DIVA Revolving Mid Back with Fixed Loop Arms) / equivalent approved make of Featherlite / Wipro	1.00	nos
B	Chair for Visitors (Godrej model- DIVA Revolving Mid Back with Fixed Loop	2.00	nos
C	Chairs for Meeting Room (Godrej model- DIVA Revolving Mid Back with Fixed		

14 GYPBOARD FALSE CEILING

Providing and fixing false ceiling at all height including providing and fixing of frame work made galvanized M.S. sections as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64

mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval.

Fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of Engineer in charge including cost of painting the false ceiling with two coats of acrylic emulsion paint over a coat of putty

12.5 mm thick tapered edge gypsum plain board conforming to IS: 2095- (Part I):2011 (Board with BIS certification marks) to be used. Size : 19'-0" x 9'-0" x 1no	16.00	smt
---	-------	-----

16.0 COVE IN FALSE CEILING

Same as Gypsum false ceiling but providing, making and fixing Gypsum cove (inside height 150 - 200mm and border 75mm) to hide strip/ cover light in ceiling or to act as pelment for roller blinds on windows or for projectro screen, etc.	8.00	rmt
---	------	-----

17.0 Center Table (3'-0" X 2'-0" Oval / Rectangular)

Providing and supplying in position oval or rectangular centre table to be made out of 2" X 2" teakwood frame including 12mm thk clear glass top with bevelled edges including bottom glass shelf with etching etc complete. The rate shall also include SS lining design to the teakwood frames including all the necessary hardware, fittings, fixtures as per manufacturers specifications complete.	1.00	no
---	------	----

21.0 WOODEN FLOORING + SKIRTING :

Providing and placing in position wooden laminate flooring with planks of size not less than 1200 mm x 190mm (with unlinke panels/ tongue-groove locking arrangement) having a 0.2 mm thick top abrasive layer followed by decorative layer upon HDF (high density fiberboard) substrate over 2 mm thick underlayer of polyurethane foam on 250-micron poluthene sheet	11.00	smt
--	-------	-----

over a smooth, flat, hard and free from moisture floor surface complete in all respect with required accessories like end profile, transition profile, reducer 'T' profile etc. and preparation of base including all other incidental works as per direction & satisfaction of architect in charge. Cost of laminate floor accessories, skirting end edge, T- molding Reducer shall have to be added in the cost, wherever required.
SBI Wealth size : 16'-6" x 7'-2"

30.0 Polyester Film over glazed partitions:

Providing and fixing in position high impact resistant Polyester Films of approved design & pattern, which once installed on glass, give additional strength to glass, reduce glare & prevent glass from splintering on impact. thickness not less than 4 Mil (100 mic.) or 7 Mil (175 mic.)

2.86 smt

Size : 10'-3" x 3'-0" x 1no

Total estimated amount

Rs

Note:

- [a] In all furniture work, contractor shall make necessary cutout in panelling/partitions / wooden members to facilitate electrical/data cabling and No extra amount shall be paid for this.
- [b] All internal surface (non visible surfaces) shall be provided with the 0.60 mm thick balancing laminate of aproved make & shade in the all S.W Counters/Tables/ Credenza,Storage Cup Board etc.