

**BILL OF QUANTITIES FOR INTERIOR FURNISHING WORKS AT STATE BANK OF INDIA, REGIONAL BUSINESS OFFICE AT HAMIRPUR., (H.P)**

Sr.no	Description Item of Work	Qty	Unit	Rate	Total Amount
<b>1</b>	<b>Wooden Partitions with Laminate</b>				
	<b>Low/Full Height partly Glazed (with etching/filming) &amp; partly both side laminated Partitions:</b> Providing & fixing partition made of 44 mm X 44 mm X 16 Gauge aluminium extruded sections frame @ 2'-0" to 2'-0" c/c vertically & horizontally. The frame shall be fixed rigidly at floor level as well as ceiling with rawl plugs. The frame work to be clad with 8mm thick commercial ply and 1.0mm thick laminate of APPROVED make in specified pattern as per interiors details on both sides .				
	Also 2 1/2"X5/8" teak wood section shall be provided with 12mm thk. glass with etching/ filming work as per interior details where ever specified. The rate shall also include for providing grooves in laminate & wood. <b>Note: (i) All ply to be sprayed with anty termite and anti borer spray. (ii) Rates to include all necessary supports and as per details (iii) Measurements to be recorded up to finished false ceiling level.</b>				
	Full ht.	82.00	Sq.mt		
	Low ht.	110.00	Sq.mt		
<b>2</b>	<b>Wooden Partitions with Teak Ply</b>				
	<b>Low/Full Height partly Glazed (with etching) &amp; partly both side laminated Partitions:</b> Providing & fixing partition made of 44 mm X 44 mm X 16 Gauge aluminium extruded sections frame @ 2'-0" to 2'-0" c/c vertically & horizontally. The frame shall be fixed rigidly at floor level as well as ceiling with rawl plugs. The frame work to be clad with 8mm thick commercial ply and 4.0mm thick TEAK PLY as/approval make in specified pattern as per interiors details on both sides .				
	Also 2 1/2"X5/8" teak wood section shall be provided with 12mm thk. glass with etching work as per interior details where ever specified. The work includes spirit polishing of apprv. shade on teak wood moulding and Teak Ply complete in all respect to the entire satisfaction of the Architect/Engineer in charge. <b>Note: (i) All ply to be sprayed with anty termite and anti borer spray. (ii) Rates to include all necessary supports and as per details (iii) Measurements to be recorded up to finished false ceiling level.</b>	70.00	Sq.mt		
<b>4</b>	<b>Fixed Toughned Glass Partitions</b>				
	Providing & Fixing 12mm thk. Toughned Glass Panels with SS glass connectors as per manufacturers guidelines of (Godrej/Dorma/Ozone/Stanley) make,rested on 12 mm x 25 mm 'U' channel grouted with in floor surface,fixed in position, as per interior details & recessed in ceiling fixed as per the instruction of the Achitect/Engineer in charge.	10.50	Sq.mt		
<b>5</b>	<b>Wall Connecting Profile</b>				
	Providing and fixing wall connecting profile in floor to hold 12mm thk. Toughened glass.,make: DORMA/OZONE	6.00	Rmt		
<b>6</b>	<b>Toughned Glass Doors</b>				
	Providing & Fixing Openable 12mm thk. Toughned Glass Door,holded with Patch fitting ( i.e. bottom & top patch,L-Patch, floor machine & Door lock) of (Godrej/Dorma/Ozone/Stanley) make,fixed in position as per manufacturers guidelines. The Job also includes providing & fixing of 24" long SS handle & provisions of holes/cuts in glass panel to facilitate fixing of Patch fitting & Handle. The job shall be complete in all respects,including necessary hardware, complete in all respects as per the instruction of the Architect / Engineer in charge.	5.50	Sq.mt		
<b>7</b>	<b>Wall Paneling</b>				
	Providing and fixing paneling over the existing wall made out of framework of 50 mm X 25 mm - 18 gauge section un annodised Aluminium ( as per requirement) frame work @ 16" to 24" c/c vertically & horizontally.The frame work to be clad with 12.0 mm thick commercial ply/12mm thk. water proof MDF as per detail and following finishigs as per drawing and instructions. All exposed surfaces to be clad with teakwood moulding of size 30 mm X 12.0 mm made to shape.				

	The work should be complete in all respects including provisions of grooves duly designed & finished. All wood to be treated with wood preservatives of approved ISI quality. All exposed teak wood shall be spirit polished with matching pigment. Payments shall be made only for exposed surfaces & actual measurement at site, no payment shall be made for paneling behind furniture such as tables, Credenza , storage etc.				
i.	Panelling with Teak Ply with Spirit Polish	30.00	Sq.mt		
ii.	Panelling with laminate	38.00	Sq.mt		
iii.	Panelling with 12mmMDF with Spray Paint/Texture	18.00	Sq.mt		
iv.	Panelling with 1mm thk. <b>Lethaerite sheets</b> of Furns & Lams/Sibu make pasted with adhesives of Pidilite (probone) as per manufacturers specification and drawing.	7.50	Sq.mt		
v.	Panelling with 3.0mm thk. Onax Sheets of EuroPratik Make with adhesives as per manufacturers specification and drawing.	3.00	Sq.mt		
vi.	Panelling with laminate with additional 6mm thk. Mdf over existing ply base to create groove.	10.00	Sq.mt		
vii.	<b>Korian Laminate (Charcolite) panelling.</b> Providing and fixing as/drawing 3-4mm thk.Korian Laminate (Charcolite) panelling of Furns & Lams/Sibu make pasted with adhesives of Pidilite (probone) as per manufacturers specification and drawing.	16.00	Sq.ft		
7a	<b>Paneling with Lacquered Glass panels on SS studs :</b> Providing and fixing 6mm thick Lacquered glass fixed with SS studs and Dow Corning make Neutral Silicone sealant 896 over the frame of 12mm thk. Comm.ply fixed against the wall as panelling as per the drawing to complete satisfaction of the Architect/Bank Engg. in charge. <b>(Make: Saint gobain/AIS)</b>	6.00	Sq.mt		
7b	<b>ENGRAVED/CARVING OR ROUTING CORIAN</b>				
	<b>Du pont Corian Sheet Cladding : Glacier White :</b> Providing and fixing (12mm thick) white acrylic stone (non-absorbent, non-porous solid surface composite material, belonging to the solid surface category) with Engaring/Carving or Routing as over 12mm thk. commercial ply framing as per drawings/design.providing by the Architects complete in all respect including buffing and wastage.	5.00	Sq.mt		
7c	<b>Du pont Corian Sheet Cladding</b>				
	<b>Du pont Corian Sheet Cladding : Glacier White :</b> Providing and fixing (12mm thick) white acrylic stone (non-absorbent, non-porous solid surface composite material, belonging to the solid surface category) over 12mm thk. commercial ply surface as per drawings/design.providing by the Architects complete in all respect including buffing and wastage.	4.00	Sq.mt		
7d	<b>Stonelam (Laminam) panelling.</b> Providing and fixing as/drawing 5mm thk.Laminam panelling of lyca make asted with adhesives of Mapei/karakol as per manufacturers specification and drawing.	8.00	Sq.mt		
8	<b>Officer's &amp; Staff Tables</b> Table made of 19 mm thk. Commercial ply with front and side visible vertical surfaces to be finished with laminate 1mm thick (of approved shade); with 35mm thk. Post forming top, as per drawing and thickness made by joining two boards.. The front of the table top shall be projected as per drawing.The modesty guard shall be finished with 12.0 mm thk. toughed glass with 4" wide S.S. Spacer. Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the table. The PVC Edge binding tape will be provided on all the edges of the table, including bottom touching the floor and the drawers. The table shall have a keyboard tray of size 600 X 270 of EBCO make fixed on channels, as per manufacturers instructions / specifications.				
	A full depth CPU shelf 15" wide shall be provided at left hand side of counter underneath the working top, at 4" above the floor level and 3" away (horizontally), from vertical end which will be made of 19mm thick commercial ply finished with laminate 1mm thk. and PVC Edge binding tape on two visible sides. three lockable drawer running on side mounting drawer slides (channels) of EBCO make made of 19 mm thick commercial ply with 1mm thick laminate on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12 mm thick plywood / 19 mm ply, bottom of 6 mm thick plywood & front of 19 mm thick bply. A full length foot rest made of hard wood 3" x 1½" section shall be provided at 4" above floor level. Non-Visible/inside surfaces i.e. inside / leg-space of table, inside of drawer / cupboard shall be finished in 0.8mm thk. laminate of white/off white shade.				
a	Size 5'0" X 2'6" X 2'6"	15.00	Nos		

b	Size 6'0" X 3'0" X 2'6"	3.00	Nos		
9	<p><b>AGM TABLE</b></p> <p>Table made of 19 mm thk. Commercial ply with front and side visible vertical surfaces to be finished with Teak Veneer 4mm thick (as/selection); with 35mm thk. Table top, as per drawing and thickness made by joining two boards and sealed with Teak Wood Gola 3" wide and 1 1/2" thk. as per drawing. as The front of the table top shall be projected as per drawing. The modesty guard shall be finished with 12.0 mm thk. toughed glass with 4" wide S.S. Spacer.</p> <p>Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the table. The PVC Edge binding tape will be provided on all the edges of the table, including bottom touching the floor and the drawers. The table shall have a keyboard tray of size 600 X 270 of EBCO make fixed on channels, as per manufacturers instructions / specifications.</p> <p>A full depth CPU shelf 15" wide shall be provided at left hand side of counter underneath the working top, at 4" above the floor level and 3" away (horizontally), from vertical end which will be made of 19mm thick commercial ply finished with teak veneer 4mm thk. and PVC Edge binding tape on two visible sides. three lockable drawer running on side mounting drawer slides (channels) of EBCO make made of 19 mm thick commercial ply with 1mm thick laminate on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12 mm thick plywood / 19 mm ply, bottom of 6 mm thick plywood &amp; front of 19 mm thick bply. A full length foot rest made of hard wood 3" x 1 1/2" section shall be provided at 4" above floor level. Non-Visible/inside surfaces i.e. inside / leg-space of table, inside of drawer / cupboard shall be finished in 0.8mm thk. laminate of white/off white shade.</p>				
c	Size 8'0" X 3'0" X 2'6"	1.00	Nos		
10	<p><b>RECEPTION/ATTENDENT Desk</b></p> <p>Split Level Reception desk made of 19 mm thk. Commercial ply with front and side visible vertical surfaces to be finished with Teak Veneer 4mm thick (as/selection); with Table top @ 2'-6" ht finished in laminate, and customer top at 3'-3"/3'-6" ht. with as per drawing finished in corian stone. Also the modesty guard made out of comm. ply shall be finished with corian stone as per drawing.</p> <p>Provision for 3" dia. round / 3" square cable manager for computer / electrical cables at appropriate place will be made in the top surface of the table. The PVC Edge binding tape will be provided on all the edges of the table, including bottom touching the floor and the drawers. The table shall have a keyboard tray of size 600 X 270 of EBCO make fixed on channels, as per manufacturers instructions / specifications. A full depth CPU shelf 15" wide shall be provided at left hand side of counter underneath the working top, at 4" above the floor level and 3" away (horizontally), from vertical end which will be made of 19mm thick commercial ply finished with teak veneer</p> <p>4mm thk. and PVC Edge binding tape on two visible sides. three lockable drawer running on side mounting drawer slides (channels) of EBCO make made of 19 mm thick commercial ply with 1mm thick laminate on front face, handle / knob and magnetic catcher shall be provided on one side of the table as per layout. The sides of the drawer shall be made of 12 mm thick plywood / 19 mm ply, bottom of 6 mm thick plywood &amp; front of 19 mm thick bply. A full length foot rest made of hard wood 3" x 1 1/2" section shall be provided at 4" above floor level. Non-Visible/inside surfaces i.e. inside / leg-space of table, inside of drawer / cupboard shall be finished in 0.8mm thk. laminate of white/off white shade.</p>				
d	Size 6'6"-7'-0" X 2'0" X ( 2'6" and 3'-3") split ht.	1.00	Nos		

11	<b>Providing and placing the Conference Table (Size : 10'-0"/12'-0" x 24'-0")</b> base made out of premium quality 18mmthk. marine ply as per design/detailed drawing (i.e providing vertical supports at 4'-0"distances and wrapped with18mm . thk. marine ply from both sides ) the outer surface shall be clad with additional 6mm flexi ply to attain smooth finish, finally wrapped with teak veneer polished in approved shade.The top of table shall be made with 2 no's 18mm thk. marine ply . The outer exposed side of table top shall be finished with Teak Wood moulding of 3"x 1.5" made to shape.Table top shall have additional 4mm thk. teak veneer in 2 different shades pasted on commercial ply base, fixed with approved adhesives finished with polish.An additional strip of 5mm thk. lacquered glass of size 9"x 10'-0" shall be fixed on top as per design.The entire surface shall be polished as specified in the interior details to the satisfaction of Architect Engineer in charge, complete in all respects.finished with PU Polish.	1.00	Nos		
12	<b>8.0 MM thk glass on top of officers tables.</b> All the edges of the glass shall be grinded polished including Hole for cable manager.	24.00	Sq.mt		
13	<b>Side Credenza</b> Providing & fixing Side credenza ( 15" to 18" deep ) made of 19 mm thick commercial ply and 6 mm thick plywood on back side & 1mm thick laminate of approved shade on top horizontal surface & vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have three drawers, horizontally running on side mounting drawer slides (channels) of EBCO make.				
	The remaining part of the credenza will have cupboard with shutters and one shelf. The shutters with handle / knob and magnetic catcher shall be provided beneath the drawers all non visible/inside surfaces shall be finished with white/off white laminate 1mm thk. and teak wood edges / lipping / beading shall be Spirit polished with matching pigment.				
a	Officer's & Staff side credenzas per Drawing & specification mention in item above. Size - 3'-0" / 4'-0" X 1'-6" X 2'-6" (W X D X H)	18.00	Rmt		
	Finished with 4mm thk. Teak veneer with polish	2.00	Rmt		
14	<b>Back credenza / Storage</b> Providing & fixing back credenza 18" deep ( top surface 18" to 24" as per site ) & 30"/36" HT. made of 19 mm thick commercial ply board and 6 mm thick plywood on back side & 1mm thk laminate of approved shade on top horizontal surface & vertical visible side only, with teak wood lipping on all edges including bottom touching floor. The credenza will have drawers 4"high, horizontally running on side mounting drawer slides (channels) of EBCO make. The remaining part of the credenza will have cupboard with shutters and one shelf. The shutters with handle / knob and magnetic catcher shall be				
	provided beneath the drawers and non-visible/inside surfaces should be finished in 1mm thk. laminate of white/off white shade and teak wood edges / lipping / beading shall be Spirit polished with matching pigment	40.00	Sq.mt		
B	Finished with 4mm thk. Teak veneer with polish	4.00	Sq.mt		
15	<b>5'-0" + 5'-0" (Cubicals) Workstations</b> Providing & fixing 5'-0" x 2'-6" high workstation cubicals made of 19mm thk. Comm.Ply having 2'-0" wide Post forming laminated worktop and vertical supports (2 no's). The Unit shall also consist of one storage unit,CPU unit and keyboard tray with mouse platform of size 600x270 made of 19mm thk. comm. ply make fixed on channels of EBCO make. as per interior details.The storage unit shall be comprising of 2 nos 5" wide drawers & 1 no. pull out drawers on telescopic channels of EBCO make as approval. The CPU unit shall be comprising of 1 no. 5" wide drawer & 4" high platform. All visible surface should be clad with 1mm thk laminate of approved shade and edges to be sealed with contrast shade edge biding PVC beading.The The job shall be completed in all respects with required hardware of approved make to the satisfaction of Engineer in charge/Architect.	12.00	NO		
	<b>MISCELLANEOUS</b>				
16	<b>Softboard</b> Providing and fixing in position soft board ( 12mm) including fabric cover wooden beading of size 25mmx 19mm on all sides finished with polish of approved shade(Basic rate Rs. 175/- per mtr. )	35.00	Sq.mt		
17	<b>MDF JALI</b>				

