

PRICE BID FOR PROPOSED FURNISHING WORK FOR STATE BANK OF INDIA, ADANI SHANTIGRAM BRANCH, AHMEDABAD.

Sr. No.	Description	Quantity	Unit	Rate	Amount															
Note :	Rate should be inclusive of material,labour,tools, machinery, scaffolding, final disposal of debris, cleaning cutting wastage etc. All taxes, transportation etc. complete. (Excluding GST) GST will be paid as Applicable at the time of payment of Bills																			
[A]	FURNISHING WORK																			
1.0	SINGLE WINDOW COUNTER / CASH COUNTER with White corian, blue lacquered glass finishing, front glass partition, front vertical glass and side units.	6.00	RMT																	
	<p>Providing, Supplying, fixing and keeping in position new single window counter complete as per design and drawing made out of 18 mm thick commercial ply wood of approved make, complete with 19 mm. C.P. Teak wood lipping on all edges wherever required.</p> <p>The cost shall be inclusive of S & F of a drawer unit or drawer & shelf unit with 18 mm thick commercial plywood and with approved make multipurpose Auto Lock in drawer and shelf unit. The cost shall also be inclusive of the following.</p>																			
[a]	<p>size :</p> <table border="0"> <tr> <td>Description:</td> <td>L</td> <td>B</td> <td>Ht.</td> <td>No.</td> </tr> <tr> <td>Writing Top</td> <td>5'-0"</td> <td>2'-9"</td> <td>2'-6"</td> <td>4</td> </tr> <tr> <td>4 Drawers with pigeon hole</td> <td>2'-0"</td> <td>1'-3"</td> <td>2'-0"</td> <td></td> </tr> </table> <p>Computer key Board tray with mouse ped Supplying and fixing metal key Board of approved make in counter as per design and instructions.</p>					Description:	L	B	Ht.	No.	Writing Top	5'-0"	2'-9"	2'-6"	4	4 Drawers with pigeon hole	2'-0"	1'-3"	2'-0"	
Description:	L	B	Ht.	No.																
Writing Top	5'-0"	2'-9"	2'-6"	4																
4 Drawers with pigeon hole	2'-0"	1'-3"	2'-0"																	
[b]	Working table top and edges shall be finished with 6 mm thick white corian of DUPONT or equivalent approved make as per drawing and direction with all labour and material.																			
[c]	Front Apron : 2 nos 6 mm thick flexy ply wood in round shape with 6 mm thick white corian shall be provided at front as per design. All edges should be finished with corian of DUPONT make.																			
[d]	Front pannel shall be finished with 6 mm thick 18" high blue back painted glass of approved make and fixed on 18 mm thick commercial ply wood with Natural Silicon gum as per manufacturer's specification and to be completed as per drawing																			
[e]	INCLUDING Ready made M. S. Foot rest and CPU stand with castors .																			
[f]	All wood work shall be laquer polished to a smooth and uniform finish of choice colour and shade.																			
[g]	All fittings like S.S. handle, Auto Lock to each drawer and cabinet doors, piano / auto hinges, ball catcher, stopper, metal cable manager etc. should be fixed of approved make.																			
[h]	Heavy duty telescopic full extension sliding channel of approved make shall be used in all drawers.																			

Sr. No.	Description	Quantity	Unit	Rate	Amount
[i]	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade etc. complete				
[j]	Counter shall be made independent in Length of 5'-0" and properly placed between two partitions. Counter will be measured in RMtr between two partition and paid				
[k]	Front glass : Providing and fixing 12 mm thick Toughened float glass with polished edges to be fixed with necessary S.S Brush finish brackets & support on wooden partition as directed with necessary cut out in glass. All edges of glass shall have Diamond cut polished edges as directed.				
[l]	Vertical Curvilinear glass : 12 mm thick Toughened clear float glass with polished edges shall be fixed with silicon and T.W beading support in front of the wooden partition separating the counters wooden partition as directed. All edges of glass shall be Diamond cut polished edges as directed complete. Wooden partition will be paid separately. Maximum length and height will be measured for payment purpose.				
[m]	SIDE storage units with drawer box For S.W Countwer Same as above item No-7 but Side Table Top and edges shall be finished with 6 mmThick White Corian on Top and Edges. All other visible surface shall be finished with 1.00 mm th laminate. Size shall be 3'-0"x 1'-4"x2'-6" ht. x 4 nos With openable shutter as directed				
	FINISHING DETAILS IN NUTSHELL:				
	1) Table Top : 6 mm thick white corian				
	2) Front Apron: Round corian and 6 mm thick backpainted blue glass fixed with Natural Silicon				
	3) Facing of Drawers: 1.00 mm thick laminate finish				
	4) All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
	TABLES				
2.0	MANAGER TABLE SIZE: 6'-0" X 3'-0" X2'-6" HT. with Laninate finish on Table Top , sides and all other visible surfaces etc complete as follows (with side credenza)	1	NO		
	Supplying and installation of Table as per the following description : Size 6'-0" x 2'-9". Table top shall be made from 18 mm thick commercial ply wood with 1.0 mm thick Laminate with necessary intermediate support. Table top shall be supported by 18 mm thick commercial ply wood with wooden framing. Drawer unit of 1'-3" x 2'-0" x 2'-6" shall be provided using 18 mm thick commercial ply wood having 4 Nos drawers as directed with heavy duty telescope sliding channel of approved make , grouplock, S.S. Handle. Computer Key board tray of metal of approved make shall be provided. Exposed surfaces of the CABINET shall have laminate. All internal surface will have 0.60 mm thick balacing laminate				
	Apron (Modesty Panel) made from 18 mm thick ply wood finished with laminate as per drawing				

Sr. No.	Description	Quantity	Unit	Rate	Amount
---------	-------------	----------	------	------	--------

Table side made from 18 mm thick ply wood with 1.0 mm thick Laminate finish shall be provided in a pattern as per drawing. Laminate to be provided on all visible

Drawer Fascia made out of 18 mm thick Plywood. The sides/back/base of drawers be made of 12 mm thick Ply wood & Bottom of drawers shall be of 6 mm thick ply wood. fixing laminate on front side and all the internal surfaces shall be 0.60 mm thick balancing laminate. The drawers to be fitted with Telescopic sliding channel with SS Group locks of approved make and 100 mm long brush finish Stainless Steel handles for each drawer. All the edges of Drawer Fascia be provided with teak wood edge bending with laquer polished etc complete as directed.

Table shall have ready made CPU stand with castors, ready made foot rest and metallic cable Manager shall be provided in table top. All exposed edges of teak wood shall have polished with smooth edges & corners.

Exposed edges of Table Top, Leg panel & Side Shelf shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.

All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate of approved shade. Etc. complete.

All the surface without laminate / balancing laminate shall be lacquered polished of approved shade

As per drawing and instruction of Architect/Bank work to be Completed

Side Credenza Size 4'-0" x1'-6" x 2'-6" ht. Openable shutter with 1.00 mm thick Laminate finish on Top , front, sides, shutter and 35 mmx 6 mm thick Burma Teak beading on Top Edges. Laminate to be provided only on visible surface etc complete as follows. Only Front elevation will be measured for payment purpose. (For BM & Officer's) Rate for length Less than 3'-3"

FINISHING DETAILS IN NUTSHELL:

- 1) Table Top : 1.0 mm thick Dark laminate & Burma Teak beading on Edges with polished
- 2) Front Apron & Sides: 1.0 mm thick Dark Laminate
- 3) Facing of Drawers: 1.0 mm thick Dark Laminate
- 4) All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate

3.0 GRAHAK MITRA TABLE OF 2'-3" WIDE with laminate finish (siz : 5'-0" x 2'-3" x 2'-6")

1.50 RMT

Same as above item no 2 but Size 2'-3" wide with storage unit in Table with 4mm thick MDF board + Blue and white 1mm thick laminate finishing on all exposed visible surface as per drawing and instruction of Architect/Bank For Grahak Mitra/Tech Mitra (Help Desk Table)

Table top made from 18 mm thick ply wood + 4mm thick MDF board with 1mm thick laminate finish

Apron (Front side) made from 18 mm thick ply wood + 4mm MDF board with 1 mm thick laminate finish

Both sides made from 18 mm thick ply wood + 4mm MDF board with 1mm thick laminate finish

3" thick Partition above working table top made from 18 mm thick+6 mm thick ply wood with necessary framing with 4mm thick MDF board + 1mm thick laminate finish as per drawing.

Sr. No.	Description	Quantity	Unit	Rate	Amount
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width.				
	Drawer Storage Unit- 1'-4" W x 2'-0" D, 2 Nos Drawer on top and rest 1 No shutter				
	All the internal surface (non visible surface) shall be provided with 0.60 mm thick balancing laminate				
	(FOR DETAILS REFER DRG. NO-6) FINISHING DETAILS IN NUTSHELL:				
	1) Table Top : 18 mm Thick Plywood with 1.0 mm thick matt finish super white laminate AICA Make-UGM- G 324/1324 & sapphire Bule laminate G 452/1452				
	2) Front Apron & Sides: 1.0 mm thick high gloss super white laminate AICA Make- UGM- G 324/1324 & sapphire Bule laminate G 452/1452				
	3) Facing of Drawers: 1.0 mm thick Laminate finish				
4.0	DINING TABLE Approx Size 7'-0"x 1'-6"	0.97	SQ MT		
	Supplying and installation of Dining Table of 2'-6" height, 1" x 1.5" ht. T.W beading shall be fixed on border. Top shall be made of 18 mm thick commercial plywood with additional 18 mm thick Ply wood patta of required width on edges with 1.0 mm thick laminate on top of approved shade and supports of the Table shall be made of 2" x 2" T.W. members in a Design as directed. All surfaces not laminated shall be lacquer polished.				
	Exposed edges of Table Top shall be made 36 mm thick by providing additional 18 mm thick ply wood patta of required width. [Only Top shall be measured for payment purpose.]				
5.0	CUSTOMER WRITING DESK	1	NO		
	Writing Desk Size 3'-0" L x 1'-3" x (0'-6"+3'-0") ht. Verticle Sides and bottom shall be made out of 36 mm (2X18) thick Commercial plywood and back side 12 mm thick ply wood with Laminate on Top and Edges on all sides including inside divisions. Top and vertical sides of the divisions shall be made from 12mm th Toughend glass with polished edges for slips or forms as per detail drawing and inststruction complete. Openable shutters made of 18 mm thick commercial ply wood with laminate finishjed and asproved make lock, handle, hinges, magnet latch etc. shall be provided below the glass compartments. (Drawing as enclosed herewith) Laminate to be provided on all visible ply wood surfaces. Including front side openable shutters with ss hinged, godreg lock ect. complete.				
6.0	P/F ELECTRIC CUB BOARD (Size : 4'-0" x 7'-0")	2.60	SQMT		

Sr. No.	Description	Quantity	Unit	Rate	Amount
	<p>Providing and fixing Electric cup board using 18 mm thick Bison board for inside verticle division, shelves and shutter. Aluminium framing of 50x25x1.20mm thick with 6 mm thick Bison board on both side for outer partition with 1.0 mm thick laminate on all exposed surface and polishing/ synthetic enamel paint on all internal surface. Shutter will have approved make lock, handle, hinges, ball catches & S.S Perforated jali etc.complete as directed. Depth of cup board will be around 1'-3". Height of shutter will be maximum 7'-0". Only Front elevation shall be measured for payment purpose.</p>				
7.0	<p>P/F LOW HEIGHT BOTH SIDE LAMINATE PARTITION FOR BACK SIDE AND IN BETWEEN S. W. COUNTER AND CASH CABIN WITH TOUGHENED</p> <p>Providing and fixing low height partition using 50mm x 25mm x 1.50mm thick Aluminium members maximum in grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply of approved brand on both side of aluminium framing and fixing 1.0 mm thick laminate of approved shade on both sides, fixing 12 mm thick transparent toughened glass as directed. Applying polish on exposed steam beach members with lacquer polished edges as directed. Laminate to be provided only on visible surface.</p> <p>For Low height Single window and Cash cabin partition, Average height of partition shall be measured and paid.</p>	13.00	SQMT		
8.0	<p>PROVIDING AND FIXING WICKET GATE WITH BOTH SIDE LAMINATE</p> <p>Same as item no 10 but P/F 30 / 32 mm thick flush shutter with both side laminate including SS hinges with countersunk SS screws, Approved make Night latch Lock, S.S Handles,Door stoppers, doorstoper etc complete as directed.</p> <p>Size : 3'-0" x 4'-0" x 1no</p>	1.12	SQMT		
9.0	<p>FULL HEIGHT PARTITION WORK</p> <p>P/F BOTH SIDE LAMINATE SOLID/ PARTLY GLAZED FULL HEIGHT PARTITION WITH DOOR</p> <p>Providing and fixing both sides laminate full height partly glazed partition using 50mm x 25mm x 1.50mm thick Aluminium members in a maximum grid of 2'-0" x 2'-0" fixing 12 mm thick MDF Board exterior grade / 6 mm thick ply on both sides,1.0 mm laminate of approved make shall be fixed on MDF / plywood. Providing and fixing 5.0/8.0 mm thick float glass as directed in the partition. Providing and fixing door shutter using 32 mm thick flush shutter both side laminated and fixing 6 mm thick glass with beading patti, 5" Long 3 Nos stainless steel hinges, doorstop shall be provided as directed. Godrej Mortice lock shall be provided in door shutter. All visible members if not laminated shall have lacquer polished as directed</p> <p>For purpose of payment partition height up to bottom of false ceiling only shall be measured and paid. No extra payment shall be made for members going up to slab/beam bottom.</p>	9.06	SQMT		
10.0	<p>Providing and fixing UPS door shutter with Aluminium Frame and both side Hilux sheet</p>	5		1.63	SQMT

Sr. No.	Description	Quantity	Unit	Rate	Amount
	<p>Providing and fixing door shutter made out of 50x25x1.5mm thick aluminium framing at maximum 1'-6" C/C both way with 8 mm thick Hilux Board on both side with painting. Providing 6 mm thick clear float glass vision panel secured with 12 mm thick steam beach beading. Steam beach beading of size 31x 12 mm should be placed around shutter edges, aluminium stopper patti on frame including 3 Nos 5" long SS hinges with countersunk SS screws, Approved make Dead Lock, S.S Handles, Door stoppers, doorstopper to be fixed as per drawing & instructions. All beadings should be polished.</p>				
	<p>GLASS DOORS AND PARTITIONS</p>				
11.0	<p>P & F FULLY GLAZED DOOR WITH PATCH FITTINGS for Manager chamber & VIP lounge room</p>				
	<p>Providing & Fixing fully glazed door at the manager chamber (Single) & VIP lounge (Double shutter). The Item includes fixing of 12 mm th. Toughened glass with the help of top patch & bottom patch fittings. The door will have patch lock, pti pivot, 100 Kg floor spring & 25mm dia D shape 400 mm long handles both sides, (Ozone Make OGH-55P11-25X400), fixed with the glass by making necessary cutouts & holes. The glass edges shall be polished on all sides. The entire door shall be erected in complete line & level. The door will have S.S brush finish Signage for pull & push.</p>	5.20	SQMT		
	<p>The patch fittings (Ozone make) shall be of aluminium with s. s. matt finish coating & signage shall be of kich make. The entire door complete in all respect should be installed in positions as required.</p>				
11[a]	<p>Same as above item but P & F FULLY GLAZED PARTITION With Patch Fitting for front side of Branch manager chamber & VIP lounge room door [FIXED PORTION]</p>	27.04	SQMT		
	<p>PANELLING WORK</p>				
12.0	<p>P/F Wall panelling with laminate finishing for wall and Pillar etc</p>	23.70	SQMT		
	<p>Providing and laying panelling on walls & pillars having 12 mm thick MDF Board exterior grade / 6 mm thick ply and 1.0 mm th laminate fixed on wall & pillars with Aluminium. framing of 25mmx25mmx1.20mm thick at maximum 2'-0" c/c bothways on wall and pillar etc complete as directed as per design and instruction of Architect.</p>				
12[a]	<p>Panelling for Digital wall with Blue / white high gloss PU Coating finishing</p>	6.39	SQMT		
	<p>Providing and laying panelling on wall having 8mm th MDF Board exterior grade with PU coating fixed on wall with Aluminium framing of 25mm x 25mm x 1.20 mm thick at maximum 2'-0" c/c bothways etc. complete as directed. Only finished visible surface area shall be measured for payment.</p>				
13.0	<p>P/A WALL PAPERS on Digital wall</p>	5.36	SQMT		
	<p>Providing and applying Wall paper approved by Architect / Bank's Engineer having basic price of Rs 100=00 Per Sq.Ft</p>				

Sr. No.	Description	Quantity	Unit	Rate	Amount
14.0	<p>ALUMINUM COMPOSITE PANEL FOR ROLLING SHUTTER WITH TRAP DOOR</p> <p>Providing and fixing 3 mm thick aluminium composite panel of Flexi Bond / Euro Bond / Timex with 0.25 mm foil with 50 mm x 25 mm x 1.20 mm thick aluminium hollow section tray system with minimum 20 mm bending with silicon Dow Coming of GE seal proof - ACP of approved indian make complete as per selection and direction of Architect for front facade for the building. This item will be carried out as per manufacturer's specifications. Rate also includes providing trap door shutter with hinges, stoppers etc complete as directed. Design as per Bank standered Drawing and Architect's instructions etc complete. TIMEX - DIAMOND WHITE - 111, NAVY BLUE - 117 or equivalent</p>	7.74	SQMT		
15.0	<p>FALSE CEILING WORK</p> <p>P/F GYPSUM BOARD FALSE CEILING</p> <p>Providing and fixing Gypsum board 12.50 mm thick false ceiling in steps and design using Original Indian Gypsum board with original GI sheet section of Gypsteel ULTRA (Gypsteel Ultra shall be used) supporting system in line and level. Finishing the surface and applying 3 coats of Plastic emulsion paint as directed complete. Entire work to be done as per standard specifications of Saint Gobin Gyproc India. After completion of work, certificate from Saint Gobain Gyproc Company shall be submitted along with bill stating that work is satisfactorily completed as per their specification.</p> <p>Note : (1) Rate includes making necessary cut-outs for lighting fixtures (2) Pattas if any shall be measured in SqM and not in Rmt and paid in SqM (3) Only finished visible surface area shall be measured for payment.</p>	107.86	SMT		
15 a)	<p>Providing and Fixing of Armstrong Mineral Fibre Accoustical Suspended ceiling system with FINE FISSURED (MICRO LOCK) EDGE TILES With Armstrong Silhouette Exposed Grid</p> <p>Using Silhouette Grid with Fine Fissured microlook Edge Tiles. With necessary Angles at junctions as per company specifications as directed complete. Rate includes necessary cut outs for A/C Grills, diffusers light fixtures complete as directed. Cutout for light and Diffusers will be deducted from area. Only Tiles cost will be deducted for payment purpose</p> <p>After completion of work, certificate from Company to be obtained and submitted with bill that work is carried out as per their specifications</p>	53.90	SMT		
16.0	<p>SOFT BOARD</p> <p>Providing & fixing soft board for pin up using moulded Steam beach frame of 1" x 1/2" with 6 mm thick commercial plywood on back side and 12mm th soft board on front covered with cloth of selected design of Basic rate of Rs. 150 per Rmt. Steam beach member shall have lacquer polish as directed.</p>	2	SQMT		

Sr. No.	Description	Quantity	Unit	Rate	Amount
17.0	Providing and Fixing Frosted polyster film of 3M (Scotchcal 7725 - 324) or equivalent make over glass surface as per drawing & direction with all labour & materials to the satisfaction of the Architect/Bank as per manufacturer's specification. No deduction will be made for any cutting in the film.	25.25	SQMT		
18.0	Supplying and installation 3'-0" x 1'-9"x 1'-3" height Center Tepoy as follows.	2	NO		
	1'-6" x 2'-0" x 1'-3" x 2nos	2	NO		
	Providing and making open box structure type Tepoy made out of 36 mm (2X18) thick plywood with all over 1.0 mm thick laminate finish provided with bevelled & diamond polished edges 12mm thick glass top supported on 75 mm X 25 mm SS studs complete as directed.				
TOTAL COST "A"					<hr/> <hr/>

Sign & Seal with contractor